



# RADIO TEST REPORT FCC ID: 2ACPR-DTTAB-116-1

**Product:** 2in1 tablet pc

Trade Mark: N/A

Model No.: DTTAB2in1-116-1

Serial Model: W1549

**Report No.:** NTEK-2017NT08075526F2

**Issue Date:** 21 Aug. 2017

## **Prepared for**

SHENZHEN BMORN TECHNOLOGY CO.,LTD.

5/F, Hengfang Verteran Industrial Park, Xingye Road, Xixiang, Bao'an, Shenzhen, Guangdong, China

### Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599 Website:http://www.ntek.org.cn

Version.1.2 Page 1 of 42





## **TABLE OF CONTENTS**

1 TE	EST RESULT CERTIFICATION	3
2 SI	JMMARY OF TEST RESULTS	4
3 FA	ACILITIES AND ACCREDITATIONS	5
3.1	FACILITIES	5
3.2 3.3	LABORATORY ACCREDITATIONS AND LISTINGS MEASUREMENT UNCERTAINTY	
4 GI	ENERAL DESCRIPTION OF EUT	6
5 DE	ESCRIPTION OF TEST MODES	8
6 SE	ETUP OF EQUIPMENT UNDER TEST	9
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	
6.2 6.3	SUPPORT EQUIPMENT EQUIPMENTS LIST FOR ALL TEST ITEMS	10 11
7 TE	ST REQUIREMENTS	13
7.1	CONDUCTED EMISSIONS TEST	13
7.2 7.3	RADIATED SPURIOUS EMISSION6DB BANDWIDTH	
7.3 7.4	PEAK OUTPUT POWER	
7.5	POWER SPECTRAL DENSITY	33
7.6 7.7	CONDUCTED BAND EDGE MEASUREMENTSPURIOUS RF CONDUCTED EMISSIONS	
7.8	ANTENNA APPLICATION	





### 1 TEST RESULT CERTIFICATION

Applicant's name:	SHENZHEN BMORN TECHNOLOGY CO.,LTD.
Address:	5/F, Hengfang Verteran Industrial Park, Xingye Road, Xixiang, Bao'an, Shenzhen, Guangdong, China
Manufacturer's Name:	SHENZHEN BMORN TECHNOLOGY CO.,LTD.
Address	5/F, Hengfang Verteran Industrial Park, Xingye Road, Xixiang, Bao'an, Shenzhen, Guangdong, China
Product description	
Product name:	2in1 tablet pc
Model and/or type reference:	DTTAB2in1-116-1
Serial Model:	W1549

#### Measurement Procedure Used:

APPLICABLE STANDARDS				
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT			
FCC 47 CFR Part 2, Subpart J				
FCC 47 CFR Part 15, Subpart C				
KDB 174176 D01 Line Conducted FAQ v01r01	Complied			
ANSI C63.10-2013				
FCC KDB 558074 D01 DTS Meas Guidance v04				

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test	: 07 Aug. 2017 ~ 21 Aug. 2017		
Testing Engineer	:	Gusan Su	
		(Susan Su)	
Technical Manager	:	Jason chen	
-		(Jason Chen)	
		Sam. Chen	
Authorized Signatory	:		
		(Sam Chen)	

Version.1.2 Page 3 of 42





### 2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C						
Standard Section	ndard Section Test Item Verdict Rem					
15.207	Conducted Emission	ducted Emission PASS				
15.247 (a)(2)	6dB Bandwidth PASS					
15.247 (b)	Peak Output Power	PASS				
15.247 (c)	Radiated Spurious Emission	PASS				
15.247 (d)	Power Spectral Density	PASS				
15.205	Band Edge Emission	PASS				
15.203	Antenna Requirement	PASS				

#### Remark:

- 1. "N/A" denotes test is not applicable in this Test Report.
- 2. All test items were verified and recorded according to the standards and without any deviation during the test.
- This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Version.1.2 Page 4 of 42





### 3 FACILITIES AND ACCREDITATIONS

#### 3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

#### 3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L5516.

IC-Registration The Certificate Registration Number is 9270A-1.

FCC- Accredited Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for

the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang

Street, Bao'an District, Shenzhen 518126 P.R. China.

### 3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±2.80dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(30MHz~1GHz)	±2.64dB
5	All emissions, radiated(1GHz~6GHz)	±2.40dB
6	All emissions, radiated(>6GHz)	±2.52dB
7	Temperature	±0.5°C
8	Humidity	±2%

Version.1.2 Page 5 of 42





### 4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification					
Equipment	2in1 tablet pc				
Trade Mark N/A					
FCC ID 2ACPR-DTTAB-116-1					
Model No.	DTTAB2in1-116-1				
Serial Model	W1549				
Model Difference	All the model are the same circuit and RF module, except the model No. and the colour.				
Operating Frequency 2402MHz~2480MHz					
Modulation	GFSK				
Number of Channels	40 Channels				
Bluetooth Version BT V4.0(BLE)					
Antenna Type	FPCB Antenna				
Antenna Gain	2 dBi				
	☑DC supply: DC 3.8V/8000mAh from Battery or DC 5V from Adapter.				
Power supply	⊠Adapter supply: Model: BI18-050300-AdU Input:AC 100~240V 50~60Hz 0.8A Output:5V, 3A				
HW Version	S101C REV:1.1				
SW Version	WINDOS 10 HOME 64-bit				

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Version.1.2 Page 6 of 42





## **Revision History**

Report No.	Version	Description	Issued Date
NTEK-2017NT08075526F2	Rev.01	Initial issue of report	Aug 21, 2017

Version.1.2 Page 7 of 42





### 5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2404
19	2440
20	2442
***	•••
38	2478
39	2480

Note:  $fc=2402MHz+k\times 2MHz$  k=0 to 39

The following summary table is showing all test modes to demonstrate in compliance with the standard.

_	Test Cases					
Test Item	Data Rate/ Modulation					
rest item	Bluetooth 4.0_LE / GFSK					
AC Conducted Emission	Mode 1: normal link mode					
	Mode 1: normal link mode					
Radiated Test	Mode 2: Bluetooth Tx Ch00_2402MHz_1Mbps					
Cases	Mode 3: Bluetooth Tx Ch19_2440MHz_1Mbps					
	Mode 4: Bluetooth Tx Ch39_2480MHz_1Mbps					
Conducted Test	Mode 2: Bluetooth Tx Ch00_2402MHz_1Mbps					
Conducted Test	Mode 3: Bluetooth Tx Ch19_2440MHz_1Mbps					
Cases	Mode 4: Bluetooth Tx Ch39_2480MHz_1Mbps					

### Note:

- 1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
- 2. AC power line Conducted Emission was tested under maximum output power.
- 3. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.
- 4. EUT is set to continuous transmission mode. duty cycle greater than 98%.


Version.1.2 Page 8 of 42







### **6 SETUP OF EQUIPMENT UNDER TEST**

### 6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM







Note:The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Version.1.2 Page 9 of 42





#### **6.2 SUPPORT EQUIPMENT**

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

เบอเอ.					
Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
E-1	2in1 tablet pc	N/A	DTTAB2in1-116-1	2ACPR-DTTAB-116 -1	EUT
E-2	Adapter	N/A	BI18-050300-AdU	N/A	

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	1.2m
C-2	RF Cable	NO	NO	0.5m

### Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

Version.1.2 Page 10 of 42





### 6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Naulalic	on Test equipmen	IL					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibrati on period
1	Spectrum Analyzer	Aglient	E4407B	MY45108040	2017.06.06	2018.06.05	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2016.11.10	2017.11.09	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2017.06.06	2018.06.05	1 year
4	Test Receiver	R&S	ESPI	101318	2017.06.06	2018.06.05	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2017.04.09	2018.04.08	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2017.06.06	2018.06.05	1 year
7	Horn Antenna	EM	EM-AH-1018 0	2011071402	2017.04.09	2018.04.08	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.07.06	2018.07.05	1 year
9	Amplifier	EMC	EMC051835 SE	980246	2017.08.09	2018.08.08	1 year
10	Amplifier	MITEQ	TTA1840-35- HG	177156	2017.06.06	2018.06.05	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.06	2018.06.05	1 year
12	Power Meter	DARE	RPR3006W	15I00041SN O84	2017.08.07	2018.08.06	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40G Hz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
16	High Test Cable(1G-40G Hz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
17	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

### Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test And this temporary antenna connector is listed within the instrument list

Version.1.2 Page 11 of 42





Conduction Test equipment Kind of Last Calibrated Calibration Item Manufacturer Type No. Serial No. Equipment calibration until period Test Receiver R&S **ESCI** 101160 2017.06.06 2018.06.05 1 year 1 2 R&S LISN **ENV216** 101313 2017.04.19 2018.04.18 1 year **SCHWARZBE** 3 LISN NNLK 8129 8129245 2017.06.06 2018.06.05 1 year CK 50Ω Coaxial ANRITSU 4 MP59B 6200983704 2017.06.06 2018.06.05 1 year Switch **CORP** Test Cable N/A C01 N/A 5 (9KHz-30MH 2017.04.21 2020.04.20 3 year z) Test Cable 6 (9KHz-30MH N/A C02 N/A 2017.04.21 2020.04.20 3 year Test Cable 7 (9KHz-30MH C03 2017.04.21 2020.04.20 N/A N/A 3 year Z)

1	Filter	TRILTHIC	2400MHz	29	2017.04.19	2018.04.18	1 year
---	--------	----------	---------	----	------------	------------	--------

Note: Each piece of equipment is scheduled for calibration once a year.

Version.1.2 Page 12 of 42





#### 7 TEST REQUIREMENTS

#### 7.1 CONDUCTED EMISSIONS TEST

### 7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

#### 7.1.2 Conformance Limit

Fraguaray/MLIz)	Conducted Emission Limit				
Frequency(MHz)	Quasi-peak	Average			
0.15-0.5	66-56*	56-46*			
0.5-5.0	56	46			
5.0-30.0	60	50			


Note: 1. \*Decreases with the logarithm of the frequency

- 2. The lower limit shall apply at the transition frequencies
- 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

#### 7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.1.4 Test Configuration



#### 7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
- 2. The EUT was placed on a table which is 0.8m above ground plane.
- 3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- 4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
- 5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 6. LISN at least 80 cm from nearest part of EUT chassis.
- 7. The frequency range from 150KHz to 30MHz was searched.
- Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
- 9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Version.1.2 Page 13 of 42






#### 7.1.6 **Test Results**

EUT:	2in1 tablet pc	Model Name:	DTTAB2in1-116- 1
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Damanic
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1675	45.18	9.82	55.00	65.08	-10.08	QP
0.1675	27.07	9.82	36.89	55.08	-18.19	AVG
0.3659	33.97	9.83	43.80	58.59	-14.79	QP
0.3659	17.26	9.83	27.09	48.59	-21.50	AVG
0.5897	30.72	9.83	40.55	56.00	-15.45	QP
0.5897	12.93	9.83	22.76	46.00	-23.24	AVG
1.2540	29.32	9.90	39.22	56.00	-16.78	QP
1.2540	13.48	9.90	23.38	46.00	-22.62	AVG
2.4219	28.73	9.92	38.65	56.00	-17.35	QP
2.4219	16.01	9.92	25.93	46.00	-20.07	AVG
5.1539	29.53	10.05	39.58	60.00	-20.42	QP
5.1539	16.26	10.05	26.31	50.00	-23.69	AVG

### Remark:

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 14 of 42






EUT:	2in1 tablet pc	Model Name:	DTTAB2in1-116- 1
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Damanis
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1980	41.79	9.92	51.71	63.69	-11.98	QP
0.1980	11.44	9.92	21.36	53.69	-32.33	AVG
0.3458	35.24	9.92	45.16	59.06	-13.90	QP
0.3458	18.84	9.92	28.76	49.06	-20.30	AVG
0.7860	29.60	9.93	39.53	56.00	-16.47	QP
0.7860	14.37	9.93	24.30	46.00	-21.70	AVG
1.3500	30.86	9.93	40.79	56.00	-15.21	QP
1.3500	15.09	9.93	25.02	46.00	-20.98	AVG
2.7540	29.75	9.95	39.70	56.00	-16.30	QP
2.7540	17.68	9.95	27.63	46.00	-18.37	AVG
5.4537	26.92	9.98	36.90	60.00	-23.10	QP
5.4537	15.41	9.98	25.39	50.00	-24.61	AVG

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 15 of 42






EUT:	2in1 tablet pc	Model Name:	DTTAB2in1-116 -1
Temperature:	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Domork
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1819	41.88	9.82	51.70	64.39	-12.69	QP
0.1819	23.06	9.82	32.88	54.39	-21.51	AVG
0.3659	33.97	9.83	43.80	58.59	-14.79	QP
0.3659	16.40	9.83	26.23	48.59	-22.36	AVG
0.5655	32.27	9.83	42.10	56.00	-13.90	QP
0.5655	21.91	9.83	31.74	46.00	-14.26	AVG
0.9220	30.00	9.90	39.90	56.00	-16.10	QP
0.9220	10.55	9.90	20.45	46.00	-25.55	AVG
2.1299	29.50	9.87	39.37	56.00	-16.63	QP
2.1299	12.13	9.87	22.00	46.00	-24.00	AVG
6.5339	29.98	9.99	39.97	60.00	-20.03	QP
6.5339	18.02	9.99	28.01	50.00	-21.99	AVG

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 16 of 42






EUT:	2in1 tablet pc	Model Name :	DTTAB2in1- 116-1
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Damanis
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	Remark
0.1675	42.38	9.92	52.30	65.08	-12.78	QP
0.1675	13.39	9.92	23.31	55.08	-31.77	AVG
0.2548	37.46	9.92	47.38	61.60	-14.22	QP
0.2548	15.83	9.92	25.75	51.60	-25.85	AVG
0.6820	30.87	9.93	40.80	56.00	-15.20	QP
0.6820	15.88	9.93	25.81	46.00	-20.19	AVG
1.8140	33.58	9.94	43.52	56.00	-12.48	QP
1.8140	21.27	9.94	31.21	46.00	-14.79	AVG
3.1059	32.65	9.95	42.60	56.00	-13.40	QP
3.1059	22.57	9.95	32.52	46.00	-13.48	AVG
15.6219	35.48	10.25	45.73	60.00	-14.27	QP
15.6219	23.50	10.25	33.75	50.00	-16.25	AVG

- All readings are Quasi-Peak and Average values.
   Factor = Insertion Loss + Cable Loss.



Version.1.2 Page 17 of 42





#### 7.2 RADIATED SPURIOUS EMISSION

#### 7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

#### 7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). According to FCC Part15.205, Restricted bands

According to FCC Part 15.20	according to FCC Part 15.205, Restricted bands							
MHz	MHz	MHz	GHz					
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15					
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46					
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75					
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5					
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2					
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5					
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7					
6.26775-6.26825	123-138	2200-2300	14.47-14.5					
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2					
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4					
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12					
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0					
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8					
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5					
12.57675-12.57725	322-335.4	3600-4400	(2)					
13.36-13.41								

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

(- //	. ` '	
Field Strength (µV/m)	Field Strength (dB <sub>µ</sub> V/m)	Measurement Distance
2400/F(KHz)	20 log (uV/m)	300
2400/F(KHz)	20 log (uV/m)	30
30	29.5	30
100	40	3
150	43.5	3
200	46	3
500	54	3
	Field Strength (µV/m)  2400/F(KHz)  2400/F(KHz)  30  100  150  200	Field Strength (μV/m)       Field Strength (dBμV/m)         2400/F(KHz)       20 log (uV/m)         2400/F(KHz)       20 log (uV/m)         30       29.5         100       40         150       43.5         200       46

<u>Limits of Radiated Emission Measurement(Above 1000MHz)</u>

Frequency(MHz)	Class B (dBuV/m) (at 3M)			
	PEAK	AVERAGE		
Above 1000	74	54		

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.

Version.1.2 Page 18 of 42






### 7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

### 7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



Version.1.2 Page 19 of 42





#### 7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

eco are renewing opeoutain analyzor country	see the lenething operation analyzer cettinge.						
Spectrum Parameter	Setting						
Attenuation	Auto						
Start Frequency	1000 MHz						
Stop Frequency	10th carrier harmonic						
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average						

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For the radiated emission test above 1GHz:
  - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- e. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- f. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- g. For the actual test configuration, please refer to the related Item -EUT Test Photos.

#### Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

Version.1.2 Page 20 of 42





During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
Above 1000	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10\*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

### 7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK AV		PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =20log(Specific distance/ test distance)( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

Version.1.2 Page 21 of 42






Spurious Emission below 1GHz (30MHz to 1GHz)
 All the modulation modes have been tested, and the worst result was report as below:

7 111 1110 1110 1110 1110 1110 1110 111	THE GOVERNMENT OF THE CONTROL OF THE	and the moretrocalt mass repor	
EUT:	2in1 tablet pc	Model Name:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1
Test Voltage:	DC 3.8V		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	32.6340	15.12	20.04	35.16	40.00	-4.84	QP
V	43.8119	19.10	14.49	33.59	40.00	-6.41	QP
V	88.6524	19.74	11.76	31.50	43.50	-12.00	QP
V	116.9495	19.69	10.27	29.96	43.50	-13.54	QP
V	230.9068	16.74	12.06	28.80	46.00	-17.20	QP
V	399.0300	15.55	15.13	30.68	46.00	-15.32	QP

### Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




Version.1.2 Page 22 of 42





Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Н	30.4237	6.48	21.02	27.50	40.00	-12.50	QP
Н	56.0007	12.75	12.21	24.96	40.00	-15.04	QP
Н	83.8156	15.16	11.24	26.40	40.00	-13.60	QP
Н	120.6991	20.74	10.62	31.36	43.50	-12.14	QP
Н	205.6750	18.15	13.80	31.95	43.50	-11.55	QP
Н	417.6409	15.68	16.35	32.03	46.00	-13.97	QP

### Remark:



Version.1.2 Page 23 of 42





Spurious Emission Above 1GHz (1GHz to 25GHz)

	- Spanisas Ennission / Reversion ( Perile to Edenie)							
EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1					
Temperature:	20 ℃	Relative Humidity:	48%					
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su					

Frequenc y	Read Level	Cable loss	Antenna Factor	Preamp Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	$(dB\mu V/m)$	(dB)		
			Low	Channel (2	402 MHz)-/	Above 1G			
4804.568	61.94	5.21	35.59	44.30	58.44	74.00	-15.56	Pk	Vertical
4804.568	41.11	5.21	35.59	44.30	37.61	54.00	-16.39	AV	Vertical
7206.337	60.91	6.48	36.27	44.60	59.06	74.00	-14.94	Pk	Vertical
7206.337	40.75	6.48	36.27	44.60	38.90	54.00	-15.10	AV	Vertical
4804.399	62.95	5.21	35.55	44.30	59.41	74.00	-14.59	Pk	Horizontal
4804.399	43.32	5.21	35.55	44.30	39.78	54.00	-14.22	AV	Horizontal
7206.444	62.00	6.48	36.27	44.52	60.23	74.00	-13.77	Pk	Horizontal
7206.444	40.81	6.48	36.27	44.52	39.04	54.00	-14.96	AV	Horizontal
			Mid	Channel (24	440 MHz)- <i>A</i>	Above 1G			
4880.703	62.93	5.21	35.66	44.20	59.60	74.00	-14.40	Pk	Vertical
4880.703	43.63	5.21	35.66	44.20	40.30	54.00	-13.70	AV	Vertical
7320.495	64.94	7.10	36.50	44.43	64.11	74.00	-9.89	Pk	Vertical
7320.495	41.18	7.10	36.50	44.43	40.35	54.00	-13.65	AV	Vertical
4880.596	63.30	5.21	35.66	44.20	59.97	74.00	-14.03	Pk	Horizontal
4880.596	41.10	5.21	35.66	44.20	37.77	54.00	-16.23	AV	Horizontal
7320.464	59.64	7.10	36.50	44.43	58.81	74.00	-15.19	Pk	Horizontal
7320.464	43.27	7.10	36.50	44.43	42.44	54.00	-11.56	AV	Horizontal
			High	Channel (2	480 MHz)-	Above 1G			
4960.712	62.85	5.21	35.52	44.21	59.37	74.00	-14.63	Pk	Vertical
4960.712	42.65	5.21	35.52	44.21	39.17	54.00	-14.83	AV	Vertical
7440.361	64.10	7.10	36.53	44.60	63.13	74.00	-10.87	Pk	Vertical
7440.361	41.02	7.10	36.53	44.60	40.05	54.00	-13.95	AV	Vertical
4960.556	64.28	5.21	35.52	44.21	60.80	74.00	-13.20	Pk	Horizontal
4960.556	44.72	5.21	35.52	44.21	41.24	54.00	-12.76	AV	Horizontal
7440.429	65.17	7.10	36.53	44.60	64.20	74.00	-9.80	Pk	Horizontal
7440.429	44.07	7.10	36.53	44.60	43.10	54.00	-10.90	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).
(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor
(3)All other emissions more than 20dB below the limit.

Version.1.2 Page 24 of 42





_	Spurious Emission	Till Restricted Darid 23	10-2390WITZ aliu 2463.	.5-2500WITZ
_	Spurious Emission	n in Restricted Band 23	10 2200MHz and 2492	5 2500MHz

EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Susan Su

Frequenc	Meter	Cable	Antenna	Preamp	Emission	Limits	Margin	Detector	
У	Reading	Loss	Factor	Factor	Level	LIIIIIIS	Margin	Detector	Comment
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type	
				GF	SK				
2310.00	63.90	2.97	27.80	43.80	50.87	74	-23.13	Pk	Horizontal
2310.00	43.36	2.97	27.80	43.80	30.33	54	-23.67	AV	Horizontal
2310.00	61.50	2.97	27.80	43.80	48.47	74	-25.53	Pk	Vertical
2310.00	42.91	2.97	27.80	43.80	29.88	54	-24.12	AV	Vertical
2390.00	64.72	3.14	27.21	43.80	51.27	74	-22.73	Pk	Vertical
2390.00	43.20	3.14	27.21	43.80	29.75	54	-24.25	AV	Vertical
2390.00	64.41	3.14	27.21	43.80	50.96	74	-23.04	Pk	Horizontal
2390.00	42.38	3.14	27.21	43.80	28.93	54	-25.07	AV	Horizontal
2483.50	62.95	3.58	27.70	44.00	50.23	74	-23.77	Pk	Vertical
2483.50	42.34	3.58	27.70	44.00	29.62	54	-24.38	AV	Vertical
2483.50	66.09	3.58	27.70	44.00	53.37	74	-20.63	Pk	Horizontal
2483.50	43.40	3.58	27.70	44.00	30.68	54	-23.32	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

Version.1.2 Page 25 of 42





### ■ Spurious Emission in Restricted Band 3260MMHz-18000MHz

EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Susan Su

Frequenc	Readin g Level	Cable Loss	Antenn a	Preamp Factor	Emission Level	Limits	Margin	Detect or	
(MHz)	(dBµV)	(dB)	dB/m	(dB)	(dBµ V/m)	(dBµ V/m)	(dB)	Туре	Comment
3260	62.15	4.04	29.57	44.70	51.06	74	-22.94	Pk	Vertical
3260	55.32	4.04	29.57	44.70	44.23	54	-9.77	AV	Vertical
3260	64.43	4.04	29.57	44.70	53.34	74	-20.66	Pk	Horizontal
3260	57.97	4.04	29.57	44.70	46.88	54	-7.12	AV	Horizontal
3332	64.37	4.26	29.87	44.40	54.10	74	-19.90	Pk	Vertical
3332	55.45	4.26	29.87	44.40	45.18	54	-8.82	AV	Vertical
3332	64.49	4.26	29.87	44.40	54.22	74	-19.78	Pk	Horizontal
3332	51.08	4.26	29.87	44.40	40.81	54	-13.19	AV	Horizontal
17797	44.16	10.99	43.95	43.50	55.60	74	-18.40	Pk	Vertical
17797	34.18	10.99	43.95	43.50	45.62	54	-8.38	AV	Vertical
17788	42.86	11.81	43.69	44.60	53.76	74	-20.24	Pk	Horizontal
17788	35.47	11.81	43.69	44.60	46.37	54	-7.63	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

Version.1.2 Page 26 of 42





#### 7.3 6DB BANDWIDTH

### 7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v04

#### 7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

### 7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.3.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v04

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

 $VBW \geq 3^*RBW$ 

Sweep = auto

Detector function = peak

Trace = max hold

#### 7.3.6 Test Results

EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	534.7	≥500	Pass
Middle	2440	536.0	≥500	Pass
High	2480	536.7	≥500	Pass

Version.1.2 Page 27 of 42








Version.1.2 Page 28 of 42







Version.1.2 Page 29 of 42





#### 7.4 PEAK OUTPUT POWER

#### 7.4.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v04

#### 7.4.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

#### 7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.4.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v04

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Set the RBW ≥ DTS bandwidth(about 1MHz).

Set VBW =3\*RBW(about 3MHz)

Set the span ≥3\*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

#### 7.4.6 Test Results


EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Test Channel	Frequency (MHz)	Power Setting	Peak Output Power (dBm)	LIMIT (dBm)	Verdict	
1Mbps						
00	2402	Default	5.045	30	PASS	
19	2440	Default	5.218	30	PASS	
39	2480	Default	6.084	30	PASS	

Version.1.2 Page 30 of 42








Version.1.2 Page 31 of 42







Version.1.2 Page 32 of 42





#### 7.5 POWER SPECTRAL DENSITY

### 7.5.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v04

#### 7.5.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

#### 7.5.5 Test Procedure

The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04

This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle ≥ 98%); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times DTS bandwidth.
- c) Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{kHz}$ .
- d) Set VBW ≥3 x RBW.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$ .
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing

Version.1.2 Page 33 of 42






### 7.5.6 Test Results

EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Susan Su

Test Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Verdict		
1Mbps						
00	2402	-12.518	8	PASS		
19	2440	-12.163	8	PASS		
39	2480	-11.342	8	PASS		



Version.1.2 Page 34 of 42







Version.1.2 Page 35 of 42





#### 7.6 CONDUCTED BAND EDGE MEASUREMENT

### 7.6.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v04

#### 7.6.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

#### 7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

### 7.6.5 Test Procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.


#### 7.6.6 Test Results

EUT:	2in1 tablet pc	Model No.:	DTTAB2in1-116-1
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode2/Mode4	Test By:	Susan Su

Version.1.2 Page 36 of 42







Version.1.2 Page 37 of 42





#### 7.7 SPURIOUS RF CONDUCTED EMISSIONS

#### 7.7.1 Conformance Limit

- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### 7.7.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

#### 7.7.3 Test Setup

Please refer to Section 6.1 of this test report.

### 7.7.4 Test Procedure

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequeny range from 9KHz to 26.5GHz.

#### 7.7.5 Test Results

Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Version.1.2 Page 38 of 42





#### **Test Plot**


### GFSK on channel 00



### GFSK on channel 00



#### GFSK on channel 00



GFSK on channel 00



Version.1.2 Page 39 of 42






#### **Test Plot**


### GFSK on channel 19



### GFSK on channel 19



GFSK on channel 19



GFSK on channel 19



Version.1.2 Page 40 of 42






#### **Test Plot**


### GFSK on channel 39



### GFSK on channel 39



#### GFSK on channel 39



#### GFSK on channel 39



Version.1.2 Page 41 of 42





### 7.8 ANTENNA APPLICATION

### 7.8.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 7.8.2 Result

The	EUT	antenna	is	permanent	attached	<b>FPCB</b>	antenna(Gain:2dBi).	lt	comply	with	the	standard
requirement.												

**END OF REPORT** 

Version.1.2 Page 42 of 42