

FCC 47 CFR PART 15 SUBPART C CERTIFICATION TEST REPORT

For

Smart Delite 2

MODEL No.: LTB012

FCC ID: 2ACQ5-LTB012

Trademark: Revogi

REPORT NO.: ES151222010E

ISSUE DATE: January 13, 2016

Prepared for

Revogi Innovation Co., Ltd.

2018, Anhui Building, No. 6007, Shennan Boulevard, Shenzhen, Guangdong, China

Prepared by

EMTEK (SHENZHEN) CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

TEL: 86-755-26954280 FAX: 86-755-26954282



Table of Contents

1	TEST RESULT CERTIFICATION3					
2	EUT	TECHNICAL DESCRIPTION	4			
3	SUM	MARY OF TEST RESULT	5			
4	TES	「METHODOLOGY	6			
	4.1 4.2 4.3	General Description Of Applied Standards Measurement Equipment Used Description Of Test Modes	6			
5	FAC	LITIES AND ACCREDITATIONS	8			
	5.1 5.2	FacilitiesLaboratory Accreditations And Listings				
6	TES	SYSTEM UNCERTAINTY	9			
7	SET	JP OF EQUIPMENT UNDER TEST	.10			
	7.1 7.2 7.3 7.4 7.5	Radio Frequency Test Setup 1 Radio Frequency Test Setup 2 Conducted Emission Test Setup Block Diagram Configuration Of Test System Support Equipment	10 12 13			
8	TES	FREQUIREMENTS	14			
	8.1 8.2 8.3 8.4 8.5 8.6 8.7	Dts (6db) Bandwidth	17 20 23 29 42			



1 TEST RESULT CERTIFICATION

Applicant:	Revogi Innovation Co., Ltd. 2018, Anhui Building, No. 6007, Shennan Boulevard, Shenzhen, Guangdong, China
Manufacturer:	SkyRC Technology Co., Ltd. 4/F, Building No. 6, Meitai Industry Park, Guanguang South Road, Guihua,Guanlan, Baoan District, Shenzhen, China
Product Description:	Smart Delite 2
Model Number:	LTB012
File Number:	ES151222010E
Date of Test:	December 20, 2015 to January 12, 2016

Measurement Procedure Used:

APPLICABLE STANDARDS		
STANDARD	TEST RESULT	
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS	

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report

Date of Test :	December 20, 2015 to January 12, 2016
Prepared by :	Rui Zhai
	Rui Zhou/Editor
Reviewer:	Yaping Shen
	Yaping Shen /Supervisor
Approve & Authorized Signer :	
	Lisa Wang /Manager



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Device Type	Bluetooth 4.0 with BLE model
Data Rate 1Mbps;	
Modulation	GFSK;
Operating Frequency Range	2402-2480MHz
Number of Channels 40 Channels	
Transmit Power Max	-8.938 dBm
Antenna Type	PCB Antenna
Antenna Gain	0dBi;
Power supply	AC 120V/60HZ
Temperature Range	-20°C ~ +55°C

Note: for more details, please refer to the User's manual of the EUT.



3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	PASS	
15.247(b)	Antenna Application	PASS	

NOTE1: N/A (Not Applicable)

NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ACQ5-LTB012 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.



4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 DTS Meas Guidance v03r04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/16/2015
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/16/2015
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/16/2015
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/16/2015
I.S.N Rohde & Schwarz		ENY22	1109.9508.02	05/16/2015

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2015
Pre-Amplifier	HP	8447D	2944A07999	05/16/2015
Bilog Antenna	Schwarzbeck	VULB9163	142	05/16/2015
Loop Antenna	ARA	PLA-1030/B	1029	05/16/2015
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/16/2015
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/16/2015
Cable	Schwarzbeck	AK9513	ACRX1	05/16/2015
Cable	Rosenberger	N/A	FP2RX2	05/16/2015
Cable	Schwarzbeck	AK9513	CRPX1	05/16/2015
Cable	Schwarzbeck	AK9513	CRRX2	05/16/2015

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/16/2015
Spectrum Analyzer	Agilent	N9010A	My53470879	05/16/2015
Power meter	Anritsu	ML2495A	0824006	05/16/2015
Power sensor	Anritsu	MA2411B	0738172	05/16/2015

Remark: Each piece of equipment is scheduled for calibration once a year.



4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (Bluetooth V4.0:1Mbps) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V4.0:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440		
1	2404	20	2442	37	2476
2	2406	21	2444	38	2478
				39	2480
Note: fc=2402MHz+k×2MHz k=1 to 39					

Test Frequency and channel for Bluetooth V4.0:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	39	2480



5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2013.10.29

The certificate is valid until 2016.10.28

The Laboratory has been assessed and proved to be in compliance

with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)

The Certificate Registration Number is L2291

: Accredited by TUV Rheinland Shenzhen, 2010.5.25 The Laboratory has been assessed according to the requirements

ISO/IEC 17025.

: Accredited by FCC, April 17, 2014

The Certificate Registration Number is 406365.

: Accredited by FCC, February 28, 2013

The Certificate Registration Number is 709623.

: Accredited by Industry Canada, May 24, 2008 The Certificate Registration Number is 4480A-2



6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

аррагация.			
Parameter	Uncertainty		
Radio Frequency	±1x10^-5		
Maximum Peak Output Power Test	±1.0dB		
Conducted Emissions Test	±2.0dB		
Radiated Emission Test	±2.0dB		
Power Density	±2.0dB		
Occupied Bandwidth Test	±1.0dB		
Band Edge Test	±3dB		
All emission, radiated	±3dB		
Antenna Port Emission	±3dB		
Temperature	±0.5℃		
Humidity	±3%		


Measurement Uncertainty for a level of Confidence of 95%



7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth 4.0 DTS component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

(a)Radiated Emission Test Set-Up, Frequency Below 30MHz






(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz






7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.


Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.





7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand Model/Type No.		Series No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Notes:

- All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.



8 TEST REQUIREMENTS

8.1 DTS (6DB) BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.2 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.3 Test Procedure

The EUT was operating in Bluetooth 4.0DTS mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test re+port.

Test Results

Temperature :	24 ℃	Test Date :	January 7, 2015
Humidity:	53 %	Test By:	King Kong

		Channel	Measurement Bandwidth	Limit	Verdict
		Frequency (MHz) (kHz)		(kHz)	verdict
	0	2402	674.00	>500	PASS
GFSK	19	2440	676.50	>500	PASS
	39	2480	685.50	>500	PASS



Test Model DTS (6dB) Bandwidth
GFSK
Channel 9: 2402MUs

Channel 0: 2402MHz



DTS (6dB) Bandwidth

Test Model GFSK Channel 19: 2440MHz





DTS (6dB) Bandwidth
Test Model GFSK

Channel 39: 2480MHz





8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r04

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part15.247(b)(3)

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. For smart system, Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Set the RBW ≧DTS bandwidth(about 1MHz). Set VBW =3*RBW(about 3MHz)

Set the span ≥3*RBW

Set Sweep time = auto couple.

Set Detector = peak. Set Trace mode = max hold.

Allow trace to fully stabilize. Use peak marker function to determine the peak amplitude level.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Results

Temperature:	24 ℃	Test Date:	January 7, 2015
Humidity:	53 %	Test By:	King Kong

Operation Channel C Mode Number		Channel Frequency	Measurement Level	Limit	Verdict
		(MHz)	(dBm)	(dBm)	verdict
	0	2402	-8.938	30	PASS
GFSK	19	2440	-10.257	30	PASS
	39	2480	-11.361	30	PASS




Maximum Conducted Output Power Test Model GFSK

Channel 0: 2402MHz



Maximum Conducted Output Power
Test Model GFSK





Maximum Conducted Output Power

Test Model GFSK

Channel 39: 2480MHz





8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r04

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple. Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

8.3.5 Test Results

Temperature:	24 ℃	Test Date:	January 7, 2015
Humidity:	53 %	Test By:	King Kong

Operation Mode	Channel Channel Frequency (MHz)		Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
	0	2402	-20.95	8	PASS
GFSK	19	2440	-22.65	8	PASS
	39	2480	-24.37	8	PASS
Note: N/A					



Power Spectral Density
Test Model GFSK

Channel 0: 2402MHz



Power Spectral Density
GFSK

Channel 19: 2440MHz





Power Spectral Density

Test Model GFSK

Channel 39: 2480MHz





8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to = 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW \geq 3 x RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW =300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results



PSD(Power Spectral Density) RBW=100kHz
Test Model GFSK

Channel 0: 2402MHz



Test Model

Unwanted Emissions in non-restricted frequency bands

GFSK

Channel 0: 2402MHz





Test Model Band edge GFSK

Channel 0: 2402MHz





Test Model

PSD(Power Spectral Density) RBW=100kHz

GFSK

Channel 19: 2440MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands

GFSK

Channel 19: 2440MHz





Test Model

PSD(Power Spectral Density) RBW=100kHz

GFSK

Channel 19: 2480MHz



Test Model

Unwanted Emissions In Non-Restricted Frequency Bands

GFSK

Channel 39: 2480MHz





Test Model

Band edge GFSK

Channel 39: 2480MHz





8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 DTS 01 Meas. Guidance v03r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

7 toodraing to 1 00 1 dit 10:200; 1 toothotoa bahao							
MHz	MHz	MHz	GHz				
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15				
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46				
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75				
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5				
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2				
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5				
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7				
6.26775-6.26825	123-138	2200-2300	14.47-14.5				
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2				
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4				
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12				
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0				
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8				
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5				
12.57675-12.57725 322-335.4		3600-4400	(2)				
13.36-13.41							

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

	Restricted Frequency(MHz)	Field Strength (µV/m)	Field Strength (dBµV/m)	Measurement Distance	
	. , ,	• \i ,	U \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Measurement Distance	
	0.009-0.490	2400/F(KHz)	20 log (uV/m)	300	
	0.490-1.705	2400/F(KHz)	20 log (uV/m)	30	
	1.705-30	30	29.5	30	
	30-88	100	40	3	
	88-216	150	43.5	3	
	216-960	200	46	3	
Above 960		500	54	3	

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.

for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz])., the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.



8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

 $VBW \ge RBW$

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

 $VBW \geq RBW$

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from 20log(dwell time/100 ms), in an effort to demonstrate

Repeat above procedures until all frequency measured was complete.

compliance with the 15.209 limit. Submit this data.



8.5.5 Test Results

Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature: **24**℃ Test Date: January 8, 2015 Humidity: 53 % Test By: King Kong Test mode: TX Mode

Freq.	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK `	ÁV	PK	AV	PK	AV

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Temperature: 24℃ Test Date: January 8, 2015

Humidity: 53 % Test By: King Kong

Test mode: GFSK Frequency: Channel 0: 2402MHz

Freq.	Ant.Pol.	Emission Lev	/el(dBuV/m)	Limit 3m	(dBuV/m)	Ove	er(dB)
(MHz)	H/V	PK	ÀV	PK	AV	PK	` ´AV
5318.00	V	44.45	30.10	74.00	54.00	-29.55	-23.90
7477.00	V	47.11	32.60	74.00	54.00	-26.89	-21.40
10707.0	V	49.90	34.30	74.00	54.00	-24.10	-19.70
				-		-	-
8259.00	Н	46.92	31.60	74.00	54.00	-27.08	-22.40
10435.0	Н	49.65	34.70	74.00	54.00	-24.35	-19.30
12662.0	Н	50.94	35.80	74.00	54.00	-23.06	-18.20

Temperature: 24℃ Test Date: January 8, 2015

Humidity: 53 % Test By: King Kong

Test mode: GFSK Frequency: Channel 19: 2440MHz

Freq.	Ant.Pol.	Emission Lev	vel(dBuV/m)	Limit 3m	(dBuV/m)	Ove	er(dB)
(MHz)	H/V	PK	AV	PK	AV	PK	AV
9126.00	V	48.27	33.60	74.00	54.00	-25.73	-20.40
10707.0	V	49.90	34.10	74.00	54.00	-24.10	-19.90
13699.0	V	52.60	37.80	74.00	54.00	-21.40	-16.20
	-			1		1	-
	-			-		-	-
				-		-	
8463.00	Н	48.38	33.10	74.00	54.00	-25.62	-20.90
11030.0	Н	51.11	36.50	74.00	54.00	-22.89	-17.50
12220.0	Н	51.84	36.70	74.00	54.00	-22.16	-17.30

Temperature: 24℃ Test Date: January 8, 2015

Humidity: 53 % Test By: King Kong

Test mode: GFSK Frequency: Channel 39: 2480MHz

Freq.	Ant.Pol.	Emission Lev	vel(dBuV/m)	Limit 3m((dBuV/m)	Ove	er(dB)
(MHz)	H/V	PK	AV	PK	AV	PK	AV
7477.00	V	48.11	31.50	74.00	54.00	-25.89	-22.50
9619.00	V	49.71	34.20	74.00	54.00	-24.29	-19.80
10707.0	V	50.90	35.90	74.00	54.00	-23.10	-18.10
	-			-			
				-			
7698.00	Н	47.19	32.10	74.00	54.00	-26.81	-21.90
9024.00	Н	48.77	33.40	74.00	54.00	-25.23	-20.60
11030.0	Н	50.61	35.60	74.00	54.00	-23.39	-18.40

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Temperature: 24℃ Test Date: January 8, 2015

Humidity: 53 % Test By: King Kong

Test mode: GFSK Frequency: Channel 0: 2402MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2387.360	Н	47.96	74.00	32.60	54.00
2388.800	V	47.41	74.00	33.10	54.00

Temperature: 24℃ Test Date: January 8, 2015

Humidity: 53 % Test By: King Kong

Test mode: GFSK Frequency: Channel 39: 2480MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.582	Н	44.84	74.00	28.60	54.00
2483.797	V	47.36	74.00	32.10	54.00

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

All the modulation modes were tested, the data of the worst mode are described in the following table




Spurious Emission in Restricted Band 2310-2390MHz

GFSK
Channel 0: 2402MHz

H

Test By: King Kong




Test Model

Spurious Emission in Restricted Band 2310-2390MHz

GFSK
Channel 0: 2402MHz

V
Test By: King Kong






Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz

GFSK
Channel 39: 2480MHz

H
Test By: King Kong



Test Model


Spurious Emission in Restricted Band 2483.5-2500MHz

GFSK

Channel 39: 2480MHz

V


Test By: King Kong





53 %

Spurious Emission below 1GHz (30MHz to 1GHz)



Limit: (RE)FCC PART 15C

Mode:BLE 2402


Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		50.3700	37.64	-14.55	23.09	40.00	-16.91	QP			
2		76.5600	41.98	-19.33	22.65	40.00	-17.35	QP			
3		103.7200	41.20	-15.30	25.90	43.50	-17.60	QP			
4		129.9100	37.40	-18.46	18.94	43.50	-24.56	QP			
5		235.6400	42.41	-14.06	28.35	46.00	-17.65	QP			
6	*	314.2100	42.84	-11.42	31.42	46.00	-14.58	QP			

*:Maximum data x:Over limit !:over margin Operator: CSL



53 %



Site 3m Chamber #3

Limit: (RE)FCC PART 15C Mode:BLE 2402

Note:

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		103.7200	40.01	-15.30	24.71	43.50	-18.79	QP			
2		184.2300	37.71	-17.01	20.70	43.50	-22.80	QP			
3		223.0300	39.61	-14.41	25.20	46.00	-20.80	QP			
4		248.2500	43.61	-13.55	30.06	46.00	-15.94	QP			
5	*	293.8400	46.58	-11.87	34.71	46.00	-11.29	QP			
6		361.7400	33.70	-10.59	23.11	46.00	-22.89	QP			

Power: AC 120V/60Hz

*:Maximum data x:Over limit !:over margin Operator: CSL



53 %

Raulateu Ellission Weasulement



Limit: (RE)FCC PART 15C

Mode:BLE 2440

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		50.3700	36.64	-14.55	22.09	40.00	-17.91	QP			
2		76.5600	41.98	-19.33	22.65	40.00	-17.35	QP			
3	1	103.7200	44.70	-15.30	29.40	43.50	-14.10	QP			
4	1	129.9100	38.40	-18.46	19.94	43.50	-23.56	QP			
5	2	235.6400	46.91	-14.06	32.85	46.00	-13.15	QP			
6	* (314.2100	44.84	-11.42	33.42	46.00	-12.58	QP			

Power: AC 120V/60Hz

^{*:}Maximum data x:Over limit !:over margin Operator: CSL



53 %



Power: AC 120V/60Hz

Limit: (RE)FCC PART 15C


Mode:BLE 2440

Note:

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		103.7200	37.51	-15.30	22.21	43.50	-21.29	QP			
2		138.6400	37.49	-19.01	18.48	43.50	-25.02	QP			
3		184.2300	40.71	-17.01	23.70	43.50	-19.80	QP			
4		222.0600	40.49	-14.44	26.05	46.00	-19.95	QP			
5		256.0100	44.77	-13.18	31.59	46.00	-14.41	QP			
6	*	293.8400	47.58	-11.87	35.71	46.00	-10.29	QP			

^{*:}Maximum data x:Over limit !:over margin Operator: CSL





Mode:BLE 2480


Note:

Reading Correct Measure-Antenna Table No. Mk. Freq. Limit Over Level Factor ment Height Degree MHz dBuV dB dBuV/m dBuV/m dB Detector cm degree Comment 50.3700 37.14 -14.55 22.59 40.00 -17.41 QP 1 2 76.5600 41.98 -19.33 22.65 40.00 -17.35 QP 3 103.7200 44.70 -15.30 29.40 43.50 -14.10 QP 235.6400 44.41 -14.06 30.35 46.00 -15.65 QP 4 42.32 46.00 -15.22 5 304.5100 -11.54 30.78 QP 6 320.0300 43.34 -11.34 32.00 46.00 -14.00 QP

^{*:}Maximum data x:Over limit !:over margin Operator: CSL



53 %



Limit: (RE)FCC PART 15C

Mode: BLE 2480

Note:

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		103.7200	39.01	-15.30	23.71	43.50	-19.79	QP			
2		138.6400	36.49	-19.01	17.48	43.50	-26.02	QP			
3		231.7600	40.62	-14.17	26.45	46.00	-19.55	QP			
4		256.0100	43.77	-13.18	30.59	46.00	-15.41	QP			
5	*	299.6600	46.54	-11.61	34.93	46.00	-11.07	QP			
6		317.1200	44.08	-11.38	32.70	46.00	-13.30	QP			

Power: AC 120V/60Hz

^{*:}Maximum data x:Over limit !:over margin Operator: CSL



8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Conducted Emission Limit							
Frequency(MHz)	Quasi-peak	Average					
0.15-0.5	66-56	56-46					
0.5-5.0	56	46					
5.0-30.0	60	50					

Note: 1. The lower limit shall apply at the transition frequencies

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.


8.6.5 Test Results

Pass

We test the EUT at both 120V & 240V, and show the worst result as bellow.

^{2.} The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.





Power: AC 120V/60Hz

Limit: (CE)FCC PART 15 class B_QP


Mode: ON Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBu∨	dB	dBu∨	dBu∨	dB	Detector	Comment
1		0.1500	56.60	0.00	56.60	66.00	-9.40	QP	
2		0.1500	36.86	0.00	36.86	56.00	-19.14	AVG	
3	*	0.1750	56.36	0.00	56.36	64.72	-8.36	QP	
4		0.1750	36.17	0.00	36.17	54.72	-18.55	AVG	
5		0.6050	40.55	0.00	40.55	56.00	-15.45	QP	
6		0.6050	23.23	0.00	23.23	46.00	-22.77	AVG	
7		1.1850	37.94	0.00	37.94	56.00	-18.06	QP	
8		1.1850	19.64	0.00	19.64	46.00	-26.36	AVG	
9		1.4400	34.20	0.00	34.20	56.00	-21.80	QP	
10		1.4400	12.56	0.00	12.56	46.00	-33.44	AVG	
11		1.7800	34.56	0.00	34.56	56.00	-21.44	QP	
12		1.7800	16.12	0.00	16.12	46.00	-29.88	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



50 %



Power: AC 120V/60Hz

Limit: (CE)FCC PART 15 class B QP

Mode: ON Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBu∨	dB	dBu∨	dBu∀	dB	Detector	Comment
1	*	0.1500	56.20	0.00	56.20	66.00	-9.80	QP	
2		0.1500	39.85	0.00	39.85	56.00	-16.15	AVG	
3		0.3500	43.03	0.00	43.03	58.96	-15.93	QP	
4		0.3500	23.75	0.00	23.75	48.96	-25.21	AVG	
5		0.5650	45.83	0.00	45.83	56.00	-10.17	QP	
6		0.5650	31.13	0.00	31.13	46.00	-14.87	AVG	
7		1.0600	43.95	0.00	43.95	56.00	-12.05	QP	
8		1.0600	25.15	0.00	25.15	46.00	-20.85	AVG	
9		1.1200	44.80	0.00	44.80	56.00	-11.20	QP	
10		1.1200	27.73	0.00	27.73	46.00	-18.27	AVG	
11		1.5650	42.68	0.00	42.68	56.00	-13.32	QP	
12		1.5650	24.19	0.00	24.19	46.00	-21.81	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 **Result**

PASS.

The EU Note:	\boxtimes	1 antenna: a PCB Antenna for BT4.0 with BLE model, the gain is 0 dBi; Antenna use a permanently attached antenna which is not replaceable. Not using a standard antenna jack or electrical connector for antenna replacement The antenna has to be professionally installed (please provide method of installation)
	which	in accordance to section 15.203, please refer to the internal photos.