

FCC Part 1 Subpart I FCC Part 2 Subpart J ISED RSS-102 ISSUE 5

### RF EXPOSURE REPORT

FOR

**WIRELESS INTEGRATED MODULE** 

MODEL NAME: WIM-CMB-OEM

FCC ID: 2ACQ6-WMB IC: 11481A-WMB

REPORT NUMBER: R12663786-E7

**ISSUE DATE: 2019-09-19** 

Prepared for IDEAL INDUSTRIES LIGHTING LLC, DBA CREE LIGHTING 4401 SILICON DRIVE DURHAM, NC 27703, USA

Prepared by
UL LLC
12 LABORATORY DR.
RESEARCH TRIANGLE PARK, NC 27709 USA
TEL: (919) 549-1400



# **Revision History**

Ver.	Issue Date	Revisions	Revised By
1	2019-06-29	Initial Issue	Brian T. Kiewra
2	2019-07-17	Updated applicant name and FCC/IC IDs	Niklas Haydon
3	2019-09-19	Updated BLE power	Niklas Haydon

DATE: 2019-09-19

# **TABLE OF CONTENTS**

1.	ATT	FESTATION OF TEST RESULTS	4
2.	TES	ST METHODOLOGY	5
3.	REF	FERENCES	5
4.	FAC	CILITIES AND ACCREDITATION	5
5.	DE\	VICE UNDER TEST	5
6	et/	ANDALONE SAR TEST EXCLUSION CONSIDERATIONS	6
6	<i>5.1.</i>	FCC	6
6	5.2.	ISED CANADA	7
EN	ID OF	TEST REPORT	7

DATE: 2019-09-19

REPORT NO: R12663786-E7 DATE: 2019-09-19 FCC ID: 2ACQ6-WMB IC: 11481A-WMB

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** Ideal Industries Lighting LLC, DBA CREE Lighting

4401 Silicon Drive

Durham, NC 27703, USA

**EUT DESCRIPTION:** 802.15.4/BLE radio module

MODEL: WIM-CMB-OEM

#### **APPLICABLE STANDARDS**

**STANDARD** 

**TEST RESULTS** 

FCC PART 1 SUBPART I & PART 2 SUBPART J

Compliant

ISED CANADA RSS-102 ISSUE 5

Compliant

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. government.

Approved & Released

For UL LLC By:

Prepared By:

Jeffrey Moser Operations Leader

UL – Consumer Technology Division

Brian T. Kiewra Project Engineer

UL – Consumer Technology Division

FORM NO: 03-EM-F00858

REPORT NO: R12663786-E7 FCC ID: 2ACQ6-WMB

# 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 2.1091, 2.1093 and KDB 447498 D01 v06 and IC Safety Code 6, RSS 102 Issue 5.

### 3. REFERENCES

All measurements were made as documented in test report UL LLC Document R12663786-E5 and R12663786-E6 for operation in the 2.4 GHz band.

Duty cycle and Antenna gain data is excerpted from the applicable test reports.

Output power as declared by manufacturer, including tolerance.

#### 4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 12 Laboratory Dr., Research Triangle Park, NC 27709, USA and 2800 Perimeter Park Dr., Suite B, Morrisville, NC 27560, USA.

UL LLC (RTP) is accredited by NVLAP, Laboratory Code 200246-0.

#### 5. DEVICE UNDER TEST

The EUT is a 802.15.4 and BLE radio module.

TEL: (919) 549-1400

FORM NO: 03-EM-F00858

DATE: 2019-09-19

REPORT NO: R12663786-E7 DATE: 2019-09-19 FCC ID: 2ACQ6-WMB IC: 11481A-WMB

# 6. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

### 6.1. FCC

SAR test exclusion in accordance with KDB 447498.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]·[ $\sqrt{f(GHz)}$ ]  $\leq$  3.0, for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

This test exclusion is applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances > 50 mm are determined by:

- {[Power allowed at numeric threshold for 50 mm)] + [(test separation distance 50 mm)·(f(MHz)/150)]} mW, for 100 MHz to 1500 MHz
  - $\bullet \quad \ \ f_{(MHz)} \ is \ the \ RF \ channel \ transmit \ frequency \ in \ MHz$
- {[Power allowed at numeric threshold for 50 mm)] + [(test separation distance 50 mm)·10]} mW, for > 1500 MHz and ≤ 6 GHz

#### SAR Exclusion Calculation Table for Portable Devices (separation distance ≤ 50mm)

Tx	Frequency	Avg Output power		Separation	Calculated
1.X	(MHz)	dBm	mW	distances (mm)	Threshold
802.15.4	2480	6.00	3.98	50	0.125
BLE	2480	6.00	3.98	50	0.125
Total	2480	9.01	7.96	50	0.251

#### **Conclusion:**

The computed values are < 3; therefore, the device qualifies for Standalone SAR test exclusion.

### 6.2. ISED CANADA

The SAR exclusion table from RSS-102 issue 5 is reproduced below:

Table 1: SAR evaluation - exemption limits for routine evaluation based on frequency and separation distance.

and separation distance.						
	Exemption Limits (mW)					
Frequency MHz	At separation distance of ≤5mm	At separation distance of 10mm	At separation distance of 15mm	At separation distance of 20mm	At separation distance of 25mm	
≤300	71 mW	101 mW	132 mW	162 mW	193 mW	
450	52 mW	70 mW	88 mW	106 mW	123 mW	
835	17 mW	30 mW	42 mW	55 mW	67 mW	
1900	7 mW	10 mW	18 mW	34 mW	60 mW	
2450	4 mW	7 mW	15 mW	30 mW	52 mW	
3500	2 mW	6 mW	16 mW	32 mW	55 mW	
5800	1 mW	6 mW	15 mW	27 mW	41 mW	

	Exemption Limits (mW)					
Frequency MHz	At separation distance of 30mm	At separation distance of 35mm	At separation distance of 40mm	At separation distance of 45mm	At separation distance of ≥50mm	
≤300	223 mW	254 mW	284 mW	315 mW	345 mW	
450	141 mW	159 mW	177 mW	195 mW	213 mW	
835	80 mW	92 mW	105 mW	117 mW	130 mW	
1900	99 mW	153 mW	225 mW	316 mW	431 mW	
2450	83 mW	123 mW	173 mW	235 mW	309 mW	
3500	86 mW	124 mW	170 mW	225 mW	290 mW	
5800	56 mW	71 mW	85 mW	97 mW	106 mW	

The minimum antenna to user distance that will be encountered in normal use is 50mm. This results in an exemption limit of 309mW at 2450 MHz.

Tx	Frequency (MHz)	Maximum Ava Dowar	Antenna Gain	0.5 dBi
IX		Maximum Avg Power	(dBm)	(mW)
802.15.4	2480	Conducted	6.0	3.98
002.13.4		E.I.R.P	6.5	4.47
BLE	2480	Conducted	6.0	3.98
DLE		E.I.R.P	6.5	4.47
		Total	Conducted	7.96
		Total	E.I.R.P.	8.93

As the total maximum output power is 7.96mW conducted and 8.93mW EIRP the DUT qualifies for SAR test exclusion.

## **END OF TEST REPORT**

DATE: 2019-09-19