

**Shortcut Labs AB
Drottning Kristinas Vag 41 Stockholm Sweden 11428**

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: Flic Hub LR
Model No: Hub LR

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the
Product : Flic Hub LR
will be integrated in the user's manual to provide end-users with transmitter operating
conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21906-19172-C-1,
W6M21906-19172-C-7and the accompanying calculations.

Company: Shortcut Labs AB
Address: Drottning Kristinas Vag 41 Stockholm Sweden 11428

Date: 2019-10-21


Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21906-19172-C-1

FCC ID: 2ACR9-HUBLR

3.2 Equivalent isotropic radiated power

FCC Rule: 15.247(b)(3)

WLAN

EIRP = max. conducted output power + antenna gain

EIRP = 16.34 dBm + (4.6 dBi) = 20.94 dBm = 124.1652 mW

BLE

EIRP = max. conducted output power + antenna gain

EIRP = 3.99 dBm + (3.4 dBi) = 7.39 dBm = 5.4828 mW

Test equipment used: ETSTW-RE 055

3.3 Exemption Limits for Routine Evaluation according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21906-19172-C-1

FCC ID: 2ACR9-HUBLR

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd \cdot \frac{30 \times P \times G}{377 \times d^2} \text{ mW/cm}^2.$$

WLAN

Established separation distance is 20 cm.

Operating frequency band: 802.11b, g, n 20MHz: 2412-2462 MHz, 802.11n 40MHz: 2422-2452 MHz,

The product meets RF exposure requirement.

Because the power density of 0.0247 mW/cm² at 2412 MHz is below the power density limit of 1 mW/cm².

BLE

Established separation distance is 20 cm.


Operating frequency band: 2402-2480 MHz

The product meets RF exposure requirement.

Because the power density of 0.0011 mW/cm² at 2402 MHz is below the power density limit of 1 mW/cm².

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm ²)
1500 – 100.000	1.0



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21906-19172-C-7

FCC ID: 2ACR9-HUBLR

3.6 Automatic Discontinuation of transmission, FCC 15.407 (c)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure.

This function will be declared by manufacturer.

3.7 Reserved, FCC 15.407 (d)

3.8 Indoor Operation Restriction, FCC 15.407 (e)

Within the 5.15–5.25 GHz band, U- NII devices will be restricted to indoor operations to reduce any potential for harmful interference to co-channel MSS operations. This equipment has to be declared by manufacturer of the final product as content of the user manual.

3.9 Equivalent isotropic radiated power, FCC 15.407 (f)

FCC Rule: 15.407(b)(3)

EIRP= max. conducted output power + antenna gain

EIRP=Band 1=Test exclusion=8.36 dBm+(1.5 dBi)=9.86 dBm=9.68 mW

EIRP=Band 2=Test exclusion=9.03 dBm+(1.9 dBi)=10.93 dBm=12.39 mW

EIRP=Band 3=Test exclusion=9.58 dBm+(2.1 dBi)=11.68 dBm=14.72 mW

EIRP=Band 4=Test exclusion=8.87 dBm +(2.2 dBi)=11.07 dBm=12.79 mW

Test equipment used: ETSTW-RE 055

3.10 Exemption Limits for Routine Evaluation according to

47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21906-19172-C-7

FCC ID: 2ACR9-HUBLR

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

*Plane-wave equivalent power density

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d \cdot \frac{30 \times P \times G}{377 \times d^2} \text{ mW/cm}^2$$

Band 1

Established separation distance is 20 cm.

Operating frequency band: 5.15-5.25 MHz

The product meets RF exposure requirement.

Because the power density of 0.0019 mW/cm² at 5190 MHz is below the power density limit of 1mW/cm².

Band 2

Established separation distance is 20 cm.

Operating frequency band: 5.25-5.35 MHz

The product meets RF exposure requirement.

Because the power density of 0.0025 mW/cm² at 5190 MHz is below the power density limit of 1mW/cm².

Band 3

Established separation distance is 20 cm.

Operating frequency band: 5.47-5.725 MHz

The product meets RF exposure requirement.

Because the power density of 0.0028 mW/cm² at 5190 MHz is below the power density limit of 1mW/cm².

Band 4

Established separation distance is 20 cm.

Operating frequency band: 5.725-5.85 MHz

The product meets RF exposure requirement.

Because the power density of 0.0025 mW/cm² at 5745 MHz is below the power density limit of 1 mW/cm².

Limits:

Limit for General Population / Uncontrolled Exposure

Frequency(MHz)	Power Density(mW/cm ²)
1500 – 100.000	1.0