

TEST REPORT

Reference No...... : WTX21X12150432W
FCC ID : 2ACRJZS-300L
Applicant : ZillionSource Technologies (Shanghai) Co., Ltd.
Address..... : Room 2207a, No. 28, Maji Road, Shanghai Free Trade Zone, Shanghai, China
Product Name : Environmental variable collector for logistics
Model No...... : ZS-300L
FCC Part 2.1093
Standards : IEEE Std C95.1: 2019
IEEE Std C95.3: 2002 + Rev. 2008
IEEE 62209-1528: 2020
Date of Receipt sample ... : Dec. 29, 2021
Date of Test..... : Dec. 29, 2021 to Feb. 28, 2022
Date of Issue : Feb. 28, 2022
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,

Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Jack Sun

Jack Sun / Project Engineer

Reviewed By:

Jason Su

Jason Su / RF Manager

Approved & Authorized By:

Silin Chen

Silin Chen / Manager

TABLE OF CONTENTS

1. General Information	4
1.1 Product Description for Equipment Under Test (EUT)	4
1.2 Test Standards	6
1.3 Test Methodology	6
1.4 Test Facility	6
2. Summary of Test Results	7
3. Specific Absorption Rate (SAR)	8
3.1 Introduction	8
3.2 SAR Definition	8
4. SAR Measurement System	9
4.1 The Measurement System	9
4.2 Probe	9
4.3 Probe Calibration Process	11
4.4 Phantom	12
4.5 Device Holder	12
4.6 Test Equipment List	13
5. Tissue Simulating Liquids	14
5.1 Composition of Tissue Simulating Liquid	14
5.2 Tissue Dielectric Parameters for Head and Body Phantoms	15
5.3 Tissue Calibration Result	16
6. SAR Measurement Evaluation	17
6.1 Purpose of System Performance Check	17
6.2 System Setup	17
6.3 Validation Results	19
7. EUT Testing Position	20
7.1 Body Position	20
7.2 EUT Antenna Position	20
7.3 EUT Testing Position	21
8. SAR Measurement Procedures	22
8.1 Measurement Procedures	22
8.2 Spatial Peak SAR Evaluation	22
8.3 Area & Zoom Scan Procedures	23
8.4 Volume Scan Procedures	23
8.5 SAR Averaged Methods	23
8.6 Power Drift Monitoring	23
9. SAR Test Result	24
9.1 Conducted RF Output Power	24
9.2 Test Results for Standalone SAR Test	35
10. Measurement Uncertainty	37
10.1 Uncertainty for SAR Test	37
Annex A. Plots of System Performance Check	39
Annex B. Plots of SAR Measurement	47
Annex C. EUT Photos	55
Annex D. Test Setup Photos	59
Annex E. Calibration Certificate	62

Report version

Version No.	Date of issue	Description
Rev.00	Feb. 28, 2022	Original
/	/	/

1. General Information

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: ZillionSource Technologies (Shanghai) Co., Ltd.
Address of applicant: Room 2207a, No. 28, Maji Road, Shanghai Free Trade Zone, Shanghai, China

Manufacturer: ZillionSource Technologies (Shanghai) Co., Ltd.
Address of manufacturer: Room 2207a, No. 28, Maji Road, Shanghai Free Trade Zone, Shanghai, China

General Description of EUT:	
Product Name:	Environmental variable collector for logistics
Brand Name:	ZillionTrace
Model No.:	ZS-300L
Adding Model(s):	ZS-300 S, ZS-300 X, ZS-300 E, ZS-300 C, ZS-300, ZS-300 W
Rated Voltage:	DC3.7V
Battery:	3000mAh
Software Version:	V1.7.2.2a4
Hardware Version:	V1.1.2
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model ZS-300L, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT:	
2G	
Support Networks:	GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GPRS/EDGE 850: 824~849MHz GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GPRS/EDGE 850: 869~894MHz GPRS/EDGE 1900: 1930~1990MHz
RF Output Power:	GPRS 850: 33.01dBm, GPRS 1900: 29.38dBm EDGE850: 27.22dBm, EDGE1900: 24.22dBm
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: 3dBi; PCS1900: 3dBi
GPRS/EDGE Class:	Class 12
4G	
Support Networks:	FDD-LTE
Support Band:	FDD-LTE Band 5, 7
Uplink Frequency:	FDD-LTE Band 5: Tx: 824-849MHz, FDD-LTE Band 7: Tx: 2500-2570MHz,
Downlink Frequency:	FDD-LTE Band 5: Rx: 869-894MHz, FDD-LTE Band 7: Rx: 2620-2690MHz,
RF Output Power:	FDD-LTE Band 5: 24.81dBm, FDD-LTE Band 7: 24.35dBm
Type of Modulation:	QPSK, 16QAM
Antenna Type:	Integral Antenna
Antenna Gain:	FDD-LTE Band 5: 3dBi, FDD-LTE Band 7: 3dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The following report is accordance with FCC 47 CFR Part 2.1093, IEEE Std C95.1: 2019, IEEE Std C95.3: 2002 + Rev. 2008, IEEE 62209-1528: 2020, KDB 447498 D01 v06, KDB 648474 D04 v01r03, KDB 248227 D01 v02r02, KDB 941225 D01 v03r01, KDB 941225 D05 v02r05 , and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02.

The objective is to determine compliance with FCC Part 2.1093 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02. The public notice KDB 447498 D01 v06 for Mobile and Portable Devices RF Exposure Procedure also.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010.Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

2. Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Body SAR (0mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	
GSM	0.691	1.6
LTE	0.791	1.6

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and IEEE Std C95.1: 2019 and had been tested in accordance with the measurement methods and procedure specified in IEEE 62209-1528: 2020 and KDB 865664 D01 v01r04 and KDB 865664 D02 v01r02

3. Specific Absorption Rate (SAR)

3.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

3.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$\text{SAR} = C \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

4. SAR Measurement System

4.1 The Measurement System

Comosar is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The Comosar system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 10g mass.

4.2 Probe


For the measurements the Specific Dosimetric E-Field Probe SSE2 SN 45/15 EPGO280 with following specifications is used

- Dynamic range: 0.01-100 W/kg
- Probe Length: 330 mm
- Length of Individual Dipoles: 4.5 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter : 5 mm

Waltek Testing Group (Shenzhen) Co., Ltd.
[Http://www.waltek.com.cn](http://www.waltek.com.cn)

- Distance between dipoles / probe extremity: 2.7mm
 - Probe linearity: <0.25 dB
 - Axial Isotropy: <0.25 dB
 - Spherical Isotropy: <0.50 dB
 - Calibration range: 700 to 3000MHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°

Probe calibration is realized, in compliance with EN 62209-1 and IEEE 1528 STD, with CALISAR, Antennessa proprietary calibration system. The calibration is performed with the EN 62209-1 annexe technique using reference guide at the five frequencies.



$$SAR = \frac{4(P_{fw} - P_{bw})}{ab\delta} \cos^2\left(\pi \frac{y}{a}\right) e^{-(2z/\delta)}$$

Where :

P_{fw} = Forward Power

P_{bw} = Backward Power

a and b = Waveguide dimensions

δ = Skin depth

Keithley configuration:

Rate = Medium; Filter = ON; RDGS = 10; Filter type = Moving Average; Range auto after each calibration, a SAR measurement is performed on a validation dipole and compared with a NPL calibrated probe, to verify it.

Waltek Testing Group (Shenzhen) Co., Ltd.

[Http://www.waltek.com.cn](http://www.waltek.com.cn)

The calibration factors, CF(N), for the 3 sensors corresponding to dipole 1, dipole 2 and dipole 3 are:

$$CF(N)=SAR(N)/V_{lin}(N) \quad (N=1,2,3)$$

The linearised output voltage $V_{lin}(N)$ is obtained from the displayed output voltage $V(N)$ using

$$V_{lin}(N)=V(N)*(1+V(N)/DCP(N)) \quad (N=1,2,3)$$

where DCP is the diode compression point in mV.

4.3 Probe Calibration Process

Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. SATIMO Probe calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an with CALISAR, Antenna proprietary calibration system.

Free Space Assessment Procedure

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1mW/cm².

Temperature Assessment Procedure

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

Where:

$$SAR = C \frac{\Delta T}{\Delta t}$$

Δt = exposure time (30 seconds),

C = heat capacity of tissue (brain or muscle),

ΔT = temperature increase due to RF exposure.

SAR is proportional to $\Delta T / \Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

σ = simulated tissue conductivity,


ρ = Tissue density (1.25 g/cm³ for brain tissue)

4.4 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.

4.5 Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 °.



System Material	Permittivity	Loss Tangent
Delrin	3.7	0.005


4.6 Test Equipment List

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
E-Field Probe	MVG	SSE2	SN 18/21 EPG0356	2021-07-16	2022-07-15
750MHz Dipole	MVG	SID750	SN 47/12 DIP 0G750-203	2020-03-11	2023-03-10
835MHz Dipole	MVG	SID835	SN 47/12 DIP 0G835-204	2020-03-11	2023-03-10
900MHz Dipole	MVG	SID900	SN 47/12 DIP 0G900-205	2020-03-11	2023-03-10
1800MHz Dipole	MVG	SID1800	SN 47/12 DIP 1G800-206	2020-03-11	2023-03-10
1900MHz Dipole	MVG	SID1900	SN 47/12 DIP 1G900-207	2020-03-11	2023-03-10
2000MHz Dipole	MVG	SID2000	SN 47/12 DIP 2G000-208	2020-03-11	2023-03-10
2300 MHz Dipole	MVG	SID2300	SN 50/20 DIP 2G300-513	2021-01-14	2024-01-13
2450MHz Dipole	MVG	SID2450	SN 13/15 DIP 2G450-364	2020-03-11	2023-03-10
2600MHz Dipole	MVG	SID2600	SN 28/21 DIP 2G600-590	2021-07-16	2024-07-15
3300MHz Dipole	MVG	SID3300	SN 28/21 DIP 3G300-591	2021-07-19	2024-07-18
3500MHz Dipole	MVG	SID3500	SN 28/21 DIP 3G500-592	2021-07-19	2024-07-18
3700MHz Dipole	MVG	SID3700	SN 28/21 DIP 3G700-593	2021-07-19	2024-07-18
3900MHz Dipole	MVG	SID3900	SN 28/21 DIP 3G900-594	2021-07-19	2024-07-18
4200MHz Dipole	MVG	SID4200	SN 28/21 DIP 4G200-595	2021-07-19	2024-07-18
4600MHz Dipole	MVG	SID4600	SN 28/21 DIP 4G600-596	2021-07-19	2024-07-18
4900MHz Dipole	MVG	SID4900	SN 28/21 DIP 4G900-597	2021-07-19	2024-07-18
5 GHz Dipole	MVG	SWG5500	SN 49/16 WGA45	2020-07-03	2023-07-02
Dielectric Probe	SATIMO	SCLMP	SN 47/12 OCPG49	2021-03-27	2022-03-26
SAM Phantom	SATIMO	SAM	SN/ 47/12 SAM95	N/A	N/A
Multi Meter	Keithley	Keithley 2000	4006367	2021-03-27	2022-03-26
Power meter	Keithley	3500	JC-2017-09-001	2021-03-27	2022-03-26
Power meter	Keithley	3500	JC-2017-09-001	2021-03-27	2022-03-26
Power Sensor	HP	11636B	JC-2017-10-002	2021-03-27	2022-03-26
MXG X-Series RF Vector Signal Generato	KEYSIGHT	N5182B	MY57300664	2021-04-14	2022-04-13
Universal Tester	Rohde & Schwarz	CMU200	112315	2021-03-27	2022-03-26
Communications Tester	Rohde & Schwarz	CMW500	148650	2021-03-27	2022-03-26
Network Analyzer	HP	8753C	2901A00831	2021-03-27	2022-03-26
Directional Couplers	Agilent	778D	20160	2021-03-27	2022-03-26

5. Tissue Simulating Liquids

5.1 Composition of Tissue Simulating Liquid

For the measurement of the field distribution inside the SAM phantom with SMTIMO, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. Please see the following photos for the liquid height.



Liquid Height for Head/Body SAR

The Composition of Tissue Simulating Liquid

Frequency (MHz)	Water (%)	Salt (%)	Sugar (%)	HEC (%)	Preventol (%)	DGBE (%)
Head/Body						
750	41.1	1.4	57.0	0.2	0.3	0
835	40.3	1.4	57.9	0.2	0.2	0
1700-1900	55.2	0.3	0	0	0	44.5
2450	55.0	0.1	0	0	0	44.9
2600	54.9	0.1	0	0	0	45.0

5.2 Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Target Frequency (MHz)	Body	
	Conductivity (σ)	Permittivity (ϵ_r)
150	0.80	61.9
300	0.92	58.2
450	0.94	56.7
750	0.96	55.5
835	0.97	55.2
900	1.05	55.0
915	1.06	55.0
1450	1.30	54.0
1610	1.40	53.8
1750	1.49	53.4
1800-2000	1.52	53.3
2450	1.95	52.7
2600	2.16	52.5
3000	2.73	52.0

5.3 Tissue Calibration Result

The dielectric parameters of the liquids were verified prior to the SAR evaluation using COMOSAR Dielectric Probe Kit and an Agilent Network Analyzer.

Calibration Result for Dielectric Parameters of Tissue Simulating Liquid

Body Tissue Simulating Liquid									
Freq. MHz.	Temp. (°C)	Conductivity			Permittivity			Limit (%)	Date
		Reading (σ)	Target (σ)	Delta (%)	Reading (ϵ_r)	Target (ϵ_r)	Delta (%)		
835	22.2	0.95	0.97	-2.06	54.85	55.2	-0.63	± 5	2022-02-28
1800	22.2	1.51	1.52	-0.66	54.72	53.3	2.66	± 5	2022-02-28
1900	22.2	1.50	1.52	-1.32	52.42	53.30	-1.65	± 5	2022-02-28
2600	22.2	2.12	2.16	-1.85	52.24	52.50	-0.50	± 5	2022-02-28


6. SAR Measurement Evaluation

6.1 Purpose of System Performance Check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

6.2 System Setup

In the simplified setup for system evaluation, the EUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave which comes from a signal generator at frequency 835MHz ,1800MHz, 1900MHz 2450MHz,2600MHz,and 5GHz. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom.



System Verification Setup Block Diagram



Setup Photo of Dipole Antenna

The output power on dipole port must be calibrated to 24 dBm(250 mW) before dipole is connected.

The output power on 5 GHz Waveguide must be calibrated to 20 dBm (100mW) before 5 GHz Waveguide is connected.

6.3 Validation Results

Comparing to the original SAR value provided by SATIMO, the validation data should be within its specification of 10 %. Table 6.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion.

Frequency	Targeted SAR _{1g}	Measured SAR _{1g}	Normalized SAR _{1g}	Tolerance	Date
MHz	(W/kg)	(W/kg)	(W/kg)	(%)	
Body					
835	9.36	2.51	10.04	7.26	2022-02-28
1800	38.29	9.46	37.84	-1.18	2022-02-28
1900	39.01	9.91	39.64	1.61	2022-02-28
2600	55.79	13.54	54.16	-2.92	2022-02-28

Remark: Referring to IEEE 62209-1528: 2020, Section 8.2, The system check shall be performed at a test frequency that is within $\pm 10\%$ or ± 100 MHz of the compliance test mid-band frequency, so the 1750 MHz system verification is made of 1800MHz Dipole.

Targeted and Measurement SAR

Please refer to Annex A for the plots of system performance check.

7. EUT Testing Position

7.1 Body Position

- (a) To position the device parallel to the phantom surface with each side.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 0mm.





Illustration for Body Position

7.2 EUT Antenna Position



EUT Sizes: Long 90mm; width:60mm; height:25mm

Block Diagram for EUT Antenna Position

Distance of EUT antenna-to-edge/surface(mm), Test distance:0mm						
Antennas	Back side	Front side	Left Edge	Right Edge	Top Edge	Bottom Edge
WWAN	<25	<25	60	<25	<25	<25

7.3 EUT Testing Position

Body mode SAR assessments are required for this device. This EUT was tested in different positions for different SAR test modes, more information as below:

Body SAR tests, Test distance: 0mm						
Antennas	Front	Back	Right Side	Left Side	Top Side	Bottom Side
WWAN	Yes	Yes	Yes	No	Yes	Yes

Remark:

- Referring to KDB 447498 D01v06, SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
- Referring to KDB 648474 D04 Handset SAR v01r03, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

Please refer to Annex D for the EUT test setup photos.

8. SAR Measurement Procedures

8.1 Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep EUT to radiate maximum output power or 100% factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as Annex D demonstrates.
- (e) Set scan area, grid size and other setting on the SATIMO software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.2 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The SATIMO software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine. The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.3 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

8.4 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.5 SAR Averaged Methods

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimize measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10g and 1 g requires a very fine resolution in the three dimensional scanned data array.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In SATIMO measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

9. SAR Test Result

9.1 Conducted RF Output Power

GSM - Burst Average Power (dBm)								
Band	GSM850			Tune-up power (dBm)	PCS1900			Tune-up power (dBm)
Channel	128	190	251		512	661	810	
Frequency (MHz)	824.2	836.6	848.8		1850.2	1880	1909.8	
GSM	/	/	/	/	/	/	/	/
GPRS (1 slot)	33.01	32.85	32.78	33.5	29.23	28.96	29.38	29.5
GPRS (2 slots)	31.53	31.41	31.29	32.0	26.56	26.00	25.72	27.0
GPRS (3 slots)	29.91	29.96	29.84	30.0	24.89	24.46	24.00	25.0
GPRS (4 slots)	28.44	28.38	28.26	28.5	23.22	23.27	22.88	23.5
EDGE (1 slot)	27.22	27.14	27.07	27.5	24.22	23.57	23.47	24.5
EDGE (2 slots)	26.1	26.02	25.93	26.5	23.15	22.41	22.30	23.5
EDGE (3 slots)	24.52	24.5	24.39	26.0	21.51	20.79	20.70	22.0
EDGE (4 slots)	23.51	23.43	23.25	24.0	20.40	19.62	19.38	20.5

GSM - Source-Based Time-Average Power (dBm)								
Band	GSM850			Tune-up power (dBm)	PCS1900			Tune-up power (dBm)
Channel	128	190	251		512	661	810	
Frequency (MHz)	824.2	836.6	848.8		1850.2	1880	1909.8	
GSM	/	/	/	/	/	/	/	/
GPRS (1 slot)	24.01	23.85	23.78	24.5	20.23	19.96	20.38	20.5
GPRS (2 slots)	25.53	25.41	25.29	26.0	20.56	20.00	19.72	21.0
GPRS (3 slots)	25.66	25.71	25.59	26.0	20.64	20.21	19.75	21.0
GPRS (4 slots)	25.44	25.38	25.26	25.5	20.22	20.27	19.88	20.5
EDGE (1 slot)	18.22	18.14	18.07	18.5	15.22	14.57	14.47	15.5
EDGE (2 slots)	20.10	20.02	19.93	20.5	17.15	16.41	16.30	17.5
EDGE (3 slots)	20.27	20.25	20.14	20.5	17.26	16.54	16.45	17.5
EDGE (4 slots)	20.51	20.43	20.25	21.0	17.40	16.62	16.38	17.5

Note: The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time-average power = Burst averaged power - Duty cycle factor in dB

Duty cycle factor = 9 dB for 1 Tx slot, 6 dB for 2 Tx slots, 4.25 dB for 3 Tx slots, 3 dB for 4 Tx slots

Remark:

1. For Body SAR testing, GPRS should be evaluated; therefore the EUT was set in GPRS (2TX slots) for GSM850 and GPRS (3TX slots) for GSM1900 due to its highest source-based time-average power.
2. Per KDB 447498 D01 v06, the maximum output power channel is used for SAR testing and for further SAR test reduction.

Waltek Testing Group (Shenzhen) Co., Ltd.

[Http://www.waltek.com.cn](http://www.waltek.com.cn)

3. The DUT do not support DTM function.
4. The DUT do not support Hotspot function.

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band5	1.4MHz	QPSK	20407	1RB#0	24.30	PASS
Band5	1.4MHz	QPSK	20407	1RB#2	24.25	PASS
Band5	1.4MHz	QPSK	20407	1RB#5	23.94	PASS
Band5	1.4MHz	QPSK	20407	3RB#0	24.31	PASS
Band5	1.4MHz	QPSK	20407	3RB#1	24.25	PASS
Band5	1.4MHz	QPSK	20407	3RB#3	24.04	PASS
Band5	1.4MHz	QPSK	20407	6RB#0	23.20	PASS
Band5	1.4MHz	QPSK	20525	1RB#0	23.78	PASS
Band5	1.4MHz	QPSK	20525	1RB#2	23.70	PASS
Band5	1.4MHz	QPSK	20525	1RB#5	23.71	PASS
Band5	1.4MHz	QPSK	20525	3RB#0	23.74	PASS
Band5	1.4MHz	QPSK	20525	3RB#1	23.85	PASS
Band5	1.4MHz	QPSK	20525	3RB#3	23.87	PASS
Band5	1.4MHz	QPSK	20525	6RB#0	22.96	PASS
Band5	1.4MHz	QPSK	20643	1RB#0	24.41	PASS
Band5	1.4MHz	QPSK	20643	1RB#2	24.33	PASS
Band5	1.4MHz	QPSK	20643	1RB#5	24.36	PASS
Band5	1.4MHz	QPSK	20643	3RB#0	24.71	PASS
Band5	1.4MHz	QPSK	20643	3RB#1	24.52	PASS
Band5	1.4MHz	QPSK	20643	3RB#3	24.38	PASS
Band5	1.4MHz	QPSK	20643	6RB#0	23.44	PASS
Band5	1.4MHz	16QAM	20407	1RB#0	23.36	PASS
Band5	1.4MHz	16QAM	20407	1RB#2	23.46	PASS
Band5	1.4MHz	16QAM	20407	1RB#5	22.99	PASS
Band5	1.4MHz	16QAM	20407	3RB#0	23.02	PASS
Band5	1.4MHz	16QAM	20407	3RB#1	23.11	PASS
Band5	1.4MHz	16QAM	20407	3RB#3	22.93	PASS
Band5	1.4MHz	16QAM	20407	6RB#0	22.32	PASS
Band5	1.4MHz	16QAM	20525	1RB#0	22.71	PASS
Band5	1.4MHz	16QAM	20525	1RB#2	22.98	PASS
Band5	1.4MHz	16QAM	20525	1RB#5	22.81	PASS

Band5	1.4MHz	16QAM	20525	3RB#0	22.64	PASS
Band5	1.4MHz	16QAM	20525	3RB#1	22.64	PASS
Band5	1.4MHz	16QAM	20525	3RB#3	22.64	PASS
Band5	1.4MHz	16QAM	20525	6RB#0	21.86	PASS
Band5	1.4MHz	16QAM	20643	1RB#0	23.44	PASS
Band5	1.4MHz	16QAM	20643	1RB#2	23.59	PASS
Band5	1.4MHz	16QAM	20643	1RB#5	23.40	PASS
Band5	1.4MHz	16QAM	20643	3RB#0	23.26	PASS
Band5	1.4MHz	16QAM	20643	3RB#1	23.26	PASS
Band5	1.4MHz	16QAM	20643	3RB#3	23.20	PASS
Band5	1.4MHz	16QAM	20643	6RB#0	22.64	PASS
Band5	3MHz	QPSK	20415	1RB#0	24.13	PASS
Band5	3MHz	QPSK	20415	1RB#8	23.56	PASS
Band5	3MHz	QPSK	20415	1RB#14	23.58	PASS
Band5	3MHz	QPSK	20415	8RB#0	23.10	PASS
Band5	3MHz	QPSK	20415	8RB#4	23.02	PASS
Band5	3MHz	QPSK	20415	8RB#7	22.86	PASS
Band5	3MHz	QPSK	20415	15RB#0	22.87	PASS
Band5	3MHz	QPSK	20525	1RB#0	23.53	PASS
Band5	3MHz	QPSK	20525	1RB#8	24.09	PASS
Band5	3MHz	QPSK	20525	1RB#14	24.09	PASS
Band5	3MHz	QPSK	20525	8RB#0	22.79	PASS
Band5	3MHz	QPSK	20525	8RB#4	22.70	PASS
Band5	3MHz	QPSK	20525	8RB#7	22.87	PASS
Band5	3MHz	QPSK	20525	15RB#0	22.84	PASS
Band5	3MHz	QPSK	20635	1RB#0	24.16	PASS
Band5	3MHz	QPSK	20635	1RB#8	24.37	PASS
Band5	3MHz	QPSK	20635	1RB#14	24.26	PASS
Band5	3MHz	QPSK	20635	8RB#0	23.27	PASS
Band5	3MHz	QPSK	20635	8RB#4	23.27	PASS
Band5	3MHz	QPSK	20635	8RB#7	23.45	PASS
Band5	3MHz	QPSK	20635	15RB#0	23.31	PASS
Band5	3MHz	16QAM	20415	1RB#0	23.25	PASS
Band5	3MHz	16QAM	20415	1RB#8	22.69	PASS
Band5	3MHz	16QAM	20415	1RB#14	22.68	PASS
Band5	3MHz	16QAM	20415	8RB#0	21.96	PASS
Band5	3MHz	16QAM	20415	8RB#4	22.21	PASS

Band5	3MHz	16QAM	20415	8RB#7	21.89	PASS
Band5	3MHz	16QAM	20415	15RB#0	21.99	PASS
Band5	3MHz	16QAM	20525	1RB#0	22.60	PASS
Band5	3MHz	16QAM	20525	1RB#8	22.99	PASS
Band5	3MHz	16QAM	20525	1RB#14	22.90	PASS
Band5	3MHz	16QAM	20525	8RB#0	21.86	PASS
Band5	3MHz	16QAM	20525	8RB#4	21.68	PASS
Band5	3MHz	16QAM	20525	8RB#7	22.11	PASS
Band5	3MHz	16QAM	20525	15RB#0	21.71	PASS
Band5	3MHz	16QAM	20635	1RB#0	23.22	PASS
Band5	3MHz	16QAM	20635	1RB#8	23.39	PASS
Band5	3MHz	16QAM	20635	1RB#14	23.39	PASS
Band5	3MHz	16QAM	20635	8RB#0	22.38	PASS
Band5	3MHz	16QAM	20635	8RB#4	22.38	PASS
Band5	3MHz	16QAM	20635	8RB#7	22.65	PASS
Band5	3MHz	16QAM	20635	15RB#0	22.53	PASS
Band5	5MHz	QPSK	20425	1RB#0	23.99	PASS
Band5	5MHz	QPSK	20425	1RB#12	23.66	PASS
Band5	5MHz	QPSK	20425	1RB#24	23.70	PASS
Band5	5MHz	QPSK	20425	12RB#0	22.87	PASS
Band5	5MHz	QPSK	20425	12RB#6	22.88	PASS
Band5	5MHz	QPSK	20425	12RB#13	22.75	PASS
Band5	5MHz	QPSK	20425	25RB#0	22.79	PASS
Band5	5MHz	QPSK	20525	1RB#0	23.59	PASS
Band5	5MHz	QPSK	20525	1RB#12	24.09	PASS
Band5	5MHz	QPSK	20525	1RB#24	23.87	PASS
Band5	5MHz	QPSK	20525	12RB#0	22.76	PASS
Band5	5MHz	QPSK	20525	12RB#6	22.76	PASS
Band5	5MHz	QPSK	20525	12RB#13	22.80	PASS
Band5	5MHz	QPSK	20525	25RB#0	22.85	PASS
Band5	5MHz	QPSK	20625	1RB#0	23.90	PASS
Band5	5MHz	QPSK	20625	1RB#12	24.24	PASS
Band5	5MHz	QPSK	20625	1RB#24	24.30	PASS
Band5	5MHz	QPSK	20625	12RB#0	23.12	PASS
Band5	5MHz	QPSK	20625	12RB#6	23.12	PASS
Band5	5MHz	QPSK	20625	12RB#13	23.42	PASS
Band5	5MHz	QPSK	20625	25RB#0	23.31	PASS

Band5	5MHz	16QAM	20425	1RB#0	23.05	PASS
Band5	5MHz	16QAM	20425	1RB#12	22.16	PASS
Band5	5MHz	16QAM	20425	1RB#24	22.53	PASS
Band5	5MHz	16QAM	20425	12RB#0	21.88	PASS
Band5	5MHz	16QAM	20425	12RB#6	21.80	PASS
Band5	5MHz	16QAM	20425	12RB#13	21.73	PASS
Band5	5MHz	16QAM	20425	25RB#0	21.90	PASS
Band5	5MHz	16QAM	20525	1RB#0	22.72	PASS
Band5	5MHz	16QAM	20525	1RB#12	23.05	PASS
Band5	5MHz	16QAM	20525	1RB#24	22.77	PASS
Band5	5MHz	16QAM	20525	12RB#0	21.69	PASS
Band5	5MHz	16QAM	20525	12RB#6	21.78	PASS
Band5	5MHz	16QAM	20525	12RB#13	21.93	PASS
Band5	5MHz	16QAM	20525	25RB#0	21.78	PASS
Band5	5MHz	16QAM	20625	1RB#0	22.98	PASS
Band5	5MHz	16QAM	20625	1RB#12	23.21	PASS
Band5	5MHz	16QAM	20625	1RB#24	23.06	PASS
Band5	5MHz	16QAM	20625	12RB#0	22.20	PASS
Band5	5MHz	16QAM	20625	12RB#6	22.00	PASS
Band5	5MHz	16QAM	20625	12RB#13	22.49	PASS
Band5	5MHz	16QAM	20625	25RB#0	22.42	PASS
Band5	10MHz	QPSK	20450	1RB#0	24.32	PASS
Band5	10MHz	QPSK	20450	1RB#24	24.81	PASS
Band5	10MHz	QPSK	20450	1RB#49	24.33	PASS
Band5	10MHz	QPSK	20450	25RB#0	23.47	PASS
Band5	10MHz	QPSK	20450	25RB#12	23.49	PASS
Band5	10MHz	QPSK	20450	25RB#25	23.50	PASS
Band5	10MHz	QPSK	20450	50RB#0	23.50	PASS
Band5	10MHz	QPSK	20525	1RB#0	24.28	PASS
Band5	10MHz	QPSK	20525	1RB#24	24.38	PASS
Band5	10MHz	QPSK	20525	1RB#49	24.33	PASS
Band5	10MHz	QPSK	20525	25RB#0	23.40	PASS
Band5	10MHz	QPSK	20525	25RB#12	23.38	PASS
Band5	10MHz	QPSK	20525	25RB#25	23.43	PASS
Band5	10MHz	QPSK	20525	50RB#0	23.38	PASS
Band5	10MHz	QPSK	20600	1RB#0	24.41	PASS
Band5	10MHz	QPSK	20600	1RB#24	24.42	PASS

Band5	10MHz	QPSK	20600	1RB#49	24.29	PASS
Band5	10MHz	QPSK	20600	25RB#0	23.55	PASS
Band5	10MHz	QPSK	20600	25RB#12	23.54	PASS
Band5	10MHz	QPSK	20600	25RB#25	23.46	PASS
Band5	10MHz	QPSK	20600	50RB#0	23.53	PASS
Band5	10MHz	16QAM	20450	1RB#0	23.40	PASS
Band5	10MHz	16QAM	20450	1RB#24	23.51	PASS
Band5	10MHz	16QAM	20450	1RB#49	23.42	PASS
Band5	10MHz	16QAM	20450	25RB#0	22.45	PASS
Band5	10MHz	16QAM	20450	25RB#12	22.45	PASS
Band5	10MHz	16QAM	20450	25RB#25	22.47	PASS
Band5	10MHz	16QAM	20450	50RB#0	22.49	PASS
Band5	10MHz	16QAM	20525	1RB#0	23.41	PASS
Band5	10MHz	16QAM	20525	1RB#24	23.47	PASS
Band5	10MHz	16QAM	20525	1RB#49	23.47	PASS
Band5	10MHz	16QAM	20525	25RB#0	22.38	PASS
Band5	10MHz	16QAM	20525	25RB#12	22.36	PASS
Band5	10MHz	16QAM	20525	25RB#25	22.36	PASS
Band5	10MHz	16QAM	20525	50RB#0	22.36	PASS
Band5	10MHz	16QAM	20600	1RB#0	23.52	PASS
Band5	10MHz	16QAM	20600	1RB#24	23.47	PASS
Band5	10MHz	16QAM	20600	1RB#49	23.40	PASS
Band5	10MHz	16QAM	20600	25RB#0	22.51	PASS
Band5	10MHz	16QAM	20600	25RB#12	22.54	PASS
Band5	10MHz	16QAM	20600	25RB#25	22.45	PASS
Band5	10MHz	16QAM	20600	50RB#0	22.46	PASS

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dBm)	Verdict
Band7	5MHz	QPSK	20775	1RB#0	23.75	PASS
Band7	5MHz	QPSK	20775	1RB#12	23.80	PASS
Band7	5MHz	QPSK	20775	1RB#24	23.89	PASS
Band7	5MHz	QPSK	20775	12RB#0	23.01	PASS
Band7	5MHz	QPSK	20775	12RB#6	22.99	PASS
Band7	5MHz	QPSK	20775	12RB#13	23.00	PASS
Band7	5MHz	QPSK	20775	25RB#0	22.97	PASS
Band7	5MHz	QPSK	21100	1RB#0	24.06	PASS

Band7	5MHz	QPSK	21100	1RB#12	24.04	PASS
Band7	5MHz	QPSK	21100	1RB#24	24.13	PASS
Band7	5MHz	QPSK	21100	12RB#0	22.84	PASS
Band7	5MHz	QPSK	21100	12RB#6	22.84	PASS
Band7	5MHz	QPSK	21100	12RB#13	22.90	PASS
Band7	5MHz	QPSK	21100	25RB#0	22.92	PASS
Band7	5MHz	QPSK	21425	1RB#0	24.23	PASS
Band7	5MHz	QPSK	21425	1RB#12	24.22	PASS
Band7	5MHz	QPSK	21425	1RB#24	24.24	PASS
Band7	5MHz	QPSK	21425	12RB#0	23.09	PASS
Band7	5MHz	QPSK	21425	12RB#6	23.09	PASS
Band7	5MHz	QPSK	21425	12RB#13	23.10	PASS
Band7	5MHz	QPSK	21425	25RB#0	23.09	PASS
Band7	5MHz	16QAM	20775	1RB#0	23.08	PASS
Band7	5MHz	16QAM	20775	1RB#12	23.17	PASS
Band7	5MHz	16QAM	20775	1RB#24	23.18	PASS
Band7	5MHz	16QAM	20775	12RB#0	22.04	PASS
Band7	5MHz	16QAM	20775	12RB#6	22.16	PASS
Band7	5MHz	16QAM	20775	12RB#13	22.19	PASS
Band7	5MHz	16QAM	20775	25RB#0	22.20	PASS
Band7	5MHz	16QAM	21100	1RB#0	22.18	PASS
Band7	5MHz	16QAM	21100	1RB#12	22.34	PASS
Band7	5MHz	16QAM	21100	1RB#24	22.30	PASS
Band7	5MHz	16QAM	21100	12RB#0	22.01	PASS
Band7	5MHz	16QAM	21100	12RB#6	22.03	PASS
Band7	5MHz	16QAM	21100	12RB#13	21.95	PASS
Band7	5MHz	16QAM	21100	25RB#0	22.18	PASS
Band7	5MHz	16QAM	21425	1RB#0	22.49	PASS
Band7	5MHz	16QAM	21425	1RB#12	22.55	PASS
Band7	5MHz	16QAM	21425	1RB#24	22.62	PASS
Band7	5MHz	16QAM	21425	12RB#0	22.17	PASS
Band7	5MHz	16QAM	21425	12RB#6	22.17	PASS
Band7	5MHz	16QAM	21425	12RB#13	22.19	PASS
Band7	5MHz	16QAM	21425	25RB#0	22.34	PASS
Band7	10MHz	QPSK	20800	1RB#0	24.07	PASS
Band7	10MHz	QPSK	20800	1RB#24	23.90	PASS
Band7	10MHz	QPSK	20800	1RB#49	24.01	PASS

Band7	10MHz	QPSK	20800	25RB#0	23.07	PASS
Band7	10MHz	QPSK	20800	25RB#12	23.07	PASS
Band7	10MHz	QPSK	20800	25RB#25	23.05	PASS
Band7	10MHz	QPSK	20800	50RB#0	23.01	PASS
Band7	10MHz	QPSK	21100	1RB#0	23.74	PASS
Band7	10MHz	QPSK	21100	1RB#24	23.79	PASS
Band7	10MHz	QPSK	21100	1RB#49	23.87	PASS
Band7	10MHz	QPSK	21100	25RB#0	22.92	PASS
Band7	10MHz	QPSK	21100	25RB#12	22.92	PASS
Band7	10MHz	QPSK	21100	25RB#25	22.87	PASS
Band7	10MHz	QPSK	21100	50RB#0	22.98	PASS
Band7	10MHz	QPSK	21400	1RB#0	24.02	PASS
Band7	10MHz	QPSK	21400	1RB#24	23.90	PASS
Band7	10MHz	QPSK	21400	1RB#49	23.96	PASS
Band7	10MHz	QPSK	21400	25RB#0	23.09	PASS
Band7	10MHz	QPSK	21400	25RB#12	23.11	PASS
Band7	10MHz	QPSK	21400	25RB#25	23.10	PASS
Band7	10MHz	QPSK	21400	50RB#0	23.11	PASS
Band7	10MHz	16QAM	20800	1RB#0	22.48	PASS
Band7	10MHz	16QAM	20800	1RB#24	22.50	PASS
Band7	10MHz	16QAM	20800	1RB#49	22.55	PASS
Band7	10MHz	16QAM	20800	25RB#0	22.27	PASS
Band7	10MHz	16QAM	20800	25RB#12	22.27	PASS
Band7	10MHz	16QAM	20800	25RB#25	22.21	PASS
Band7	10MHz	16QAM	20800	50RB#0	22.24	PASS
Band7	10MHz	16QAM	21100	1RB#0	22.72	PASS
Band7	10MHz	16QAM	21100	1RB#24	22.65	PASS
Band7	10MHz	16QAM	21100	1RB#49	22.69	PASS
Band7	10MHz	16QAM	21100	25RB#0	22.06	PASS
Band7	10MHz	16QAM	21100	25RB#12	21.95	PASS
Band7	10MHz	16QAM	21100	25RB#25	22.06	PASS
Band7	10MHz	16QAM	21100	50RB#0	22.18	PASS
Band7	10MHz	16QAM	21400	1RB#0	22.96	PASS
Band7	10MHz	16QAM	21400	1RB#24	22.93	PASS
Band7	10MHz	16QAM	21400	1RB#49	22.94	PASS
Band7	10MHz	16QAM	21400	25RB#0	22.18	PASS
Band7	10MHz	16QAM	21400	25RB#12	22.18	PASS

Band7	10MHz	16QAM	21400	25RB#25	22.24	PASS
Band7	10MHz	16QAM	21400	50RB#0	22.25	PASS
Band7	15MHz	QPSK	20825	1RB#0	24.17	PASS
Band7	15MHz	QPSK	20825	1RB#38	24.18	PASS
Band7	15MHz	QPSK	20825	1RB#74	24.09	PASS
Band7	15MHz	QPSK	20825	38RB#0	23.31	PASS
Band7	15MHz	QPSK	20825	38RB#18	23.30	PASS
Band7	15MHz	QPSK	20825	38RB#37	23.28	PASS
Band7	15MHz	QPSK	20825	75RB#0	22.97	PASS
Band7	15MHz	QPSK	21100	1RB#0	23.79	PASS
Band7	15MHz	QPSK	21100	1RB#38	23.87	PASS
Band7	15MHz	QPSK	21100	1RB#74	23.88	PASS
Band7	15MHz	QPSK	21100	38RB#0	22.68	PASS
Band7	15MHz	QPSK	21100	38RB#18	22.73	PASS
Band7	15MHz	QPSK	21100	38RB#37	22.85	PASS
Band7	15MHz	QPSK	21100	75RB#0	22.81	PASS
Band7	15MHz	QPSK	21375	1RB#0	23.96	PASS
Band7	15MHz	QPSK	21375	1RB#38	23.86	PASS
Band7	15MHz	QPSK	21375	1RB#74	23.94	PASS
Band7	15MHz	QPSK	21375	38RB#0	22.95	PASS
Band7	15MHz	QPSK	21375	38RB#18	22.96	PASS
Band7	15MHz	QPSK	21375	38RB#37	23.00	PASS
Band7	15MHz	QPSK	21375	75RB#0	23.03	PASS
Band7	15MHz	16QAM	20825	1RB#0	23.37	PASS
Band7	15MHz	16QAM	20825	1RB#38	23.30	PASS
Band7	15MHz	16QAM	20825	1RB#74	23.28	PASS
Band7	15MHz	16QAM	20825	38RB#0	23.35	PASS
Band7	15MHz	16QAM	20825	38RB#18	23.30	PASS
Band7	15MHz	16QAM	20825	38RB#37	23.32	PASS
Band7	15MHz	16QAM	20825	75RB#0	22.21	PASS
Band7	15MHz	16QAM	21100	1RB#0	22.72	PASS
Band7	15MHz	16QAM	21100	1RB#38	22.71	PASS
Band7	15MHz	16QAM	21100	1RB#74	22.85	PASS
Band7	15MHz	16QAM	21100	38RB#0	22.72	PASS
Band7	15MHz	16QAM	21100	38RB#18	22.72	PASS
Band7	15MHz	16QAM	21100	38RB#37	22.81	PASS
Band7	15MHz	16QAM	21100	75RB#0	22.07	PASS

Band7	15MHz	16QAM	21375	1RB#0	22.98	PASS
Band7	15MHz	16QAM	21375	1RB#38	22.96	PASS
Band7	15MHz	16QAM	21375	1RB#74	22.97	PASS
Band7	15MHz	16QAM	21375	38RB#0	22.96	PASS
Band7	15MHz	16QAM	21375	38RB#18	22.96	PASS
Band7	15MHz	16QAM	21375	38RB#37	22.99	PASS
Band7	15MHz	16QAM	21375	75RB#0	22.29	PASS
Band7	20MHz	QPSK	20850	1RB#0	24.10	PASS
Band7	20MHz	QPSK	20850	1RB#49	24.07	PASS
Band7	20MHz	QPSK	20850	1RB#99	24.12	PASS
Band7	20MHz	QPSK	20850	50RB#0	23.10	PASS
Band7	20MHz	QPSK	20850	50RB#25	23.08	PASS
Band7	20MHz	QPSK	20850	50RB#50	23.03	PASS
Band7	20MHz	QPSK	20850	100RB#0	22.89	PASS
Band7	20MHz	QPSK	21100	1RB#0	24.24	PASS
Band7	20MHz	QPSK	21100	1RB#49	24.23	PASS
Band7	20MHz	QPSK	21100	1RB#99	24.35	PASS
Band7	20MHz	QPSK	21100	50RB#0	22.95	PASS
Band7	20MHz	QPSK	21100	50RB#25	22.99	PASS
Band7	20MHz	QPSK	21100	50RB#50	22.87	PASS
Band7	20MHz	QPSK	21100	100RB#0	22.93	PASS
Band7	20MHz	QPSK	21350	1RB#0	24.24	PASS
Band7	20MHz	QPSK	21350	1RB#49	24.27	PASS
Band7	20MHz	QPSK	21350	1RB#99	24.34	PASS
Band7	20MHz	QPSK	21350	50RB#0	23.03	PASS
Band7	20MHz	QPSK	21350	50RB#25	23.05	PASS
Band7	20MHz	QPSK	21350	50RB#50	23.06	PASS
Band7	20MHz	QPSK	21350	100RB#0	23.04	PASS
Band7	20MHz	16QAM	20850	1RB#0	22.71	PASS
Band7	20MHz	16QAM	20850	1RB#49	22.59	PASS
Band7	20MHz	16QAM	20850	1RB#99	22.57	PASS
Band7	20MHz	16QAM	20850	50RB#0	22.23	PASS
Band7	20MHz	16QAM	20850	50RB#25	22.22	PASS
Band7	20MHz	16QAM	20850	50RB#50	22.26	PASS
Band7	20MHz	16QAM	20850	100RB#0	22.01	PASS
Band7	20MHz	16QAM	21100	1RB#0	22.62	PASS
Band7	20MHz	16QAM	21100	1RB#49	22.57	PASS

Band7	20MHz	16QAM	21100	1RB#99	22.77	PASS
Band7	20MHz	16QAM	21100	50RB#0	22.14	PASS
Band7	20MHz	16QAM	21100	50RB#25	22.15	PASS
Band7	20MHz	16QAM	21100	50RB#50	22.13	PASS
Band7	20MHz	16QAM	21100	100RB#0	22.08	PASS
Band7	20MHz	16QAM	21350	1RB#0	22.86	PASS
Band7	20MHz	16QAM	21350	1RB#49	22.84	PASS
Band7	20MHz	16QAM	21350	1RB#99	22.95	PASS
Band7	20MHz	16QAM	21350	50RB#0	22.31	PASS
Band7	20MHz	16QAM	21350	50RB#25	22.32	PASS
Band7	20MHz	16QAM	21350	50RB#50	22.29	PASS
Band7	20MHz	16QAM	21350	100RB#0	22.27	PASS

Remark:

1. Per KDB941225 D05 v02r05, Start with the largest channel bandwidth then measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle, and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required for 1 RB allocation; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. 6 When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.
2. Per KDB941225 D05 v02r05, The procedures required for 1 RB allocation in 5.2.1 are applied to measure the SAR for QPSK with 50% RB allocation.
3. Per KDB941225 D05 v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations, and the highest reported SAR for 1 RB and 50% RB allocation in 5.2.1 and 5.2.2 are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB941225 D05 v02r05, For each modulation besides QPSK; e.g., 16-QAM, 64-QAM, apply the QPSK procedures in 5.2.1, 5.2.2, and 5.2.3 to determine the QAM configurations that may need SAR measurement. For each configuration identified as required for testing, SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> \frac{1}{2}$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

9.2 Test Results for Standalone SAR Test

Body SAR

GSM850 – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	GPRS_3TX	Back Face	190	836.6	29.96	30.0	1.009	0.524	0.529
1.	GPRS_3TX	Front Face	190	836.6	29.96	30.0	1.009	0.685	0.691
	GPRS_3TX	Right Side	190	836.6	29.96	30.0	1.009	0.134	0.135
	GPRS_3TX	Top Side	190	836.6	29.96	30.0	1.009	0.164	0.166
	GPRS_3TX	Bottom Side	190	836.6	29.96	30.0	1.009	0.090	0.091

GSM1900 – Body SAR Test (Gap: 0mm)									
Plot No.	Mode	Test Position Body	Frequency		Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
			CH.	MHz					
	GPRS_3TX	Back Face	512	1850.2	24.89	25.0	1.026	0.267	0.274
2.	GPRS_3TX	Front Face	512	1850.2	24.89	25.0	1.026	0.384	0.394
	GPRS_3TX	Right Side	512	1850.2	24.89	25.0	1.026	0.055	0.056
	GPRS_3TX	Top Side	512	1850.2	24.89	25.0	1.026	0.101	0.104
	GPRS_3TX	Bottom Side	512	1850.2	24.89	25.0	1.026	0.044	0.045

LTE Band 5–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Freque ncy	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
	QPSK 10MHz 1RB	Back Face	829.0	24.81	25.0	1.045	0.073	0.076
3.	QPSK 10MHz 1RB	Front Face	829.0	24.81	25.0	1.045	0.639	0.668
	QPSK 10MHz 1RB	Right Side	829.0	24.81	25.0	1.045	0.105	0.110
	QPSK 10MHz 1RB	Top Side	829.0	24.81	25.0	1.045	0.110	0.115
	QPSK 10MHz 1RB	Bottom Side	829.0	24.81	25.0	1.045	0.054	0.056
	QPSK 10MHz 50%RB	Back Face	829.0	24.81	25.0	1.045	0.054	0.056
	QPSK 10MHz 50%RB	Front Face	829.0	24.81	25.0	1.045	0.472	0.493
	QPSK 10MHz 50%RB	Right Side	829.0	24.81	25.0	1.045	0.077	0.080
	QPSK 10MHz 50%RB	Top Side	829.0	24.81	25.0	1.045	0.084	0.088
	QPSK 10MHz 50%RB	Bottom Side	829.0	24.81	25.0	1.045	0.038	0.040

LTE Band 7–Body SAR Test (Gap: 0mm)								
Plot No.	Mode	Test Position Body	Frequency	Output Power (dBm)	Rated Limit (dBm)	Scaling Factor	SAR1g (W/kg)	Scaled SAR1g (W/kg)
	Modulation, Bandwidth, RB		MHz					
	QPSK 20MHz 1RB	Back Face	2535.0	24.35	24.5	1.035	0.656	0.679
4.	QPSK 20MHz 1RB	Front Face	2535.0	24.35	24.5	1.035	0.764	0.791
	QPSK 20MHz 1RB	Right Side	2535.0	24.35	24.5	1.035	0.706	0.731
	QPSK 20MHz 1RB	Top Side	2535.0	24.35	24.5	1.035	0.176	0.182
	QPSK 20MHz 1RB	Bottom Side	2535.0	24.35	24.5	1.035	0.124	0.128
	QPSK 20MHz 50%RB	Back Face	2535.0	24.35	24.5	1.035	0.480	0.497
	QPSK 20MHz 50%RB	Front Face	2535.0	24.35	24.5	1.035	0.599	0.620
	QPSK 20MHz 50%RB	Right Side	2535.0	24.35	24.5	1.035	0.554	0.573
	QPSK 20MHz 50%RB	Top Side	2535.0	24.35	24.5	1.035	0.138	0.143
	QPSK 20MHz 50%RB	Bottom Side	2535.0	24.35	24.5	1.035	0.101	0.105

Remark:

1. Per KDB 447498 D01 v06, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.
2. GSM and LTE share the same antenna, and cannot transmit simultaneously.

10. Measurement Uncertainty

10.1 Uncertainty for SAR Test

a	b	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Sec.	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System									
Probe calibration	E.2.1	7.0	N	1	1	1	7.00	7.00	∞
Axial Isotropy	E.2.2	2.5	R	$\sqrt{3}$	$(1_{-Cp})^{1/2}$	$(1_{-Cp})^{1/2}$	1.02	1.02	∞
Hemispherical Isotropy	E.2.2	4.0	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	1.63	1.63	∞
Boundary effect	E.2.3	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	E.2.4	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
System detection limits	E.2.5	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	E.2.6	0.02	N	1	1	1	0.02	0.02	∞
Reponse Time	E.2.7	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Integration Time	E.2.8	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
RF ambient Conditions – Noise	E.6.1	0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	E.6.1	0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	E.6.2	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Probe positioning with respect to Phantom Shell	E.6.3	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	E.5	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Test Sample Related									
Test sample positioning	E.4.2	0.03	N	1	1	1	0.03	0.03	N-1
Device Holder Uncertainty	E.4.1	5.00	N	1	1	1	5.00	5.00	
Output power Variation - SAR drift measurement	E.2.9	12.02	R	$\sqrt{3}$	1	1	6.94	6.94	∞
SAR scaling	E6.5	0.0	R	$\sqrt{3}$	1	1	0.0	0.0	∞
Phantom and Tissue Parameters									
Phantom Uncertainty (Shape and thickness tolerances)	E.3.1	0.05	R	$\sqrt{3}$	1	1	0.03	0.03	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E3.2	1.9	R	$\sqrt{3}$	1	0.84	1.10	0.90	∞

Liquid conductivity - deviation from target value	E.3.2	5.00	R	$\sqrt{3}$	0.64	0.43	1.85	1.24	∞
Liquid conductivity - measurement uncertainty	E.3.3	5.00	N	1	0.64	0.43	3.20	2.15	∞
Liquid permittivity - deviation from target value	E.3.2	0.37	R	$\sqrt{3}$	0.6	0.49	0.13	0.10	∞
Liquid permittivity - measurement uncertainty	E.3.3	10.00	N	1	0.6	0.49	6.00	4.90	∞
Combined Standard Uncertainty			RSS				10.20	10.00	
Expanded Uncertainty (95% Confidence interval)			K=2				20.40	20.00	

Annex A. Plots of System Performance Check

MEASUREMENT 1


Type: Validation measurement (Fast, 75.00 %)
Measurement duration: 7 minutes 21 seconds
E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 1.79; Calibrated: 2021-07-16

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW835
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative Permittivity (real part)	54.850245
Conductivity (S/m)	0.951245
Power Variation (%)	0.428437
Ambient Temperature	22.0
Liquid Temperature	22.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	1.519489
SAR 1g (W/Kg)	2.511253

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	2.4900	1.8942	1.4811	1.3541	1.1123	1.0539



3D screen shot	Hot spot position
	

MEASUREMENT 2


Type: Validation measurement (Fast, 75.00 %)
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 2.15; Calibrated: 2021-07-16

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Signal	CW (Crest factor: 1.0)

B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative Permittivity (real part)	54.723090
Conductivity (S/m)	1.512510
Power Variation (%)	1.041232
Ambient Temperature	22.0
Liquid Temperature	22.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.081252
SAR 1g (W/Kg)	9.461217

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.3455	7.1125	5.1026	3.425	3.0242	2.1125



3D screen shot	Hot spot position
	

MEASUREMENT 3


Type: Validation measurement (Fast, 75.00 %)
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 2.31; Calibrated: 2021-07-16

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative Permittivity (real part)	52.420124
Conductivity (S/m)	1.503607
Power Variation (%)	1.022540
Ambient Temperature	22.0
Liquid Temperature	22.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	5.174526
SAR 1g (W/Kg)	9.913214

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	10.2354	6.8400	5.0121	4.1189	3.0522	2.8424



3D screen shot	Hot spot position
	

MEASUREMENT 4


Type: Validation measurement (Fast, 75.00 %)
Measurement duration: 12 minutes 21 seconds
E-field Probe: SSE2 - SN 18/21 EPGO356; ConvF: 2.41; Calibrated: 2021-07-16

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Signal	Duty Cycle 1:1

B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative Permittivity (real part)	52.244092
Conductivity (S/m)	2.123182
Power Variation (%)	0.886021
Ambient Temperature	22.0
Liquid Temperature	22.2






Maximum location: X=0.00, Y=0.00

SAR 10g (W/Kg)	8.230801
SAR 1g (W/Kg)	13.539282

Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.0000	14.0426	12.1354	10.2965	7.4854	5.9354	4.5186



3D screen shot	Hot spot position
	

Annex B. Plots of SAR Measurement

MEASUREMENT 1

Type: Phone measurement (Complete)

Date of measurement: 2022-02-28


Measurement duration: 11 minutes 48 seconds

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=8mm dy=8mm dz=5mm
Phantom	Flat Plane
Device Position	Front
Band	GPRS900_3TX
Channels	Middle
Signal	Duty Cycle: 1: 2.66

B. SAR Measurement Results


Frequency (MHz)	836.600000
Relative Permittivity (real part)	54.850245
Conductivity (S/m)	0.951245
Power Variation (%)	1.074536
Ambient Temperature	22.0
Liquid Temperature	22.2




Maximum location: X=-2.00, Y=-1.00

SAR Peak: 0.89 W/kg

SAR 10g (W/Kg)	0.491925
SAR 1g (W/Kg)	0.685022



3D screen shot	Hot spot position
	

MEASUREMENT 2

Type: Phone measurement (Complete)

Date of measurement: 2022-02-28


Measurement duration: 11 minutes 48 seconds

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=8mm dy=8mm dz=5mm
Phantom	Flat Plane
Device Position	Front
Band	GPRS1800_3TX
Channels	Low
Signal	Duty Cycle: 1: 2.66

B. SAR Measurement Results



Frequency (MHz)	1850.200000
Relative Permittivity (real part)	54.720124
Conductivity (S/m)	1.513694
Power Variation (%)	-0.150000
Ambient Temperature	22.0
Liquid Temperature	22.2



Maximum location: X=-17.00, Y=-14.00

SAR Peak: 0.74 W/kg

SAR 10g (W/Kg)	0.194624
SAR 1g (W/Kg)	0.384107



MEASUREMENT 3


Type: Phone measurement (Complete)
Date of measurement: 2022-02-28
Measurement duration: 12 minutes 3 seconds

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=8mm dy=8mm dz=5mm
Phantom	Flat Plane
Device Position	Front
Band	LTE Band 5
Channels	QPSK, 10MHz, 1RB,Low
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	829.000000
Relative Permittivity (real part)	54.850245
Conductivity (S/m)	0.951245
Power Variation (%)	-0.870000
Ambient Temperature	22.0
Liquid Temperature	22.2



Maximum location: X=18.00, Y=0.00
SAR Peak: 1.07 W/kg

SAR 10g (W/Kg)	0.380074
SAR 1g (W/Kg)	0.638538



MEASUREMENT 4


Type: Phone measurement (Complete)
Date of measurement: 2022-02-28
Measurement duration: 12 minutes 3 seconds

A. Experimental conditions

Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=8mm dy=8mm dz=5mm
Phantom	Flat Plane
Device Position	Front
Band	LTE Band 7
Channels	QPSK, 20MHz, 1RB, Middle
Signal	Duty Cycle 1:1



B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative Permittivity (real part)	52.243667
Conductivity (S/m)	2.120182
Power Variation (%)	-0.700000
Ambient Temperature	22.0
Liquid Temperature	22.2




Maximum location: X=17.00, Y=5.00
SAR Peak: 1.37 W/kg

SAR 10g (W/Kg)	0.396479
SAR 1g (W/Kg)	0.763885




Annex C. EUT Photos

EUT View 1




EUT View 2



EUT View 3




EUT View 4




EUT View 5



EUT View 6



Antenna View




Annex D. Test Setup Photos


Body mode Exposure Conditions

Test distance: 0mm

Body Front




Body Back




Body Right



Body Top



Body Bottom



Annex E. Calibration Certificate

Please refer to the exhibit for the calibration certificate

******* END OF REPORT *******