

## **Maximum Permissible Exposure Statement**

For the

**Link Labs** 

**LP Module Model LLRLP20** 

February 03, 2015

**Prepared for:** 

Link Labs

130 Holiday Ct., Suite 100

Annapolis, MD 21401

## **Prepared By:**

**H.B.** Compliance Solutions

5005 S. Ash Avenue, Suite # A-10

Tempe, Arizona 85282

**Reviewed By:** 

Hoosamuddin Bandukwala

**NADIE** 

Cert # ATL-0062-E



## Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

## $S = PG/4\pi R2$

Where,

S = power density (mW/cm2)

P = output power at the antenna terminal (mW)

G = gain of transmit antenna (numeric)

R = distance from transmitting antenna (cm)

Maximum peak output power at antenna input terminal = 17.04 (dBm)

Maximum peak output power at antenna input terminal = 50.0 (mW)

Antenna gain (typical) = 1.9(dBi)

Maximum antenna gain = 1.55(numeric)

Prediction distance = 20 (cm)

Prediction frequency = <u>927 (MHz)</u>

MPE limit for uncontrolled exposure at prediction frequency =  $0.618 \, (mW/cm^2)$ 

Power density at prediction frequency = 0.0154185898 (mW/cm<sup>2</sup>)

To solve for the minimum mounting distance required;

# $R = \sqrt{(PG/4\pi S)}$

 $R = V (84.3 \times 1.55 / 4\pi \times 0.0259957425) = 20 cm$  (Based on continuous transmission)

#### **END OF TEST REPORT**