

# FCC ID TEST REPORT

for

LED melody

Model: LED-BT II (porcelain)

FCC ID: 2ACU2LENKI

Prepared for: ShenZhen Lenki Electronic Co., Ltd

No.103, Chen Ronggui Building, Reservoir Road, Xixiang Street, Baoan

District, Shenzhen, Guangdong, China

Prepared by: Shenzhen TCT Testing Technology Co., Ltd

1F, Building 1, Yibaolai Industrial Park, Qiaotou Village, Fuyong Town,

Baoan District, Shenzhen, Guangdong, China

TEL: +86-0755-27673339 FAX: +86-0755-27673332

Report Number: TCT140724E019
Date of Test: Jul. 24-Jul. 31, 2014
Date of Report: Aug. 03, 2014

The results detailed in this test report relate only to the specific sample(s) tested. It is the Application's responsibility to ensure that all production units are manufactured with equivalent EMC characteristics. This report is not to be reproduced except in full, without written approval from TCT Testing Technology.



# **Table of Contents**

1.0 General Details	3
1.1 Test Lab Details	3
1.2 Applicant Details	3
1.3 Description of EUT	4
1.4 Statement	4
1.5 Test Engineer	4
2.0 Test equipments and Associated Equipment used during the test.	5
2.1 Test Equipments	5
2.2 AE used during the test	5
3.0 Technical Details	6
3.1 Summary of test results	6
3.2 Test Standards	6
4.0 EUT Modification	6
5.0 Measurement Uncertainty (95% confidence levels, k=2)	6
6.0 Power Line Conducted Emission Test.	7
7.0 20dB Bandwidth Measurement	11
8.0 Maximum Peak Output Power	15
9.0 Carrier Frequency Separation	21
10.0 Number of Hopping Channels	25
11.0 Time of Occupancy (Dwell Time)	27
12.0 Band edge Measurement	31
13.0 Spurious Emission Test.	40
14.0 Antenna Requirement	49



### 1.0 General Details

## 1.1 Test Lab Details

Name:	Shenzhen Tongce Testing Lab
Address:	1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China
Telephone:	13410377511
Fax:	

The test facility is recognized, certified, or accredited by the following organizations:

## FCC Registration Number: 572331

Shenzhen TCT Testing Technology Co., Ltd., Shenzhen EMC Laboratory: Shenzhen Tongce Testing Lab The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

Registration Number: 572331

## **Industry Canada (IC)**

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

Registration Number IC: 10668A-1

## 1.2 Applicant Details

Applicant:	ShenZhen Lenki Electronic Co., Ltd
Address:	No.103, Chen Ronggui Building, Reservoir Road, Xixiang Street, Baoan District, Shenzhen,
	Guangdong, China
Telephone:	13267147383
Fax:	0755- 27822655

Manufacturer:	ShenZhen Lenki Electronic Co., Ltd
Address:	No.103, Chen Ronggui Building, Reservoir Road, Xixiang Street, Baoan District, Shenzhen,
	Guangdong, China
Telephone:	13267147383
Fax:	0755- 27822655

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 3 of 49



## 1.3 Description of EUT

1:5 Bescription of Ee 1	
Product:	LED melody
Model No.:	LED-BT II (porcelain)
Additional Model No.:	LED-BT II(white)
Brand Name	N.A.
BT Version	3.0+EDR
Rating:	Input: AC 100-240V
Modulation Type:	GFSK, Pi/4DQPSK, 8DPSK
Transfer Data Rate	1/2/3 Mbps
Channel number:	79
Channel spacing:	1 MHz
Operation Frequency:	2402~2480MHz
Antenna Designation:	A PCB antenna, and the maximum antenna gain is 0dBi.

## 1.4 Statement

All models above are identical in interior structure, electrical circuits and components, and just model names are different for the marketing requirement.

## 1.5 Test Engineer

The sample tested by Jack kang

Printed name: Jack Kang

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 4 of 49



## 2.0 Test equipments and Associated Equipment used during the test.

## 2.1 Test Equipments

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	July 3, 2014	July 2, 2015
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 3, 2014	July 2, 2015
Pre-amplifier	Teseq	LNA6900		July 2, 2014	July 1, 2015
Pre-amplifier	Agilent	8447D	83153007374	July 2, 2014	July 1, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 2, 2014	July 1, 2015
Loop antenna	A.R.A.	PLA-1030/B	1029	July 2, 2014	July 1, 2015
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	July 2, 2014	July 1, 2015
Horn Antenna	ETS LINDGREN	3117	1	July 2, 2014	July 1, 2015
Horn Antenna	ETS LINDGREN	3160		July 2, 2014	July 1, 2015
EMI Test Receiver	R&S	ESCS30	100139	July 3, 2014	July 2, 2015
LISN	AFJ	LS16C	16010222119	July 2, 2014	July 1, 2015

## 2.2 AE used during the test

Equipment type	Manufacturer	Model
N/A		

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 5 of 49



## 3.0 Technical Details

## 3.1 Summary of test results

The EUT has been tested according to the following specifications

Requirement	CFR 47 Section	Result
<b>Power Line Conducted Emission Test</b>	15.207(a)	PASS
20dB Channel Bandwidth	15.247 (a)(1), 15.215(c)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Carrier Frequency Separation	15.247 (a)(1)	PASS
Number of Hopping Channels	15.247(a)(iii)	PASS
Time of Occupancy (Dwell Time)	15.247(a)(iii)	PASS
Band edge Measurement, Spurious Emission Test	15.247 (d), 15.205 (a), 15.209 (a)	PASS
Antenna Requirement	15.203	PASS

### 3.2 Test Standards

FCC Part 15:2013 Subpart C, Paragraph 15.247

FCC Public Notice DA 00-705-Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems

## 4.0 EUT Modification

No modification by Shenzhen TCT Testing Technology Co., Ltd

## 5.0 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	MU
1.	Radio Frequency	$\pm 1 \times 10^{-9}$
2.	Temperature	±0.1℃
3.	Humidity	±1.0%
4.	RF power, conducted	±0.34dB
5.	RF power density, conducted	±1.45dB
6.	Spurious emissions, conducted	±3.70dB
7.	All emissions, radiated	±4.50dB

Note: 1) Low channel: 2402MHz, Middle channel: 2441MHz, High channel: 2480MHz


2) The EUT is a portable device, and measurements were conducted in all three axis (X, Y, Z), and the worst case (X axis) was submitted only.

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 6 of 49



## **6.0 Power Line Conducted Emission Test**

### 6.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 6.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2009and ANSI C63.4-2003. The Frequency spectrum from 0.15MHz to 30MHz was investigated.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



## 6.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009 and ANSI C63.4-2003

- 1) Setup the EUT and simulators as shown on the following
- 2) Enable AF signal and confirm EUT active to normal condition

## 6.4 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
EMI Test Receiver	R&S	ESCS30	100139	July 3, 2014	July 2, 2015
LISN	AFJ	LS16C	16010222119	July 2, 2014	July 1, 2015

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 7 of 49



## 6.5 Conducted Emission Limit

Eraguanay (MHz)	Class A Lin	nits (dB µ V)	Class B Limits (dB $\mu$ V)		
Frequency(MHz)	Quasi-peak Level Average Lev		Quasi-peak Level	Average Level	
0.15 ~ 0.50	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1) \*Decreasing linearly with logarithm of frequency.
- 2) The tighter limit shall apply at the transition frequencies
- 6.6 Photo documentation of the test set-up

Please refer to the Document Setup photo

6.7 Test specification: Environmental conditions:	Temperature:	22° C	Humidity:	52%	Atmospheric pressure:	103kPa	
Frequency range: 0.15 MHz	– 30 MHz						
The test was carried out in th - Tx mode	The test was carried out in the following operation mode(s):  - Tx mode						
6.8 Test result							
Min. limit margin		>10 dB	from 0.15MH	z to 30M	IHz		
The requirements are FULFI	LLED						
Remarks:							

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 8 of 49



## A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT Description:	LED melody
Operation Mode:	Tx mode
Tested By:	SKY
Test date:	Jul. 31, 2014

Start Frequency	Stop Frequency	Step	IF BW	Detector	Final M-Time
0.15MHz	30MHz	4.5KHz	10KHz	QP+AV	1s



Reading(dB μ V)					Limit	
Frequency (MHz)	Live	<b>)</b>	Neutral		(dB µ V)	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.1539	45.20	29.23			65.78	55.78
0.2359	35.40	22.24			62.24	52.24
0.3961	35.86	33.84			57.93	47.93
1.6383	25.45	18.83			56.00	46.00
2.6500	35.54	29.05			56.00	46.00
4.4883	25.84	18.51			56.00	46.00

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 9 of 49



## B Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT Description:	LED melody
Operation Mode:	Tx mode
Tested By:	SKY
Test Data:	Jul. 31, 2014

Start Frequency	Stop Frequency	Step	IF BW	Detector	Final M-Time
0.15MHz	30MHz	4.5KHz	10KHz	QP+AV	1s



Eraguanav	Reading(dB μ V)					Limit	
Frequency (MHz)	Live	;	Neutral		(dB µ V)		
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average	
0.1500			45.55	28.93	65.99	55.99	
0.3219			31.03	25.11	59.66	49.66	
0.4430			34.85	25.10	57.00	47.00	
1.3805			35.28	30.11	56.00	46.00	
2.5328			31.78	22.02	56.00	46.00	
4.6875			32.39	28.74	56.00	46.00	

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 10 of 49



### 7.0 20dB Bandwidth Measurement

## 7.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015

### 7.2 Test Specification:

Environmental conditions: Temperature 23° C Humidity: 51% Atmospheric pressure: 103kPa

## 7.3 Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 7.4 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4DQPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.


### 7.5 Test Result:

Modulation Type	Channel number	20dB Bandwidth (kHz)	Limit (kHz)	Conclusion
	Low	833.3		PASS
GFSK	Middle	833.3		PASS
	High	836.5		PASS
	Low	1272.4		PASS
8DPSK	Middle	1266.0		PASS
	High	1269.2		PASS


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 11 of 49

Modulation: GFSK

Low channel




## Middle channel






## High channel




Modulation: 8DPSK Low channel






## Middle channel



## High channel





## 8.0 Maximum Peak Output Power

### 8.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015

#### 8.2 Test specification:

Environmental conditions: Temperature 23° C Humidity: 51% Atmospheric pressure: 103kPa

#### 8.3 Test Procedure

- 1) Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2) Set the spectrum analyzer as follows: Span = approximately 5 times the 20 dB bandwidth, centred on a hopping channel; RBW > the 20 dB bandwidth of the emission being measured; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 3) Measure the highest amplitude appearing on spectral display and record the level to calculate results.
- 4) Repeat above procedures until all frequencies measured were complete.

#### 8.4 Limits

According to §15.247(b)(1), for frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5MHz band: 0.125 watts. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


#### 8.5 Test Result

Modulation Type	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (mW)	Peak Power Limit (dBm)	Pass/ Fail
	2402	0.30	125	20.97	Pass
GFSK	2441	1.02	125	20.97	Pass
	2480	1.50	125	20.97	Pass
	2402	-0.30	125	20.97	Pass
Pi/4 DQPSK	2441	0.23	125	20.97	Pass
	2480	0.75	125	20.97	Pass
	2402	-0.29	125	20.97	Pass
8 DPSK	2441	0.35	125	20.97	Pass
	2480	0.88	125	20.97	Pass


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 15 of 49

Modulation: GFSK






## Middle channel






## High channel




Modulation: Pi/4 DQPSK

Low channel






## Middle channel




## High channel




Modulation: 8DPSK

Low channel




## Middle channel





## High channel





## 9.0 Carrier Frequency Separation

### 9.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015

## 9.2 Test specification:

Environmental conditions: Temperature 23° C Humidity: 51% Atmospheric pressure: 103kPa

#### 9.3 Test Procedure

- 1. Set the spectrum analyzer as follows: Span = wide enough to capture the peaks of two adjacent channels: Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span; Video (or Average) Bandwidth (VBW) ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold
- 2. Measure the separation between the peaks of the adjacent channels using the marker-delta function.
- 3. Repeat above procedures until all frequencies measured were complete.

#### 9.4 Limits

According to §15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

#### 9.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 DQPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

#### 9.6 Test Result


Modulation Type	Channel number	Carrier Frequency	Limit	Pass/ Fail
		Separation		
	Low 1.000MHz ≥ 25 k		≥ 25 kHz or	Pass
GFSK	Middle 1.000MHz	two-thirds 20 dB bandwidth	Pass	
	High	1.000MHz	20 db bandwidth	Pass
	Low	1.000MHz	≥ 25 kHz or	Pass
8DPSK	Middle	1.000MHz	two-thirds 20 dB bandwidth	Pass
	High	1.000MHz	20 db bandwidth	Pass

Note: Two-thirds 20 dB bandwidth: GFSK: 557.67 kHz; 8DPSK: 844.27 kHz


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 21 of 49

Modulation: GFSK

### Low channel




## Middle channel






## High channel




Modulation: 8DPSK

Low channel






## Middle channel



## High channel





## 10.0 Number of Hopping Channels

## 10.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015

## 10.2 Test specification:

Environmental conditions: Temperature 22° C Humidity: 51% Atmospheric pressure: 103kPa

#### 10.3 Test Procedure

Set the spectrum analyzer as follows: Span = the frequency band of operation; RBW  $\geq$  1% of the span; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold

### 10.4 Limits

According to §15.247(a)(1)(iii), frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

## 10.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 DQPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.


### 10.6 Test Result

Modulation Type	Operating	Number of	Limit	Pass/ Fail	
J.1	Frequency	hopping channels			
GFSK	2402-2480MHz	79	≥ 15	Pass	
8DPSK	2402-2480MHz	79	≥ 15	Pass	


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 25 of 49



## Modulation Type: GFSK



## Modulation Type: 8DPSK





## 11.0 Time of Occupancy (Dwell Time)

## 11.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015

### 11.2 Test specification:

Environmental conditions: Temperature 22° C Humidity: 52% Atmospheric pressure: 103kPa

#### 11.3 Test Procedure

Span = zero span, centred on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Detector function = peak; Sweep = as necessary to capture the entire dwell time per hopping channel; Trace = max hold Measure the dwell time using the marker-delta function.

Repeat this test for different modes of operation (e.g., data rate, modulation format, etc.), if applicable.

#### 11.4 Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed

#### 11.5 Test status:

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 DQPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

#### 11.6 Test Result

Modulation Type	Packet	Reading (ms)	Hoping Rate	Actual (s)	Limit (s)
GFSK	DH1	0.4167	800hop/s	0.1333	0.4
	DH3	1.7188	400hop/s	0.2750	0.4
	DH5	2.9688	266.667hop/s	0.3167	0.4
8DPSK	DH1	0.4087	800hop/s	0.1308	0.4
	DH3	1.7188	400hop/s	0.2750	0.4
	DH5	2.9688	266.667hop/s	0.3167	0.4


Note: 1) The measurements were conducted in High, Middle, Low channel. The Low channel could represent the character of the other channels, so the low channel measurement was submitted in the report only.

- 2) Actual = Reading  $\times$  (Hopping rate / Number of channels)  $\times$  Test period
- 3) The EUT makes worst case 1600 hops per second or 1 time slot has a length of 625µs with 79 channels. A DH5 Packet needs 5 time slot for transmitting and 1 time slot for receiving. So the EUT makes worst case 266.667 hops per second with 79 channels, and the DH5 is the worst case.


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 27 of 49

Modulation Type: GFSK

Packet Type: DH1




Packet Type: DH3






## Packet Type: DH5




Modulation Type: 8DPSK Packet Type: 3-DH1






## Packet Type: 3-DH3



## Packet Type: 3-DH5





## 12.0 Band edge Measurement

### 12.1 Test Equipment

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015

## 12.2 Test specification:

Environmental conditions: Temperature 22° C Humidity: 52% Atmospheric pressure: 103kPa

#### 12.3 Test Procedure

For band edge test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measure method is used For signals allocated in the restricted bands above and below the 2.4-2.483GHz, a radiated measurement is made (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

### 12.4 Limit

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth). Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

#### 12.5 Test status:


Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 DQPSK and 8DPSK mode, which indicates that the worst case is 8DPSK mode, so it is reported GFSK and 8DPSK mode only.

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 31 of 49



Modulation: GFSK

EUT operation mode: Keep transmitting in low channel




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2310 to 2390 MHz was 47.52 dBuV/m@3m at 2389.0MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).



## EUT operation mode: Keep transmitting in high channel




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2483.5 to 2500MHz was 46.50dBuV/m@3m at 2494.0 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).



## EUT operation mode: Keep hopping




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2310 to 2390 MHz was 46.52dBuV/m@3m at 2378.9 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 34 of 49



## EUT operation mode: Keep hopping




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2483.5 to 2500 MHz was 46.50 dBuV/m@3m at 2488.4 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).



Modulation: 8DPSK

EUT operation mode: Keep transmitting in low channel




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2310 to 2390 MHz was 47.00 dBuV/m@3m at 2385.6 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).



### EUT operation mode: Keep transmitting in high channel




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2483.5 to 2500MHz was 45.64dBuV/m@3m at 2493.3 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).



### EUT operation mode: Keep hopping




Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2310 to 2390 MHz was 48.05 dBuV/m@3m at 2378.3 MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).



### EUT operation mode: Keep hopping



Remark: 1) The radiated measurement was made in horizontal and vertical polarity;

- 2) The maximum PK emission of restriction band 2483.5 to 2500MHz was 47.58dBuV/m@3m at 2483.8MHz, which is less than the Average limit.
- 3) Radiated emissions which fall in the restricted band, as defined in 15.205(a), comply with the radiated emission limits specified in 15.209(a).




# 13.0 Spurious Emission Test

#### 13.1 Radiated emissions

- 13.1.1 Test Method and test Procedure:
  - 1) The EUT was tested according to ANSI C63.10 –2009 and ANSI C63.4-2003.
  - 2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2009 and ANSI C63.4-2003.
  - 3) The frequency spectrum from 9 kHz to 25 GHz was investigated. All readings from 9 kHz to 30 MHz are quasi-peak values with a resolution bandwidth of 9 kHz. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
  - 4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
  - 5) The antenna polarization: Vertical polarization and Horizontal polarization.


#### 13.1.2 Block diagram of Test setup




FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 40 of 49



Block diagram of Test setup for frequency below 30MHz



Block diagram of Test setup for frequency above 1GHz



FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 41 of 49



#### 13.1.3 EUT Operating Condition

Operating condition is according to ANSI C63.10 -2009 and ANSI C63.4-2003.

#### 13.1.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
0.009-0.490	3	20log 2400/F (kHz) + 80
0.490-1.705	3	20log 24000/F (kHz) + 40
1.705-30	3	20log 30 + 40
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1) RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2) In the Above Table, the tighter limit applies at the band edges.
- 3) Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4) This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5) All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK and AV detector.
- 6) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula Ld1 = Ld2 \* (d2/d1)

### 13.1.5 Photo documentation of the test set-up

Please refer to the Document Setup photo

#### 13.1.6 Test Equipment:

Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	July 2, 2014	July 1, 2015
Spectrum Analyzer	ROHDE&SCHWARZ	FSEM	848597/001	July 2, 2014	July 1, 2015
Pre-amplifier	Teseq	LNA6900		July 2, 2014	July 1, 2015
Pre-amplifier	Agilent	8447D	8315300737 4	July 2, 2014	July 1, 2015
Pre-amplifier	Agilent	8449B	3008A01738	July 2, 2014	July 1, 2015
Loop antenna	A.R.A.	PLA-1030/B	1029	July 2, 2014	July 1, 2015
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	July 2, 2014	July 1, 2015
Horn Antenna	ETS LINDGREN	3117		July 2, 2014	July 1, 2015
Horn Antenna	ETS LINDGREN	3160		July 2, 2014	July 1, 2015

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 42 of 49



13.1.7 Test specification:

Environmental conditions: Temperature 23°C Humidity: 50% Atmospheric pressure: 103kPa

13.1.8 Test result

Pass

#### A Radiated Emission (9 kHz----30 MHz)

Note: 1) Emission Level=Reading+ Cable loss+ Antenna factor-Amp factor

2) The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Result: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Limit@3m (dB \u03b4 V/m)


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 43 of 49



# B General Radiated Emissions Data Radiated Emission In Horizontal (30MHz----1000MHz)

Please refer to following diagram for individual

High channel: 2480 MHz



Frequency (MHz)	Level@3m (dB $\mu$ V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
30.0000	28.86	Н	40.00
37.7754	25.99	Н	40.00
74.7094	25.52	Н	40.00
168.0160	37.14	Н	43.50
255.4910	42.04	Н	46.00
391.5631	42.32	Н	46.00


FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 44 of 49



#### Radiated Emission In Vertical (30MHz----1000MHz)

Please refer to following diagram for individual

High channel: 2480 MHz



Note: Measurements were conducted in all three channels (high, middle, low), and the worst case (high channel) was submitted only.

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 45 of 49



#### C Fundamental & Harmonics Radiated Emission Data (1000MHz-25000MHz)

Pre-tests were made in continuous transmitting mode at lowest (2402 MHz), middle (2441 MHz) and highest (2480MHz) channel with GFSK, Pi/4 DQPSK and 8DPSK mode, which indicates that the worst case is GFSK mode, so it is reported GFSK mode only.

Modulation Type: GFSK

Low channel: 2402 MHz									
Freq.	Ant. Pol.	Peak reading	AV Correction reading Factor		Emissic	Emission Level		AV limit	Margin
(MHz)	H/V	(dBuV)	(dBuV)	Factor (dB)	Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
1303.12	Н	44.53		-4.20	40.33		74	54	-13.67
4804.00	Н	49.27		-3.94	45.33		74	54	-8.67
7206.00	Н	44.74		0.52	45.26		74	54	-8.74
	Н								
	Н								
1304.09	V	46.33		-4.25	42.08		74	54	-11.92
4804.00	V	43.21		-3.94	39.27		74	54	-14.73
7206.00	V	44.20		0.59	44.79		74	54	-9.21
	V								
	V								

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

- 2) Radiated emissions measured in frequencies above 1GHz were made (Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector).
- 3) Average test would be performed if the peak readings were greater than the average limit.
- 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- 5) Emission Level=Peak (AV) Reading + Correction Factor;Correction Factor= Antenna Factor + Cable loss Pre-amplifier
- 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 46 of 49



Middle channel: 2441 MHz									
Freq.	Ant. Pol.	Peak reading	AV reading			on Level	Peak limit	AV limit	Margin
(MHz)	H/V	(dBuV)	(dBuV)	(dB)	Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
1241.87	Н	48.32		-4.20	44.12		74	54	-9.88
4882.00	Н	49.19		-3.98	45.21		74	54	-8.79
7323.00	Н	43.08		0.56	43.64		74	54	-10.36
	Н								
	Н								
1306.45	V	48.66		-4.25	44.41		74	54	-9.59
4882.00	V	51.36		-3.98	47.38		74	54	-6.62
7323.00	V	42.55		0.57	43.12		74	54	-10.88
	V								
	V								

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

- 2) Radiated emissions measured in frequencies above 1GHz were made (Peak values with RBW=VBW=1MHz and PK detector). AV value with RBW=1MHz, VBW=10Hz and PK detector).
- 3) Average test would be performed if the peak result were greater than the average limit.
- 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- 5) Emission Level=Peak (AV) Reading + Correction Factor;Correction Factor= Antenna Factor + Cable loss Pre-amplifier
- 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 47 of 49



High channel: 2480 MHz									
Freq.	Ant. Pol.	Peak reading	AV reading			on Level	Peak limit	AV limit	Margin
(MHz)	H/V	(dBuV)	(dBuV)	(dB)	Peak (dBuV/m)	AV (dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
1303.34	Н	48.64		-4.20	44.44		74	54	-9.56
4960.00	Н	48.46		-3.98	44.48		74	54	-9.52
7440.00	Н	44.62		0.52	45.14		74	54	-8.86
	Н								
	Н								
1309.82	V	50.01		-4.25	45.76		74	54	-8.24
4960.00	V	50.32		-3.98	46.34		74	54	-7.66
7440.00	V	45.13		0.57	45.7		74	54	-8.3
	V								
	V								

Notes: 1) Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.

- 2) Radiated emissions measured in frequencies above 1GHz were made (Peak values with RBW=VBW=1MHz and PK detector). AV value with RBW=1MHz, VBW=10Hz and PK detector).
- 3) Average test would be performed if the peak result were greater than the average limit.
- 4) Data of measurement shown "---"in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.
- 5) Emission Level=Peak (AV) Reading + Correction Factor;Correction Factor= Antenna Factor + Cable loss Pre-amplifier
- 6) Margin (dB) = Emission Level (Peak) (dBuV/m)-Average limit (dBuV/m)

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 48 of 49



# 14.0 Antenna Requirement


#### 14.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

## 14.2 Antenna Specification

According to the manufacturer declared, the EUT has a PCB antenna; the directional gain of antenna is 0 dBi, and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.



\*\*END OF REPORT\*\*

FCC ID: 2ACU2LENKI Report Number: TCT140724E019 Page 49 of 49