

FCC RADIO TEST REPORT FCC ID: 2ACU5-JTSMART3

Product: Mobile phone

Trade Name: N/A

Model Name: JT Smart 3

Serial Model: N/A

Report No.: NTEK-2014NT0701029F3

Prepared for

UNICAIR INDUSTRIAL LIMITED.

7C-7D,Guanghao International Building,No.441 Meilong road, MinZhi Street,Longhua New District,Shenzhen,China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn



TEST RESULT CERTIFICATION


Report No.: NTEK-2014NT0701029F3

Applicant's name	UNICAIR IND	DUSTRIAL LIN	IITED.	
Address				
		, 0	w District,Shenzhen,C	hina
Manufacture's Name				
Address			onal Building,No.441 w District,Shenzhen,C	
Product description				
Product name	Mobile phone			
Model and/or type reference	JT Smart 3			
Serial Model	N/A			
Standards	FCC Part15.24	47 01 Oct. 20	13	
Test procedure	ANSI C63.4-20	003		
This device described all equipment under test (E to the tested sample ide	UT) is in compl	iance with the		
This report shall not be r	reproduced exc	ept in full, with	out the written approval	of NTEK, this
document may be altere	d or revised by	NTEK, person	al only, and shall be not	ted in the revision of
the document.				
Date of Test				
Date (s) of performance			Jul. 2014	
Date of Issue	22	Jul. 2014		
Test Result	Pa	ss		
Testing	g Engineer	:	Kyle Xu	
			(Kyle Xu)	
Techni	cal Manager	:	Brown Ln	
			(Brown Lu)	
Author	ized Signatory	:	Bin	
			(Bill Yao)	



Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS 1.1 TEST FACILITY 1.2 MEASUREMENT UNCERTAINTY	5 6 6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	_
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13 13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS 3.1.6 TEST RESULTS	14 15
3.2 RADIATED EMISSION MEASUREMENT	17
3.2.1 RADIATED EMISSION MEASUREMENT 3.2.1 RADIATED EMISSION LIMITS	17 17
3.2.2 TEST PROCEDURE	18
3.2.3 DEVIATION FROM TEST STANDARD	18
3.2.4 TEST SETUP 3.2.5 EUT OPERATING CONDITIONS	19 20
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	21
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	22
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	23
4 . POWER SPECTRAL DENSITY TEST	24
4.1 APPLIED PROCEDURES / LIMIT	24
4.1.1 TEST PROCEDURE	24
4.1.2 DEVIATION FROM STANDARD 4.1.3 TEST SETUP	24 24
4.1.4 EUT OPERATION CONDITIONS	24
4.1.5 TEST RESULTS	25
5 . BANDWIDTH TEST	27
5.1 APPLIED PROCEDURES / LIMIT	27
5.1.1 TEST PROCEDURE	27





1	-	h	_	٥f	00	nte	nts
ı	ıa	D	æ	OT	L.O	INTE	ints

rable of contents	Page
5.1.2 EUT OPERATION CONDITIONS 5.1.3 TEST RESULTS	27 28
6 . PEAK OUTPUT POWER TEST	30
6.1 APPLIED PROCEDURES / LIMIT	30
6.1.1 TEST PROCEDURE	30
6.1.2 DEVIATION FROM STANDARD	30
6.1.3 TEST SETUP	30
6.1.4 EUT OPERATION CONDITIONS	30
6.1.5 TEST RESULTS	31
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	32
7.1 DEVIATION FROM STANDARD	32
7.2 TEST SETUP	32
7.3 EUT OPERATION CONDITIONS	32
7.4 TEST RESULTS	33
8 . ANTENNA REQUIREMENT	35
8.1 STANDARD REQUIREMENT	35
8.2 EUT ANTENNA	35
9 . EUT TEST PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	36



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % $^{\circ}$

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Mobile phone			
Trade Name	N/A			
Model Name	JT Smart 3			
Serial Model	N/A			
Model Difference	N/A			
	The EUT is a Mobile	phone		
	Operation Frequency:	2402~2480MHz		
	Modulation Type:	GFSK		
	Number Of Channel	40CH		
	Antenna	Please see Note 3.		
	Designation:			
Product Description	Output	5.608dBm(MAX)		
	Power(Conducted):			
	Antenna Gain (dBi)	1.0dbi		
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.			
Channel List	Please refer to the Note 2.			
Ratings	DC 3.7V			
Adapter	Input: 100-240V~,50/60Hz,0.15A Output: 5.0V===, 700mAh			
Battery	DC 3.7V, 1150mAh	·		

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel	Frequency (MHz)
00	2402
01	2404
•••••	•••••
•••••	·····.
38	2478
39	2480

Page 8 of 37

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
А	N/A	N/A	FPCB Antenna	N/A	1.0	BT Antenna



2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Link Mode

For Radiated Emission		
Final Test Mode	Description	
Mode 1	CH00	
Mode 2	CH19	
Mode 3	CH39	
Mode 4	Link Mode	


Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test

E-1 EUT



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Mobile phone	N/A	JT Smart 3	N/A	EUT
E-2	Adapter	N/A	AD1		
E-3	Earphone	N/A	2688		

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8m	
C-2	NO	NO	1.2m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibratio n period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-101 80	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2013.12.22	2014.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2014.07.06	2015.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufactu rer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2013.08.24	2014.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2013.08.24	2014.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B	Standard	
FREQUENCT (MITZ)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.


Report No.: NTEK-2014NT0701029F3

- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




3.1.6 TEST RESULTS

EUT:	Mobile phone	Model Name. :	JT Smart 3
Temperature:	26 ℃	Relative Humidity:	56%
Pressure :	1010hPa	Phase :	L
TASI VOHADA .	DC 5V form Adapter AC 120V/60Hz	Test Mode:	Mode 4

Page 15 of 37

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	
0.1860	38.28	9.53	47.81	64.21	-16.40	QP
0.1860	28.12	9.53	37.65	54.21	-16.56	AVG
0.2580	33.23	9.49	42.72	61.49	-18.77	QP
0.2580	24.83	9.49	34.32	51.49	-17.17	AVG
0.3700	24.06	9.50	33.56	58.50	-24.94	QP
0.3700	19.18	9.50	28.68	48.50	-19.82	AVG
0.7380	24.91	9.53	34.44	56.00	-21.56	QP
0.7380	18.89	9.53	28.42	46.00	-17.58	AVG
1.9620	28.52	9.55	38.07	56.00	-17.93	QP
1.9620	20.02	9.55	29.57	46.00	-16.43	AVG
4.4380	21.90	9.60	31.50	56.00	-24.50	QP
4.4380	13.99	9.60	23.59	46.00	-22.41	AVG

Remark:






EUT:	Mobile phone	Model Name. :	JT Smart 3
Temperature :	26 ℃	Relative Humidity:	56%
Pressure :	1010hPa	Phase :	N
HEST VOUZOE .	DC 5V form Adapter AC 120V/60Hz	Test Mode :	Mode 4

Page 16 of 37

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(MHz)	(dBµV)	(dB)	(dBµV)	(dBµV)	(dB)	
0.1500	38.61	9.66	48.27	65.99	-17.72	QP
0.1500	27.73	9.66	37.39	55.99	-18.60	AVG
0.1819	36.59	9.56	46.15	64.39	-18.24	QP
0.1819	24.12	9.56	33.68	54.39	-20.71	AVG
0.3020	27.48	9.51	36.99	60.19	-23.20	QP
0.3020	17.49	9.51	27.00	50.19	-23.19	AVG
1.1780	19.13	9.55	28.68	56.00	-27.32	QP
1.1780	11.73	9.55	21.28	46.00	-24.72	AVG
1.5859	21.08	9.56	30.64	56.00	-25.36	QP
1.5859	12.83	9.56	22.39	46.00	-23.61	AVG
4.0379	20.27	9.59	29.86	56.00	-26.14	QP
4.0379	8.25	9.59	17.84	46.00	-28.16	AVG

Remark:





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBu	ıV/m) (at 3M)	Class B (dBuV/m) (at 3M)		
PREQUENCT (WITZ)	PEAK AVERAGE		PEAK	AVERAGE	
Above 1000	80	60	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted	4 Mile / 4 Mile for Dook 4 Mile / 401/e for Average
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.

Report No.: NTEK-2014NT0701029F3

- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz


Page 19 of 37




(B) Radiated Emission Test-Up Frequency 30MHz~1GHz









3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



3.2.6 TEST RESULTS (BETWEEN 9KHZ - 30 MHZ)

EUT:	Mobile phone	Model Name. :	JT Smart 3
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode:	TX	Polarization :	

Report No.: NTEK-2014NT0701029F3

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				N/A
				N/A

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT:	Mobile phone	Model Name :	JT Smart 3
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage:	DC 3.7V
Test Mode:	TX		

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	83.4277	21.52	9.03	30.55	40.00	-9.45	QP
V	141.0368	17.98	11.93	29.91	43.50	-13.59	QP
V	299.4562	22.37	14.58	36.95	46.00	-9.05	QP
V	897.9823	12.04	25.59	37.63	46.00	-8.37	QP
Н	85.0183	25.75	9.08	34.83	43.50	-8.67	QP
Н	143.1457	24.23	11.93	36.16	43.50	-7.34	QP
Н	316.2352	24.64	14.61	39.25	46.00	-6.75	QP
Н	236.1232	21.13	10.63	31.76	46.00	-14.24	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT:	Mobile phone	Model Name :	JT Smart 3
Temperature :	20 ℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage:	DC 3.7V
Test Mode:	TX		

Frequency (MHz)	Reading (dBµV)	Factor (dB)	Corrected Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)	or (PK/AV	Polar (H/V)
	L	ow Char	nel (2402 MHz	z)-Above 1	G		
4804.237	65.26	-3.64	61.62	74.00	-12.38	Pk	Vertical
4804.237	47.33	-3.64	43.69	54.00	-10.31	AV	Vertical
7206.088	57.47	-0.95	56.52	74.00	-17.48	Pk	Vertical
7206.088	43.56	-0.95	42.61	54.00	-11.39	AV	Vertical
4804.106	64.27	-3.64	60.63	74.00	-13.37	Pk	Horizontal
4804.106	51.21	-3.64	47.57	54.00	-6.43	AV	Horizontal
7206.813	58.56	-0.96	57.6	74.00	-16.4	Pk	Horizontal
7206.813	45.14	-0.96	44.18	54.00	-9.82	AV	Horizontal
	1	Mid Char	nnel (2440 MHz	2)-Above 1	G		
4880.000	64.73	-3.67	61.06	74.00	-12.94	Pk	Vertical
4880.000	49.28	-3.67	45.61	54.00	-8.39	AV	Vertical
7320.000	58.12	-0.82	57.30	74.00	-16.70	Pk	Vertical
7320.000	43.41	-0.82	42.59	54.00	-11.41	AV	Vertical
4880.000	64.64	-3.67	60.97	74.00	-13.03	Pk	Horizontal
4880.000	45.56	-3.67	41.89	54.00	-12.11	AV	Horizontal
7320.000	58.67	-0.82	57.85	74.00	-16.15	Pk	Horizontal
7320.000	48.14	-0.82	47.32	54.00	-6.68	AV	Horizontal
	F	ligh Cha	nnel (2480MHz	:)- Above 1	G		
4960.000	58.23	-3.59	54.64	74.00	-19.36	Pk	Vertical
4960.000	45.24	-3.59	41.65	54.00	-12.35	AV	Vertical
7440.000	57.12	-0.68	56.44	74.00	-17.56	Pk	Vertical
7440.000	43.64	-0.68	42.96	54.00	-11.04	AV	Horizontal
4960.000	66.35	-3.59	62.76	74.00	-11.24	Pk	Horizontal
4960.000	46.47	-3.59	42.88	54.00	-11.12	AV	Horizontal
7440.000	59.35	-0.68	58.67	74.00	-15.33	Pk	Horizontal
7440.000	44.13	-0.68	43.45	54.00	-10.55	AV	Horizontal



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS	


4.1.1 TEST PROCEDURE

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS channel bandwidth.
- 3. 3 kHz ≤Set the RBW≤100 kHz.
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.




4.1.5 TEST RESULTS


EUT:	Mobile phone	Model Name :	JT Smart 3
Temperature :	25 ℃	Relative Humidity:	56%
Pressure:	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX Mode /CH00, CH19, CH39		

Page 25 of 37


Frequency	Power Density (dBm)	Limit (dBm)	Result
2402 MHz	-9.000	8	PASS
2440 MHz	-9.632	8	PASS
2480 MHz	-9.804	8	PASS







Page 26 of 37






5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result		
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS		

5.1.1 TEST PROCEDURE

- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.1.3 TEST RESULTS


EUT:	Mobile phone	Model Name :	JT Smart 3
Temperature :	25 ℃	Relative Humidity:	56%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX Mode /CH00, CH19, CH39		


Page 28 of 37

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
Low	2402	715.026	500	Pass
Middle	2440	717.415	500	Pass
High	2480	711.596	500	Pass











6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C					
Section	Test Item	Limit	Frequency Range (MHz)	Result	
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS	

6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

EUT:	Mobile phone	Model Name :	JT Smart 3
Temperature :	25 ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX Mode		

Test Channe	Frequency	Maximum Conducted Output Power (PK)	LIMIT
	(MHz)	(dBm)	dBm
CH00	2402	5.368	30
CH19	2440	5.608	30
CH39	2480	5.605	30



7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD

No deviation.

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



7.4 TEST RESULTS

EUT:	Mobile phone	Model Name :	JT Smart 3
Temperature:	25 ℃	Relative Humidity:	56%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V

Frequency Band	Delta Peak to band emission (dBc)	>Limit (dBc)	Result
Left-band	53.43	20	Pass
Right-band	55.57	20	Pass


Radiated band edge:


Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type	Comment
2390	48.34	-13.06	35.28	74	-38.72	peak	Vertical
2390	53.21	-13.06	40.15	74	-33.85	peak	Horizontal
2483.5	61.46	-12.78	48.68	74	-25.32	peak	Vertical
2483.5	62.65	-12.78	49.87	74	-24.13	peak	Horizontal

Note: Test method to see chapter 3.2. When PK value is lower than the Average value limit, average not record.

Page 34 of 37









8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party

shall be used with the device. **8.2 EUT ANTENNA** The EUT antenna is FPCB antenna. It comply with the standard requirement.



9. EUT TEST PHOTO



