



## Shenzhen Asia Test Technology Co., Ltd.

1/6, Bldg.8, Zhonghua Industrial City, Chuangye Rd.,  
Nanshan District, Shenzhen, Guangdong, China

Tel: +86-0755-23284990

Email: att@att-lab.com

Http: www.att-lab.cn

Report No. ATT-2014SZ1224025F

- Page 1 of 81 -

# FCC RADIO TEST REPORT

## FCC ID: 2ACULBTD-MINI2

**Product :** Bluetooth dongle

**Trade Name :** N/A

**Model Name :** BTD-MINI2

**Serial Model :** N/A

### Prepared for

Shenzhen Gembird Electronics Ltd

5th floor, Building B, Shifeng park, Huaning Road, Dalang Street, Longhua  
District, Shenzhen, China

### Prepared by

Shenzhen Asia Test Technology Co.,Ltd.

1/6, Bldg.8, Zhonghua Industrial City, Chuangye Rd., Nanshan District,  
Shenzhen, Guangdong, China

Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990  
Http: www.att-lab.net

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 2 of 81 -

## TEST RESULT CERTIFICATION

**Applicant's name** ..... Shenzhen Gembird Electronics Ltd  
Address ..... 5th floor, Building B, Shifeng park, Huaning Road, Dalang Street, Longhua District, Shenzhen, China  
**Manufacturer's Name** ..... Shenzhen Gembird Electronics Ltd  
Address ..... 5th floor, Building B, Shifeng park, Huaning Road, Dalang Street, Longhua District, Shenzhen, China

### Product description

Product name ..... Bluetooth dongle

Model and/or type reference ..... BTD-MINI2

Additional Model ..... N/A

**Standards** ..... FCC Part15.247

Test procedure ..... ANSI C63.4-2003

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

**Date of Test** .....

Date (s) of performance of tests ..... Dec. 24 2014 ~ Dec. 31 2014

Date of Issue ..... Dec. 31 2014

Test Result ..... **Pass**

Tested by: Eric Wang  
Eric Wang

Project Leader

Reviewed by: Jerry You  
Jerry You

Laboratory Supervisor

Approved by: Jack Yu  
Jack Yu

Technical Director



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 3 of 81 -

Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>6</b>
<b>1.1 TEST FACILITY</b>	<b>7</b>
<b>1.2 MEASUREMENT UNCERTAINTY</b>	<b>7</b>
<b>2 . GENERAL INFORMATION</b>	<b>8</b>
<b>2.1 GENERAL DESCRIPTION OF EUT</b>	<b>8</b>
<b>2.2 DESCRIPTION OF TEST MODES</b>	<b>10</b>
<b>2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING</b>	<b>10</b>
<b>2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	<b>11</b>
<b>2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)</b>	<b>12</b>
<b>2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	<b>13</b>
<b>3 . EMC EMISSION TEST</b>	<b>14</b>
<b>3.1 CONDUCTED EMISSION MEASUREMENT</b>	<b>14</b>
<b>3.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	<b>14</b>
<b>3.1.2 TEST PROCEDURE</b>	<b>15</b>
<b>3.1.3 DEVIATION FROM TEST STANDARD</b>	<b>15</b>
<b>3.1.4 TEST SETUP</b>	<b>15</b>
<b>3.1.5 EUT OPERATING CONDITIONS</b>	<b>15</b>
<b>3.1.6 TEST RESULTS</b>	<b>16</b>
<b>3.2 RADIATED EMISSION MEASUREMENT</b>	<b>18</b>
<b>3.2.1 RADIATED EMISSION LIMITS</b>	<b>18</b>
<b>3.2.2 TEST PROCEDURE</b>	<b>19</b>
<b>3.2.3 DEVIATION FROM TEST STANDARD</b>	<b>19</b>
<b>3.2.4 TEST SETUP</b>	<b>20</b>
<b>3.2.5 EUT OPERATING CONDITIONS</b>	<b>21</b>
<b>3.2.6 TEST RESULTS (BELOW 30 MHZ)</b>	<b>22</b>
<b>3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)</b>	<b>23</b>
<b>3.2.8 TEST RESULTS (ABOVE 1000 MHZ)</b>	<b>24</b>
<b>4 . NUMBER OF HOPPING CHANNEL</b>	<b>39</b>
<b>4.1 APPLIED PROCEDURES / LIMIT</b>	<b>39</b>
<b>4.1.1 TEST PROCEDURE</b>	<b>39</b>
<b>4.1.2 DEVIATION FROM STANDARD</b>	<b>39</b>



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 4 of 81 -

Table of Contents	Page
4.1.3 TEST SETUP	39
4.1.4 EUT OPERATION CONDITIONS	39
4.1.5 TEST RESULTS	40
<b>5 . AVERAGE TIME OF OCCUPANCY</b>	<b>41</b>
5.1 APPLIED PROCEDURES / LIMIT	41
5.1.1 TEST PROCEDURE	41
5.1.2 DEVIATION FROM STANDARD	41
5.1.3 TEST SETUP	42
5.1.4 EUT OPERATION CONDITIONS	42
5.1.5 TEST RESULTS	43
<b>6 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>49</b>
6.1 APPLIED PROCEDURES / LIMIT	49
6.1.1 TEST PROCEDURE	49
6.1.2 DEVIATION FROM STANDARD	49
6.1.3 TEST SETUP	49
6.1.4 EUT OPERATION CONDITIONS	49
6.1.5 TEST RESULTS	50
<b>7 . BANDWIDTH TEST</b>	<b>56</b>
7.1 APPLIED PROCEDURES / LIMIT	56
7.1.1 TEST PROCEDURE	56
7.1.2 DEVIATION FROM STANDARD	56
7.1.3 TEST SETUP	56
7.1.4 EUT OPERATION CONDITIONS	56
7.1.5 TEST RESULTS	57
<b>8 . PEAK OUTPUT POWER TEST</b>	<b>63</b>
8.1 APPLIED PROCEDURES / LIMIT	63
8.1.1 TEST PROCEDURE	63
8.1.2 DEVIATION FROM STANDARD	63
8.1.3 TEST SETUP	63
8.1.4 EUT OPERATION CONDITIONS	63
8.1.5 TEST RESULTS	64
<b>9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>69</b>



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 5 of 81 -

## Table of Contents

## Page

<b>9.1 DEVIATION FROM STANDARD</b>	<b>69</b>
<b>9.2 TEST SETUP</b>	<b>70</b>
<b>9.3 EUT OPERATION CONDITIONS</b>	<b>70</b>
<b>9.4 TEST RESULTS</b>	<b>71</b>
<b>10 . ANTENNA REQUIREMENT</b>	<b>79</b>
<b>10.1 STANDARD REQUIREMENT</b>	<b>79</b>
<b>10.2 EUT ANTENNA</b>	<b>79</b>
<b>11 . EUT TEST PHOTO</b>	<b>80</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 6 of 81 -

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 7 of 81 -

## 1.1 TEST FACILITY

Shenzhen STONE Testing Technology Co.,Ltd.

Add.: F/6, Bldg.12, Zhongxing Industrial City, Chuangye Rd., Nanshan District Shenzhen P.R. China

FCC Registration No.: 323508; IC Registration No.: 11043A

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 8 of 81 -

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth dongle												
Model Name	BTD-MINI2												
Serial Model	N/A												
Model Difference	N/A												
Product Description	<p>The EUT is a Bluetooth dongle</p> <table border="1"><tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr><tr><td>Modulation Type:</td><td>BT(2.1): GFSK BT EDR(2Mbps): 1/4-DQPSK BT EDR(3Mbps): 8-DPSK</td></tr><tr><td>Bit Rate of Transmitter</td><td>1Mbps/2Mbps/3Mbps</td></tr><tr><td>Number Of Channel</td><td>79 CH</td></tr><tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr><tr><td>Output Power(Conducted):</td><td>BT(1Mbps): 0.303 dBm BT EDR(2Mbps): -0.202dBm BT EDR(3Mbps): -0.21dBm</td></tr></table>	Operation Frequency:	2402~2480 MHz	Modulation Type:	BT(2.1): GFSK BT EDR(2Mbps): 1/4-DQPSK BT EDR(3Mbps): 8-DPSK	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps	Number Of Channel	79 CH	Antenna Designation:	Please see Note 3.	Output Power(Conducted):	BT(1Mbps): 0.303 dBm BT EDR(2Mbps): -0.202dBm BT EDR(3Mbps): -0.21dBm
Operation Frequency:	2402~2480 MHz												
Modulation Type:	BT(2.1): GFSK BT EDR(2Mbps): 1/4-DQPSK BT EDR(3Mbps): 8-DPSK												
Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps												
Number Of Channel	79 CH												
Antenna Designation:	Please see Note 3.												
Output Power(Conducted):	BT(1Mbps): 0.303 dBm BT EDR(2Mbps): -0.202dBm BT EDR(3Mbps): -0.21dBm												
	<p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>												
Channel List	Please refer to the Note 2.												
Adapter	N/A												
Battery	N/A												
Connecting I/O Port(s)	Please refer to the User's Manual												

#### Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 9 of 81 -

05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant .	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	2	BT Antenna



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 10 of 81 -

### 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

### 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF




# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2014SZ1224025F  
- Page 11 of 81 -

## 2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 12 of 81 -

## 2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Bluetooth dongle	Gembird	BTD-MINI2	N/A	EUT
E-2	Notebook	IBM	IBM-3426	N/A	
E-3	Adapter	IBM	IBM-0192000A	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8m	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 13 of 81 -

## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year
12	Test Receiver	R&S	FSU	550062	2014.06.07	2015.06.06	1 year
13	Cable 30-1000MHz	R&S	ATT-R01	201309R001	2014.06.08	2015.06.07	1 year
14	Cable 1-26.5GHz	R&S	ATT-R02	201309R048	2014.06.08	2015.06.07	1 year

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year
7	Cable 0.009-30MHz	R&S	ATT-C01	201309C006	2014.06.08	2015.06.07	1 year



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 14 of 81 -

## 3. EMC EMISSION TEST

### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 15 of 81 -


## 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

## 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

## 3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

## 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 16 of 81 -


## 3.1.6 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	DC 5V from PC AC 120V/60Hz	Test Mode :	Mode 4

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
						QP
0.202	32.91	10.44	43.35	63.52	-20.17	QP
0.202	31.03	10.44	41.47	53.52	-12.05	AVG
3.974	26.76	10.62	37.38	46	-8.62	AVG
4.494	36.04	10.64	46.68	56	-9.32	QP
16.99	31.46	10.71	42.17	60	-17.83	QP
17.11	21.78	10.71	32.49	50	-17.51	AVG

### Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2014SZ1224025F  
- Page 17 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V from PC AC 120V/60Hz	Test Mode :	Mode 4

Freq. (MHz)	Reading (dBuV)	Factor (dBuV)	Measurement (dBuV)	Limit (dBuV)	Over (dB)	Detector
0.202	36.23	10.43	46.66	63.52	-16.86	QP
0.202	30.26	10.43	40.69	53.52	-12.83	AVG
3.77	28.39	10.66	39.05	46	-6.95	AVG
4.242	36.3	10.65	46.95	56	-9.05	QP
17.05	31.27	10.74	42.01	60	-17.99	QP
17.18	22.26	10.74	33	50	-17	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 18 of 81 -

## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 19 of 81 -

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

## 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


## 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




## 3.2.4 TEST SETUP

### (A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 21 of 81 -

## (C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 22 of 81 -

### 3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	TX	Polarization :	---

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	P
--	--	--	--	P

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $20 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 23 of 81 -

## 3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Test Mode :	TX BDR-2402
Test Voltage :	DC 5V from PC AC 120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Vertical	145.85	25.36	9.14	34.5	43.5	-9	QP
Vertical	240.63	25.16	9.87	35.03	43.5	-8.47	QP
Vertical	379.16	24.28	11.74	36.02	46	-9.98	QP
Vertical	480.46	22.77	15.88	38.65	46	-7.35	QP
Vertical	521.85	15.743	19.48	35.223	46	-10.777	QP
Vertical	642.88	11.74	22.17	33.91	46	-12.09	QP
Horizontal	78.37	25.75	8.74	34.49	40	-5.51	QP
Horizontal	108.86	22.72	9.77	32.49	43.5	-11.01	QP
Horizontal	239.84	20.66	9.48	30.14	46	-15.86	QP
Horizontal	381.77	16.61	11.53	28.14	46	-17.86	QP
Horizontal	479.83	17.94	15.73	33.67	46	-12.33	QP
Horizontal	520.85	15.545	18.94	34.485	46	-11.515	QP



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 24 of 81 -

## 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010hPa	Test Mode :	TX BDR
Test Mode :	DC 5V from PC AC 120V/60Hz		

Low Channel (2402 MHz)-Above 1G							
Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detec- or Type	Polar (H/V)
4804.25	58.95	-3.64	55.31	74	-18.69	Pk	Vertical
4804.25	47.73	-3.64	44.09	54	-9.91	Av	Vertical
7206.56	55.13	-0.95	54.18	74	-19.82	Pk	Vertical
7206.56	46.36	-0.95	45.41	54	-8.59	Av	Vertical
4804.41	57.28	-3.64	53.64	74	-20.36	Pk	Horizontal
4804.41	46.84	-3.64	43.2	54	-10.8	Av	Horizontal
7206.29	52.77	-0.96	51.81	74	-22.19	Pk	Horizontal
7206.29	42.91	-0.96	41.95	54	-12.05	Av	Horizontal
Mid Channel (2441 MHz)-Above 1G							
4882.12	59.64	-3.67	55.97	74	-18.03	Pk	Vertical
4882.512	48.74	-3.67	45.07	54	-8.93	Av	Vertical
7324.12	52.84	-0.82	52.02	74	-21.98	Pk	Vertical
7324.412	41.83	-0.82	41.01	54	-12.99	Av	Vertical
4882.35	56.48	-3.67	52.81	74	-21.19	Pk	Horizontal
4882.35	42.74	-3.67	39.07	54	-14.93	Av	Horizontal
7324.26	52.54	-0.82	51.72	74	-22.28	Pk	Horizontal
7324.26	41.53	-0.82	40.71	54	-13.29	Av	Horizontal
High Channel (2480MHz)- Above 1G							
4960.22	58.63	-3.59	55.04	74	-18.96	Pk	Vertical
4960.22	43.63	-3.59	40.04	54	-13.96	Av	Vertical
7440.31	55.71	-0.68	55.03	74	-18.97	Pk	Vertical
7440.31	42.63	-0.68	41.95	54	-12.05	Av	Vertical
4960.34	58.27	-3.59	54.68	74	-19.32	Pk	Horizontal
4960.34	45.33	-3.59	41.74	54	-12.26	Av	Horizontal
7440.67	54.88	-0.68	54.2	74	-19.8	Pk	Horizontal
7440.67	42.45	-0.68	41.77	54	-12.23	Av	Horizontal

Note: All transmission rate has been test only the worst mode reported.

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 25 of 81 -

## Conducted Spurious Emissions at Antenna Port:


CH00 -1Mbps






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 26 of 81 -





## CH39 -1Mbps





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 27 of 81 -







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 28 of 81 -


## CH78 -1Mbps






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 29 of 81 -





## CH00 -2Mbps





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 30 of 81 -







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 31 of 81 -


## CH39 -2Mbps






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 32 of 81 -





## CH78 -2Mbps





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 33 of 81 -







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 34 of 81 -


## CH00 -3Mbps






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 35 of 81 -





## CH39 -3Mbps





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 36 of 81 -







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 37 of 81 -


## CH78 -3Mbps





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 38 of 81 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 39 of 81 -

## 4. NUMBER OF HOPPING CHANNEL

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW =100kHz
VB	VBW $\geq$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 100kHz, VBW=100kHz, Sweep time = Auto.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### 4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 40 of 81 -

## 4.1.5 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	Hopping Mode		

Number of Hopping Channel	79
---------------------------	----





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 41 of 81 -

## 5. AVERAGE TIME OF OCCUPANCY

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. A Period Time = (channel number)\*0.4  
DH1 Time Slot: Reading \* (1600/2)\*31.6/(channel number)  
DH3 Time Slot: Reading \* (1600/4)\*31.6/(channel number)  
DH5 Time Slot: Reading \* (1600/6)\*31.6/(channel number)

#### 5.1.2 DEVIATION FROM STANDARD


No deviation.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 42 of 81 -

### 5.1.3 TEST SETUP



### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 43 of 81 -

## 5.1.5 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2	
Temperature :	25 °C	Relative Humidity :	60%	
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz	
Test Mode :	DH5,2DH5,3DH5			


Data Packet	Frequency	Plus Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2402MHz	3.04	0.324	0.4
2DH5	2441MHz	3.06	0.326	0.4
3DH5	2480MHz	3.04	0.324	0.4





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 44 of 81 -



---

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 45 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	DH3,2DH3,3DH3		

Data Packet	Frequency	Plus Duration (ms)	Dwell Time (s)	Limits (s)
DH3	2402MHz	1.675	0.278	0.4
2DH3	2441MHz	1.688	0.280	0.4
3DH3	2480MHz	1.663	0.266	0.4







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 46 of 81 -

## CH39-2DH3



## CH79-3DH3






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 47 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	DH1,2DH1,3DH1		


Data Packet	Frequency	Plus Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2402MHz	0.425	0.136	0.4
2DH1	2441MHz	0.425	0.136	0.4
3DH1	2480MHz	0.425	0.136	0.4





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 48 of 81 -





## 6. HOPPING CHANNEL SEPARATION MEASUREMENT

### 6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised for channel separation measurement.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.



# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2014SZ1224025F  
- Page 50 of 81 -

## 6.1.5 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.005	Complies
2441 MHz	1.004	Complies
2480 MHz	1.012	Complies


Ch. Separation Limits: >20dB bandwidth





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 51 of 81 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 52 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.005	Complies
2441 MHz	1.012	Complies
2480 MHz	1.020	Complies


Ch. Separation Limits: >2/3 of 20dB bandwidth





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 53 of 81 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 54 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.020	Complies
2441 MHz	1.013	Complies
2480 MHz	1.010	Complies


Ch. Separation Limits: >2/3 of 20dB bandwidth





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 55 of 81 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 56 of 81 -

## 7. BANDWIDTH TEST

### 7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 57 of 81 -

## 7.1.5 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	885.805	PASS
2441 MHz	938.510	PASS
2480 MHz	937.215	PASS





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 58 of 81 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 59 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00 / CH39 /C78(2Mbps)		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.134	PASS
2441 MHz	1.116	PASS
2480 MHz	1.153	PASS





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 60 of 81 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 61 of 81 -

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00 / CH39 /C78(3Mbps)		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.197	PASS
2441 MHz	1.191	PASS
2480 MHz	1.195	PASS





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 62 of 81 -



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 63 of 81 -

## 8. PEAK OUTPUT POWER TEST

### 8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	0.125 w or 1w	2400-2483.5	PASS

#### 8.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel  
 $VBW \geq RBW$

Sweep = auto


Detector function = peak

Trace = max hold

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 64 of 81 -

## 8.1.5 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	0.158	20.96
CH39	2441	0.303	20.96
CH78	2480	-0.258	20.96
2Mbps			
CH00	2402	-0.202	20.96
CH39	2441	-0.24	20.96
CH78	2480	-0.759	20.96
3Mbps			
CH00	2402	-0.82	20.96
CH39	2441	-0.21	20.96
CH78	2480	-0.5	20.96





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2014SZ1224025F  
- Page 65 of 81 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2014SZ1224025F  
- Page 66 of 81 -





# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT-2014SZ1224025F  
- Page 67 of 81 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 68 of 81 -





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 69 of 81 -

## 9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

### APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 9.1 DEVIATION FROM STANDARD


No deviation.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 70 of 81 -

### 9.2 TEST SETUP



### 9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 71 of 81 -

### 9.4 TEST RESULTS

EUT :	Bluetooth dongle	Model Name :	BTD-MINI2
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from PC AC 120V/60Hz

Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
1Mbps Non-hopping			
Left-band	47.2	20	Pass
Right-band	47.74	20	Pass
2Mbps Non-hopping			
Left-band	46.71	20	Pass
Right-band	47.64	20	Pass
3Mbps Non-hopping			
Left-band	46.49	20	Pass
Right-band	45.94	20	Pass
1Mbps hopping			
Left-band	46.47	20	Pass
Right-band	46.99	20	Pass
2Mbps hopping			
Left-band	46.53	20	Pass
Right-band	45.57	20	Pass
3Mbps hopping			
Left-band	45.98	20	Pass
Right-band	45.98	20	Pass



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 72 of 81 -

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment
1Mbps Non-hopping							
2390	54.85	-8.67	46.18	54	-7.82	peak	Vertical
2390	51.38	-8.67	42.71	54	-11.29	peak	Horizontal
2483.5	52.77	-7.84	44.93	54	-9.07	peak	Vertical
2483.5	50.73	-7.84	42.89	54	-11.11	peak	Horizontal
2Mbps Non-hopping							
2390	53.85	-8.67	45.18	54	-8.82	peak	Vertical
2390	52.18	-8.67	43.51	54	-10.49	peak	Horizontal
2483.5	53.85	-7.84	46.01	54	-7.99	peak	Vertical
2483.5	54.48	-7.84	46.64	54	-7.36	peak	Horizontal
3Mbps Non-hopping							
2390	52.74	-8.67	44.07	54	-9.93	peak	Vertical
2390	50.36	-8.67	41.69	54	-12.31	peak	Horizontal
2483.5	49.48	-7.84	41.64	54	-12.36	peak	Vertical
2483.5	51.567	-7.84	43.727	54	-10.273	peak	Horizontal



Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average didn't record.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 73 of 81 -

## 1Mbps: Band Edge, Left Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 74 of 81 -

## 1Mbps: Band Edge, Right Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 75 of 81 -

## 2Mbps: Band Edge, Left Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 76 of 81 -

## 2Mbps: Band Edge, Right Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 77 of 81 -

## 3Mbps: Band Edge, Left Side







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 78 of 81 -

## 3Mbps: Band Edge, Right Side





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2014SZ1224025F  
- Page 79 of 81 -

## 10. ANTENNA REQUIREMENT

### 10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 10.2 EUT ANTENNA

The EUT antenna is Built-in antenna. It comply with the standard requirement.