



FCC Test Report

APPLICANT : Hi-P Electronics Pte Ltd
EQUIPMENT : Mobile Phone
BRAND NAME : Hi-P
MODEL NAME : H450R
FCC ID : 2ACUZH450R
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on May 14, 2015 and testing was completed on Jun. 11, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2009 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Louis Wu / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.
1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION.....	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification subjective to this standard.....	6
1.5. Modification of EUT	6
1.6. Test Location.....	7
1.7. Applicable Standards	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1. Test Mode	8
2.2. Connection Diagram of Test System	10
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup	12
3. TEST RESULT.....	13
3.1. Test of AC Conducted Emission Measurement	13
3.2. Test of Radiated Emission Measurement	19
4. LIST OF MEASURING EQUIPMENT.....	23
5. UNCERTAINTY OF EVALUATION	24

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.26 dB at 0.520 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.03 dB at 240.060 MHz for Peak



1. General Description

1.1. Applicant

Hi-P Electronics Pte Ltd

12 Ang Mo Kio Street 64, #03-02, UE BizHub Central Blk A, Singapore 569088

1.2. Manufacturer

Hi-P Electronics Technology Co Ltd (Suzhou)

No.86 Liu Feng Road, Wu Zhong District, Jiangsu China Suzhou: 215128

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Hi-P
Model Name	H450R
FCC ID	2ACUZH450R
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE
IMEI Code	Conduction: 004402800006292 Radiation: 004402800006276
HW Version	A850-03A
SW Version	A850_03A_HI-P_FWVGA_BAND245_V002_20150512_1200
EUT Stage	Pre-Production

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900 : 1850.2 MHz ~ 1909.8MHz WCDMA Band V : 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II : 1852.4 MHz ~ 1907.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850 : 869.2 MHz ~ 893.8 MHz GSM1900 : 1930.2 MHz ~ 1989.8 MHz WCDMA Band V : 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GPS : 1.57542 GHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GPS: PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: QPSK (Uplink) HSDPA / DC-HSDAP: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM(Downlink Only) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GPS : BPSK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.



1.6. Test Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595
Test Site No.	Sporton Site No.
	CO01-SZ

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-SZ	831040

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2009

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2009 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Note 1
2.	Data application transferred mode (EUT connected with notebook)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Abbreviations:

- EMI AC: AC conducted emissions
- EMI RE \geq 1G: EUT radiated emissions \geq 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz

Note 1: Testing for this mode is not required or not the worst case.

Remark: For signal above 1GHz, the worst case was test item 2.




Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera<Fig.1> Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4<Fig.1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.2>
Radiated Emissions < 1GHz	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera<Fig.1> Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + MPEG4<Fig.1> Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.2>
Radiated Emissions \geq 1GHz	2	Mode 1: WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx<Fig.2>


Remark:

1. The worst case of AC is mode 1 and the USB Link mode of AC is mode 3, the test data of these modes were reported.
2. The worst case of RE < 1G is mode 3; only the test data of this mode was reported.
3. Link with Notebook means data application transferred mode between EUT and Notebook.

2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	E540	PRC4	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	N/A
5.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
6.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
7.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
8.	iPod	Apple	A1199	FCC DoC	Unshielded, 1.2 m	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Execute "Video Player" to play MPEG4 files.
3. Turn on camera to capture images.
4. Turn on GPS function to make the EUT receive continuous signals from GPS station.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup







3.1.5 Test Result of AC Conducted Emission











3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission





Test Mode :	Mode 3	Temperature :	23~25°C																																																																																																																																																																													
Test Engineer :	Gavin Zhang	Relative Humidity :	48~52%																																																																																																																																																																													
Test Distance :	3m	Polarization :	Vertical																																																																																																																																																																													
Function Type :	WCDMA Band V Idle + Bluetooth Idle + WLAN Idle + USB Cable (Data Link with Notebook) + Earphone + GPS Rx																																																																																																																																																																															
<p>Level (dBuV/m)</p> <p>Date: 2015-06-11</p> <p>FCC CLASS-B</p> <p>FCC CLASS-B (AVG)</p> <p>Frequency (MHz)</p>																																																																																																																																																																																
<p>Site : 03CH01-SZ Condition : FCC CLASS-B 3m LF_ANT_141107 VERTICAL Project : (FC) 551401 Mode : Mode 3 IMEI : 004402800006276</p> <table border="1"> <thead> <tr> <th></th> <th>Over Limit</th> <th>Limit</th> <th>Read</th> <th>Antenna</th> <th>Cable</th> <th>Preamp</th> <th>A/Pos</th> <th>T/Pos</th> <th>Remark</th> </tr> <tr> <th>Freq</th> <th>Level</th> <th>Limit</th> <th>Line</th> <th>Level</th> <th>Factor</th> <th>Loss</th> <th>Factor</th> <th></th> <th></th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV</th> <th>dB/m</th> <th>dB</th> <th>dB</th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>48.09</td> <td>26.30</td> <td>-13.70</td> <td>40.00</td> <td>40.48</td> <td>10.74</td> <td>1.06</td> <td>25.98</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>2</td> <td>166.08</td> <td>28.50</td> <td>-15.00</td> <td>43.50</td> <td>39.93</td> <td>12.00</td> <td>2.00</td> <td>25.43</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>3</td> <td>206.85</td> <td>31.85</td> <td>-11.65</td> <td>43.50</td> <td>43.13</td> <td>11.71</td> <td>2.25</td> <td>25.24</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>4</td> <td>479.90</td> <td>36.20</td> <td>-9.80</td> <td>46.00</td> <td>40.34</td> <td>18.59</td> <td>3.50</td> <td>26.23</td> <td>100</td> <td>0 Peak</td> </tr> <tr> <td>5</td> <td>762.00</td> <td>33.40</td> <td>-12.60</td> <td>46.00</td> <td>33.50</td> <td>21.67</td> <td>4.48</td> <td>26.25</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>6</td> <td>881.70</td> <td>39.17</td> <td>-6.83</td> <td>46.00</td> <td>38.44</td> <td>21.77</td> <td>4.89</td> <td>25.93</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>7</td> <td>960.10</td> <td>38.41</td> <td>-15.59</td> <td>54.00</td> <td>37.40</td> <td>21.36</td> <td>5.06</td> <td>25.41</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>8</td> <td>2974.00</td> <td>42.55</td> <td>-31.45</td> <td>74.00</td> <td>28.55</td> <td>33.07</td> <td>9.85</td> <td>28.92</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>9</td> <td>4192.00</td> <td>40.42</td> <td>-33.58</td> <td>74.00</td> <td>22.66</td> <td>34.02</td> <td>12.19</td> <td>28.45</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>10</td> <td>6588.00</td> <td>43.27</td> <td>-30.73</td> <td>74.00</td> <td>20.30</td> <td>36.27</td> <td>14.45</td> <td>27.75</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>11</td> <td>8696.00</td> <td>43.84</td> <td>-30.16</td> <td>74.00</td> <td>16.86</td> <td>36.44</td> <td>16.61</td> <td>26.07</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>12</td> <td>10160.00</td> <td>45.33</td> <td>-28.67</td> <td>74.00</td> <td>14.53</td> <td>38.23</td> <td>17.76</td> <td>25.19</td> <td>---</td> <td>--- Peak</td> </tr> <tr> <td>13</td> <td>12714.00</td> <td>46.27</td> <td>-27.73</td> <td>74.00</td> <td>12.67</td> <td>39.17</td> <td>18.63</td> <td>24.20</td> <td>120</td> <td>50 Peak</td> </tr> </tbody> </table>		Over Limit	Limit	Read	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Level	Factor	Loss	Factor			MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	1	48.09	26.30	-13.70	40.00	40.48	10.74	1.06	25.98	---	--- Peak	2	166.08	28.50	-15.00	43.50	39.93	12.00	2.00	25.43	---	--- Peak	3	206.85	31.85	-11.65	43.50	43.13	11.71	2.25	25.24	---	--- Peak	4	479.90	36.20	-9.80	46.00	40.34	18.59	3.50	26.23	100	0 Peak	5	762.00	33.40	-12.60	46.00	33.50	21.67	4.48	26.25	---	--- Peak	6	881.70	39.17	-6.83	46.00	38.44	21.77	4.89	25.93	---	--- Peak	7	960.10	38.41	-15.59	54.00	37.40	21.36	5.06	25.41	---	--- Peak	8	2974.00	42.55	-31.45	74.00	28.55	33.07	9.85	28.92	---	--- Peak	9	4192.00	40.42	-33.58	74.00	22.66	34.02	12.19	28.45	---	--- Peak	10	6588.00	43.27	-30.73	74.00	20.30	36.27	14.45	27.75	---	--- Peak	11	8696.00	43.84	-30.16	74.00	16.86	36.44	16.61	26.07	---	--- Peak	12	10160.00	45.33	-28.67	74.00	14.53	38.23	17.76	25.19	---	--- Peak	13	12714.00	46.27	-27.73	74.00	12.67	39.17	18.63	24.20	120	50 Peak			
	Over Limit	Limit	Read	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																							
Freq	Level	Limit	Line	Level	Factor	Loss	Factor																																																																																																																																																																									
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																							
1	48.09	26.30	-13.70	40.00	40.48	10.74	1.06	25.98	---	--- Peak																																																																																																																																																																						
2	166.08	28.50	-15.00	43.50	39.93	12.00	2.00	25.43	---	--- Peak																																																																																																																																																																						
3	206.85	31.85	-11.65	43.50	43.13	11.71	2.25	25.24	---	--- Peak																																																																																																																																																																						
4	479.90	36.20	-9.80	46.00	40.34	18.59	3.50	26.23	100	0 Peak																																																																																																																																																																						
5	762.00	33.40	-12.60	46.00	33.50	21.67	4.48	26.25	---	--- Peak																																																																																																																																																																						
6	881.70	39.17	-6.83	46.00	38.44	21.77	4.89	25.93	---	--- Peak																																																																																																																																																																						
7	960.10	38.41	-15.59	54.00	37.40	21.36	5.06	25.41	---	--- Peak																																																																																																																																																																						
8	2974.00	42.55	-31.45	74.00	28.55	33.07	9.85	28.92	---	--- Peak																																																																																																																																																																						
9	4192.00	40.42	-33.58	74.00	22.66	34.02	12.19	28.45	---	--- Peak																																																																																																																																																																						
10	6588.00	43.27	-30.73	74.00	20.30	36.27	14.45	27.75	---	--- Peak																																																																																																																																																																						
11	8696.00	43.84	-30.16	74.00	16.86	36.44	16.61	26.07	---	--- Peak																																																																																																																																																																						
12	10160.00	45.33	-28.67	74.00	14.53	38.23	17.76	25.19	---	--- Peak																																																																																																																																																																						
13	12714.00	46.27	-27.73	74.00	12.67	39.17	18.63	24.20	120	50 Peak																																																																																																																																																																						



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2015	Jun. 11, 2015	May 25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz; Max 30dBm	Sep. 25, 2014	Jun. 11, 2015	Sep. 24, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Nov. 07, 2014	Jun. 11, 2015	Nov. 06, 2015	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Oct. 15, 2014	Jun. 11, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz / 30 dB	Jan 28, 2015	Jun. 11, 2015	Jan 27, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 28, 2015	Jun. 11, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 05, 2015	Jun. 11, 2015	May 04, 2016	Radiation (03CH01-SZ)
EMI Receiver	R&S	ESCI7	100724	9kHz~3GHz	Jan. 28, 2015	May 18, 2015	Jan. 27, 2016	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	103892	9kHz~30MHz	Feb. 02, 2015	May 18, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	AN3016	16850	9kHz~30MHz	Feb. 02, 2015	May 18, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	61602000089 1	100Vac~250Vac	Sep. 29, 2014	May 18, 2015	Sep. 28, 2015	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 24, 2014	May 18, 2015	Oct. 23, 2015	Conduction (CO01-SZ)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.9dB
---	-------