FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.247

Report Reference No...... A15N0166217-BLE

FCC ID.....: 2ACWO-MT7

Compiled by

(position+printed name+signature)..: File administrators Tony Li

Supervised by

(position+printed name+signature)..: Technique principal Robin Fang

Approved by

(position+printed name+signature)..: Manager Andy Zhang

Date of issue...... Nov,25 2015

Representative Laboratory Name: Shenzhen CTL Electron Technology Co., Ltd.

community, Guanlan, Baoan, Shenzhen, China

Testing Laboratory Name...... Dongguan Dongdian Testing Service Co.,Ltd

Dongguan City, Guangdong Province, China

Applicant's name...... AURA TECHNOLOGY LIMTED

Address FLAT/RM810, Star House, 3 Salisbury Road, Tsimshatsui,

Hong Kong

Test specification:

Standard FCC Part 15.247: Operation within the bands 902-928 MHz,

2400-2483.5 MHz and 5725-5850 MHz

TRF Originator...... Shenzhen CTL Electron Technology Co., Ltd.

Master TRF...... Dated 2012-06

Shenzhen CTL Electron Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electron Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electron Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description TELPAD

Trade Mark /

Model/Type reference..... MT7

Listed Models /

Manufacturer SHENZHEN KWANG SUNG ELECTRONICS CO.,LTD

Modulation Type GFSK

Operation Frequency...... From 2402MHz to 2480MHz

Rating DC 3.70V

Hardware version V01.00.22

Software version: V01

Result..... PASS

Page 2 of 48 Report No.: A15N0166217-BLE

TEST REPORT

Test Report No. :	A15N0166217-BLE	Nov 25, 2015
	A 13N0 1002 17-DLL	Date of issue

Equipment under Test : TELPAD

Model /Type : MT7

Listed Models : /

Applicant : AURA TECHNOLOGY LIMTED

Address : FLAT/RM810, Star House, 3 Salisbury Road, Tsimshatsui,

Hong Kong

Manufacturer : SHENZHEN KWANG SUNG ELECTRONICS CO.,LTD

Address : Shitoushan Industrial Zone, Shi Yan Town, Baoan District,

Shenzhen, PRC

Test Result:	PASS

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revison History

Revision	Issue Date	Revisions	Revised By
00	2015-11-25	Initial Issue	Andy Zhang

Contents

Equipment Under Test 7 Short description of the Equipment under Test (EUT) 7 EUT operation mode 8 Block Diagram of Test Setup 8 Related Submittal(s) / Grant (s) 8 Modifications 8 NOTE 9 TEST ENVIRONMENT 1 Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions <	General	Remarks	6
Short description of the Equipment under Test (EUT) 7 EUT operation mode 8 Block Diagram of Test Setup 8 Related Submittal(s) / Grant (s) 8 Modifications 8 NOTE 9 TEST ENVIRONMENT 1 Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF C	Product	Description	6
### EUT operation mode ### Block Diagram of Test Setup ### 8 Related Submittal(s) / Grant (s) ### 8 Modifications ### 8 Modifications ### 8 MOTE ### 9 ### TEST ENVIRONMENT ### 1	Equipm	ent Under Test	7
Block Diagram of Test Setup 8 Related Submittal(s) / Grant (s) 8 8 Modifications 8 8 NOTE 9 9 TEST ENVIRONMENT	Short de	scription of the Equipment under Test (EUT)	7
Related Submittal(s) / Grant (s) 8 Modifications 8 NOTE 9 TEST ENVIRONMENT 1 Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4			8
Modifications 8 NOTE 9 TEST ENVIRONMENT 1 Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4			
NOTE 9 TEST ENVIRONMENT 1 Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4			
TEST ENVIRONMENT 1 Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4	Modifica	itions	
Address of the test laboratory 10 Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4	NOTE		9
Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4	TEST	ENVIRONMENT	10
Test Facility 10 Environmental conditions 10 Test Description 10 Statement of the measurement uncertainty 11 Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4	Addrose	of the test laboratory	10
Environmental conditions Test Description Statement of the measurement uncertainty Equipments Used during the Test TEST CONDITIONS AND RESULTS 4.1. AC Power Conducted Emission 4.2. Radiated Emission 4.3. Duty Cycle 4.4. Maximum Peak Output Power 4.5. Power Spectral Density 4.6. 6dB Bandwidth 4.7. Band-edge measurements for radiated emissions 4.8. Band-edge measurements for RF conducted emissions 4.9. Spurious RF Conducted Emission 4.10. Antenna Requirement.			
Test Description Statement of the measurement uncertainty Equipments Used during the Test TEST CONDITIONS AND RESULTS 4.1. AC Power Conducted Emission 4.2. Radiated Emission 4.3. Duty Cycle 4.4. Maximum Peak Output Power 4.5. Power Spectral Density 4.6. 6dB Bandwidth 4.7. Band-edge measurements for radiated emissions 4.8. Band-edge measurements for RF conducted emissions 4.9. Spurious RF Conducted Emission 4.10. Antenna Requirement 4.10. Antenna Requirement 4.11. AC Power Conducted Emission 4.12. Test Conducted Emission 4.13. Duty Cycle 4.4. Maximum Peak Output Power 4.5. Power Spectral Density 4.6. Godb Bandwidth 4.7. Band-edge measurements for radiated emissions 4.8. Band-edge measurements for RF conducted emissions 4.9. Spurious RF Conducted Emission 4.10. Antenna Requirement			. •
Statement of the measurement uncertainty Equipments Used during the Test TEST CONDITIONS AND RESULTS 4.1. AC Power Conducted Emission			
Equipments Used during the Test 12 TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4			11
TEST CONDITIONS AND RESULTS 1 4.1. AC Power Conducted Emission 1 4.2. Radiated Emission 1 4.3. Duty Cycle 2 4.4. Maximum Peak Output Power 2 4.5. Power Spectral Density 2 4.6. 6dB Bandwidth 2 4.7. Band-edge measurements for radiated emissions 3 4.8. Band-edge measurements for RF conducted emissions 3 4.9. Spurious RF Conducted Emission 3 4.10. Antenna Requirement 4			12
4.1. AC Power Conducted Emission			
4.2. Radiated Emission			
4.2.Radiated Emission.14.3.Duty Cycle24.4.Maximum Peak Output Power.24.5.Power Spectral Density24.6.6dB Bandwidth24.7.Band-edge measurements for radiated emissions34.8.Band-edge measurements for RF conducted emissions34.9.Spurious RF Conducted Emission34.10.Antenna Requirement4	TEST	CONDITIONS AND RESULTS	13
4.3.Duty Cycle24.4.Maximum Peak Output Power24.5.Power Spectral Density24.6.6dB Bandwidth24.7.Band-edge measurements for radiated emissions34.8.Band-edge measurements for RF conducted emissions34.9.Spurious RF Conducted Emission34.10.Antenna Requirement4			
4.4. Maximum Peak Output Power	4.1.	AC Power Conducted Emission	13
4.5. Power Spectral Density	4.1. 4.2.	AC Power Conducted Emission	13
4.6. 6dB Bandwidth	4.1. 4.2. 4.3.	AC Power Conducted Emission	13 18 23
4.7. Band-edge measurements for radiated emissions	4.1. 4.2. 4.3. 4.4.	AC Power Conducted Emission Radiated Emission Duty Cycle Maximum Peak Output Power	13 18 23
4.8. Band-edge measurements for RF conducted emissions	4.1. 4.2. 4.3. 4.4. 4.5.	AC Power Conducted Emission	
4.9. Spurious RF Conducted Emission	4.1. 4.2. 4.3. 4.4. 4.5. 4.6.	AC Power Conducted Emission Radiated Emission Duty Cycle Maximum Peak Output Power Power Spectral Density 6dB Bandwidth	
4.10. Antenna Requirement4	4.1. 4.2. 4.3. 4.4. 4.5. 4.6. 4.7.	AC Power Conducted Emission	
	4.1. 4.2. 4.3. 4.4. 4.5. 4.6. 4.7. 4.8.	AC Power Conducted Emission	
TEST SETUP PHOTOS OF THE EUT 4	4.1. 4.2. 4.3. 4.4. 4.5. 4.6. 4.7. 4.8. 4.9.	AC Power Conducted Emission	
	4.1. 4.2. 4.3. 4.4. 4.5. 4.6. 4.7. 4.8. 4.9.	AC Power Conducted Emission	

1. TEST STANDARDS

The tests were performed according to following standards:

<u>FCC Rules Part 15.247</u>: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

<u>ANSI C63.10-2009</u>: American National Standard for Testing Unlicensed Wireless Devices KDB558074 D01 V03r03: Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Nov 15, 2015
Testing commenced on	:	Nov 15, 2015
Testing concluded on	:	Nov 24, 2015

2.2. Product Description

The **AURA TECHNOLOGY LIMTED**'s Model: MT7 or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

	ELPAD		
Model Number M ⁻			
	ACWO-MT7		
71	MSK for GSM/GPRS, 8-PSK for EDGE,QPSK for UMTS		
J ₁	ternal		
UMTS Operation Frequency Band De	evice supported UMTS FDD Band V		
	EE 802.11b:2412-2462MHz		
WLAN FCC Operation frequency	IEEE 802.11g:2412-2462MHz		
' ' IE	EE 802.11n HT20:2412-2462MHz		
	EE 802.11n HT40:2422-2452MHz		
	02MHz-2480MHz		
	elease 8		
HSUPA Release Version Re	elease 6		
DC-HSUPA Release Version No	ot Supported		
WCDMA Release Version R9	99		
	EE 802.11b: DSSS(CCK,DQPSK,DBPSK)		
WLAN FCC Modulation Type	EE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK)		
'' IE	EE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)		
	EE 802.11n HT40: OFDM (64QAM, 16QAM, QPSK,BPSK)		
	FSK,8DPSK,π/4DQPSK(BT 3.0+HS)		
	01.00.22		
Software version VC			
Android version Ar	ndroid 4.4.2		
GPS function Su	upported		
WLAN Su	upported 802.11b/802.11g/802.11n		
	upported BT 4.0/BT 3.0+HS		
	upported GSM/GPRS/EDGE		
GSM/EDGE/GPRS Power Class GS	SM850:Power Class 4/ PCS1900:Power Class 1		
GSM/EDGE/GPRS Operation	SM850 :824.2MHz-848.8MHz/PCS1900:1850.2MHz-1909.8MHz		
Frequency	SIVIOSU .024.2IVIHZ-040.0IVIHZ/PGS 1900.1050.2IVIHZ-1909.0IVIHZ		
GSM/EDGE/GPRS Operation	SM850/PCS1900/GPRS850/GPRS1900/EDGE850/EDGE1900		
Frequency Band	3101030/PC31900/GPR3630/GPR31900/EDGE630/EDGE1900		
GSM Release Version R9			
GPRS/EDGE Multislot Class GF	PRS/EDGE: Multi-slot Class 12		
Extreme temp. Tolerance -30	0°C to +50°C		
Extreme vol. Limits 3.4	40VDC to 4.20VDC (nominal: 3.70VDC)		
	ass B		

Page 7 of 48 Report No.: A15N0166217-BLE

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	٠.	0	120V / 60 Hz	0	115V / 60Hz
		0	12 V DC	0	24 V DC
		•	Other (specified in blank below))

DC 3.70V/DC 5.0V Adapter from AC 120V/60Hz

2.4. Short description of the Equipment under Test (EUT)

2.4.1 General Description

TELPAD is subscriber equipment in the WCDMA/GSM system. The HSPA/UMTS frequency band is Band V; The GSM/GPRS/EDGE frequency band includes GSM850 and GSM900 and DCS1800 and PCS1900, but only Band V and GSM850 and PCS1900 bands test data included in this report. The TELPAD implements such functions as RF signal receiving/transmitting, HSPA/UMTS and GSM/GPRS/EDGE protocol processing, voice, video MMS service, GPS and WIFI etc. Externally it provides micro SD card interface, earphone port (to provide voice service) and SIM card interface. It also provides Bluetooth module to synchronize data between a PC and the TELPAD, or to use the built-in modem of the phone to access the Internet with a PC, or to exchange data with other Bluetooth devices.

NOTE: Unless otherwise noted in the report, the functional boards installed in the units shall be selected from the below list, but not means all the functional boards listed below shall be installed in one unit.

2.4.2 Test Modes

2.4.2 Test Wodes	I —				
Test Case	Test Conditions				
Test Case	Configuration	Description			
DTS (6 dB) Bandwidth	Measurement Method	FCC KDB 558074 §8.2 Option 2			
	Test Environment	NTNV			
	EUT Configuration	GFSK_L, GFSK _M, GFSK _H			
	Measurement Method	FCC KDB 558074§9.1.2			
Maximum Peak Conducted Output	Test Environment	NTNV			
Power	Test Setup	Test Setup 1			
	EUT Configuration	GFSK_L, GFSK _M, GFSK _H			
Maximum Dawar Spectral Danaity	Measurement Method	FCC KDB 558074 §10.2 (peak PSD).			
Maximum Power Spectral Density Level	Test Environment	NTNV			
Level	EUT Configuration	GFSK_L, GFSK _M, GFSK _H			
	Measurement Method	FCC KDB 558074§11.0.			
Unwanted Emissions into Non-	Test Environment	NTNV			
Restricted Frequency Bands	Test Setup	Test Setup 1			
	EUT Configuration	GFSK_L, GFSK _M, GFSK _H			
	Measurement Method	FCC KDB 558074§12.2, Conducted			
Unwanted Emissions into Restricted	Measurement Method	(antenna-port).			
Frequency Bands (Conducted)	Test Environment	NTNV			
	EUT Configuration	GFSK_L, GFSK _M, GFSK _H			
Unwanted Emissions into	Measurement Method	FCC KDB			
Restricted		558074§12.1,Radiated(cabinet/case			
		emissions with			
		Impedance matching for antenna-port).			
	Test Environment	NTNV			
	EUT Configuration	GFSK_L, GFSK _M, GFSK _H			

Toot Coop	Test Conditions			
Test Case	Configuration	Description		
AC Power Line Conducted	Measurement Method	AC mains conducted.		
Emissions	Test Environment	NTNV		
	EUT Configuration	GFSK_M (Worst Conf.).		

2.4.3 Customized Configurations

#EUT Conf.	Signal Description	Operating Frequency
TM1_ Ch0	GFSK modulation	Ch No. 00/2402MHz
TM1_ Ch19	GFSK modulation	Ch No. 19/ 2440MHz
TM1_ Ch39	GFSK modulation	Ch No. 39/ 2480MHz

2.5. EUT operation mode


The application provider specific test software to control sample in continuous TX and RX by software for testing meet KDB558074 test requirement.

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 40 channels of EUT, and the test carried out at the lowest channel, middle channel and highest channel.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

2.6. Block Diagram of Test Setup

Fig. 2-1 Configuration of Tested System



Adapter:

MODEL:JY-05210

INPUT:100-240V~0.3A 50/60Hz 0.3A

OUTPUT: 5.0V DC 2.1A

♦ Shielded

2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2ACWO- MT7** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.8. Modifications

No modifications were implemented to meet testing criteria.

Page 9 of 48 Report No.: A15N0166217-BLE

2.9. NOTE

The values used in the test report maybe stringent than the declared.

Environment Parameter	Selected Values During Tests					
NTNV	Temperature	Voltage	Relative Humidity			
	Ambient	3.70VDC	Ambient			

1. The EUT is a TELPAD with GSM/UMTS/WLAN and Bluetooth function, The functions of the EUT listed as below:

	Test Standards	Reference Report
GSM	FCC Part 22H/ FCC Part 24 E	A15N0166217-GSM
UMTS	FCC Part 22H	A15N0166217-WCDMA
WLAN	FCC Part 15.247	A15N0166217-WLAN
Bluetooth-BR	FCC Part 15.247	A15N0166217-BR
Bluetooth-LE	FCC Part 15.247	A15N0166217-BLE
JBC	FCC Part 15 Subpart B	A15N0166217-JBC
SAR	FCC Per 47 CFR 2.1093(d)	A15N0166217-SAR

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Dongguan Dongdian Testing Service Co.,Ltd

No.17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 10288A-1

The 3m alternate test site of Dongguan Dongdian Testing Service Co.,Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 10288A-1 on May, 2012.

FCC-Registration No.: 270092

Dongguan Dongdian Testing Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 270092, Mar, 2015.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C			
Humidity:	30-60 %			
Atmospheric pressure:	950-1050mbar			

3.4. Test Description

	-									
Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	GFSK	 Lowest Middle Highest	GFSK	 Lowest Middle Highest	\boxtimes				complies
§15.247(e)	Power spectral density	GFSK	 Lowest Middle Highest	GFSK	☑ Lowest☑ Middle☑ Highest	\boxtimes				complies
§15.247(a)(1)	Spectrum bandwidth - 6 dB bandwidth	GFSK	☑ Lowest☑ Middle☑ Highest	GFSK	☑ Lowest☑ Middle☑ Highest	\boxtimes				complies
§15.247(b)(1)	Maximum output power	GFSK	 Lowest Middle Highest	GFSK	 Lowest Middle Highest					complies
§15.247(d)	Band edge compliance conducted	GFSK		GFSK	☑ Lowest☑ Highest	\boxtimes				complies
§15.205	Band edge compliance radiated	GFSK		GFSK		\boxtimes				complies
§15.247(d)	TX spurious emissions conducted	GFSK	 Lowest Middle Highest	GFSK	 Lowest Middle Highest	\boxtimes				complies
§15.247(d)	TX spurious	GFSK		GFSK		\boxtimes				complies

	emissions radiated		⊠ Middle ⊠ Highest					
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	\boxtimes		complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	GFSK	-/-	GFSK	-/-	\boxtimes		complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	GFSK	-/-	GFSK	-/-	\boxtimes		complies

Remark:

- 1. The measurement uncertainty is not included in the test result.
- 2. NA = Not Applicable; NP = Not Performed

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 " Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Dongguan Dongdian Testing Service Co.,Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Dongguan Dongdian Testing Service Co.,Ltd is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.14 dB	(1)
Radiated Emission	1~18GHz	2.56 dB	(1)
Radiated Emission	18-40GHz	3.90 dB	(1)
Conducted Disturbance	0.15~30MHz	2.44 dB	(1)
Conducted Power	9KHz~18GHz	0.60 dB	(1)
Power Spectral Density	9KHz~18GHz	1.20 dB	(1)
Spurious RF Conducted Emission	9KHz~40GHz	0.60 dB	(1)
Band Edge Compliance of RF Emission	9KHz~40GHz	0.60 dB	(1)
Occuiped Bandwidth	9KHz~40GHz	±1%	(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3.6. Equipments Used during the Test

Radia	ted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	462	2014/04/12	3 years
2	EMI TEST Receiver	Rohde&Schwarz	ESU8	100316	2015/10/21	1 years
3	EMI TEST Software	Audix	E3	6.111111	N/A	N/A
4	Horn Anternna	EMCO	3116	00060095	2014/04/12	3 years
5	Pre-Amplifer	er Rohde&Schwarz SCU-01		10049	2015/10/21	1 years
6	Pre-Amplifer	A.H.	PAM0-0118	360	2015/10/21	1 years
7	Pre-Amplifer	A.H.	PAM- 1840VH	562	2015/10/21	1 years
8	Double Ridged Horn Antenna	Rohde&Schwarz	HF907	100265	2014/04/12	3 years
9	Active Loop Antenna	Schwarz beck	FMZB1519	0.38	2014/04/12	3 years
11	TURNTABLE	MATURO	TT2.0		N/A	N/A
12	ANTENNA MAST	MATURO	TAM-4.0-P		N/A	N/A
13	Spectrum Analyzer	Rohde&Schwarz	FSU26	1166.1660.26	2015/10/21	1 years


Maximum Peak Output Power / 20dB Bandwidth / Number of hopping frequency& Time of Occupancy / Band										
Edge Compliance of RF Emission / Spurious RF Conducted Emission/ Frequency Separation										
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval				
1	Power Sensor	Rohde&Schwarz	NRP-Z81	102638	2015/10/28	1 years				
2	Spectrum Analyzer	Rohde&Schwarz	FSU26	1166.1660.26	2015/10/21	1 years				

AC Po	AC Power Conducted Emission												
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval							
1	Artificial Mains	Rohde&Schwarz	ENV216	101109	2015/10/22	1 years							
2	Artificial Mains	Rohde&Schwarz	ESH3-Z5	100309	2015/10/22	1 years							
3	EMI Test Receiver	Rohde&Schwarz	ESU8	100316	2015/10/22	1 years							
4	Pulse Limiter	Rohde&Schwarz	ESH3-Z2	101242	2015/10/22	1 years							
5	EMI TEST Software	Audix	E3	6.111111	N/A	N/A							

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC5V power from PC, the adapter of PC received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:


Eroguanav	Maximum RF Line Voltage (dBμV)								
Frequency (MHz)	CLA	SS A	CLASS B						
(IVITIZ)	Q.P.	Ave.	Q.P.	Ave.					
0.15 - 0.50	79	66	66-56*	56-46*					
0.50 - 5.00	73	60	56	46					
5.00 - 30.0	73	60	60	50					

^{*} Decreasing linearly with the logarithm of the frequency

TEST RESULTS


The AC Power Conducted Emission measurement are performed BT Link mode.

For AC 120V/60Hz from Power Adapter



Item	Freq	Read Level	LISN Factor	Cable Loss	Pulse Limiter	Result Level	Limit Line	Over Limit	Detector	Phase
		2010.	1 40101		Factor	2010.	0			
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)		
1	0.20	20.64	9.62	0.02	9.85	40.13	53.80	-13.67	Average	LINE
2	0.20	31.76	9.62	0.02	9.85	51.25	63.80	-12.55	QP	LINE
3	0.32	19.00	9.63	0.02	9.85	38.50	49.66	-11.16	Average	LINE
4	0.32	27.73	9.63	0.02	9.85	47.23	59.66	-12.43	QP	LINE
5	0.56	16.38	9.63	0.04	9.86	35.91	46.00	-10.09	Average	LINE
6	0.56	27.77	9.63	0.04	9.86	47.30	56.00	-8.70	QP	LINE
7	0.77	15.95	9.62	0.08	9.86	35.51	46.00	-10.49	Average	LINE
8	0.77	25.40	9.62	0.08	9.86	44.96	56.00	-11.04	QP	LINE
9	0.97	14.76	9.62	0.05	9.87	34.30	46.00	-11.70	Average	LINE
10	0.97	25.74	9.62	0.05	9.87	45.28	56.00	-10.72	QP	LINE


- 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
- 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.



Item	Freq	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)		
1	0.19	20.63	9.59	0.02	9.85	40.09	53.84	-13.75	Average	NEUTRAL
2	0.19	32.24	9.59	0.02	9.85	51.70	63.84	-12.14	QP	NEUTRAL
3	0.32	18.54	9.60	0.02	9.85	38.01	49.71	-11.70	Average	NEUTRAL
4	0.32	26.96	9.60	0.02	9.85	46.43	59.71	-13.28	QP	NEUTRAL
5	0.56	16.21	9.61	0.04	9.86	35.72	46.00	-10.28	Average	NEUTRAL
6	0.56	27.37	9.61	0.04	9.86	46.88	56.00	-9.12	QP	NEUTRAL
7	0.77	15.71	9.61	0.08	9.86	35.26	46.00	-10.74	Average	NEUTRAL
8	0.77	24.93	9.61	0.08	9.86	44.48	56.00	-11.52	QP	NEUTRAL
9	0.97	14.50	9.60	0.05	9.87	34.02	46.00	-11.98	Average	NEUTRAL
10	0.97	25.28	9.60	0.05	9.87	44.80	56.00	-11.20	QP	NEUTRAL


- 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
- 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.

For USB from PC



Item	Freq	Read Level	LISN Factor	Cable Loss	Pulse Limiter	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	Factor (dB)	(dBµV)	(dBµV)	(dB)		
1	0.20	20.62	9.59	0.02	9.85	40.08	53.80	-13.72	Average	NEUTRAL
2	0.20	34.01	9.59	0.02	9.85	53.47	63.80	-10.33	QP	NEUTRAL
3	0.26	15.87	9.60	0.02	9.85	35.34	51.51	-16.17	Average	NEUTRAL
4	0.26	25.24	9.60	0.02	9.85	44.71	61.51	-16.80	QP	NEUTRAL
5	0.32	16.63	9.60	0.02	9.85	36.10	49.66	-13.56	Average	NEUTRAL
6	0.32	24.57	9.60	0.02	9.85	44.04	59.66	-15.62	QP	NEUTRAL
7	0.45	14.82	9.61	0.03	9.87	34.33	46.89	-12.56	Average	NEUTRAL
8	0.45	23.22	9.61	0.03	9.87	42.73	56.89	-14.16	QP	NEUTRAL
9	0.56	14.66	9.61	0.04	9.86	34.17	46.00	-11.83	Average	NEUTRAL
10	0.56	24.67	9.61	0.04	9.86	44.18	56.00	-11.82	QP	NEUTRAL
11	0.78	15.55	9.61	0.08	9.86	35.10	46.00	-10.90	Average	NEUTRAL
12	0.78	23.45	9.61	0.08	9.86	43.00	56.00	-13.00	QP	NEUTRAL

- 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
- 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.




Item	Freq	Read	LISN	Cable	Pulse	Result	Limit	Over	Detector	Phase
		Level	Factor	Loss	Limiter Factor	Level	Line	Limit		
(Mark)	(MHz)	(dBµV)	(dB)	(dB)	(dB)	(dBµV)	(dBµV)	(dB)		
1	0.15	14.71	9.61	0.01	9.84	34.17	56.00	-21.83	Average	LINE
2	0.15	27.99	9.61	0.01	9.84	47.45	66.00	-18.55	QP	LINE
3	0.20	20.34	9.62	0.02	9.85	39.83	53.71	-13.88	Average	LINE
4	0.20	33.13	9.62	0.02	9.85	52.62	63.71	-11.09	QP	LINE
5	0.33	16.97	9.63	0.02	9.85	36.47	49.57	-13.10	Average	LINE
6	0.33	25.09	9.63	0.02	9.85	44.59	59.57	-14.98	QP	LINE
7	0.53	14.72	9.63	0.04	9.87	34.26	46.00	-11.74	Average	LINE
8	0.53	23.84	9.63	0.04	9.87	43.38	56.00	-12.62	QP	LINE
9	0.56	14.83	9.63	0.04	9.86	34.36	46.00	-11.64	Average	LINE
10	0.56	25.34	9.63	0.04	9.86	44.87	56.00	-11.13	QP	LINE
11	0.78	16.08	9.62	0.08	9.86	35.64	46.00	-10.36	Average	LINE
12	0.78	23.87	9.62	0.08	9.86	43.43	56.00	-12.57	QP	LINE

- 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
- 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
- 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz), Step size: 4 kHz, Scan time: auto.


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9KHz - 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane.

- 2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° C to 360°C to acquire the highest emissions from EUT.
- 3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4. Repeat above procedures until all frequency measurements have been completed.
- 5. The EUT minimum operation frequency was 32.768KHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9KHz to 25GHz.

6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Anternna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
	Peak Value: RBW=1MHz/VBW=3MHz,	
1GHz-40GHz	Sweep time=Auto	Peak
1GHZ-40GHZ	Average Value: RBW=1MHz/VBW=10Hz,	reak
	Sweep time=Auto	

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency	FS	RA	AF	CL	AG	Transd
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	(dB)	(dB)	(dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

Transd=AF +CL-AG

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: 1. We tested three positions and recorded worst case.

2. We tested BT Link mode for below 1G;


For 9KHz to 30MHz

Frequency (MHz)	Corrected Reading (dBµV/m)@3m	FCC Limit (dBµV/m) @3m	Over Limit (dB)	Detector
				QP

Remark:


- 1. Over Limit = Emission level Limit value
- 2. "---" states emission level at least lower than limit 20dB, so without recorded any values;

For 30MHz to 1000MHz



Item	Freq	Read Level	Antenna Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector	Polarization
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	(dBµV/m)	(dBµV/m)	(dB)		
1	41.28	17.47	14.00	1.00	32.47	40.00	-7.53	QP	VERTICAL
2	148.44	29.70	8.67	1.79	40.16	43.50	-3.34	QP	VERTICAL
3	287.99	20.92	14.25	2.67	37.84	46.00	-8.16	QP	VERTICAL
4	478.85	19.95	15.98	3.62	39.55	46.00	-6.45	QP	VERTICAL
5	742.26	18.64	19.26	4.50	42.40	46.00	-3.60	QP	VERTICAL

- 1. Result Level = Read Level + Antenna Factor + Cable loss.
- 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	148.44	25.60	8.67	1.79	36.06	43.50	-7.44	QP	HORIZONTAL
2	218.31	24.80	10.90	2.20	37.90	46.00	-8.10	QP	HORIZONTAL
3	239.99	25.86	11.70	2.32	39.88	46.00	-6.12	QP	HORIZONTAL
4	287.99	24.34	14.25	2.67	41.26	46.00	-4.74	QP	HORIZONTAL
5	651.94	14.23	18.40	4.21	36.84	46.00	-9.16	QP	HORIZONTAL
6	742.26	18.99	19.26	4.50	42.75	46.00	-3.25	QP	HORIZONTAL

- 1. Result Level = Read Level + Antenna Factor + Cable loss.
- 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
- 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

For 1GHz to 25GHz

Low Channel @ Channel 0 @ 2402 MHz

Itom	From	Read	Antenna	PRM	Cable	Result	Limit	Over		
Item (Mark)	Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Detector	Polarization
(IVIaIK)	(MHz)	(dBµV)	(dB/m)	dB	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
1	4804.00	42.47	35.40	29.13	12.07	48.27	74.00	-25.73	Peak	Horizontal
1	4804.00	29.36	35.40	29.13	12.07	35.16	54.00	-18.84	AV ^[1]	Horizontal
2	7206.00	43.10	37.22	29.68	15.18	50.74	74.00	-23.26	Peak	Horizontal
2	7206.00	28.97	37.22	29.68	15.18	36.61	54.00	-17.39	AV ^[1]	Horizontal

Item (Mark)	Freq (MHz)	Read Level	Antenna Factor	PRM Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector	Polarization
(iviairt)	(111112)	(dBµV)	(dB/m)	dB	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
1	4804.00	39.37	35.40	29.13	12.07	45.17	74.00	-28.83	Peak	Vertical
1	4804.00	26.48	35.40	29.13	12.07	32.28	54.00	-21.72	AV ^[1]	Vertical
2	7206.00	41.18	37.22	29.68	15.18	48.82	74.00	-25.18	Peak	Vertical
2	7206.00	27.51	37.22	29.68	15.18	35.15	54.00	-18.85	$AV^{\scriptscriptstyle{[1]}}$	Vertical

Middle Channel @ Channel 19 @ 2440 MHz

Item	Eroa	Read	Antenna	PRM	Cable	Result	Limit	Over		
	Freq	Level	Factor	Factor	Loss	Level	Line	Limit	Detector	Polarization
(Mark)	(MHz)	(dBµV)	(dB/m)	dB	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
1	4880.00	44.61	35.51	29.08	12.04	50.22	74.00	-23.78	Peak	Horizontal
1	4880.00	31.32	35.51	29.08	12.04	36.93	54.00	-17.07	AV ^[1]	Horizontal
2	7320.00	43.24	37.30	29.88	15.32	51.14	74.00	-22.86	Peak	Horizontal
2	7320.00	29.35	37.30	29.88	15.32	37.25	54.00	-16.75	AV ^[1]	Horizontal

Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over	Datastas	Delevinetiev
(Mark)	(MHz)	Level	Factor	Factor	Loss	Level	Line	Limit	Detector	Polarization
,	,	(dBµV)	(dB/m)	dB	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
1	4880.00	41.07	35.51	29.08	12.04	46.68	74.00	-27.32	Peak	Vertical
1	4880.00	28.30	35.51	29.08	12.04	33.91	54.00	-20.09	AV ^[1]	Vertical
2	7320.00	41.16	37.30	29.88	15.32	49.06	74.00	-24.94	Peak	Vertical
2	7320.00	28.95	37.30	29.88	15.32	36.85	54.00	-17.15	AV ^[1]	Vertical

High Channel @ Channel 39 @ 2480 MHz

Item	Freq	Read	Antenna	PRM	Cable	Result	Limit	Over		
(Mark)	(MHz)	Level	Factor	Factor	Loss	Level	Line	Limit	Detector	Polarization
(IVIaIK)	(IVITIZ)	(dBµV)	(dB/m)	dB	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
1	4960.00	44.28	35.64	29.04	12.02	49.70	74.00	-24.30	Peak	Horizontal
1	4960.00	31.10	35.64	29.04	12.02	36.52	54.00	-17.48	AV ^[1]	Horizontal
2	7440.00	43.78	37.37	30.12	15.60	52.13	74.00	-21.87	Peak	Horizontal
2	7440.00	29.31	37.37	30.12	15.60	37.66	54.00	-16.34	AV ^[1]	Horizontal

Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	4960.00	41.71	35.64	29.04	12.02	47.13	74.00	-26.87	Peak	Vertical
1	4960.00	28.66	35.64	29.04	12.02	34.08	54.00	-19.92	AV ^[1]	Vertical
2	7440.00	42.07	37.37	30.12	15.60	50.42	74.00	-23.58	Peak	Vertical
2	7440.00	28.99	37.37	30.12	15.60	37.34	54.00	-16.66	AV ^[1]	Vertical


REMARKS

- 1. Result Level = Read Level + Antenna Factor + Cable loss PRM Factor.
- 2. The other emission levels were very low against the limit.
- 3. Over Limit=Emission Level Limit.
- 4. The average measurement was not performed when the peak measured data under the limit of average detection.
- 5. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;
- 6. Average values was add Duty Cycle factor;

Page 23 of 48 Report No.: A15N0166217-BLE

4.3. Duty Cycle

TEST CONFIGURATION



LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternate procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle. Within this guidance document, the duty cycle refers to the fraction of time over which the transmitter is on and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than \pm 2 percent, otherwise the duty cycle is considered to be non-constant.

TEST PROCEDURE


- a. A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal.
- b. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set VBW ≥ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T ≤ 16.7 microseconds.)

TEST RESULTS

The Manufacturer provide engineer mode *#3646633#* cannot make BT-LE work at 100% continuous transmit;


Test Mode	Channel	Frequency (MHz)	Duty Cycle	Duty Cycle Factor (dB)
GFSK-BLE	0	2402	0.6111	-2.14
	19	2440	0.6393	-1.94
	39	2480	0.5806	-2.36

- Test results including cable loss;
- Duty Cycle Factor = 10*log (Duty Cycle)
- please refer to following plots;



4.4. Maximum Peak Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power,9.1.1.

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW ≥ DTS bandwidth.
- b) Set VBW \geq 3 × RBW.
- c) Set span ≥ 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.


LIMIT

The Maximum Peak Output Power Measurement is 30dBm.

TEST RESULTS


Test Mode	Channel	Frequency (MHz)	Measured Maximum Peak Power (dBm)	Limits (dBm)	Verdict
	0	2402	-2.14		
GFSK-BLE	19	2440	-1.76	30	PASS
	39	2480	-2.06		

- 1. Test results including cable loss;
- 2. please refer to following plots;



4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

- 1.Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2.Set the RBW =100 kHz.
- 3.Set the VBW =300 KHz.
- 4.Set the span to 1.5 times the DTS channel bandwidth.
- 5.Detector = peak.
- 6.Sweep time = auto couple.
- 7. Trace mode = \max hold.
- 8. Allow trace to fully stabilize.
- 9.Use the peak marker function to determine the maximum power level.
- 10.If measured value exceeds limit, reduce RBW(no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be 8 dBm.


LIMIT

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

TEST RESULTS


Test Mode	Channel	Frequency (MHz)	Measured Peak Power Spectral Density (dBm/100KHz)	Limits (dBm/3KHz)	Verdict
	0	2402	-3.43		
GFSK-BLE	19	2440	-3.02	8	PASS
	39	2480	-3.46		

- 1. Test results including cable loss;
- 2. please refer to following plots;



4.6. 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=100 KHz and VBW=300KHz. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB. According to KDB558074 D01 V03 for one of the following procedures may be used to determine the modulated DTS device signal bandwidth.

- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW) ≥ 3 RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


<u>LIMIT</u>

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Measured 6 dB Bandwidth (MHz)	Limits (MHz)	Verdict
	0	2402	0.7019		
GFSK-BLE	19	2440	0.6947	≥0.5000	PASS
	39	2480	0.6803		

- 1. Test results including cable loss;
- 2. please refer to following plots;



2480 MHz

4.7. Band-edge measurements for radiated emissions

TEST REQUIREMENT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

According to KDB 558074 D01 V03 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=10Hz for Peak detector.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.
- 6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
- 7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
- 8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- 9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
- 10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship: E = EIRP 20log D + 104.8

where:

 $E = electric field strength in dB\mu V/m$,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

- 11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
- 12. Compare the resultant electric field strength level to the applicable regulatory limit.
- 13. Perform radiated spurious emission test dures until all measured frequencies were complete.

LIMIT

Below -20dB of the highest emission level in operating band. Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)

TEST RESULTS

	GFSK – BLE								
Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Ground Reflection Factor (dB)	Covert Radiated E Level At 3m (dBuV/m)	Detector	Limit (dBuV/m)	Verdict		
2390.00	-48.53	0.00	0.00	48.73	Peak	74.00	PASS		
2390.00	-57.38	0.00	0.00	39.88	AV	54.00	PASS		
2402.05	-2.25	0.00	0.00	95.01	Peak		PASS		
2402.05	-23.20	0.00	0.00	74.06	AV		PASS		
2479.73	-2.16	0.00	0.00	95.10	Peak		PASS		
2479.73	-23.07	0.00	0.00	74.19	AV		PASS		
2483.50	-42.84	0.00	0.00	54.42	Peak	74.00	PASS		
2483.50	-50.66	0.00	0.00	46.60	AV	54.00	PASS		


Remark:

- 1. Test results including cable loss;
- 2. "---" means that the fundamental frequency not for 15.209 limits requirement.
- 3. Average Values additional Duty Cycle Factor;

Average Values = Average Reading Values - Duty Cycle Factor

Frequency (MHz)	Average Reading Values (dBm)	Duty Cycle Factor (dB)	Average Values (dBm)
2390.00	-59.52	-2.14	-57.38
2402.05	-25.34	-2.14	-23.20
2479.73	-25.43	-2.36	-23.07
2483.50	-53.02	-2.36	-50.66

4. please refer to following plots;




4.8. Band-edge measurements for RF conducted emissions

LIMIT

- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

TEST CONFIGURATION



TEST PROCEDURE


According to KDB 558074 D01 V03 for Antenna-port conducted measurement.

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge,
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.
- 6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Conductd Band-edge Emission (dBc)	Limits (dBc)	Verdict
GFSK-BLE	0	2402	<-20dBc	-20	DACC
Gran-BLE	39	2480	<-20dBc	-20	PASS

- 1. Test results including cable loss;
- "---" means that the fundamental frequency not for 15.209 limits requirement.
- 3. please refer to following plots;



4.9. Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2009 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequeny range from 9KHz to 26.5GHz.


<u>LIMIT</u>


- 1. Below -20dB of the highest emission level in operating band.
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.


TEST RESULTS


Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBc)	Limits (dBc)	Verdict
	0	2402	<-20dBc	-20	
GFSL-BLE	19	2440	<-20dBc	-20	PASS
	39	2480	<-20dBc	-20	

- 1. Test results including cable loss;
- 2. "---" means that the fundamental frequency not for 15.209 limits requirement.
- 3. please refer to following plots;









4.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refer ANSI C63.10 :2009 Section 11.9 Output power test procedure for DTS devices Radiated power refer to ANSI C63.10 :2009 Section 6.6.4 Radiated emissions tests.

Measurement parameters

Measurement parameter			
Detector:	Peak		
Sweep time:	Auto		
Resolution bandwidth:	1MHz		
Video bandwidth:	3MHz		
Trace-Mode:	Max hold		

Limits

FCC	IC				
Antenna Gain					
6 dBi					

Results

T_nom	V_{nom}	Lowest Channel 2402 MHz	Middle Channel 2440 MHz	Highest Channel 2480 MHz
	power [dBm] GFSK modulation	-2.16	-1.81	-2.12
	ower [dBm] GFSK modulation	-3.97	-3.03	-4.35
	[dBi] ulated	-1.81	-1.22	-2.23
Measuremer	nt uncertainty	± 0.60 dB (cond.) / ± 2.56 dB (rad.)		

Report No.: A15N0166217-BLE

5. Test Setup Photos of the EUT







6. External and Internal Photos of the EUT

External Photos

Report No.: A15N0166217-BLE








TELPAD















Report No.: A15N0166217-BLE


Internal Photos




GSM/UMTS Antenna


WLAN/BT/G PS Antenna














.....End of Report.....