

Job No.: 140812032GZU

Page: 1 of 2

FCC ID: 2ACX3-D033

**RF Exposure Compliance Requirement****1. Standard requirement**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

**(a) Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	F/300	6
1500-100000	--	--	5	6

**(b) Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	F/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

Job No.: 140812032GZU

Page: 2 of 2

FCC ID: 2ACX3-D033

**2. MPE Calculation Method**

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E=Electric Field (V/m)

P=Peak RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

**3. Calculated Result and Limit**

(1) 802.11b 11Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2412	2	19.89	97.50	0.39	1	Complies
2437	2	20.69	117.22	0.47	1	Complies
2462	2	21.41	138.36	0.55	1	Complies

(2) 802.11g 54Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2412	2	19.88	97.27	0.39	1	Complies
2437	2	20.74	118.58	0.47	1	Complies
2462	2	21.54	142.56	0.57	1	Complies

(3) 802.11n HT20 72.2Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2412	2	19.69	93.11	0.37	1	Complies
2437	2	20.42	110.15	0.44	1	Complies
2462	2	21.17	130.92	0.52	1	Complies

(4) 802.11n HT40 150Mbps data rate:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2422	2	19.80	95.50	0.38	1	Complies
2437	2	20.00	100.00	0.40	1	Complies
2452	2	21.05	127.35	0.51	1	Complies