

RF EXPOSURE REPORT



Report No.: 17071405-FCC-H

Supersede Report No.: N/A

| | | |
|--|--|-------------------------------------|
| Applicant | ASKA ELECTRONICS CO., LIMITED | |
| Product Name | Bluetooth ANC headphone | |
| Model No. | F5AS | |
| Serial No. | F5HA | |
| Test Standard | FCC 2.1093:2016 | |
| Test Date | December 13 to 29, 2017 | |
| Issue Date | December 30, 2017 | |
| Test Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail | |
| Equipment complied with the specification | | <input checked="" type="checkbox"/> |
| Equipment did not comply with the specification | | <input type="checkbox"/> |
| Aarron Liang | David Huang | |
| Aarron Liang Test Engineer | David Huang Checked By | |
| This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only | | |

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

| Country/Region | Scope |
|----------------|------------------------------------|
| USA | EMC, RF/Wireless, SAR, Telecom |
| Canada | EMC, RF/Wireless, SAR, Telecom |
| Taiwan | EMC, RF, Telecom, SAR, Safety |
| Hong Kong | RF/Wireless, SAR, Telecom |
| Australia | EMC, RF, Telecom, SAR, Safety |
| Korea | EMI, EMS, RF, SAR, Telecom, Safety |
| Japan | EMI, RF/Wireless, SAR, Telecom |
| Singapore | EMC, RF, SAR, Telecom |
| Europe | EMC, RF, SAR, Telecom, Safety |

This page has been left blank intentionally.

CONTENTS

| | |
|--|---|
| 1. REPORT REVISION HISTORY | 5 |
| 2. CUSTOMER INFORMATION | 5 |
| 3. TEST SITE INFORMATION..... | 5 |
| 4. EQUIPMENT UNDER TEST (EUT) INFORMATION | 6 |
| 5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES. | 7 |
| 5.1 RF EXPOSURE..... | 7 |
| 5.2 TEST RESULT | 8 |

1. Report Revision History

| Report No. | Report Version | Description | Issue Date |
|----------------|----------------|-------------|-------------------|
| 17071405-FCC-H | NONE | Original | December 30, 2017 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

2. Customer information

| | |
|------------------|--|
| Applicant Name | ASKA ELECTRONICS CO., LIMITED |
| Applicant Add | ROOM A 11/F HO LEE COMMERCIAL BUILDING38-44 D' AGUILAR STREET CENTRAL HK |
| Manufacturer | ASKA Electronics Co., Ltd |
| Manufacturer Add | 3F, building 19#, Road Da Ling Bian, Shahu Community, Tangxia Town, Dongguan, China |

3. Test site information

| | |
|----------------------|--|
| Lab performing tests | SIEMIC (Shenzhen-China) LABORATORIES |
| Lab Address | Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108 |
| FCC Test Site No. | 535293 |
| IC Test Site No. | 4842E-1 |
| Test Software | Radiated Emission Program-To Shenzhen v2.0 |

4. Equipment under Test (EUT) Information

Description of EUT: Bluetooth ANC headphone

Main Model: F5AS

Serial Model: F5HA

Date EUT received: December 12, 2017

Test Date(s): December 13 to 29, 2017

Antenna Gain: Bluetooth: 2.0dBi

Antenna Type: PCB antenna

Type of Modulation: Bluetooth: GFSK, π /4DQPSK, 8DPSK

RF Operating Frequency (ies): Bluetooth: 2402-2480 MHz

Number of Channels: Bluetooth: 79CH

Port: USB Port

Input Power: Battery
Spec: 3.7V, 270mAh

Trade Name : ASKA

FCC ID: 2ACXHF5AS

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

| Modulation | CH | Frequency (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|------------|------|-----------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| GFSK | Low | 2402 | 6.326 | 7±1 | 8 | 6.310 | 1.96 | 3 |
| | Mid | 2441 | 7.340 | 7±1 | 8 | 6.310 | 1.97 | 3 |
| | High | 2480 | 7.811 | 7±1 | 8 | 6.310 | 1.99 | 3 |
| π /4 DQPSK | Low | 2402 | 5.857 | 6±1 | 7 | 5.012 | 1.55 | 3 |
| | Mid | 2441 | 6.159 | 6±1 | 7 | 5.012 | 1.57 | 3 |
| | High | 2480 | 6.516 | 6±1 | 7 | 5.012 | 1.58 | 3 |
| 8-DPSK | Low | 2402 | 5.384 | 6±1 | 7 | 5.012 | 1.55 | 3 |
| | Mid | 2441 | 6.543 | 6±1 | 7 | 5.012 | 1.57 | 3 |
| | High | 2480 | 6.287 | 6±1 | 7 | 5.012 | 1.58 | 3 |

Result: Compliance

No SAR measurement is required.