

FCC Test Report

Report No.: RF150930D07

FCC ID: 2ACYESK-60GTDD-B1

Test Model: EH-600T Rev: D0

Received Date: Sep. 30, 2015

Test Date: Oct. 7 ~ 8, 2015

Issued Date: Oct. 26, 2015

Applicant: Siklu Communication Ltd

Address: 43 Hasivim St., Petach-Tikva 49517, Israel

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF150930D07 Page No. 1 / 34 Report Format Version: 6.1.1



Table of Contents

R	Release Control Record4				
1	C	ertificate of Conformity	. 5		
2	S	ummary of Test Results	. 6		
	2.1 2.2	Measurement Uncertainty			
3		eneral Information			
•					
	3.1 3.2	General Description of EUT Description of Test Modes			
	3.2.1	Test Mode Applicability and Tested Channel Detail			
	3.3	Duty cycle of test signal			
	3.4	Description of Support Units			
	3.4.1	Configuration of System under Test	11		
	3.5	General Description of Applied Standards	12		
4	Т	est Types and Results	13		
	4.1	Radiated Emission and Bandedge Measurement			
		Limits of Radiated Emission and Bandedge Measurement			
		Test Instruments			
		Test Procedures			
		Deviation from Test Standard			
		Test Set Up			
		EUT Operating Conditions			
	4.1. <i>7</i> 4.2	Test Results			
		Conducted Emission Measurement			
		Test Instruments			
		Test Procedures			
		Deviation from Test Standard			
		TEST SETUP			
		EUT Operating Conditions			
		Test Results			
	4.3	6dB Bandwidth Measurement			
		Limits of 6dB Bandwidth Measurement			
		Test Setup Test Instruments	25 25		
		Test Procedure			
		Deviation fromTest Standard			
		EUT Operating Conditions			
		Test Result			
	4.4	Conducted Output Power Measurement			
		Limits OF Conducted Output Power Measurement			
		Test Setup			
		Test Instruments			
		Test Procedures			
		Deviation from Test Standard			
		EUT Operating Conditions			
	4.5	Power Spectral Density Measurement			
		Limits of Power Spectral Density Measurement			
		Test Setup			
		Test Instruments			
		Test Procedure			
	4.5.5	Deviation from Test Standard	28		



4.5.6	EUT Operating Condition	28				
4.5.7	Test Results	29				
4.6	Conducted Out of Band Emission Measurement	30				
4.6.1	Limits of Conducted Out of Band Emission Measurement	30				
	Test Setup					
4.6.3	Test Instruments	30				
4.6.4	Test Procedure	30				
4.6.5	Deviation from Test Standard	30				
4.6.6	EUT Operating Condition	30				
4.6.7	TEST RESULTS	31				
5 P	Pictures of Test Arrangements	33				
Append	Appendix – Information on the Testing Laboratories					



Release Control Record

Issue No.	Description	Date Issued
RF150930D07	Original release.	Oct. 26, 2015



1 Certificate of Conformity

Product: 60G V-Band BackHaul

Brand: Siklu Communication

Test Model: EH-600T Rev: D0

Sample Status: Engineering sample

Applicant: Siklu Communication Ltd

Test Date: Oct. 7 ~ 8, 2015

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Jessica Cheng / Senior Specialist

Approved by : , Date: Oct. 26, 2015

Rex Lai / Assistant Manager



2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)						
FCC Clause	Test Item	Result	Remarks			
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -8.01dB at 0.15001MHz.			
15.205 & 209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -6.7dB at 36.84MHz.			
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -11.3dB at 2483.50MHz.			
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.			
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.			
15.247(b)	Conducted power	PASS	Meet the requirement of limit.			
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.			
15.203	Antenna Requirement	PASS	No antenna connector is used.			

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	3.43 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1000MHz	4.00 dB
Radiated Emissions above 1 GHz	1GHz ~ 40GHz	3.36 dB

2.2 Modification Record

There were no modifications required for compliance.



3 General Information

3.1 General Description of EUT

Product	60G V-Band BackHaul		
Brand	Siklu Communication		
Test Model	EH-600T Rev: D0		
Status of EUT	Engineering sample		
Power Supply Rating	55Vdc from POE adapter		
Modulation Type	GFSK		
Transfer Rate	1Mbps		
Operating Frequency	2402-2480MHz		
Number of Channel	40		
Output Power	1.069mW		
Antenna Type	PIFA antenna with -3.22dBi gain		
Antenna Connector	N/A		
Accessory Device	N/A		
Data Cable Supplied	N/A		

Note:

1. The EUT power from the POE adapter (for support units only) as following.

Brand	Microsemi
Model	PD-9601G/AC
Input Power	100-240Vac, 50-60Hz, 1.3A
Output Power	55Vdc, 1.75A

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



3.2 Description of Test Modes

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE		APPLICA	ABLE TO		PECCEIPTION
MODE	RE ³ 1G	RE<1G	PLC	APCM	DESCRIPTION
-	√	√	√	√	-

Where **RE**³**1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

cc	EUT ONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
	-	0 to 39	0	GFSK	1

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

(EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
	-	0 to 39	0	GFSK	1



Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.


EUT CONFIGUURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Test Condition:

APPLICABLE TO ENVIRONMENTAL CONDITIONS		INPUT POWER	TESTED BY	
RE ³ 1G	26deg. C, 71%RH	120Vac, 60Hz	Aaron You	
RE<1G 26deg. C, 71%RH		120Vac, 60Hz	Aaron You	
PLC 26deg. C, 71%RH		120Vac, 60Hz	Aaron You	
APCM	,		Saxon Lee	

3.3 Duty cycle of test signal

Duty cycle of test signal is < 98% Duty cycle = 0.414/0.626 = 0.661, Duty factor = 10 * log(1/0.661) = 1.80





3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	POE adapter	Microsemi	PD-9601G/AC	N/A	N/A	Supplied by client


Note: All power cords of the above support units are non-shielded (1.8m).

	ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
ĺ	1.	LAN cable	1	10	Υ	0	Provided by Lab


Note: The core(s) is(are) originally attached to the cable(s).

3.4.1 Configuration of System under Test

Conducted Emission Test



Radiated Emission Test



Report No.: RF150930D07 Page No. 11 / 34 Report Format Version: 6.1.1



3.5 **General Description of Applied Standards** The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards: FCC Part 15, Subpart C (15.247) 558074 D01 DTS Meas Guidance v03r03 ANSI C63.10-2013 All test items have been performed and recorded as per the above standards.

Report No.: RF150930D07 Page No. 12 / 34 Report Format Version: 6.1.1



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

potron				
Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)		
0.009 ~ 0.490	2400/F(kHz)	300		
0.490 ~ 1.705	24000/F(kHz)	30		
1.705 ~ 30.0	30	30		
30 ~ 88	100	3		
88 ~ 216	150	3		
216 ~ 960	200	3		
Above 960	500	3		

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 26, 2015	Feb. 25, 2016
HP Preamplifier	8449B	3008A01201	Feb. 26, 2015	Feb. 25, 2016
MITEQ Preamplifier	AMF-6F-260400-3 3-8P	892164	Mar. 01, 2015	Feb. 28, 2016
Agilent Spectrum	E4446A	MY51100050	Oct. 24, 2014	Oct. 23, 2015
Agilent TEST RECEIVER	N9038A	MY51210129	Jan. 20, 2015	Jan. 19, 2016
Schwarzbeck Antenna	VULB 9168	139	Feb. 04, 2015	Feb. 03, 2016
Schwarzbeck Antenna	VHBA 9123	480	May 29, 2015	May 28, 2017
Schwarzbeck Horn Antenna	BBHA-9170	212	Feb. 09, 2015	Feb. 08, 2016
Schwarzbeck Horn Antenna	BBHA 9120-D1	D130	Feb. 10, 2015	Feb. 09, 2016
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	Radiated_V7.6.15. 9.4	NA	NA	NA
SUHNER RF cable With 4dB PAD	SF104	CABLE-CH6	Aug. 15, 2015	Aug. 14, 2016
SUHNER RF cable With 3dB PAD	SF102	Cable-CH8-3.6m	Aug. 15, 2015	Aug. 14, 2016
EMCO Horn Antenna	3115	00028257	Feb. 05, 2015	Feb. 04, 2016
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
ROHDE & SCHWARZ Spectrum Analyzer	FSV40	101042	Sep. 23, 2015	Sep. 22, 2016
Anritsu Power Sensor	MA2411B	0738404	Apr. 21, 2015	Apr. 20, 2016
Anritsu Power Meter	ML2495A	0842014	Apr. 21, 2015	Apr. 20, 2016

- **NOTE:** 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.
 - 2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 - 3. The test was performed in Chamber No. 6.
 - 4. The Industry Canada Reference No. IC 7450E-6.
 - 5. The FCC Site Registration No. is 447212.



4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.


T. I.T Deviation from rest etaildan	4.1.4	Deviation 1	from Test	Standard
-------------------------------------	-------	-------------	-----------	----------

No deviation.




4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.



4.1.7 Test Results

Above 1GHz Data:

CHANNEL	TX Channel 0		Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	2390.00	55.3 PK	74.0	-18.7	1.54 H	200	54.77	0.52	
2	2390.00	41.6 AV	54.0	-12.4	1.54 H	200	41.06	0.52	
3	*2402.00	78.4 PK			1.54 H	200	77.79	0.60	
4	*2402.00	76.7 AV			1.54 H	200	76.14	0.60	
5	4804.00	49.7 PK	74.0	-24.3	1.72 H	166	41.89	7.79	
6	4804.00	37.1 AV	54.0	-16.9	1.72 H	166	29.27	7.79	
	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	2390.00	53.7 PK	74.0	-20.3	1.00 V	112	53.20	0.52	
2	2390.00	41.1 AV	54.0	-13.0	1.00 V	112	40.53	0.52	
3	*2402.00	75.4 PK			1.00 V	112	74.76	0.60	
4	*2402.00	73.9 AV			1.00 V	112	73.27	0.60	
5	4804.00	49.0 PK	74.0	-25.0	1.45 V	167	41.24	7.79	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2440.00	77.1 PK			1.01 H	223	76.34	0.77	
2	*2440.00	75.7 AV			1.01 H	223	74.88	0.77	
3	4880.00	50.0 PK	74.0	-24.0	1.76 H	177	42.03	7.94	
4	4880.00	37.2 AV	54.0	-16.8	1.76 H	177	29.30	7.94	
	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2440.00	75.8 PK			1.14 V	208	75.02	0.77	
2	*2440.00	74.2 AV			1.14 V	208	73.41	0.77	
3	4880.00	49.1 PK	74.0	-24.9	1.40 V	169	41.13	7.94	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2480.00	78.9 PK			1.00 H	112	77.92	0.95	
2	*2480.00	77.3 AV			1.00 H	112	76.35	0.95	
3	2483.50	55.8 PK	74.0	-18.2	1.00 H	112	54.78	0.98	
4	2483.50	42.7 AV	54.0	-11.3	1.00 H	112	41.71	0.98	
5	4960.00	50.4 PK	74.0	-23.6	1.62 H	169	42.18	8.22	
6	4960.00	37.6 AV	54.0	-16.4	1.62 H	169	29.40	8.22	
		ANTENNA	POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2480.00	75.8 PK			1.29 V	208	74.81	0.95	
2	*2480.00	74.2 AV			1.29 V	208	73.24	0.95	
3	2483.50	54.2 PK	74.0	-19.9	1.29 V	208	53.17	0.98	
4	2483.50	41.3 AV	54.0	-12.7	1.29 V	208	40.29	0.98	
5	4960.00	49.7 PK	74.0	-24.3	1.31 V	148	41.51	8.22	
6	4960.00	36.9 AV	54.0	-17.2	1.31 V	148	28.63	8.22	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



Below 1GHz Data:

CHANNEL	TX Channel 0	DETECTOR	Ougai Baak (OB)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	62.45	21.1 QP	40.0	-19.0	4.00 H	112	30.76	-9.71	
2	125.01	22.8 QP	43.5	-20.7	3.41 H	126	33.36	-10.52	
3	250.07	26.0 QP	46.0	-20.0	2.65 H	121	34.93	-8.97	
4	656.23	39.0 QP	46.0	-7.0	1.44 H	223	38.70	0.30	
5	750.03	36.2 QP	46.0	-9.8	1.12 H	144	34.30	1.88	
6	874.97	36.5 QP	46.0	-9.5	1.00 H	160	32.86	3.63	
7	999.99	37.8 QP	54.0	-16.3	1.00 H	258	31.94	5.81	
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	36.84	33.3 QP	40.0	-6.7	1.52 V	183	43.25	-9.95	
2	125.01	26.7 QP	43.5	-16.8	1.00 V	154	37.20	-10.52	
3	375.08	27.8 QP	46.0	-18.2	1.24 V	360	33.09	-5.32	
4	656.23	37.6 QP	46.0	-8.4	2.13 V	92	37.27	0.30	
5	750.02	35.7 QP	46.0	-10.4	2.44 V	112	33.77	1.88	
6	999.99	40.5 QP	54.0	-13.5	2.73 V	208	34.67	5.81	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Fraguency (MHz)	Conducted Limit (dBuV)			
Frequency (MHz)	Quasi-peak	Average		
0.15 - 0.5	66 - 56	56 - 46		
0.50 - 5.0	56	46		
5.0 - 30.0	60	50		

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

4.Z.Z Test instruments				
Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100276	Apr. 01, 2015	Mar. 31, 2016
ROHDE & SCHWARZ				
Artificial Mains Network	ENV216	101197	Apr. 27, 2015	Apr. 26, 2016
(for EUT)				
LISN With Adapter	AD10	C10Ada-002	Apr. 27, 2015	Apr. 26, 2016
(for EUT)			, , , ,	, -, -
ROHDE & SCHWARZ				
Artificial Mains Network	ESH3-Z5	100218	Nov. 25, 2014	Nov. 24, 2015
(for peripherals)				
SCHWARZBECK				
Artificial Mains Network (For	NNLK8129	8129229	May 06, 2015	May 05, 2016
EUT)				
Software	Cond_V7.3.7	NA	NA	NA
RF cable (JYEBAO)	5D 5D	O-bl- 040 04	Fab 47 0045	Fab. 40, 0040
With 10dB PAD	5D-FB	Cable-C10.01	Feb. 17, 2015	Feb. 16, 2016
SUHNER Terminator				
(For ROHDE & SCHWARZ	65BNC-5001	E1-011484	May 19, 2015	May 18, 2016
LISN)				
ROHDE & SCHWARZ				
Artificial Mains Network (For	ESH3-Z5	100220	Nov. 20, 2014	Nov. 19, 2015
TV EUT)				
LISN With Adapter	100220	N/A	Nov. 20, 2014	Nov. 19, 2015
(for TV EUT)	100220	1N//\(\)	1404. 20, 2014	1100. 13, 2013

Notes:

- 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- 2. The test was performed in Shielded Room No. 10.
- 3. The VCCI Site Registration No. C-1852.



4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.



4.2.7 Test Results


CONDUCTED WORST-CASE DATA

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26℃, 71%RH
Tested by	Aaron You		

	Phase Of Power : Line (L)									
No	Frequency	Correction Factor		g Value uV)		on Level uV)		nit uV)	Mar (d	gin B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15001	9.67	45.77	38.32	55.44	47.99	66.00	56.00	-10.56	-8.01
2	0.36515	9.67	32.75	24.87	42.42	34.54	58.61	48.61	-16.19	-14.07
3	1.22656	9.70	32.78	16.30	42.48	26.00	56.00	46.00	-13.52	-20.00
4	1.35156	9.71	27.68	14.59	37.39	24.30	56.00	46.00	-18.61	-21.70
5	6.54688	9.81	21.64	15.41	31.45	25.22	60.00	50.00	-28.55	-24.78
6	18.67188	9.91	21.28	15.91	31.19	25.82	60.00	50.00	-28.81	-24.18

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26℃, 71%RH
Tested by	Aaron You		

	Phase Of Power : Neutral (N)									
No	Frequency	Correction Factor		g Value uV)		n Level uV)		mit uV)	Mar (d	gin B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15001	9.70	45.63	37.91	55.33	47.61	66.00	56.00	-10.67	-8.39
2	0.22031	9.71	37.34	29.94	47.05	39.65	62.81	52.81	-15.76	-13.16
3	0.36484	9.71	32.33	24.45	42.04	34.16	58.62	48.62	-16.58	-14.46
4	1.14453	9.73	29.39	15.33	39.12	25.06	56.00	46.00	-16.88	-20.94
5	1.23047	9.73	36.97	20.39	46.70	30.12	56.00	46.00	-9.30	-15.88
6	6.51563	9.85	23.28	16.61	33.13	26.46	60.00	50.00	-26.87	-23.54

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times RBW$, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.


4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 Test Result

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.69	0.5	PASS
19	2440	0.71	0.5	PASS
39	2480	0.71	0.5	PASS






4.4 Conducted Output Power Measurement

4.4.1 Limits OF Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

CHANNEL	FREQUENCY (MHz)	PEAK POWER (mW)	PEAK POWER (dBm)	LIMIT (dBm)	PASS/FAIL
0	2402	1.069	0.29	30	PASS
19	2440	1.002	0.01	30	PASS
39	2480	0.927	-0.33	30	PASS



4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d. Set the VBW \geq 3 × RBW.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.


4.5.6 EUT Operating Condition

Same as Item 4.3.6



4.5.7 Test Results

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-14.39	8	PASS
19	2440	-15.47	8	PASS
39	2480	-16.34	8	PASS






4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep = auto couple.
- 5. Trace Mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum amplitude level.


4.6.5 Deviation from Test Standard No deviation.

4.6.6 EUT Operating Condition


Same as Item 4.3.6



4.6.7 TEST RESULTS









5 Pictures of Test Arrangements		
Please refer to the attached file (Test Setup Photo).		

Report No.: RF150930D07 Page No. 33 / 34 Report Format Version: 6.1.1



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab/Telecom Lab

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---