

198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555 Fax: +86 (0) 20 82075059 Email: ee.guangzhou@sgs.com Report No.: GZEM140800444301

Page: 1 of 34 FCC ID: 2ACYNA014302

# TEST REPORT

Application No.:	GZEM1408004443RF
Applicant:	ALT PARTNERS/BABYMOOV
FCC ID:	2ACYNA014302
Product Name:	Expert Care baby monitor
Product Description:	Radio digital Baby Monitor with 915 MHz as carrier.
Model No.:	A014302
Manufacturer's model No.	BC-62.
*	Please refer to section 3 of this report for details
Standards:	CFR 47 PART 15 Subpart C: 2013 section 15.249
Date of Receipt:	2014-08-26
Date of Test:	2014-09-01
Date of Issue:	2014-12-19
Test Result :	Pass*

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 3 of this report for further detail.

Authorized Signature

Jerry Chan

Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> and conditions.htm</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/terms">www.sgs.com/terms</a> e-document.htm</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only"



Report No.: GZEM140800444301

Page: 2 of 34

### 2 Version

Revision Record									
Version Chapter Date Modifier Remark									
00		2014-12-19		Original					

Authorized for issue by:		
Tested By	Sangal Huarla  (Sangdi Huang) /Project Engineer	2014-09-01  Date
	(Sungar Huang) / 1 Tojoot Engineer	
Prepared By	Sangoli Huang	2014-09-25
	(Sangdi Huang) /Project Engineer	Date
Checked By	ful. Nu	2014-09-25
	(Fred Zhu)/Reviewer	Date



Report No.: GZEM140800444301

Page: 3 of 34

### 3 Test Summary

Test Test Requirement		Test method	Result
Field Strength of	FCC PART 15 C	ANSI C63.10:	PASS
Fundamental	section 15.249 (a)	Clause 6.6	FAGG
F: 110:	FCC PART 15 C	ANSI C63.10:	
Field Strength of Unwanted Emissions	section 15.249 (a)	Clause 6.4, 6.6 and	PASS
Onwanted Emissions	section 15.249 (d)	6.7	
Dand Edges	FCC PART 15 C	ANSI C63.10:	PASS
Band Edges	section 15.249 (d)	Clause 6.9.2	FASS
Occursied Depolecialth	FCC PART 15 C	ANSI C63.10:	DACC
Occupied Bandwidth	section 15.215(c)	Clause 6.9.1	PASS
Conducted Emissions	FCC PART 15 C	ANSI C63.10:	PASS**
at Mains Terminals	section 15.207	Clause 6.2	FAGG

#### Remark:

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.

\*\*: The EUT passed Conducted Emissions at Mains Terminals test after modification carried out by applicant.



Report No.: GZEM140800444301

Page: 4 of 34

### 4 Contents

1	COVE	ER PAGE	1							
2 VERSION  3 TEST SUMMARY	2									
4										
5	GENE	ERAL INFORMATION	5							
	5.1	Client Information	5							
	5.2	General Description of E.U.T.	5							
	5.3 Details of E.U.T. 5.4 Description of Support Units									
	5.5	Other Information Requested by the Customer	7							
	5.6	Abnormalities from Standard Conditions	7							
	5.7	Deviation from Standards	7							
	5.8	Test Location	7							
	5.9	Test Facility	8							
6	EQUI	PMENT USED DURING TEST	9							
7	TEST	RESULTS	10							
	7.1	E.U.T. Operation	10							
	7.2	Antenna Requirement	11							
	7.3	Field Strength of Fundamental Field Strength of Unwanted Emissions & Band Edge	12							
	7.4	Occupied Bandwidth	29							
	7.5	Conducted Emissions at Mains Terminals 150 kHz to 30 MHz	31							



Report No.: GZEM140800444301

Page: 5 of 34

### 5 General Information

#### 5.1 Client Information

Applicant: ALT PARTNERS/BABYMOOV

Address of Applicant: Parc Industriel des Gravanches- 16 rue Jacqueline AURIOL-63051

Clermont-Ferrand Cedex2

### 5.2 General Description of E.U.T.

Product Name: Expert Care baby monitor

Model No.: A014302

5.3 Details of E.U.T.

Operating Frequency 915.8 MHz to 927.0 MHz

Type of Modulation: GFSK

Number of Channels 57

Channel Separation: 0.2 MHz

Antenna Type Integral antenna

Antenna gain: 0dBi

Function: Wireless baby monitor with audio function to transmit and receive GFSK

signal.

Power Supply: Working voltage: DC  $4.5V = 3 \times 1.5V$  size "AAA" batteries or

AC 100-240V 50/60Hz 0.1A Max.

Adapter Information: Model: SWP-27125-00

Input: AC 100-240V 50/60Hz 0.1A Max.

Output: DC 5.0V 600mA

Power cord: 1.2 m x 2 wires unscreened DC cable



Report No.: GZEM140800444301

Page: 6 of 34

### EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	915.8	27	921.2	54	926.6
1	916.0	28	921.4	55	926.8
2	916.2	29	921.6	56	927.0
3	916.4	30	921.8		
4	916.6	31	922.0		
5	916.8	32	922.2		
6	917.0	33	922.4		
7	917.2	34	922.6		
8	917.4	35	922.8		
9	917.6	36	923.0		
10	917.8	37	923.2		
11	918.0	38	923.4		
12	918.2	39	923.6		
13	918.4	40	923.8		
14	918.6	41	924.0		
15	918.8	42	924.2		
16	919.0	43	924.4		
17	919.2	44	924.6		
18	919.4	45	924.8		
19	919.6	46	925.0		
20	919.8	47	925.2		
21	920.0	48	925.4		
22	920.2	49	925.6		
23	920.4	50	925.8		
24	920.6	51	926.0		
25	920.8	52	926.2		
26	921.0	53	926.4		

Test frequencies are the lowest channel: 0 channel(915.8 MHz), middle channel: 28 channel(921.4 MHz) and highest channel: 56 channel(927.0 MHz)



Report No.: GZEM140800444301

Page: 7 of 34

### 5.4 Description of Support Units

The EUT has been test as an independent unit.

### 5.5 Other Information Requested by the Customer

None.

#### 5.6 Abnormalities from Standard Conditions

The EUT passed Conducted Emissions at Mains Terminals test after modification carried out by applicant.

### 5.7 Deviation from Standards

Biconical and log periodic antennas were used instead of dipole antennas.

#### 5.8 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



Report No.: GZEM140800444301

Page: 8 of 34

### 5.9 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### NVLAP (Lab Code: 200611-0)

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

#### ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

### SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

#### CNAS (Lab Code: L0167)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

### • FCC (Registration No.: 282399)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

#### Industry Canada (Registration No.: 4620B-1)

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

### VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

### • CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01:2006-10 and Rules of procedure IECEE 02:2006-10, and the relevant IECEE CB-Scheme Operational documents.



Report No.: GZEM140800444301

Page: 9 of 34

### 6 Equipment Used during Test

RE in Chamber								
No.	Took Carringson	Manufacturer	Model No.	Carriel No.	Cal. date	Cal.Due date		
NO.	Test Equipment	Manufacturer	wodel no.	Serial No.	(YYYY-MM-DD)	(YYYY-MM-DD)		
EMC0525	Compact Semi- Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	2014-12-5	2015-12-5		
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100283	2014-04-19	2015-04-19		
EMC0056	EMI Test Receiver	Rohde & Schwarz	ESCI	100236	2014-03-03	2015-03-03		
EMC0528	RI High frequency Cable	SGS	20 m	N/A	2014-05-09	2015-05-09		
EMC2025	Trilog Broadband Antenna 30-1000MHz	SCHWARZBECK MESS- ELEKTRONIK	VULB 9160	9160-3372	2014-07-14	2017-07-14		
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	2013-08-31	2016-08-31		
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	2014-05-04	2017-05-04		
EMC2026	MC2026 Horn Antenna ME 1-18GHz SCHWA MEELEKT		BBHA 9120D	9120D-841	2013-08-31	2016-08-31		
EMC0518	Horn Antenna	Rohde & Schwarz	HF906	100096	2012-07-01	2015-07-01		
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	2014-03-03	2015-03-03		
EMC2065	Amplifier	HP	8447F	N/A	2014-08-25	2015-08-25		
EMC0075	310N Amplifier	Sonama	310N	272683	2014-03-03	2015-03-03		
EMC0523	Active Loop Antenna	EMCO	6502	42963	2014-03-03	2016-03-03		
EMC2041	Broad-Band SCHWARZ		BBHA 9170	9170-375	2014-05-26	2017-05-26		
EMC2079	High Pass Filter(915MHz)	FSY MICROWAVE	HM1465-9SS	009	2014-03-28	2015-03-28		
EMC2069	2.4GHz filter	Micro-Tronics	BRM 50702	149	2014-04-19	2015-04-19		
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	2014-05-03	2016-05-03		

General used equipment							
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. date	Cal.Due date	
				Serial No.	(YYYY-MM-DD)	(YYYY-MM-DD)	
EMC0006	DMM	Fluke	73	70681569	2014-09-15	2015-09-15	
EMC0007	DMM	Fluke	73	70671122	2014-09-15	2015-09-15	



Report No.: GZEM140800444301

Page: 10 of 34

### 7 Test Results

### 7.1 E.U.T. Operation

Test Voltage: AC 120V, 60 Hz or DC 4.5V

**Temperature:** 20.0 -25.0 °C **Humidity:** 38-50 % RH

Atmospheric Pressure: 1000 -1010 mbar

Test frequencies and

frequency range: rece

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band

specified in the following table:

According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency

shown in the following table:

### Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which	Number of	Location in frequency range
device operates	frequencies	of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
Marathan 10 MHz	2	1 near top, 1 near middle and 1
More than 10 MHz	3	near bottom

#### Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement		
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz,		
9 KHZ to below 10 GHZ	whichever is lower		
At or above 10 GHz to below	5th harmonic of highest fundamental frequency or to 100 GHz,		
30 GHz	whichever is lower		
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz,		
At or above 30 GHz	whichever is lower, unless otherwise specified		



Report No.: GZEM140800444301

Page: 11 of 34

### 7.2 Antenna Requirement


### Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### **EUT Antenna**

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.



Test result: The unit does meet the FCC requirements.



Report No.: GZEM140800444301

Page: 12 of 34

# 7.3 Field Strength of Fundamental& Field Strength of Unwanted Emissions& Band Edge

Test Requirement: FCC Part15 C section 15.249

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBμV/m @ 3m)	Field Strength of Harmonics (dBμV/m @ 3m)
902 to 928	94.0	(dbµV/III @ 3III) 54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Limits: The fundamental frequency rang is in the frequency band of the EUT is 902

MHz ~ 928 MHz.

The limit for QP field strength  $dB\mu V/m$  for the fundamental frequency = 94.0

 $dB\mu V/m$ .

No fundamental is allowed in the restricted bands.

The limit for AVG field strength  $dB\mu V/m$  for the harmonics and other above

1G frequencies =  $54.0 \text{ dB}\mu\text{V/m}$ .

The limit for Peak field strength dBµV/m for the harmonics and other above

1G frequencies =  $74.0 \text{ dB}\mu\text{V/m}$ .

Test Method: ANSI C63.10: Clause 6.4, 6.6 and 6.7 for Field Strength of Fundamental&

Field Strength of Unwanted Emissions

ANSI C63.10: Clause 6.9.2 for Band Edge

Status Pre-test the EUT in continuous transmitting mode with setup as stand-alone

in X, Y, Z threes axes, found the worst case is X axes and report the data.

Measurement

Distance:

3m (Semi-Anechoic Chamber)

Frequency range 9 kHz – 10 GHz for transmitting mode.

Test instrumentation resolution bandwidth

9 kHz (9 kHz - 30 MHz), 120 kHz (30 MHz - 1000 MHz), 1 MHz (1000 MHz -

10 GHz)



Report No.: GZEM140800444301

Page: 13 of 34

Detector: For PK and QP value:

RBW = 1 MHz for  $f \ge 1$  GHz, 100 kHz for f < 1 GHz

VBW ≥ RBW Sweep = auto

Detector function = peak

Trace = max hold For AV value:

RBW = 1 MHz for  $f \ge 1$  GHz,

VBW =10 Hz Sweep = auto

Detector function = peak

Trace = max hold



Report No.: GZEM140800444301

Page: 14 of 34

And according 15.35(a)

15.35(a) On any frequency or frequencies below or equal to 1000 MHz, the limits shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified. The specifications for the measuring instrument using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Interference (CISPR) of the International Electrotechnical Commission. As an alternative to CISPR quasi-peak measurements, the responsible party, at its option, may demonstrate compliance with the emission limits using measuring equipment employing a peak detector function, properly adjusted for such factors as pulse desensitization, as long as the same bandwidths as indicated for CISPR quasi-peak measurements are employed.

Note: For pulse modulated devices with a pulse-repetition frequency of 20 Hz or less and for which CISPR quasi-peak measurements are specified, compliance with the regulations shall be demonstrated using measuring equipment employing a peak detector function, properly adjusted for such factors as pulse desensitization, using the same measurement bandwidths that are indicated for CISPR quasi-peak measurements.

According to 15.35 (b) Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz. When average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, e.g., see §§ 15.250, 15.252, 15.255, and 15.509-15.519 of this part, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device, e.g., the total peak power level. Note that the use of a pulse desensitization correction factor may be needed to determine the total peak emission level. The instruction manual or application note for the measurement instrument should be consulted for determining pulse desensitization factors, as necessary.


The average correction factor is computed by analyzing the on time in 100ms over one complete pulse train. Analysis of the remote transmitter on time in one complete pulse train, therefore the average value of fundamental frequency is: Average = Peak value + 20log (Duty cycle), where the duty factor is calculated from following formula:

 $20\log (Duty cycle) = 20\log(1) = 0dB$ 



Report No.: GZEM140800444301

Page: 15 of 34





Report No.: GZEM140800444301

Page: 16 of 34

#### **Test Procedure:**

#### 1)9 kHz to 30 MHz emissions:

For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.10. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT, During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

### 2)30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.


#### 3)1 GHz to 10 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.

For testing performed with the horn antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scan between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

### **Test Configuration:**

1) 9 kHz to 30 MHz emissions:






Report No.: GZEM140800444301

Page: 17 of 34

### 2) 30 MHz to 1 GHz emissions:



### 3) 1 GHz to 10 GHz emissions:

The field strength is calculated by adding the Antenna Factor, Cable Loss & Per-amplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor



Report No.: GZEM140800444301

Page: 18 of 34

### Quasi-peak measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
915.8	21.19	4.01	30.88	93.47	89.79	94.00	V
921.4	21.93	4.08	30.91	94.35	89.45	94.00	V
927.0	22.28	4.13	31.20	94.82	90.03	94.00	V
915.8	21.19	4.01	30.88	95.16	89.48	94.00	Н
921.4	21.93	4.08	30.91	94.88	89.98	94.00	Н
927.0	22.28	4.13	31.20	95.23	90.44	94.00	Н

Remark: During test in below 1GHz, the fundamental emission has been filtered by notch filter.



Report No.: GZEM140800444301

Page: 19 of 34

Test at Lowest Channel in transmitting status:


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement Vertical:

Peak scan

Level (dBµV/m)



### Quasi-peak measurement

Freq		intenna Factor	_	Read Level	Level	Limit Line	Over Limit
MHz	dB	dB/m	dB	dBu₹	$\overline{\text{dBuV/m}}$	dBuV/m	dB
36.51 111.35 204.96 341.98 501.18 916.07	0.60 1.23 1.43 2.04 2.60 3.62	15. 05 8. 51 10. 46 14. 19 17. 83 23. 26	27. 33 27. 13 26. 68 26. 73 27. 69 26. 71	26. 42 28. 34 28. 79 29. 37 29. 97 33. 08	14. 74 10. 95 14. 00 18. 87 22. 71 33. 25	43.50 43.50 46.00 46.00	-25. 26 -32. 55 -29. 50 -27. 13 -23. 29 -12. 75



Report No.: GZEM140800444301

Page: 20 of 34


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBµV/m)



### Quasi-peak measurement

Freq		Antenna Factor	Preamp Factor	Read Level		Limit Line	Over Limit
MHz	dB	dB/m	dB	dBu₹	dBuV/m	$\overline{\text{dBuV/m}}$	dB
47. 33 120. 70 245. 95 377. 26 515. 44 922. 52	0.75 1.26 1.65 2.14 2.62 3.62	9. 88 7. 89 12. 17 16. 03 18. 23 23. 29	27. 30 27. 06 26. 55 26. 99 27. 67 26. 68	28. 04 28. 60 28. 71 29. 02 30. 08 32. 75	11. 37 10. 69 15. 98 20. 20 23. 26 32. 98	43.50 46.00 46.00 46.00	-28. 63 -32. 81 -30. 02 -25. 80 -22. 74 -13. 02



Report No.: GZEM140800444301

Page: 21 of 34

### 1~10 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
1831.60	25.42	6.06	38.22	74.91	68.17	74.00	V
2747.40	28.29	7.49	38.31	70.23	67.70	74.00	V
3663.20	29.22	9.64	38.56	70.12	70.42	74.00	V
1831.60	25.42	6.06	38.22	60.60	53.86	74.00	Н
2747.40	28.29	7.49	38.31	64.73	62.20	74.00	Н
3663.20	29.22	9.64	38.56	60.54	60.84	74.00	Н

#### **Average Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
1831.60	25.42	6.06	38.22	55.67	48.93	54.00	V
2747.40	28.29	7.49	38.31	52.65	50.12	54.00	V
3663.20	29.22	9.64	38.56	48.95	49.25	54.00	V
1831.60	25.42	6.06	38.22	54.44	47.70	54.00	Н
2747.40	28.29	7.49	38.31	52.20	49.67	54.00	Н
3663.20	29.22	9.64	38.56	48.79	49.09	54.00	Н

<sup>1).</sup> The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor.

- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits s'pecified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.



Report No.: GZEM140800444301

Page: 22 of 34

Test at Middle Channel in transmitting status:


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement Vertical:

Peak scan

Level (dBµV/m)



#### Quasi-peak measurement

Freq		Antenna Factor	Preamp Factor	Read Level		Limit Line	Over Limit
MHz	dB	dB/m	dB	dBu√	dBuV/m	dBuV/m	dB
34. 76 88. 03 210. 05 310. 00 454. 31 854. 02	0.60 1.10 1.46 1.93 2.43 3.42	16. 03 8. 50 10. 72 14. 26 17. 06 22. 50	27. 34 27. 22 26. 66 26. 48 27. 46 26. 99	25. 14 27. 52 27. 94 28. 01 30. 21 31. 19	14. 43 9. 90 13. 46 17. 72 22. 24 30. 12	43.50 43.50 46.00 46.00	-25.57 -33.60 -30.04 -28.28 -23.76 -15.88



Report No.: GZEM140800444301

Page: 23 of 34


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBµV/m)



### Quasi-peak measurement

Freq		Antenna Factor	Preamp Factor	Read Level		Limit Line	Over Limit
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
47. 33 81. 21 131. 76 188. 41 429. 52 776. 88	0.75 1.10 1.28 1.38 2.33 3.13	9. 88 7. 82 7. 77 10. 07 16. 49 22. 01	27. 30 27. 23 27. 00 26. 74 27. 31 27. 32	26. 07 26. 38 28. 45 28. 33 29. 94 31. 58	9. 40 8. 07 10. 50 13. 04 21. 45 29. 40	40.00 43.50 43.50 46.00	-30.60 -31.93 -33.00 -30.46 -24.55 -16.60



Report No.: GZEM140800444301

Page: 24 of 34

### 1~10 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
1842.80	25.40	6.05	38.22	58.87	52.10	74.00	V
2764.20	28.33	7.52	38.32	60.44	57.97	74.00	V
3685.60	29.24	9.73	38.56	68.56	68.97	74.00	V
1842.80	25.47	6.08	38.22	72.15	65.48	74.00	Н
2764.20	28.33	7.52	38.32	72.56	70.09	74.00	Н
3685.60	29.24	9.73	38.56	61.63	62.04	74.00	Н

### Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
1842.80	25.47	6.08	38.22	55.05	48.38	54.00	V
2764.20	28.33	7.52	38.32	52.07	49.60	54.00	V
3685.60	29.24	9.73	38.56	48.85	49.26	54.00	V
1842.80	25.47	6.08	38.22	56.95	50.28	54.00	Н
2764.20	28.33	7.52	38.32	52.00	49.53	54.00	Н
3685.60	29.24	9.73	38.56	48.56	48.97	54.00	Н

#### Remark:

1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor.

- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits s`pecified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.



Report No.: GZEM140800444301

Page: 25 of 34

Test at Highest Channel in transmitting status:


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement Vertical:

Peak scan

Level (dBµV/m)



#### Quasi-peak measurement

Freq		Antenna Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
MHz	dB	dB/m	dB	dBuV	$\overline{\text{dBuV/m}}$	$\overline{\text{dBuV/m}}$	——dB
33. 92 54. 26 117. 36 209. 31 400. 43 755. 39	0.60 0.80 1.25 1.46 2.20 3.07	16. 51 8. 06 8. 08 10. 68 16. 30 21. 76	27. 34 27. 28 27. 09 26. 66 27. 13 27. 35	29. 64 28. 17 29. 93 30. 63 31. 86 33. 18	19. 41 9. 75 12. 17 16. 11 23. 23 30. 66	40.00 43.50 43.50 46.00	-20.59 -30.25 -31.33 -27.39 -22.77 -15.34



Report No.: GZEM140800444301

Page: 26 of 34


9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

Horizontal:

Peak scan

Level (dBµV/m)



### Quasi-peak measurement

Freq		Antenna Factor	Preamp Factor	Read Level		Limit Line	Over Limit
MHz	dB	dB/m	dB	dBu₹	dBuV/m	dBuV/m	dB
34. 88 103. 44 164. 33 280. 02 403. 25 747. 48	0.60 1.21 1.35 1.81 2.21 3.05	15. 97 8. 93 9. 56 13. 02 16. 31 21. 69	27. 34 27. 18 26. 84 26. 45 27. 15 27. 35	26. 36 28. 84 28. 56 29. 64 30. 00 30. 43	15. 59 11. 80 12. 63 18. 02 21. 37 27. 82	43.50 43.50 46.00 46.00	-24. 41 -31. 70 -30. 87 -27. 98 -24. 63 -18. 18



Report No.: GZEM140800444301

Page: 27 of 34

### 1~10 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### **Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2781.00	28.38	7.55	38.32	70.59	68.20	74.00	V
3708.00	29.26	9.83	38.57	62.88	63.40	74.00	V
4635.00	31.16	11.10	38.58	65.03	68.71	74.00	V
2781.00	28.38	7.55	38.32	61.30	58.91	74.00	Н
3708.00	29.26	9.83	38.57	65.99	66.51	74.00	Н
4635.00	31.16	11.10	38.58	46.12	49.80	74.00	Н

#### **Average Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
2781.00	28.38	7.55	38.32	52.53	50.14	54.00	V
3708.00	29.26	9.83	38.57	49.01	49.53	54.00	V
4635.00	31.16	11.10	38.58	45.67	49.35	54.00	V
2781.00	28.38	7.55	38.32	51.58	49.19	54.00	Н
3708.00	29.26	9.83	38.57	49.14	49.66	54.00	Н
4635.00	31.16	11.10	38.58	40.91	44.59	54.00	Н

#### Remark:

1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor.

- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test result: The unit does meet the FCC requirements.



Report No.: GZEM140800444301

Page: 28 of 34

### Band Edge:

Lowest 915.8MHz

#### **Quasi-Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB <sub>µ</sub> V)	Emission Level (dBµV/m)	Limit (dBμV/m)	Antenna polarization
902.00	21.12	4.00	30.90	35.31	29.53	46.00	V
928.00	21.28	4.04	30.84	34.55	29.03	46.00	V
902.00	21.12	4.00	30.90	35.28	29.50	46.00	Н
928.00	21.28	4.04	30.84	34.63	29.11	46.00	Н

### Highest 927.0MHz

#### **Quasi-Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
902.00	21.12	4.00	30.90	34.28	28.50	46.00	V
928.00	21.28	4.04	30.84	35.76	30.24	46.00	V
902.00	21.12	4.00	30.90	35.33	28.87	46.00	Н
928.00	21.28	4.04	30.84	34.65	29.13	46.00	Н

### Remark:

1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss - Preamplifier Factor.

Test result: The unit does meet the FCC requirements.



Report No.: GZEM140800444301

Page: 29 of 34

### 7.4 Occupied Bandwidth

Test Method:

Test Requirement: FCC Part 15 C section 15.215

(c)Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


ANSI C63.10: Clause 6.9.1

Operation within the band 902 MHz to 928 MHz

Method of A small sample of the transmitter output was fed into the Spectrum

measurement: Analyzer and the attached plot was taken.

### Test in the frequency 915.8MHz (20 dB bandwidth)







Report No.: GZEM140800444301

Page: 30 of 34

### Test in the frequency 921.4MHz (20 dB bandwidth)



### Test in the frequency 927MHz (20 dB bandwidth)





Report No.: GZEM140800444301

Page: 31 of 34

### 7.5 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz

Test Requirement: FCC Part 15 C section 15.207

Test Method: ANSI C63.10: Clause 6.2

Frequency Range: 150 kHz to 30 MHz

**Detector:** Peak for pre-scan (9 kHz Resolution Bandwidth)

**Test Limit** 

### Limits for conducted disturbance at the mains ports of class B

Frequency Range	Class B Limit dB(μV)			
(MHz)	Quasi-peak	Average		
0.15 to 0.50	66 to 56	56 to 46		
0.50 to 5	56	46		
5 to 30	60	50		

NOTE 1 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

**EUT Operation:** 

Test in normal operating mode. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.


Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).



Report No.: GZEM140800444301

Page: 32 of 34

#### **Test Configuration:**



### Test procedure:

- 1. The mains terminal disturbance voltage test was conducted in a shielded room.
- 2. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu H + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
- 4. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.



Report No.: GZEM140800444301

Page: 33 of 34


#### **Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected. For EUT the communicating was worst case mode.

### The following Quasi-Peak and Average measurements were performed on the EUT:

Neutral Line Level(dB  $\mu$  V)



#### Measure data:


Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB	dBuV	dBuV	dBuV	dB	
0.15816 0.15816 0.17124 0.17124 0.30348 0.30348	0.02 0.02 0.02 0.02 0.01	9.70 9.70 9.70 9.70 9.71 9.71	22.72 12.18 21.10 10.19 8.38 19.52	32.44 21.90 30.82 19.91 18.10 29.24	55.56 64.90 54.90 50.15	-34.08 -34.99	Äverage QP Average Average
0.43052 0.43052 0.97354 0.97354 2.309 2.309	0.01 0.01 0.02 0.02 0.02 0.02	9.80	18.35 8.93 16.61 5.05	28.16 18.74 26.43 14.87 24.44 12.20	57.24 47.24 56.00 46.00 56.00	-29.08 -28.50 -29.57 -31.13 -31.56	QP Average QP Average



Report No.: GZEM140800444301

Page: 34 of 34

### Live Line Level(dBµV)



### Measure result:

Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB	dB	dBuV	dBuV	dBuV	dB	
0.15985	0.02	9.70	24.82	34.54	65.47	-30.93	QP
0.15985	0.02	9.70	14.85	24.57	55.47	-30.90	Average
0.30188	0.01	9.70	25.88	35.59	60.19	-24.60	QP
0.30188	0.01	9.70	17.03	26.74	50.19	-23.45	Average
0.56111	0.01	9.80	24.15	33.96	56.00	-22.04	QP
0.56111	0.01	9.80	13.01	22.82	46.00	-23.18	Average
1.077	0.02	9.80	22.33	32.15	56.00	-23.85	QP
1.077	0.02	9.80	11.67	21.49	46.00	-24.51	Average
1.480	0.02	9.80	11.25	21.07	46.00	-24.93	Average
1.480	0.02	9.80	20.91	30.73		-25.27	_
1.848	0.02	9.80	20.81	30.63	56.00	-25.37	OP
1.848	0.02	9.80	11.53	21.35	46.00	-24.66	Äverage

### End of the report