

RF TEST REPORT



Report No.: 15071087-FCC-R2

Supersede Report No.: N/A

Applicant	Hunan ZTE ICT Technologies Co.,Ltd.	
Product Name	MID	
Model No.	E10Q	
Serial No.	E10G,E10H,E10K,E10P,E10T,E10S,E10Z	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013	
Test Date	November 24 to December 01, 2015	
Issue Date	December 17, 2015	
Test Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
Winnie.Zhang	David Huang	
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15071087-FCC-R2
Page	3 of 58

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH.....	14
6.4 PEAK OUTPUT POWER.....	18
6.5 NUMBER OF HOPPING CHANNEL.....	22
6.6 TIME OF OCCUPANCY (DWELL TIME)	24
6.7 BAND EDGE.....	28
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	36
6.9 RADIATED SPURIOUS EMISSIONS	42
ANNEX A. TEST INSTRUMENT.....	47
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	48
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	53
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	57
ANNEX E. DECLARATION OF SIMILARITY	58

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15071087-FCC-R2	NONE	Original	December 01, 2015
15071087-FCC-R2	V1	Update FCC ID	December 17, 2015

2. Customer information

Applicant Name	Hunan ZTE ICT Technologies Co.,Ltd.
Applicant Add	5F, ZTE ICT R&D Building, No.48 Cailun Rd. , High-Tech Development Zone, Hengyang, China
Manufacturer	Hunan ZTE ICT Technologies Co.,Ltd.
Manufacturer Add	5F, ZTE ICT R&D Building, No.48 Cailun Rd. , High-Tech Development Zone, Hengyang, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	MID
Main Model:	E10Q
Serial Model:	E10G,E10H,E10K,E10P,E10T,E10S,E10Z
Date EUT received:	November 23, 2015
Test Date(s):	November 24 to December 01, 2015
Equipment Category :	DSS
Antenna Gain:	GSM850: -0.7 dBi PCS1900: -0.8 dBi UMTS-FDD Band V: -0.7 dBi UMTS-FDD Band II: -0.8 dBi Bluetooth/BLE: 1 dBi WIFI: 1 dBi GPS: 0 dBi
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS RX: 1575.42 MHz

Test Report	15071087-FCC-R2
Page	7 of 58

Max. Output Power: 3.635dBm

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V : 102CH

UMTS-FDD Band II : 277CH

Number of Channels: WIFI :802.11b/g/n(20M): 11CH

WIFI :802.11n(40M): 7CH

Bluetooth: 79CH

BLE: 40CH

GPS:1CH

Port: Power Port, Earphone Port, USB Port, HDMI Port

Adapter:

Model: SC/10WA050200US

Input Power: Input: AC 100-240V; 50/60Hz;0.5A

Output: DC 5.0V,2.0A

Battery:

Spec:3.7V,7000mAh

Trade Name : ZTE

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2ACYS-E10Q

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- Antenna must be permanently attached to the unit.
- Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 3 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI, the gain is 1.0dBi for Bluetooth/BLE, the gain is 1.0dBi for WIFI.

A permanently attached PIFA antenna for GSM/PCS/ UMTS, the gain is -0.7dBi for GSM850, -0.8dBi for PCS1900, -0.7dBi for UMTS-FDD Band V, -0.8dBi for UMTS-FDD Band II,

A permanently attached PIFA antenna for GPS, the gain is 0dBi for GPS.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	25°C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	November 28, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) \geq 1% of the span - Video (or Average) Bandwidth (VBW) \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot. 		


Remark		
Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail
Test Data	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> N/A
Test Plot	<input checked="" type="checkbox"/> Yes (See below)	<input type="checkbox"/> N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.683	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.683	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.678	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.005	0.863	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.865	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.867	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.867	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.865	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.861	Pass
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result






6.3 20dB Bandwidth

Temperature	25°C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	November 28, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW \geq 1% of the 20 dB bandwidth - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference 		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Measurement result

Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.025	0.8970
	Mid	2441	1.024	0.8990
	High	2480	1.017	0.8960
$\pi/4$ DQPSK	Low	2402	1.295	1.1741
	Mid	2441	1.297	1.1694
	High	2480	1.301	1.1752
8-DPSK	Low	2402	1.301	1.1875
	Mid	2441	1.298	1.1862
	High	2480	1.292	1.1746

Test Plots

20dB Bandwidth measurement result






6.4 Peak Output Power

Temperature	25°C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	November 28, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (2)	a)	FHSS in 2400-2483.5MHz with \geq 75 channels: \leq 1 Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: \leq 0.125 Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with \geq 50 channels: \leq 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with \geq 25 & $<$ 50 channels: \leq 0.25 Watt	<input type="checkbox"/>
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
Test Setup			
Test Procedure		<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold 	

	<ul style="list-style-type: none"> - Allow the trace to stabilize. - Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	3.107	125	Pass
		Mid	2441	3.635	125	Pass
		High	2480	3.602	125	Pass
	$\pi/4$ DQPSK	Low	2402	2.910	125	Pass
		Mid	2441	3.382	125	Pass
		High	2480	3.389	125	Pass
	8-DPSK	Low	2402	3.000	125	Pass
		Mid	2441	3.481	125	Pass
		High	2480	3.517	125	Pass

Test Plots

Output Power measurement result





6.5 Number of Hopping Channel

Temperature	25°C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	November 28, 2015
Tested By :	Winnie Zhang

Requirement(s):

Test Data Yes

Yes (See below) N/A


Test Plot **Yes (See below)** **N/A**

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots

Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	25°C
Relative Humidity	52%
Atmospheric Pressure	1028mbar
Test date :	November 28, 2015
Tested By :	Winnie Zhang

Requirement(s):

Test Data Yes N/A

Yes (See below) N/A


Dwell Time measurement result


Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.87	306.133	400	Pass
		Mid	2.87	306.133	400	Pass
		High	2.86	305.067	400	Pass
	$\pi/4$ DQPSK	Low	2.87	306.133	400	Pass
		Mid	2.88	307.200	400	Pass
		High	2.86	305.067	400	Pass
	8-DPSK	Low	2.87	306.133	400	Pass
		Mid	2.87	306.133	400	Pass
		High	2.87	306.133	400	Pass

 Note: Dwell time=Pulse Time (ms) \times (1600 \div 6 \div 79) \times 31.6

Test Plots

Dwell Time measurement result






6.7 Band Edge

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	November 24, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. An EUT & Support Units is positioned on a Turn Table, which is placed on a Ground Plane. The Turn Table is at a height of 0.8/1.5m. An Ant. Tower is connected to the EUT via a cable, and its height is 1-4m Variable. A Test Receiver is connected to the Ant. Tower. The distance between the EUT & Support Units and the Ant. Tower is 3m.</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, 		


	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data Yes N/A



Test Plot Yes (See below) N/A


Test Plots

GFSK Mode:









π /4 DQPSK Mode:

π /4 DQPSK-Hopping Left Side-PK
Note: F1 is frequency 2400MHz
π /4 DQPSK-Hopping Right Side-PK
Note: F1 is frequency 2483.5MHz




8-DPSK Mode:


 <p>1Pk Max</p> <p>10 dBμV</p> <p>20 dBμV</p> <p>30 dBμV</p> <p>40 dBμV</p> <p>50 dBμV</p> <p>60 dBμV</p> <p>70 dBμV</p> <p>80 dBμV</p> <p>90 dBμV</p> <p>Start 2.31 GHz</p> <p>Stop 2.44 GHz</p> <p>M2[1] 47.18 dBμV 2.382100000 GHz</p> <p>* Att 5 dB * RBW 1 MHz * VBW 3 MHz Ref 102.0 dBμV SWT 2.5ms</p> <p>Limit Check Line Limit-L 74</p> <p>PASS M1[1] PASS</p> <p>64.42 dBμV 2.400000000 GHz</p> <p>M1</p> <p>F1</p>	 <p>1Pk Max</p> <p>10 dBμV</p> <p>20 dBμV</p> <p>30 dBμV</p> <p>40 dBμV</p> <p>50 dBμV</p> <p>60 dBμV</p> <p>70 dBμV</p> <p>80 dBμV</p> <p>90 dBμV</p> <p>Start 2.44 GHz</p> <p>Stop 2.5 GHz</p> <p>M1[1] 48.06 dBμV 2.486850000 GHz</p> <p>* Att 5 dB * RBW 1 MHz * VBW 3 MHz Ref 102.0 dBμV SWT 2.5ms</p> <p>Limit Check Line Limit-R 74</p> <p>PASS M1[1] PASS</p> <p>80 dBμV</p> <p>70 dBμV</p> <p>60 dBμV</p> <p>50 dBμV</p> <p>40 dBμV</p> <p>30 dBμV</p> <p>20 dBμV</p> <p>10 dBμV</p> <p>M1</p> <p>F1</p>
<p>Date: 24.NOV.2015 13:28:26</p> <p>8DPSK-Hopping Left Side-PK</p> <p>Note: F1 is frequency 2400MHz</p>	<p>Date: 24.NOV.2015 13:30:56</p> <p>8DPSK-Hopping Right Side-PK</p> <p>Note: F1 is frequency 2483.5MHz</p>
 <p>1Av Max</p> <p>10 dBμV</p> <p>20 dBμV</p> <p>30 dBμV</p> <p>40 dBμV</p> <p>50 dBμV</p> <p>60 dBμV</p> <p>70 dBμV</p> <p>80 dBμV</p> <p>90 dBμV</p> <p>Start 2.31 GHz</p> <p>Stop 2.44 GHz</p> <p>M3[1] 39.62 dBμV 2.380190000 GHz</p> <p>* Att 5 dB * RBW 1 MHz * VBW 3 MHz Ref 102.0 dBμV SWT 2.5ms</p> <p>Limit Check Line Limit-L 54</p> <p>PASS M1[1] PASS</p> <p>D2[1] 92.63 dBμV 2.410030000 GHz 93.23 dB -10.030000000 MHz</p> <p>M1</p> <p>M2</p> <p>M3</p> <p>F1</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Date: 24.NOV.2015 13:29:23</p> <p>8DPSK-Hopping Left-AV</p>	<p>8DPSK-Hopping Right-AV</p>



6.8 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	November 24, 2015
Tested By :	Winnie Zhang

Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB μ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB μ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss 																

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.3255	39.89	QP	10.03	49.92	59.57	-9.65
2	L1	0.3255	28.80	AVG	10.03	38.83	49.57	-10.74
3	L1	0.3450	39.95	QP	10.03	49.98	59.08	-9.10
4	L1	0.3450	29.29	AVG	10.03	39.32	49.08	-9.76
5	L1	0.6765	34.66	QP	10.03	44.69	56.00	-11.31
6	L1	0.6765	19.69	AVG	10.03	29.72	46.00	-16.28
7	L1	1.0080	35.65	QP	10.03	45.68	56.00	-10.32
8	L1	1.0080	22.86	AVG	10.03	32.89	46.00	-13.11
9	L1	1.4994	33.81	QP	10.04	43.85	56.00	-12.15
10	L1	1.4994	20.73	AVG	10.04	30.77	46.00	-15.23
11	L1	2.5407	31.63	QP	10.05	41.68	56.00	-14.32
12	L1	2.5407	20.20	AVG	10.05	30.25	46.00	-15.75

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1617	41.87	QP	10.02	51.89	65.38	-13.49
2	N	0.1617	24.09	AVG	10.02	34.11	55.38	-21.27
3	N	0.1890	38.28	QP	10.02	48.30	64.08	-15.78
4	N	0.1890	20.13	AVG	10.02	30.15	54.08	-23.93
5	N	0.2163	35.42	QP	10.02	45.44	62.96	-17.52
6	N	0.2163	20.88	AVG	10.02	30.90	52.96	-22.06
7	N	0.3528	35.06	QP	10.02	45.08	58.90	-13.82
8	N	0.3528	24.89	AVG	10.02	34.91	48.90	-13.99
9	N	0.4698	30.63	QP	10.02	40.65	56.52	-15.87
10	N	0.4698	14.94	AVG	10.02	24.96	46.52	-21.56
11	N	1.6515	29.27	QP	10.04	39.31	56.00	-16.69
12	N	1.6515	17.40	AVG	10.04	27.44	46.00	-18.56

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.3489	39.11	QP	10.03	49.14	58.99	-9.85
2	L1	0.3489	31.95	AVG	10.03	41.98	48.99	-7.01
3	L1	0.5322	30.85	QP	10.03	40.88	56.00	-15.12
4	L1	0.5322	18.63	AVG	10.03	28.66	46.00	-17.34
5	L1	0.8793	31.11	QP	10.03	41.14	56.00	-14.86
6	L1	0.8793	17.67	AVG	10.03	27.70	46.00	-18.30
7	L1	1.2810	31.58	QP	10.03	41.61	56.00	-14.39
8	L1	1.2810	19.63	AVG	10.03	29.66	46.00	-16.34
9	L1	2.1702	25.32	QP	10.04	35.36	56.00	-20.64
10	L1	2.1702	14.52	AVG	10.04	24.56	46.00	-21.44
11	L1	2.8800	25.52	QP	10.05	35.57	56.00	-20.43
12	L1	2.8800	14.45	AVG	10.05	24.50	46.00	-21.50

Test Mode: Bluetooth Mode



Test Data


Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.3450	43.23	QP	10.02	53.25	59.08	-5.83
2	N	0.3450	33.59	AVG	10.02	43.61	49.08	-5.47
3	N	0.5556	37.35	QP	10.02	47.37	56.00	-8.63
4	N	0.5556	24.33	AVG	10.02	34.35	46.00	-11.65
5	N	0.6141	35.83	QP	10.02	45.85	56.00	-10.15
6	N	0.6141	24.74	AVG	10.02	34.76	46.00	-11.24
7	N	0.9456	36.42	QP	10.03	46.45	56.00	-9.55
8	N	0.9456	24.52	AVG	10.03	34.55	46.00	-11.45
9	N	1.4019	34.39	QP	10.03	44.42	56.00	-11.58
10	N	1.4019	24.58	AVG	10.03	34.61	46.00	-11.39
11	N	2.0688	35.23	QP	10.04	45.27	56.00	-10.73
12	N	2.0688	25.57	AVG	10.04	35.61	46.00	-10.39

6.9 Radiated Spurious Emissions

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	November 24, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15. 205, §15.209, §15.247(d)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (μV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 – 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (μ V/m)	30 – 88	100	88 – 216	150	216 – 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (μ V/m)												
30 – 88	100												
88 – 216	150												
216 – 960	200												
Above 960	500												
Test Setup	 <p>The diagram illustrates the test setup for radiated spurious emissions. It shows a 'Turn Table' with a 'EUT & Support Units' mounted on it, positioned 3m from an 'Ant. Tower'. The 'Ant. Tower' is mounted on a 'Ground Plane' and has a '1-4m Variable' height adjustment. A 'Test Receiver' is connected to the 'Ant. Tower' to measure the emissions.</p>												
Procedure	<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: 												


	<p>a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen.</p> <p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Bluetooth Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()
1	H	36.0007	34.94	peak	-4.67	30.27	40.00	-9.73	100	14
2	H	215.2678	32.97	peak	-8.87	24.10	43.50	-19.40	100	149
3	H	287.9904	33.16	peak	-7.45	25.71	46.00	-20.29	100	96
4	H	545.1826	31.86	peak	-0.91	30.95	46.00	-15.05	100	254
5	H	701.7610	28.21	peak	1.41	29.62	46.00	-16.38	100	122
6	H	872.1832	26.20	peak	4.19	30.39	46.00	-15.61	100	325

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency (MHz)	Reading (dBuV/ m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree
1	V	30.0000	32.16	QP	-0.26	31.90	40.00	-8.10	100	196
2	V	47.8260	46.14	peak	-12.20	33.94	40.00	-6.06	100	87
3	V	82.3589	39.12	peak	-13.65	25.47	40.00	-14.53	100	188
4	V	351.7079	32.70	peak	-5.42	27.28	46.00	-18.72	100	248
5	V	537.5891	31.73	peak	-1.02	30.71	46.00	-15.29	100	184
6	V	763.3757	28.93	peak	2.62	31.55	46.00	-14.45	100	359

Test Mode:	Transmitting Mode
------------	-------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4804	38.63	AV	V	33.83	6.86	31.72	47.60	54	-6.40
4804	38.28	AV	H	33.83	6.86	31.72	47.25	54	-6.75
4804	46.82	PK	V	33.83	6.86	31.72	55.79	74	-18.21
4804	46.59	PK	H	33.83	6.86	31.72	55.56	74	-18.44

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4882	38.59	AV	V	33.86	6.82	31.82	47.45	54	-6.55
4882	38.22	AV	H	33.86	6.82	31.82	47.08	54	-6.92
4882	46.76	PK	V	33.86	6.82	31.82	55.62	74	-18.38
4882	46.51	PK	H	33.86	6.82	31.82	55.37	74	-18.63

High Channel (2480 MHz)


Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4960	38.55	AV	V	33.9	6.76	31.92	47.29	54	-6.71
4960	38.31	AV	H	33.9	6.76	31.92	47.05	54	-6.95
4960	46.79	PK	V	33.9	6.76	31.92	55.53	74	-18.47
4960	46.43	PK	H	33.9	6.76	31.92	55.17	74	-18.83


Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/19/2015	11/18/2016	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/21/2015	09/20/2016	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/24/2015	09/23/2016	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/25/2015	09/24/2016	<input checked="" type="checkbox"/>


Annex B. EUT And Test Setup Photographs


Annex B.i. Photograph: EUT External Photo






Annex B.ii. Photograph: EUT Internal Photo






Mainboard – Rear View




LCD – Front View



LCD – Rear View




GSM/PCS/UMTS-FDD Antenna View



WIFI/BT/BLE - Antenna View


Annex B.iii. Photograph: Test Setup Photo




Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Annex E. DECLARATION OF SIMILARITY

Hunan ZTE ICT Technologies Co.,Ltd.

To: SIEMIC, 775 Montague Expressway, Milpitas, CA 95035, USA

Declaration Letter

Dear Sir,


For our business issue and marketing requirement, we would like to list 8 model numbers on the FCC certificates and reports, as following:

Model No.: E10Q, E10G, E10H, E10K, E10P, E10T, E10S, E10Z

We declare that, all the model PCB, Antenna and Appearance shape, accessories are the same. The difference of these is listed as below:

Main Model No	Serial Model No	Difference
E10Q	E10G, E10H, E10K, E10P, E10T, E10S, E10Z	Different model name

Thank you!

For and on behalf of
湖南中兴网信科技有限公司
Signature: 
Xu Hong
Authorized Signature

Printed name/title: Xu Hong

Address: 5F, ZTE ICT R&D Building, No.48 Cailun Rd., High-Tech Development Zone, Hengyang, China