

FCC REPORT

Applicant: Shanghai Han Lin Electronic Technology Co. Ltd.

Address of Applicant: 7F-D Yindong Building, No. 58 New Jinqiao Rd. Pudong, Shanghai, China

Equipment Under Test (EUT)

Product Name: Cling Wearable Device

Model No.: AA0912

Trade Mark:



FCC ID: 2ACZH-AA0912

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247:2013

Date of sample receipt: August 21, 2014

Date of Test: August 21-29, 2014

Date of report issued: August 29, 2014

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature in black ink, appearing to read "Robinson Lo". To the left of the signature is a circular blue official seal. The seal contains the text "GTS" in the center, surrounded by "GLOBAL TECHNOLOGY SERVICES" at the top and "TESTING" at the bottom. The seal is partially obscured by the handwritten signature.

Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	August 29, 2014	Original

Prepared By:

Z. Edward. Pan

Date:

August 29, 2014

Project Engineer

Check By:

Hank. Jan

Date:

August 29, 2014

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	7
5.4 DESCRIPTION OF SUPPORT UNITS	7
5.5 TEST FACILITY	7
5.6 TEST LOCATION	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	9
7.1 ANTENNA REQUIREMENT	9
7.2 CONDUCTED PEAK OUTPUT POWER	10
7.3 CHANNEL BANDWIDTH	15
7.4 POWER SPECTRAL DENSITY	17
7.5 BAND EDGES	19
7.5.1 Conducted Emission Method	19
7.5.2 Radiated Emission Method	20
7.6 SPURIOUS EMISSION	23
7.6.1 Conducted Emission Method	23
7.6.2 Radiated Emission Method	25
8 TEST SETUP PHOTO	31
9 EUT CONSTRUCTIONAL DETAILS	33

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Shanghai Han Lin Electronic Technology Co. Ltd.
Address of Applicant:	7F-D Yindong Building, No. 58 New Jinqiao Rd. Pudong, Shanghai, China
Manufacturer:	Shanghai Han Lin Electronic Technology Co. Ltd
Address of Manufacturer:	7F-D Yindong Building, No. 58 New Jinqiao Rd. Pudong, Shanghai, China

5.2 General Description of EUT

Product Name:	Cling Wearable Device
Model No.:	AA0912
Operation Frequency:	2402MHz~2480MHz
Channel Numbers:	40
Channel Separation:	2MHz
Modulation Type:	GFSK
Antenna Type:	PIFA Antenna
Antenna Gain:	0dBi
Power Supply:	Charging Voltage:DC 5.0V Or DC 3.7V Li-ion Battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz

5.3 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
-------------------	--

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number
Emerson Network Power	USB Charger	A1299	N/A

5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 28 2014	Mar. 27 2015
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	Dec. 5, 2013	Dec. 4 2014
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 01 2014	Jun. 30 2015
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Jul. 01 2014	Jun. 30 2015
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 27 2014	June 26 2015
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 28 2014	Mar. 27 2015
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	Mar. 29 2014	Mar. 28 2015
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 29 2014	Mar. 28 2015
11	Coaxial cable	GTS	N/A	GTS210	Mar. 29 2014	Mar. 28 2015
12	Coaxial Cable	GTS	N/A	GTS212	Mar. 29 2014	Mar. 28 2015
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 01 2014	Jun. 30 2015
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 01 2014	Jun. 30 2015
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 27 2014	June 26 2015
16	Band filter	Amindeon	82346	GTS219	Mar. 29 2014	Mar. 28 2015

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	Sep. 07 2013	Sep. 06 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	July 01 2014	June 30 2015
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	July 01 2014	June 30 2015
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	July 01 2014	June 30 2015
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	July 01 2014	June 30 2015
6	Coaxial Cable	GTS	N/A	GTS227	July 01 2014	June 30 2015
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 08 2014	July 07 2015

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement:	
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement:	
(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
<i>The antenna is PIFA antenna, the best case gain of the antenna is 0dBi</i>	
	

7.2 Conducted Emissions


Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.4:2003		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50

* Decreases with the logarithm of the frequency.


Test setup:	Reference Plane LISN AUX Equipment E.U.T Test table/Insulation plane 40cm 80cm EMI Receiver Filter AC power Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement data:

Line:



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.157	41.43	0.15	0.12	41.70	65.60	-23.90	QP
2	0.157	33.84	0.15	0.12	34.11	55.60	-21.49	Average
3	0.317	40.11	0.11	0.10	40.32	59.80	-19.48	QP
4	0.317	30.81	0.11	0.10	31.02	49.80	-18.78	Average
5	0.644	46.16	0.13	0.13	46.42	56.00	-9.58	QP
6	0.644	36.20	0.13	0.13	36.46	46.00	-9.54	Average
7	0.743	50.26	0.14	0.13	50.53	56.00	-5.47	QP
8	0.743	40.04	0.14	0.13	40.31	46.00	-5.69	Average
9	1.210	44.39	0.13	0.13	44.65	56.00	-11.35	QP
10	1.210	31.03	0.13	0.13	31.29	46.00	-14.71	Average
11	2.664	41.66	0.14	0.15	41.95	56.00	-14.05	QP
12	2.664	29.36	0.14	0.15	29.65	46.00	-16.35	Average


Neutral:

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Factor	Loss	Level	Line	
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.162	46.12	0.07	0.12	46.31	65.34 -19.03 QP
2	0.162	37.42	0.07	0.12	37.61	55.34 -17.73 Average
3	0.242	43.39	0.06	0.12	43.57	62.04 -18.47 QP
4	0.242	32.62	0.06	0.12	32.80	52.04 -19.24 Average
5	0.327	44.25	0.06	0.10	44.41	59.53 -15.12 QP
6	0.327	34.21	0.06	0.10	34.37	49.53 -15.16 Average
7	0.727	47.19	0.07	0.13	47.39	56.00 -8.61 QP
8	0.727	36.99	0.07	0.13	37.19	46.00 -8.81 Average
9	1.216	41.86	0.08	0.13	42.07	56.00 -13.93 QP
10	1.216	27.18	0.08	0.13	27.39	46.00 -18.61 Average
11	2.346	40.56	0.10	0.15	40.81	56.00 -15.19 QP
12	2.346	25.88	0.10	0.15	26.13	46.00 -19.87 Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.


7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.4:2003 and KDB558074 D01 DTS Meas Guidance V03
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	-7.80	30.00	Pass
Middle	-6.90		
Highest	-6.55		


Test plot as follows:



Lowest channel




Middle channel



Highest channel

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.4:2003 and KDB558074 D01 DTS Meas Guidance V03
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	Channel Bandwidth (KHz)	Limit(KHz)	Result
Lowest	690.143	>500	Pass
Middle	677.765		
Highest	686.947		


Test plot as follows:



Lowest channel




Middle channel



Highest channel


7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.4:2003 and KDB558074 D01 DTS Meas Guidance V03
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	Power Spectral Density (dBm)	Limit(dBm/3kHz)	Result
Lowest	-8.67	8.00	Pass
Middle	-7.78		
Highest	-7.42		


Test plot as follows:



Lowest channel




Middle channel




Highest channel

7.6 Band edges


7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.4:2003 and KDB558074 D01 DTS Meas Guidance V03
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Test plot as follows:




Lowest channel



Highest channel

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205								
Test Method:	ANSI C63.4: 2003								
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak				
		Peak	1MHz	10Hz	Average				
Limit:	Frequency	Limit (dBuV/m @3m)		Value					
	Above 1GHz	54.00		Average					
		74.00		Peak					
Test setup:									
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. 								
Test Instruments:	Refer to section 6.0 for details								
Test mode:	Refer to section 5.3 for details								
Test results:	Pass								

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test channel:	Lowest							
---------------	--------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	44.44	27.91	5.30	30.37	47.28	74.00	-26.72	Vertical
2390.00	44.24	27.59	5.38	30.18	47.03	74.00	-26.97	Vertical
2400.00	48.47	27.58	5.39	30.18	51.26	74.00	-22.74	Vertical
2310.00	45.35	27.91	5.30	30.37	48.19	74.00	-25.81	Horizontal
2390.00	44.06	27.59	5.38	30.18	46.85	74.00	-27.15	Horizontal
2400.00	46.42	27.58	5.39	30.18	49.21	74.00	-24.79	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	34.48	27.91	5.30	30.37	37.32	54.00	-16.68	Vertical
2390.00	33.16	27.59	5.38	30.18	35.95	54.00	-18.05	Vertical
2400.00	36.26	27.58	5.39	30.18	39.05	54.00	-14.95	Vertical
2310.00	34.66	27.91	5.30	30.37	37.50	54.00	-16.50	Horizontal
2390.00	33.65	27.59	5.38	30.18	36.44	54.00	-17.56	Horizontal
2400.00	35.79	27.58	5.39	30.18	38.58	54.00	-15.42	Horizontal

Test channel:	Highest							
---------------	---------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	45.35	27.53	5.47	29.93	48.42	74.00	-25.58	Vertical
2500.00	43.49	27.55	5.49	29.93	46.60	74.00	-27.40	Vertical
2483.50	43.74	27.53	5.47	29.93	46.81	74.00	-27.19	Horizontal
2500.00	43.56	27.55	5.49	29.93	46.67	74.00	-27.33	Horizontal

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.33	27.53	5.47	29.93	37.40	54.00	-16.60	Vertical
2500.00	33.43	27.55	5.49	29.93	36.54	54.00	-17.46	Vertical
2483.50	33.16	27.53	5.47	29.93	36.23	54.00	-17.77	Horizontal
2500.00	33.43	27.55	5.49	29.93	36.54	54.00	-17.46	Horizontal

Remark:

8. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
9. *The emission levels of other frequencies are very lower than the limit and not show in test report.*


7.7 Spurious Emission

7.7.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.4:2003 and KDB558074 D01 DTS Meas Guidance V03
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected to the E.U.T (Equipment Under Test) via a cable. The E.U.T is placed on a Non-Conducted Table. The entire setup is positioned above a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Test plot as follows:

Lowest channel




30MHz~10GHz




10GHz~25GHz

Middle channel




30MHz~10GHz




10GHz~25GHz

Highest channel





30MHz~10GHz



10GHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209								
Test Method:	ANSI C63.4: 2003								
Test Frequency Range:	30MHz to 25GHz								
Test site:	Measurement Distance: 3m								
Receiver setup:	Frequency	Detector	RBW	VBW	Value				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak				
	Above 1GHz	Peak	1MHz	3MHz	Peak				
		Peak	1MHz	10Hz	Average				
Limit:	Frequency	Limit (dBuV/m @3m)		Value					
	30MHz-88MHz	40.00		Quasi-peak					
	88MHz-216MHz	43.50		Quasi-peak					
	216MHz-960MHz	46.00		Quasi-peak					
	960MHz-1GHz	54.00		Quasi-peak					
	Above 1GHz	54.00		Average					
		74.00		Peak					
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p> 								
Test Procedure:	<p>10. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>11. The EUT was set 3 meters away from the interference-receiving</p>								

	<p>antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>12. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>13. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>14. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>15. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p> <p>16. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis which it is worse case.

Measurement Data**17. Below 1GHz**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
39.85	36.21	15.53	0.66	32.06	20.34	40.00	-19.66	Vertical
61.78	38.86	14.03	0.87	31.93	21.83	40.00	-18.17	Vertical
95.76	38.26	14.90	1.16	31.74	22.58	43.50	-20.92	Vertical
228.49	37.40	13.57	2.01	32.15	20.83	46.00	-25.17	Vertical
438.66	35.56	17.55	3.04	31.75	24.40	46.00	-21.60	Vertical
912.86	36.21	23.18	4.90	31.19	33.10	46.00	-12.90	Vertical
40.70	36.11	15.58	0.67	32.05	20.31	40.00	-19.69	Horizontal
100.23	46.23	15.11	1.19	31.76	30.77	43.50	-12.73	Horizontal
233.35	46.64	13.78	2.04	32.16	30.30	46.00	-15.70	Horizontal
360.45	42.20	16.43	2.67	32.00	29.30	46.00	-16.70	Horizontal
593.05	35.94	20.35	3.70	31.07	28.92	46.00	-17.08	Horizontal
875.25	35.55	22.87	4.76	31.21	31.97	46.00	-14.03	Horizontal

18. Above 1GHz

Test channel:	Lowest							
---------------	--------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	34.22	31.78	8.60	32.09	42.51	74.00	-31.49	Vertical
7206.00	31.26	36.15	11.65	32.00	47.06	74.00	-26.94	Vertical
9608.00	31.03	37.95	14.14	31.62	51.50	74.00	-22.50	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	33.29	31.78	8.60	32.09	41.58	74.00	-32.42	Horizontal
7206.00	30.27	36.15	11.65	32.00	46.07	74.00	-27.93	Horizontal
9608.00	29.64	37.95	14.14	31.62	50.11	74.00	-23.89	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	24.66	31.78	8.60	32.09	32.95	54.00	-21.05	Vertical
7206.00	21.64	36.15	11.65	32.00	37.44	54.00	-16.56	Vertical
9608.00	21.02	37.95	14.14	31.62	41.49	54.00	-12.51	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	23.97	31.78	8.60	32.09	32.26	54.00	-21.74	Horizontal
7206.00	20.63	36.15	11.65	32.00	36.43	54.00	-17.57	Horizontal
9608.00	19.84	37.95	14.14	31.62	40.31	54.00	-13.69	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

Remark:

19. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

20. “**”, means this data is the too weak instrument of signal is unable to test.

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	34.34	31.86	8.67	32.12	42.75	74.00	-31.25	Vertical
7326.00	32.60	36.41	11.72	31.89	48.84	74.00	-25.16	Vertical
9768.00	30.30	38.35	14.27	31.62	51.30	74.00	-22.70	Vertical
12210.00	*					74.00		Vertical
14652.00	*					74.00		Vertical
4884.00	33.77	31.86	8.67	32.12	42.18	74.00	-31.82	Horizontal
7326.00	29.48	36.41	11.72	31.89	45.72	74.00	-28.28	Horizontal
9768.00	30.95	38.35	14.27	31.62	51.95	74.00	-22.05	Horizontal
12210.00	*					74.00		Horizontal
14652.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	24.51	31.86	8.67	32.12	32.92	54.00	-21.08	Vertical
7326.00	22.64	36.41	11.72	31.89	38.88	54.00	-15.12	Vertical
9768.00	20.21	38.35	14.27	31.62	41.21	54.00	-12.79	Vertical
12210.00	*					54.00		Vertical
14652.00	*					54.00		Vertical
4884.00	23.94	31.86	8.67	32.12	32.35	54.00	-21.65	Horizontal
7326.00	19.74	36.41	11.72	31.89	35.98	54.00	-18.02	Horizontal
9768.00	21.24	38.35	14.27	31.62	42.24	54.00	-11.76	Horizontal
12210.00	*					54.00		Horizontal
14652.00	*					54.00		Horizontal

Remark:

21. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

22. "", means this data is the too weak instrument of signal is unable to test.

Test channel:	Highest							
---------------	---------	--	--	--	--	--	--	--

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	34.86	31.93	8.73	32.16	43.36	74.00	-30.64	Vertical
7440.00	31.47	36.59	11.79	31.78	48.07	74.00	-25.93	Vertical
9920.00	30.23	38.81	14.38	31.88	51.54	74.00	-22.46	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	34.00	31.93	8.73	32.16	42.50	74.00	-31.50	Horizontal
7440.00	29.66	36.59	11.79	31.78	46.26	74.00	-27.74	Horizontal
9920.00	30.19	38.81	14.38	31.88	51.50	74.00	-22.50	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.02	31.93	8.73	32.16	33.52	54.00	-20.48	Vertical
7440.00	21.97	36.59	11.79	31.78	38.57	54.00	-15.43	Vertical
9920.00	20.36	38.81	14.38	31.88	41.67	54.00	-12.33	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	24.55	31.93	8.73	32.16	33.05	54.00	-20.95	Horizontal
7440.00	19.85	36.59	11.79	31.78	36.45	54.00	-17.55	Horizontal
9920.00	20.64	38.81	14.38	31.88	41.95	54.00	-12.05	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal



Remark:

23. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

24. "", means this data is the too weak instrument of signal is unable to test.

8 Test Setup Photo

Radiated Emission




Conducted Emission






9 EUT Constructional Details





























-----End-----