RF EXPOSURE TEST FCC ID: 2AD25-GEOPAD

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

<u> </u>						
MHz	5	10	15	20	25	mm
150	39	77	116	155	194	
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	SAR Test Exclusion
1900	11	22	33	44	54	Threshold (mW)
2450	10	19	29	38	48	1111 (311 (11))
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	
300	164	192	219	246	274	
450	134	157	179	201	224	
835	98	115	131	148	164	
900	95	111	126	142	158	G 4 D . T.
1500	73	86	98	110	122	SAR Test Exclusion
1900	65	76	87	98	109	Threshold (mW)
2450	57	67	77	86	96	inconoid (iii w)
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	
5800	37	44	50	56	62	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

\leq 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] •
[$\sqrt{f_{\text{(GHz)}}}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR,16 where
\square f _(GHz) is the RF channel transmit frequency in GHz
\square Power and distance are rounded to the nearest mW and mm before calculation 17
☐ The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for

transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation

distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum Rated Peak RF power for tune up:

IEEE802.11 b, 8.5dBm±1 IEEE802.11 g, 8.5 dBm±1

IEEE802.11 n/HT20 , 8.5 dBm±1

IEEE802.11 n/HT40, 7.5 dBm±1

modulation	Maximum Rated Peak RF power (dBm)	Maximum Conducted Output Power (mW)	Exclusion Thresholds Results	Limit
IEEE802.11 b	9.5	8.91	2.767	3.0
IEEE802.11 g	9.5	8.91	2.782	3.0
IEEE802.11 n/HT20	9.5	8.91	2.796	3.0
IEEE802.11 n/HT40	8.5	7.08	2.222	3.0

Conclusion: No SAR is required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, <math>mW)/(min. test separation distance, mm)] • $[\sqrt{f_{(GHz)}}]$

 $f_{(\text{GHz})}\,\text{is}$ the RF channel transmit frequency in GHz

☐ Distance=5mm

Maximum measured transmitter power.

802.11B

frequency range (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)	Exclusion Thresholds Results	Limit
2412	9.36	8.63	2.680	3.0
2437	9.22	8.36	2.610	3.0
2462	9.17	8.26	2.592	3.0

Conclusion: No SAR is required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, <math>mW)/(min. test separation distance, mm)] • $[\sqrt{f_{(GHz)}}]$

 $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz

☐ Distance=5mm

0	2	4	a	
X	ი2	1	1	(i

frequency range (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)	Exclusion Thresholds Results	Limit
2412	9.11	8.15	2.531	3.0
2437	9.04	8.02	2.504	3.0
2462	9.16	8.24	2.586	3.0

Conclusion: No SAR is required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, <math>mW)/(min. test separation distance, mm)] • $[\sqrt{f_{(GHz)}}]$ $f_{(GHz)}$ is the RF channel transmit frequency in GHz

☐ Distance=5mm

802.11N20

frequency range (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)	Exclusion Thresholds Results	Limit
2412	8.49	7.06	2.193	3.0
2437	8.35	6.84	2.135	3.0
2462	8.22	6.64	2.084	3.0

Conclusion: No SAR is required.

Note: Exclusion Thresholds Results= $[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • <math>[\sqrt{f_{(GHz)}}]$

f(GHz) is the RF channel transmit frequency in GHz

☐ Distance=5mm

802.11N 40M

frequency range (MHz)	Maximum Peak Conducted Output Power (dBm)	Maximum Conducted Output Power (mW)	Exclusion Thresholds Results	Limit
2422	7.57	5.71	1.777	3.0
2437	7.43	5.53	1.726	3.0
2452	7.41	5.51	1.726	3.0

Conclusion: No SAR is required.

Note: Exclusion Thresholds Results=[($max.\ power\ of\ channel$, including tune-up tolerance, mW)/($min.\ test\ separation\ distance,\ mm$)] • [$\sqrt{f_{(GHz)}}$]

 $f_{\left(GHz\right)}$ is the RF channel transmit frequency in GHz

☐ Distance=5mm