

FCC TEST REPORT

FCC ID: 2AD2W-LUMA500

Report No. : SSP24110368-2E

Applicant : C&A Marketing Inc.

Product Name : Projector

Model Name : RODPJS500

Test Standard : FCC Part 15.247

Date of Issue : 2025-01-02



Shenzhen CCUT Quality Technology Co., Ltd.

1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen,
Guangdong, China; (Tel.:+86-755-23406590 website: www.ccuttest.com)

This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.

Test Report Basic Information

Applicant:	C&A Marketing Inc.
Address of Applicant:	114 Tived Lane East, Edison, NJ, United States, 08837
Manufacturer:	C&A Marketing Inc.
Address of Manufacturer:	114 Tived Lane East, Edison, NJ, United States, 08837
Product Name:	Projector
Brand Name:	-
Main Model:	RODPJS500
Series Models:	RODPJS500B, RODPJS500K, RODPJS500BK
Test Standard:	FCC Part 15 Subpart C KDB 558074 D01 15.247 Meas Guidance v05r02 ANSI C63.4-2014 ANSI C63.10-2013
Date of Test	2024-11-29 to 2025-01-02
Test Result:	PASS
Tested By	<u>Coke Huang</u> (Coke Huang)
Reviewed By:	<u>Lieber Ouyang</u> (Lieber Ouyang)
Authorized Signatory:	<u>Lahm Peng</u> (Lahm Peng)
Note : This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen CCUT Quality Technology Co., Ltd.. All test data presented in this test report is only applicable to presented test sample.	



CONTENTS

1. General Information.....	5
1.1 Product Information	5
1.2 Test Setup Information.....	6
1.3 Compliance Standards.....	7
1.4 Test Facilities.....	7
1.5 List of Measurement Instruments	8
1.6 Measurement Uncertainty	9
2. Summary of Test Results	10
3. Antenna Requirement.....	11
3.1 Standard and Limit.....	11
3.2 Test Result.....	11
4. Conducted Emissions	12
4.1 Standard and Limit.....	12
4.2 Test Procedure.....	12
4.3 Test Data and Results	13
5. Radiated Emissions	16
5.1 Standard and Limit.....	16
5.2 Test Procedure.....	16
5.3 Test Data and Results	18
6. Band-edge Emissions(Radiated).....	22
6.1 Standard and Limit.....	22
6.2 Test Procedure.....	22
6.3 Test Data and Results	22
7. Maximum Conducted Output Power	24
7.1 Standard and Limit.....	24
7.2 Test Procedure.....	24
7.3 Test Data and Results	24
8. Occupied Bandwidth	38
8.1 Standard and Limit.....	38
8.2 Test Procedure.....	38
8.3 Test Data and Results	38
9. Maximum Power Spectral Density	48
9.1 Standard and Limit.....	48
9.2 Test Procedure.....	48
9.3 Test Data and Results	48
10. Band-edge Emission(Conducted).....	57
10.1 Standard and Limit.....	57
10.2 Test Procedure.....	57
10.3 Test Data and Results	57
11. Conducted RF Spurious Emissions.....	65
11.1 Standard and Limit.....	65
11.2 Test Procedure.....	65
11.3 Test Data and Results	65

Revision History

Revision	Issue Date	Description	Revised By
V1.0	2025-01-02	Initial Release	Lahm Peng

1. General Information

1.1 Product Information

Product Name:	Projector
Trade Name:	-
Main Model:	RODPJS500
Series Models:	RODPJS500B, RODPJS500K, RODPJS500BK
Rated Voltage:	DC 11.1V by battery, DC 15V/1.5A by adapter Charing
Power Adapter:	INPUT: 100-240V~50/60Hz, 1.5A, OUTPUT:5V=3A, 15W, 9V=3A, 27W, 12V=3A, 36W, 15V=3A, 45W, 20V=2.25A, 45W
Battery:	DC 11.1V, 3500mAh
Test Sample No:	SSP24110368-1
Hardware Version:	V1.0
Software Version:	V1.0
Note 1: The test data is gathered from a production sample, provided by the manufacturer.	
Note 2: The color of appearance and model name of series models listed are different from the main model, but the circuit and the electronic construction are the same, declared by the manufacturer.	

Wireless Specification	
Wireless Standard:	802.11b/g/n
Operating Frequency:	2412MHz ~ 2462MHz for 802.11b/g/n(HT20) 2422MHz ~ 2452MHz for 802.11n(HT40)
RF Output Power:	17.25dBm
Number of Channel:	11/7
Channel Separation:	5MHz
Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Antenna Gain:	ANT1:1.38dBi, ANT2:2.15dBi
Type of Antenna:	FPCB Antenna
Type of Device:	☐ Portable Device ☒ Mobile Device ☐ Modular Device
Note: The EUT incorporates a MIMO function.	

1.2 Test Setup Information

List of Test Modes			
Test Mode	Description	Remark	
TM1	802.11b	2412MHz/2437MHz/2462MHz	
TM2	802.11g	2412MHz/2437MHz/2462MHz	
TM3	802.11n(H20)	2412MHz/2437MHz/2462MHz	
TM4	802.11n(H40)	2422MHz/2437MHz/2452MHz	
List and Details of Auxiliary Cable			
Description	Length (cm)	Shielded/Unshielded	With/Without Ferrite
-	-	-	-
-	-	-	-
List and Details of Auxiliary Equipment			
Description	Manufacturer	Model	Serial Number
-	-	-	-
-	-	-	-

List of Channels							
No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)	No. of Channel	Frequency (MHz)
01	2412	05	2432	09	2452	13	--
02	2417	06	2437	10	2457	14	--
03	2422	07	2442	11	2462	15	--
04	2427	08	2447	12	--	16	--

1.3 Compliance Standards

Compliance Standards	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
All measurements contained in this report were conducted with all above standards	
According to standards for test methodology	
FCC Part 15 Subpart C	FEDERAL COMMUNICATIONS COMMISSION, RADIO FREQUENCY DEVICES, Intentional Radiators
KDB 558074 D01 15.247 Meas Guidance v05r02	GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES
ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Maintenance of compliance is the responsibility of the manufacturer or applicant. Any modification of the product, which result is lowering the emission, should be checked to ensure compliance has been maintained.	

1.4 Test Facilities

Laboratory Name:	Shenzhen CCUT Quality Technology Co., Ltd. 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China
CNAS Laboratory No.:	L18863
A2LA Certificate No.:	6893.01
FCC Registration No:	583813
ISED Registration No.:	CN0164
All measurement facilities used to collect the measurement data are located at 1F, Building 35, Changxing Technology Industrial Park, Yutang Street, Guangming District, Shenzhen, Guangdong, China.	

1.5 List of Measurement Instruments

Description	Manufacturer	Model	Serial Number	Cal. Date	Due. Date
Conducted Emissions					
AMN	ROHDE&SCHWARZ	ENV216	101097	2024-08-07	2025-08-06
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100242	2024-08-07	2025-08-06
Test Cable	N/A	Cable 5	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	EMEC-3A1+	N/A	N/A
Radiated Emissions					
EMI Test Receiver	ROHDE&SCHWARZ	ESPI	100154	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	MY48030972	2024-08-07	2025-08-06
Spectrum Analyzer	ROHDE&SCHWARZ	FSV40-N	101692	2024-08-07	2025-08-06
Amplifier	SCHWARZBECK	BBV 9743B	00251	2024-08-07	2025-08-06
Amplifier	HUABO	YXL0518-2.5-45	--	2024-08-07	2025-08-06
Amplifier	COM-MW	DLAN-18G-4G-02	10229104	2024-08-07	2025-08-06
Loop Antenna	DAZE	ZN30900C	21104	2024-08-03	2025-08-02
Broadband Antenna	SCHWARZBECK	VULB 9168	01320	2024-08-03	2025-08-02
Horn Antenna	SCHWARZBECK	BBHA 9120D	02553	2024-08-03	2025-08-02
Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2024-08-03	2025-08-02
Attenuator	QUANJUDA	6dB	220731	2024-08-07	2025-08-06
Test Cable	N/A	Cable 1	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 2	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 3	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 4	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 8	N/A	2024-08-07	2025-08-06
Test Cable	N/A	Cable 9	N/A	2024-08-07	2025-08-06
EMI Test Software	FARA	EZ-EMC	FA-03A2 RE+	N/A	N/A
Conducted RF Testing					
RF Test System	MWRFTTest	MW100-RFCB	220418SQS-37	2024-08-07	2025-08-06
Spectrum Analyzer	KEYSIGHT	N9020A	ATO-90521	2024-08-07	2025-08-06
RF Test Software	MWRFTTest	MTS 8310	N/A	N/A	N/A
Laptop	Lenovo	ThinkPad E15 Gen 3	SPPOZ22485	N/A	N/A
DUT Test Software	Microsoft	Command Prompt	N/A	N/A	N/A

1.6 Measurement Uncertainty

Test Item	Conditions	Uncertainty
Conducted Emissions	9kHz ~ 30MHz	±1.64 dB
Radiated Emissions	9kHz ~ 30MHz	±2.88 dB
	30MHz ~ 1GHz	±3.32 dB
	1GHz ~ 18GHz	±3.50 dB
	18GHz ~ 40GHz	±3.66 dB
Conducted Output Power	9kHz ~ 26GHz	±0.50 dB
Occupied Bandwidth	9kHz ~ 26GHz	±4.0 %
Conducted Spurious Emission	9kHz ~ 26GHz	±1.32 dB
Power Spectrum Density	9kHz ~ 26GHz	±0.62 dB

2. Summary of Test Results

FCC Rule	Description of Test Item	Result
FCC Part 15.203	Antenna Requirement	Passed
FCC Part 15.247(i)	RF Exposure(see the RF exposure report)	Passed
FCC Part 15.207	Conducted Emissions	Passed
FCC Part 15.209, 15.247(d)	Radiated Emissions	Passed
FCC Part 15.247(d)	Band-edge Emissions(Radiated)	Passed
FCC Part 15.247(b)(3)	Maximum Conducted Output Power	Passed
FCC Part 15.247(a)(2)	Occupied Bandwidth	Passed
FCC Part 15.247(e)	Maximum Power Spectral Density	Passed
FCC Part 15.247(d)	Band-edge Emissions(Conducted)	Passed
FCC Part 15.247(d)	Conducted RF Spurious Emissions	Passed
Passed: The EUT complies with the essential requirements in the standard Failed: The EUT does not comply with the essential requirements in the standard N/A: Not applicable		

3. Antenna Requirement

3.1 Standard and Limit

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has two FPCB antennas that meet the requirements of this section.

4. Conducted Emissions

4.1 Standard and Limit

According to the rule FCC Part 15.207, Conducted emissions limit, the limit for a wireless device as below:

Frequency of Emission (MHz)	Conducted emissions (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Note 1: Decreases with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz
 Note 2: The lower limit applies at the band edges

4.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.2.



Test Setup Block Diagram

a) The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

b) The following is the setting of the receiver

Attenuation: 10dB

Start Frequency: 0.15MHz

Stop Frequency: 30MHz

IF Bandwidth: 9kHz

c) The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

d) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

e) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

f) LISN is at least 80 cm from nearest part of EUT chassis.

g) For the actual test configuration, please refer to the related Item - photographs of the test setup.


4.3 Test Data and Results

All of the modes have been tested, the EUT complied with the FCC Part 15.207 standard limit for a wireless device, and with the worst case as below:

Remark: Level = Reading + Factor, Margin = Level - Limit

Test Plots and Data of Conducted Emissions


Tested Mode:	TM3
Test Voltage:	AC 120V/60Hz
Test Power Line:	Neutral
Remark:	DC 15V/1.5A by adapter Charing



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1635	38.72	9.24	47.96	65.28	-17.32	QP	P	
2	0.1635	24.21	9.24	33.45	55.28	-21.83	AVG	P	
3 *	0.3975	34.69	9.38	44.07	57.91	-13.84	QP	P	
4	0.3975	15.11	9.38	24.49	47.91	-23.42	AVG	P	
5	0.7755	30.64	9.41	40.05	56.00	-15.95	QP	P	
6	0.7755	13.70	9.41	23.11	46.00	-22.89	AVG	P	
7	1.8735	30.90	9.46	40.36	56.00	-15.64	QP	P	
8	1.8735	15.70	9.46	25.16	46.00	-20.84	AVG	P	
9	8.0250	29.36	9.57	38.93	60.00	-21.07	QP	P	
10	8.0250	16.79	9.57	26.36	50.00	-23.64	AVG	P	
11	18.1545	36.16	9.82	45.98	60.00	-14.02	QP	P	
12	18.1545	25.56	9.82	35.38	50.00	-14.62	AVG	P	

Test Plots and Data of Conducted Emissions

Tested Mode:	TM3
Test Voltage:	AC 120V/60Hz
Test Power Line:	Live
Remark:	DC 15V/1.5A by adapter Charing



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1635	37.89	9.24	47.13	65.28	-18.15	QP	P	
2	0.1635	23.12	9.24	32.36	55.28	-22.92	AVG	P	
3	0.3771	35.82	9.38	45.20	58.34	-13.14	QP	P	
4	0.3771	23.32	9.38	32.70	48.34	-15.64	AVG	P	
5	1.2075	31.65	9.44	41.09	56.00	-14.91	QP	P	
6	1.2075	18.18	9.44	27.62	46.00	-18.38	AVG	P	
7	4.4699	31.36	9.55	40.91	56.00	-15.09	QP	P	
8	4.4699	18.99	9.55	28.54	46.00	-17.46	AVG	P	
9	11.3010	32.08	9.55	41.63	60.00	-18.37	QP	P	
10	11.3010	21.00	9.55	30.55	50.00	-19.45	AVG	P	
11 *	19.7565	37.48	9.97	47.45	60.00	-12.55	QP	P	
12	19.7565	25.87	9.97	35.84	50.00	-14.16	AVG	P	

Note1: The test data shows only the worst case ANT. 1 and ANT. 2 Simultaneous emission mode.

5. Radiated Emissions

5.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

According to the rule FCC Part 15.209, Radiated emission limit for a wireless device as below:

Frequency of Emission (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3
Note: The more stringent limit applies at transition frequencies.		

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

5.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6.



Block Diagram of Radiated Emission Below 30MHz



Block Diagram of Radiated Emission From 30MHz to 1GHz




Block Diagram of Radiated Emission Above 1GHz

- a) The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
- b) EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- c) Use the following spectrum analyzer settings:
Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, 10kHz for $f < 30\text{MHz}$
VBW $\geq$ RBW, Sweep = auto
Detector function = peak
Trace = max hold
- d) Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- e) The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 10Hz, Detector = PK for AV value, while maintaining all of the other instrument settings.
- f) For the actual test configuration, please refer to the related item - EUT test photos.

5.3 Test Data and Results

All of the 802.11b, 802.11g and 802.11n modes have been tested, the EUT complied with the FCC Part 15.247 standard limit for a wireless device, and with the worst case 802.11n_HT20_2412MHz as below:

Remark: Level = Reading + Factor, Margin = Level - Limit




Radiated Emission Test Data (30MHz to 1GHz)

Tested Mode: TM3

Test Voltage: AC 120V/60Hz

Test Antenna Polarization: Vertical

Remark:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	228.4904	40.71	-11.22	29.49	46.00	-16.51	QP	100	105	P	
2	315.4808	37.81	-7.43	30.38	46.00	-15.62	QP	100	270	P	
3	370.7023	32.83	-6.60	26.23	46.00	-19.77	QP	100	78	P	
4 *	601.4265	40.31	-1.59	38.72	46.00	-7.28	QP	100	10	P	
5	785.0935	30.06	1.33	31.39	46.00	-14.61	QP	100	277	P	
6	962.1623	38.34	3.12	41.46	54.00	-12.54	QP	100	181	P	

Note1: The test data shows only the worst case ANT. 1 and ANT. 2 Simultaneous emission mode.

Radiated Emission Test Data (Above 1GHz)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (802.11n_HT20_2412MHz)							
4824	76.82	-14.72	62.1	74	-11.9	H	PK
4824	62.46	-14.72	47.74	54	-6.26	H	AV
7236	62.92	-8.41	54.51	74	-19.49	H	PK
7236	46.61	-8.41	38.2	54	-15.8	H	AV
4824	74.29	-14.72	59.57	74	-14.43	V	PK
4824	60.02	-14.72	45.3	54	-8.7	V	AV
7236	63.98	-8.41	55.57	74	-18.43	V	PK
7236	50	-8.41	41.59	54	-12.41	V	AV
Middle Channel (802.11n_HT20_2437MHz)							
4874	74.72	-14.64	60.08	74	-13.92	H	PK
4874	61.69	-14.64	47.05	54	-6.95	H	AV
7311	64.54	-8.28	56.26	74	-17.74	H	PK
7311	45.57	-8.28	37.29	54	-16.71	H	AV
4874	73.61	-14.64	58.97	74	-15.03	V	PK
4874	57.86	-14.64	43.22	54	-10.78	V	AV
7311	63.86	-8.28	55.58	74	-18.42	V	PK
7311	48.43	-8.28	40.15	54	-13.85	V	AV
Highest Channel (802.11n_HT20_2462MHz)							
4924	77.68	-14.53	63.15	74	-10.85	H	PK
4924	60.19	-14.53	45.66	54	-8.34	H	AV
7386	62.73	-8.13	54.6	74	-19.4	H	PK
7386	50.53	-8.13	42.4	54	-11.6	H	AV
4924	74.9	-14.53	60.37	74	-13.63	V	PK
4924	60.42	-14.53	45.89	54	-8.11	V	AV
7386	63.55	-8.13	55.42	74	-18.58	V	PK
7386	49.1	-8.13	40.97	54	-13.03	V	AV

Note 1: This EUT was tested at 3 orthogonal positions, the X-axis being the worst, and the worst-case position data is reported. The test data shows ANT. 1 and ANT. 2 Synchronous launch mode.

Note 2: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

Note 3: Other emissions are attenuated 20dB below the limits from 9kHz to 30MHz, so it does not recorded report, 18GHz-26GHz not recorded for no spurious point have a margin of less than 6 dB with respect to the limits.

6. Band-edge Emissions(Radiated)

6.1 Standard and Limit

According to §15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

6.2 Test Procedure

Test is conducting under the description of ANSI C63.10 - 2013 section 6.3 to 6.6 and section 6.10.



Test Setup Block Diagram

As the radiated emissions testing, set the Lowest and Highest Transmitting Channel, observed the outside band of 2310MHz to 2400MHz and 2483.5MHz to 2500MHz, than mark the higher-level emission for comparing with the FCC rules.

6.3 Test Data and Results

Based on all tested data, the EUT complied with the FCC Part 15.247 standard limit, and with the worst case as below:

Test Mode	Frequency	Limit	Result
	MHz	dBuV/dBc	
Lowest	2310.00	<54 dBuV	Pass
	2390.00	<54 dBuV	Pass
Highest	2483.50	<54 dBuV	Pass
	2500.00	<54 dBuV	Pass

Radiated Emission Test Data (Band edge emissions)							
Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	PK/AV
Lowest Channel (802.11n_HT20_2412MHz)							
2310	67.78	-21.34	46.44	74	-27.56	H	PK
2310	52.27	-21.34	30.93	54	-23.07	H	AV
2390	67.71	-20.96	46.75	74	-27.25	H	PK
2390	50.27	-20.96	29.31	54	-24.69	H	AV
2400	72.6	-20.91	51.69	74	-22.31	H	PK
2400	55.22	-20.91	34.31	54	-19.69	H	AV
2310	66.05	-21.34	44.71	74	-29.29	V	PK
2310	51.04	-21.34	29.7	54	-24.3	V	AV
2390	65.82	-20.96	44.86	74	-29.14	V	PK
2390	51.16	-20.96	30.2	54	-23.8	V	AV
2400	72.59	-20.91	51.68	74	-22.32	V	PK
2400	55.67	-20.91	34.76	54	-19.24	V	AV
Highest Channel (802.11n_HT20_2462MHz)							
2483.50	69.58	-20.51	49.07	74	-24.93	H	PK
2483.50	53.15	-20.51	32.64	54	-21.36	H	AV
2500	64.23	-20.43	43.8	74	-30.2	H	PK
2500	50.84	-20.43	30.41	54	-23.59	H	AV
2483.50	67.19	-20.51	46.68	74	-27.32	V	PK
2483.50	54.38	-20.51	33.87	54	-20.13	V	AV
2500	68.5	-20.43	48.07	74	-25.93	V	PK
2500	52.9	-20.43	32.47	54	-21.53	V	AV

Note 1: The test data shows ANT. 1 and ANT. 2 Simultaneous emission mode.

Remark: Level = Reading + Factor, Margin = Level - Limit

7. Maximum Conducted Output Power

7.1 Standard and Limit

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

7.2 Test Procedure

A spectrum analyzer or similar device shall be used to observe a sample of the modulated transmitter's radio frequency power output.

- 1) A measurement instrument with an integrated channel bandwidth function may be used to automate the test process.
- 2) Set center of frequency = operating frequency.
- 3) Connect the EUT to the RF input of the spectrum analyzer via a low loss RF cable
- 4) Set the RBW = 1MHz, VBW = 3MHz, Detector = RMS, Sweep = Auto.
- 5) Set the SPAN to 40MHz/80MHz for 20MHz/40MHz emission bandwidth mode.
- 6) Measure the highest amplitude appearing on spectral display and mark the value.
- 7) Repeat the above procedures until all frequency measured was complete.




Test Setup Block Diagram

7.3 Test Data and Results

Duty Cycle


Test Mode	Antenna	Test Channel MHz	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)	T(ms)
802.11b	ANT 1	2412	95.33	0.21	1.07	0.935
		2437	95.33	0.21	1.07	0.935
		2462	95.12	0.22	1.07	0.935
	ANT 2	2412	94.56	0.24	1.07	0.935
		2437	95.33	0.21	1.07	0.935
		2462	95.33	0.21	1.07	0.935
802.11g	ANT 1	2412	77.39	1.11	5.62	0.178
		2437	77.39	1.11	5.62	0.178
		2462	77.39	1.11	5.62	0.178
	ANT 2	2412	76.52	1.16	5.68	0.176
		2437	77.39	1.11	5.62	0.178
		2462	77.39	1.11	5.62	0.178
802.11n(HT20)	ANT 1	2412	76.85	1.14	6.02	0.166
		2437	76.15	1.18	6.02	0.166
		2462	77.06	1.13	5.95	0.168
	ANT 2	2412	75.23	1.24	6.1	0.164
		2437	75.23	1.24	6.1	0.164
		2462	76.15	1.18	6.02	0.166
802.11n(HT40)	ANT 1	2422	66.23	1.79	9.8	0.102
		2437	67.11	1.73	9.8	0.102
		2452	66.23	1.79	9.8	0.102
	ANT 2	2422	65.79	1.82	10	0.100
		2437	66.23	1.79	9.8	0.102
		2452	65.79	1.82	10	0.100

ANT1:




802.11n(HT20)

2412MHz




802.11n(HT40)


2422MHz




2437MHz




2437MHz




2462MHz




2452MHz



ANT2:





SISO mode:

Test Mode	Antenna	Test Channel (MHz)	Conducted Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Test Result
802.11b	ANT 1	2412	16.59	0.21	16.8	30	Pass
		2437	17	0.21	17.21	30	Pass
		2462	16.88	0.22	17.1	30	Pass
	ANT 2	2412	16.38	0.24	16.62	30	Pass
		2437	16.97	0.21	17.18	30	Pass
		2462	17.04	0.21	17.25	30	Pass
802.11g	ANT 1	2412	13.02	1.11	14.13	30	Pass
		2437	13.2	1.11	14.31	30	Pass
		2462	13.49	1.11	14.6	30	Pass
	ANT 2	2412	13.27	1.16	14.43	30	Pass
		2437	13.38	1.11	14.49	30	Pass
		2462	13.73	1.11	14.84	30	Pass
802.11n(HT20)	ANT 1	2412	12.52	1.14	13.66	30	Pass
		2437	12.66	1.18	13.84	30	Pass
		2462	12.91	1.13	14.04	30	Pass
	ANT 2	2412	12.92	1.24	14.16	30	Pass
		2437	12.98	1.24	14.22	30	Pass
		2462	13.19	1.18	14.37	30	Pass
802.11n(HT40)	ANT 1	2422	11.5	1.79	13.29	30	Pass
		2437	11.54	1.73	13.27	30	Pass
		2452	11.58	1.79	13.37	30	Pass
	ANT 2	2422	11.68	1.82	13.5	30	Pass
		2437	11.84	1.79	13.63	30	Pass
		2452	11.96	1.82	13.78	30	Pass

Note: Total Power = Conducted Power + Duty Factor


MIMO mode:

Test Mode	Antenna	Test Channel (MHz)	Power (dBm)	Duty Factor (dB)	Total Power (dBm)	Limit (dBm)	Test Result
802.11n(HT20) MIMO	ANT 1	2412	10.53	1.14	11.67	30	Pass
		2437	10.61	1.18	11.79	30	Pass
		2462	10.9	1.13	12.03	30	Pass
	ANT 2	2412	10.83	1.24	12.07	30	Pass
		2437	10.89	1.24	12.13	30	Pass
		2462	11.04	1.18	12.22	30	Pass
	MIMO	2412	13.69	-	14.89	30	Pass
		2437	13.76	-	14.97	30	Pass
		2462	13.98	-	15.14	30	Pass
802.11n(HT40) MIMO	ANT 1	2422	9.45	1.79	11.24	30	Pass
		2437	9.59	1.73	11.32	30	Pass
		2452	9.61	1.79	11.4	30	Pass
	ANT 2	2422	9.74	1.82	11.56	30	Pass
		2437	9.76	1.79	11.55	30	Pass
		2452	9.96	1.82	11.78	30	Pass
	MIMO	2422	12.61	-	14.41	30	Pass
		2437	12.69	-	14.45	30	Pass
		2452	12.8	-	14.60	30	Pass

Note: Total power=Power +Duty factor


Note: MIMO Power=ANT1 Power+ANT2 Power

ANT1:




802.11n(HT20)

2412MHz




802.11n(HT40)


2422MHz




2437MHz




2437MHz




2462MHz



2452MHz




ANT2:




802.11n(HT20)

2412MHz




802.11n(HT40)


2422MHz




2437MHz




2437MHz




2462MHz



2452MHz




MIMO:




802.11n(HT40) ANT 1

2422MHz




802.11n(HT40) ANT 2


2422MHz




2437MHz



2437MHz



2452MHz



2452MHz

