

RF EXPOSURE EVALUATION METHOD**FCC ID: 2AD37JUE301****SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

WIFI

TX 802.11b Mode				
Test Channel	Frequency	Maximum Peak Conducted Output Power (PK)	Maximum Peak Conducted Output Power (AV)	Maximum Peak Conducted Output Power (AV)
	(MHz)	(dBm)	(dBm)	mW
CH01	2412	13.71	9.36	8.630
CH06	2437	13.86	9.54	8.995
CH11	2462	13.08	9.22	8.356
TX 802.11g Mode				
CH01	2412	13.23	9.16	8.241
CH06	2437	13.42	9.22	8.356
CH11	2462	13.36	9.12	8.166
TX 802.11n(20) Mode				
CH01	2412	12.04	8.11	6.471
CH06	2437	12.25	8.43	6.966
CH11	2462	12.46	8.66	7.345
TX 802.11n(40) Mode				
CH03	2422	10.96	7.03	5.047
CH06	2437	10.03	7.22	5.272
CH09	2452	10.25	7.41	5.508

Remark: The best case gain of the antenna is 0.0dBi.

0.0 dBi logarithmic terms convert to numeric result is nearly 1.0

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

WIFI

Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)]	(min. test separation distance, mm)]	[f(GHz)]	Result	Limit
TX 802.11b Mode							
CH01	7.6~9.6	9.6	9.120	5	2.412	2.83	3
CH06	7.6~9.6	9.6	9.120	5	2.437	2.85	3
CH11	7.6~9.6	9.6	9.120	5	2.462	2.86	3
TX 802.11g Mode							
CH01	7.6~9.6	9.6	9.120	5	2.412	2.83	3
CH06	7.6~9.6	9.6	9.120	5	2.437	2.85	3
CH11	7.6~9.6	9.6	9.120	5	2.462	2.86	3
TX 802.11n-HT20 Mode							
CH01	7.0~9.0	9.0	7.943	5	2.412	2.47	3
CH06	7.0~9.0	9.0	7.943	5	2.437	2.48	3
CH11	7.0~9.0	9.0	7.943	5	2.462	2.49	3
TX 802.11n-HT40 Mode							
CH03	6.0~8.0	8.0	6.310	5	2.422	1.96	3
CH06	6.0~8.0	8.0	6.310	5	2.437	1.97	3
CH09	6.0~8.0	8.0	6.310	5	2.452	1.98	3

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: No SAR is required.