



# RF Exposure Evaluation Report

APPLICANT : Noodoe Corp.  
EQUIPMENT : BLE wristband  
BRAND NAME : Noodoe  
MODEL NAME : Noodoe Watch  
FCC ID : 2AD3D-IV2  
STANDARD : 47 CFR Part 2.1093  
**FCC KDB 447498 D01 v05r02**

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Eric Huang / Deputy Manager

Approved by: Jones Tsai / Manager



## SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



## **Table of Contents**

1. Administration Data.....	3
2. General Information.....	3
2.1 Description of Device Under Test (DUT) .....	3
3. Maximum RF output power among production units .....	3
4. RF Exposure Evaluation .....	4

## **Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA510843	Rev. 01	Initial issue of report	Mar. 03, 2015



## 1. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Noodoe Corp.
Address	15F., No.19-13, Sanchong Rd., Nangang Dist., Taipei City 115, Taiwan (R.O.C.)

Manufacturer	
Company Name	FIH Mobile Limited
Address	No.4, Mingsheng St., Tu-Cheng Dist., New Taipei City 23679, Taiwan

## 2. General Information

### 2.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	BLE wristband
Brand Name	Noodoe
Model Name	Noodoe Watch
FCC ID	2AD3D-IV2
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	• Bluetooth v4.0-LE
Antenna Type	MULTILAYER CERAMIC
DUT Stage	Identical Prototype

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 3. Maximum RF output power among production units

Mode / Band	Bluetooth
	BT4.0-LE
	(GFSK)
	2.4GHz Bluetooth
	4.0



#### **4. RF Exposure Evaluation**

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
4	3	5	2.48	0.94

**Note:**

1. Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for}$$

1-g SAR and  $\leq$  7.5 for 10-g extremity SAR

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

**Conclusion:** Per KDB 447498 D01v05r02, when the minimum test separation distance is  $<$  5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.94 which is  $\leq$  7.5, SAR testing is not required.