

RF Exposure Evaluation Declaration

Product Name : PRO SPD/CAD Sensor
Trade Name : LEZYNE
Model No. : PRO SPEED, PRO CADENCE
FCC ID. : 2AD4S-PROSV104

Applicant : Lezyne USA, Incorporated
Address : 645 Tank Farm Road Unit F, San Luis Obispo,
California, 93401, United States

Date of Receipt : Nov. 06, 2019
Date of Declaration : Jan. 13, 2020
Report No. : 19B0085R-RFUSP02V00
Report Version : V1.0



The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of DEKRA Testing and Certification Co., Ltd.

Test Report Certification

Issued Date : Jan. 13, 2020

Report No. : 19B0085R-RFUSP02V00



Product Name : PRO SPD/CAD Sensor
Applicant : Lezyne USA, Incorporated
Address : 645 Tank Farm Road Unit F, San Luis Obispo, California,
93401, United States
Manufacturer : Lezyne USA, Incorporated
Model No. : PRO SPEED, PRO CADENCE
FCC ID. : 2AD4S-PROSV104
EUT Voltage : DC 3V
Testing Voltage : DC 3V (Power by Battery)
Trade Name : LEZYNE
Applicable Standard : FCC 47 CFR Part 2.1091 Radiofrequency radiation
exposure evaluation: mobile devices.
Laboratory Name : Hsin Chu Laboratory
Address : No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township,
Hsinchu County 310, Taiwan, R.O.C.
TEL: +886-3-582-8001 / FAX: +886-3-582-8958
Test Result : Complied

Tested By :



(Scott Chang / Engineer)

Approved By :



(Louis Hsu / Deputy Manager)

Revision History

Report No.	Version	Description	Issued Date
19B0085R-RFUSP02V00	V1.0	Initial issue of report	Jan. 13, 2020

1. General Information

1.1. Test Facility

Ambient conditions in the laboratory:

Items	Test Item	Required	Test Site
Temperature (°C)	Peak Output Power	15 - 35	3
Humidity (%RH)		25 - 75	

Note: Test site information refers to Laboratory Information.

Laboratory Information

USA : FCC Registration Number: **TW3024**

Canada : IC Registration Number: **22397-1 / 22397-2 / 22397-3**

The address and introduction of DEKRA Testing and Certification Co., Ltd. laboratories can be founded in our Web site : <http://www.dekra.com.tw>

If you have any comments, Please don't hesitate to contact us. Our test sites as below:

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
Address	<ol style="list-style-type: none"> 1. No. 75-2, 3rd Lin, WangYe Keng, Yonghxing Tsuen, Qionglin Shiang, Hsinchu County 307, Taiwan, R.O.C. 2. No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. 3. No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C.
Phone number	<ol style="list-style-type: none"> 1. +886-3-592-8858 2. +886-3-582-8001 3. +886-3-582-8001
Fax number	<ol style="list-style-type: none"> 1. +886-3-592-8859 2. +886-3-582-8958 3. +886-3-582-8958
E mail address	info.tw@dekra.com
Website	http://www.dekra.com.tw

1.2. List of Test Equipment

Peak Output Power / SR10-H

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
High Speed Peak Power Meter Dual Input	Anritsu	ML2496A	1602004	2019/12/02	2020/12/01
Pulse Power Sensor	Anritsu	MA2411B	1531043	2019/12/02	2020/12/01
Pulse Power Sensor	Anritsu	MA2411B	1531044	2019/12/02	2020/12/01
Power Meter	Keysight	8990B	MY51000248	2019/05/21	2020/05/20
Power Sensor	Keysight	N1923A	MY57240005	2019/05/21	2020/05/20

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

1.3. Uncertainty

Test item	Uncertainty
Peak Output Power	± 2.26 dB

Note: Determining compliance shall be based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

Note: *f* is frequency in MHz.

RF Field Strength Limits for Controlled Use Devices (Controlled Environment)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-1023	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> 0.5	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> 0.25	0.3444/ <i>f</i> 0.25	44.72/ <i>f</i> 0.5	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> 0.25	0.04138 <i>f</i> 0.25	0.6455 <i>f</i> 0.5	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> 1.2
150000-300000	0.354 <i>f</i> 0.5	9.40 x 10-4 <i>f</i> 0.5	3.33 x 10-4 <i>f</i>	616000/ <i>f</i> 1.2

Note: *f* is frequency in MHz.

*Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

2.3. Test Result of RF Exposure Evaluation

Product	PRO SPD/CAD Sensor
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

Antenna Gain: The maximum antenna gain is -2.4 dBi.

Output Power into Antenna & RF Exposure Evaluation Distance:

Bluetooth Function					
BT 5.0					
Mode	Frequency (MHz)	Conducted Output Power		Power Density at R = 20cm (mW/cm ²)	Limit (mW/cm ²)
		dBm	mW		
GFSK	2402	-1.150	0.767	0.0001	1.000
	2440	-0.860	0.820	0.0001	1.000
	2480	-0.580	0.875	0.0001	1.000

Note:

1. The antenna information is from the customer declaration.
2. The results are evaluated using the maximum power.