

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2058

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2422MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2422.000	96.53	-7.40	89.13	/	/	peak			
2	4844.228	51.12	-0.08	51.04	74.00	-22.96	peak			
3	4844.228	41.05	-0.08	40.97	54.00	-13.03	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2059

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2422MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2422.000	96.78	-7.40	89.38	/	/	peak			
2	4844.162	48.73	-0.08	48.65	74.00	-25.35	peak			
3	4844.162	38.56	-0.08	38.48	54.00	-15.52	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2060

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2437MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2422.000	96.84	-7.40	89.44	/	/	peak			
2	4874.132	48.80	0.09	48.89	74.00	-25.11	peak			
3	4874.132	38.94	0.09	39.03	54.00	-14.97	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2061

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2437MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2437.000	95.83	-7.36	88.47	/	/	peak			
2	4874.213	50.89	0.09	50.98	74.00	-23.02	peak			
3	4874.213	39.87	0.09	39.96	54.00	-14.04	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2062

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2452MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2452.000	94.84	-7.33	87.51	/	/	peak			
2	4904.211	48.53	0.25	48.78	74.00	-25.22	peak			
3	4904.211	37.42	0.25	37.67	54.00	-16.33	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2063

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2452MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2452.000	93.96	-7.33	86.63	/	/	peak			
2	4904.215	49.09	0.25	49.34	74.00	-24.66	peak			
3	4904.215	38.97	0.25	39.22	54.00	-14.78	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2113

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2422MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	24432.700	33.82	16.94	50.76	74.00	-23.24	peak			
2	24432.700	22.57	16.94	39.51	54.00	-14.49	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2114

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2422MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	26022.626	33.23	16.50	49.73	74.00	-24.27	peak			
2	26022.626	21.54	16.50	38.04	54.00	-15.96	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2115

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2437MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25662.803	33.25	16.50	49.75	74.00	-24.25	peak			
2	25662.803	21.35	16.50	37.85	54.00	-16.15	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2116

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2437MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25249.292	33.50	16.50	50.00	74.00	-24.00	peak			
2	25249.292	22.12	16.50	38.62	54.00	-15.38	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2117

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2452MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25220.012	33.66	16.50	50.16	74.00	-23.84	peak			
2	25220.012	22.31	16.50	38.81	54.00	-15.19	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2118

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2452MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	25386.383	32.96	16.50	49.46	74.00	-24.54	peak			
2	25386.383	21.64	16.50	38.14	54.00	-15.86	AVG			

Appendix B.5: Radiated emission in restricted band, 802.11b_1TX**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: LAN2014 #2034
 Standard: FCC (Band Edge)
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 23 C / 48 %
 EUT: Wi-Fi Dongle
 Mode: TX 2412MHz
 Model: TD-2021N-USB
 Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 14/12/31/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	55.71	-7.53	48.18	74.00	-25.82	peak			
2	2390.000	45.13	-7.53	37.60	54.00	-16.40	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2035
Standard: FCC (Band Edge)
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: Wi-Fi Dongle
Mode: TX 2412MHz
Model: TD-2021N-USB
Manufacturer: HUAWEI

Polarization: Horizontal
Power Source: DC 5V
Date: 14/12/31/
Time:
Engineer Signature:
Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	53.00	-7.53	45.47	74.00	-28.53	peak			
2	2390.000	42.62	-7.53	35.09	54.00	-18.91	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2036

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2462MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 14/12/31/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.517	51.00	-7.37	43.63	74.00	-30.37	peak			
2	2483.517	40.54	-7.37	33.17	54.00	-20.83	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2037

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2462MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 14/12/31/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11b



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.615	51.62	-7.37	44.25	74.00	-29.75	peak			
2	2483.615	40.97	-7.37	33.60	54.00	-20.40	AVG			

Appendix B.6: Radiated emission in restricted band, 802.11g_1TX**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

 Job No.: LAN2014 #2044
 Standard: FCC (Band Edge)
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 23 C / 48 %
 EUT: Wi-Fi Dongle
 Mode: TX 2412MHz
 Model: TD-2021N-USB
 Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	61.95	-7.53	54.42	74.00	-19.58	peak			
2	2390.000	51.56	-7.53	44.03	54.00	-9.97	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2045

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2412MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	59.16	-7.53	51.63	74.00	-22.37	peak			
2	2390.000	48.94	-7.53	41.41	54.00	-12.59	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2046

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2462MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.533	59.07	-7.37	51.70	74.00	-22.30	peak			
2	2483.533	48.69	-7.37	41.32	54.00	-12.68	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2047

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2462MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11g



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.517	57.76	-7.37	50.39	74.00	-23.61	peak			
2	2483.517	46.58	-7.37	39.21	54.00	-14.79	AVG			

Appendix B.7: Radiated emission in restricted band, 802.11n HT20_1TX**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2054

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2412MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2389.600	61.41	-7.53	53.88	74.00	-20.12	peak			
2	2389.600	50.08	-7.53	42.55	54.00	-11.45	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2055

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2412MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2389.840	62.72	-7.53	55.19	74.00	-18.81	peak			
2	2389.840	51.94	-7.53	44.41	54.00	-9.59	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2056

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2462MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.565	54.15	-7.37	46.78	74.00	-27.22	peak			
2	2483.565	43.64	-7.37	36.27	54.00	-17.73	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2057

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2462MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n20



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.515	54.49	-7.37	47.12	74.00	-26.88	peak			
2	2483.515	53.81	-7.37	46.44	54.00	-7.56	AVG			

Appendix B.8: Radiated emission in restricted band, 802.11n HT40_1TX**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2064

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2422MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Vertical

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	61.51	-7.53	53.98	74.00	-20.02	peak			
2	2390.000	51.39	-7.53	43.86	54.00	-10.14	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2065

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2422MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2390.000	61.35	-7.53	53.82	74.00	-20.18	peak			
2	2390.000	51.01	-7.53	43.48	54.00	-10.52	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: LAN2014 #2066

Standard: FCC (Band Edge)

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: Wi-Fi Dongle

Mode: TX 2452MHz

Model: TD-2021N-USB

Manufacturer: HUAWEI

Polarization: Horizontal

Power Source: DC 5V


Date: 15/01/04/

Time:

Engineer Signature:

Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.517	54.66	-7.37	47.29	74.00	-26.71	peak			
2	2483.517	43.67	-7.37	36.30	54.00	-17.70	AVG			

**ACCURATE TECHNOLOGY CO., LTD.**
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel: +86-0755-26503290

Fax: +86-0755-26503396

Job No.: LAN2014 #2067
 Standard: FCC (Band Edge)
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 23 C / 48 %
 EUT: Wi-Fi Dongle
 Mode: TX 2452MHz
 Model: TD-2021N-USB
 Manufacturer: HUAWEI

Polarization: Vertical
 Power Source: DC 5V
 Date: 15/01/04/
 Time:
 Engineer Signature:
 Distance: 3m

Note: 802.11n40



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.582	54.61	-7.37	47.24	74.00	-26.76	peak			
2	2483.582	43.52	-7.37	36.15	54.00	-17.85	AVG			

Appendix C

Test Results of Spurious Emissions and Radiated Emissions in restricted band, ANSI C63.10:2013

APPENDIX C.1: SPURIOUS EMISSIONS, 802.11B_1TX	2
APPENDIX C.2: SPURIOUS EMISSIONS, 802.11G_1TX	29
APPENDIX C.3: SPURIOUS EMISSIONS, 802.11N HT20_1TX.....	56
APPENDIX C.4: SPURIOUS EMISSIONS, 802.11N HT40_1TX.....	83
APPENDIX C.5: RADIATED EMISSION IN RESTRICTED BAND, 802.11B_1TX.....	110
APPENDIX C.6: RADIATED EMISSION IN RESTRICTED BAND, 802.11G_1TX	114
APPENDIX C.7: RADIATED EMISSION IN RESTRICTED BAND, 802.11N HT20_1TX	118
APPENDIX C.8: RADIATED EMISSION IN RESTRICTED BAND, 802.11N HT40_1TX	122

Appendix C.1: Spurious Emissions, 802.11b_1TX

ACCURATE TECHNOLOGY CO., LTD

FCC Class B 3m Radiated

EUT: Wi-Fi Dongle M/N:TD-2021N-USB
 Manufacturer: HUAWEI
 Operating Condition: TX 2412MHz
 Test Site: 1#Shielding Room
 Operator: LAN
 Test Specification: DC 5V
 Comment: X
 Start of Test: 2015-1-6 /

SCAN TABLE: "LFRE Fin"

Short Description:			_SUB_STD_VTERM2 1.70			
Start	Stop	Step	Detector	Meas. Time	IF Bandw.	Transducer
9.0 kHz	150.0 kHz	100.0 Hz	QuasiPeak	1.0 s	200 Hz	1516M
150.0 kHz	30.0 MHz	5.0 kHz	QuasiPeak	1.0 s	9 kHz	1516M

