

实际长178MM，高114MM，圆角5。

e.TEK® USB 2.0 WIRELESS 802.11N

IEEE
802.11b/g/n

2.4
GHz

USB2.0
Hi-Speed

Windows 7
Support

Windows 8
Support

CE0197

INTERNET

Wireless Router

Computer

Specifications 产品规格书

Model : TD-2021N-USB

Wireless Standards 无线标准	IEEE 802.11n IEEE 802.11g IEEE 802.11b
Host Interface 主机接口	High speed USB2.0 interface 高速率 USB2.0 接口
Data Rate 数据速率	802.11n: up to 150Mbps 802.11n: 最高可达 150Mbps 802.11g: up to 54 Mbps 802.11g: 最高可达 54Mbps 802.11b: up to 11 Mbps 802.11b: 最高可达 11Mbps
Frequency Band 频宽	2.4G~2.4835 GHz
Radio Channel 无线信道	1~13 channels 1~13 信道
Antenna type 天线类型	Integrated Antenna 集成天线
RF Output Power 射频输出功率	13~17 dBm
Data Security 数据安全	64/128-bit WEP; WPA-PSK, WPA2-PSK, TKIP/AES 64/128位 WEP加密; 支持WPA-PSK, WPA2-PSK, TKIP/AES安全机制
Media Access Control 介质访问控制	CSMA/CA with ACK 载波侦听多点接入/冲突检测确认
Operating System 操作系统	Windows 2000, XP, Vista, WIN7, WIN8, Linux and MAC OS X

All brand names and trademarks are the properties of their respective holders.

所有品牌和商标是他们的各自持有属性。

Specifications are subject to change without any prior notice.

规格如有变更,恕不另行通知。

伊泰克科技(深圳)有限公司
ETEK TECHNOLOGY (SHENZHEN) CO., LTD.

www.etek-td.com

MADE IN CHINA

公司: 深圳市高新技术产业园科苑南路
天利科技园A区五楼
ADD: 5/F, Section A, Academy of Aerospace T-
echnology, Keji Nan 10th Road, Hi-Tech
Industrial Park, Shenzhen, P.R.C.
Tel : 0755-26718988 Fax: 0755-26727886

FCC:

(a) This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) This device must accept any interference received, including interference that may cause undesired operation.
(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
—Reorient or relocate the receiving antenna.
—Increase the separation between the equipment and receiver.

—Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
—Consult the dealer or an experienced radio/TV technician for help.

(c) Changes or modifications not expressly approved by the part responsible for compliance could void the user's authority to operate the equipment.

(d) The device has been evaluated to meet general RF exposure requirement. To comply with RF exposure compliance requirements, a separation distance of at least 20 cm must be maintained between the antenna of this device and all persons.

IC:

(a) This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions:

(a) Le présent appareil est conforme aux CNR d' Industrie Canada applicables aux appareils radio exempts de licence. L' exploitation est autorisée aux deux conditions suivantes :

(1) this device may not cause interference, and
(1) l' appareil ne doit pas produire de brouillage;

(2) this device must accept any interference, including interference that may cause undesired operation of the device.

(2) l' utilisateur de l' appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d' en compromettre le fonctionnement.

(b) The device has been evaluated to meet general RF exposure requirement. To comply with RF exposure compliance requirements, a separation distance of at least 20 cm must be maintained between the antenna of this device and all persons.

(b) Le dispositif a été évalué pour satisfaire la demande générale RF exposé. Avec exposition RF, à une distance d'au moins 20 cm doit être entre l' antenne de l' appareil de retenue et de toutes les personnes.