



# **FCC TESTREPORT**

Report No: STS1502037

Issued for

VIDAR INTERNATIONAL CO., LTD.

10F, Shuihetian Industrial Park, Tianfu Road, Qiaotou Block, Fuyong Street, Bao'an District, Shenzhen City, Guangdong Province, P.R. China

Product Name:	Bluetooth stereo headset
Brand Name:	VIDAR
Model No.:	See page 7
FCC ID:	2AD5HBH02
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may permission from STS, All Test Data Presented in this report is only applicable to presented Te

Shenzhen STS Test Services Co., Ltd.

1/F, Building B, Zhuoke Science Park, Chongging Road, Fuyong,



# **TEST RESULT CERTIFICATION**

Applicant's name.......... VIDAR INTERNATIONAL CO., LTD.

10F,ShuihetianIndustrial Park,Tianfu Road, Qiaotou Block, Fuyong Street,

Bao'an District, Shenzhen City, Guangdong Province, P.R. China

Manufacture's Name...... VIDAR INTERNATIONAL CO.,LTD.

Bao'an District, Shenzhen City, Guangdong Province, P.R. China

**Product description** 

Product name ...... Bluetooth stereo headset

Band name......VIDAR

Model and/or type

BH02

reference .....

DI 102

Ratings...... DC 3.7V by Battery

Standards..... FCC Part15.247

Test procedure...... ANSI C63.4-2009

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.. Jan.23.2015 &Jan.26,2015

Date of Issue...... Jan.27,2015

Test Result ...... Pass

Testing Engineer

(Tony Liu

Technical Manager

Authorized Signatory:

(Vita Li

Hound long

(Bovey Yang)



Table of Contents	Page
1. SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.1 DESCRIPTION OF TEST MODES	9
2.2 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.3BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS	11
2.5EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3.EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 TEST SETUP	14
3.1.4EUT OPERATING CONDITIONS 3.1.5TEST RESULTS	14 15
3.2RADIATED EMISSION LIMITS	17
3.3 TEST PROCEDURE	18
3.4 DEVIATION FROM TEST STANDARD	18
3.5 TESTSETUP 3.6EUT OPERATING CONDITIONS	19 20
3.7 TEST RESULTS(WORST CASE:GFSK)	21
BAND EDGE TEST (WORST CASE:GFSK)	34
4. CONDUCTED SPURIOUS EMISSIONS	38
4.1 REQUIREMENT	38
4.2TEST PROCEDURE	38
4.3 TEST SETUP	38
4.4 EUT OPERATION CONDITIONS	38
4.5 TEST RESULTS	39
5. NUMBER OF HOPPING CHANNEL	45
5.1APPLIED PROCEDURES / LIMIT	45
5.2 TEST PROCEDURE	45
5.3 TEST SETUP	45
5.4 EUT OPERATION CONDITIONS	45



Table of Contents	Page
5.5TEST RESULTS	46
6. AVERAGE TIME OF OCCUPANCY	47
6.1 APPLIED PROCEDURES / LIMIT	47
6.2 TEST PROCEDURE	47
6.3 TEST SETUP	47
6.4 EUT OPERATION CONDITIONS	47
6.5TEST RESULTS	48
7. HOPPING CHANNEL SEPARATION MEASUREMENT	50
7.1 APPLIED PROCEDURES / LIMIT	50
7.2 TEST PROCEDURE	50
7.3 TEST SETUP	50
7.4 EUT OPERATION CONDITIONS	50
7.5TEST RESULTS	51
8. BANDWIDTH TEST	52
8.1APPLIED PROCEDURES / LIMIT	52
8.2 TEST PROCEDURE	52
8.3 TEST SETUP	52
8.4 EUT OPERATION CONDITIONS	52
8.5TEST RESULTS	53
9. OUTPUT POWER TEST	56
9.1 APPLIED PROCEDURES / LIMIT	56
9.2 TEST PROCEDURE	56
9.3 TEST SETUP	56
9.4 EUT OPERATION CONDITIONS	56
9.5TEST RESULTS	57
10. ANTENNA REQUIREMENT	61
10.1 STANDARD REQUIREMENT	61
10.2 EUT ANTENNA	61
APPENDIX-PHOTOS OF TEST SETUP	62



# 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

st procedures according to the technical standards.					
	FCC Part15 (15.247) , Subpart C				
Standard Section	I AST ITAM				
15.207	Conducted Emission	PASS			
15.247(a)(1)	Hopping Channel Separation	PASS			
15.247(b)(1)	Peak Output Power	PASS			
15.247(c)	Radiated Spurious Emission				
15.247(d)	15.247(d) Conducted Spurious Emission				
15.247(a)(iii)	15.247(a)(iii) Number of Hopping Frequency				
15.247(a)(iii)	15.247(a)(iii) Dwell Time				
15.247(a)(1)	15.247(a)(1) Bandwidth				
15.205	15.205 Band Edge Emission				
15.203	15.203 Antenna Requirement				

Note:N/A means not applicable



#### 1.1 TEST FACILITY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F, Building 2, Zhuoke Science Park, Chongqing Road, Fuyong, Baoan District,

Shenzhen, China.

FCC Registration No.: 842334; IC Registration No.: 12108A-1

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $\mathbf{y} \pm \mathbf{U}$ , where expended uncertainty  $\mathbf{U}$  is based on a standard uncertainty multiplied by a coverage factor of  $\mathbf{k=2}$ , providing a level of confidence of approximately 95 %  $^{\circ}$ 

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.71dB
6	Temperature	±0.5°C
7	Humidity	±2%



# 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth stereo headset		
Trade Name	VIDAR		
Test Model	BH02		
Series Model	BS61, BS51, BS62, BS55, BS56, BS50, BS52, BS53, BS23, BS33, BS38, BS60, BS06, BS31, BS29, BS03, BS18, BS18S, BS16, BH02, BH03, BH08, BH05, BH06, BH09, BH10, BH11, BH12, BH13, BH15, BS66		
Difference	All the same except for the model name.		
description	All the same except for the model hame.		
Channel List	nnel List Please refer to the Note 2.		
Bluetooth Frequency:2402 – 2480 MHz Modulation: GFSK, π /4-DQPSK, 8DPSK			
Potton	Rated Voltage: 3.7V		
Battery	Charge Limit: 4.2V		
Hardware version	V1.0		
number			
Software StereoHeadset1510G_prelabel005_20141103_Patch228446421			
versioningnumber			
Connecting I/O	Diagon refer to the Hearle Manual		
Please refer to the User's Manual			

### Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

# 3. Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	NA	2.3	BT Antenna

The EUT antenna is PCB Antenna. no antenna other than that furnished by the responsible party shall be used with the device.



#### 2.1 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	Low channel TX
Mode 2	Middle channel TX
Mode 3	High channel TX
Mode 4	Hopping on

For Conducted Emission		
Final Test Mode Description		
Mode1	Keeping TX	

For Radiated Emission				
Final Test Mode	Description			
Mode 1	Low channel TX			
Mode 2	Middle channel TX			
Mode 3	High channel TX			
Mode 4	Hopping on			

#### Note:

(1)The measurements are performed at the highest, middle, lowest available channels.

#### 2.2 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: N/A		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1Mbps)	DEF	DEF	DEF
Parameters(2Mbps)	DEF	DEF	DEF
Parameters(3Mbps)	DEF	DEF	DEF




### 2.3BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED


During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Radiated Spurious EmissionTest


Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



Conducted Emission Test





#### 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Bluetooth stereo headset	VIDAR	BH02	N/A	EUT
2	Battery	Battery N/A N/A			
3	PC	N/A	A1465	N/A	FCC DOC
4	Control box	N/A	N/A	N/A	A.E

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	80	USB Cable
		11		

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length\_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".
- (4) N/A means not applicable.



### 2.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2014.10.25	2015.10.24
Test Receiver	R&S	ESCI	101427	2014.10.25	2015.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2014.10.27	2015.10.26
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.06	2015.06.06
Horn Antenna	R&S	9120D	152265	2014.10.27	2015.10.26
Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05
Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21
Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07
Power Meter	Anritsu	ML2495A	1204003	2014.10.25	2015.10.24
Power Sensor	Anritsu	MA2411B	100309	2014.10.25	2015.10.24

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Test Receiver	R&S	102086	102086	2014.10.25	2015.10.24
LISN	R&S	ENV216	101242	2014.10.25	2015.10.24
LISN	EMCO	3810/2NM	000-23625	2014.10.25	2015.10.24
50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.06	2015.06.06
Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.06	2015.06.06
Absorbing clamp	R&S	MDS-21	100668	2014.10.27	2015.10.26



#### 3.EMC EMISSION TEST

### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

Operating frequency band. In case the emission fall within the restricted band specified on Part 15.247&207(a) limit in the table below has to be followed.

	Class B	Class B (dBuV)				
FREQUENCY (MHz)	Quasi-peak	Standard				
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR			
0.50 -5.0	56.00	46.00	CISPR			
5.0 -30.0	60.00	50.00	CISPR			

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

#### Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

### The following table is the setting of the receiver


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz



#### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

### 3.1.4EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

Humidity: 60 %



### 3.1.5TEST RESULTS

EUT:	Bluetooth Speaker	Model Name. :	
Temperature:	<b>23</b> ℃	Relative Humidity:	50%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC3.7V	Test Mode:	keeping TX



Site: Conduction

Limit: FCC Class B Conduction(QP)

EUT:Bluetooth Stereo headset

M/N:BH02

Mode: Keeping TX

Note:


No.	Freq.	Rea	ding_L (dBuV)		Correct Factor	Measurement (dBuV)		Limit Margin (dBuV) (dB)		P/F	Comment			
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1980	43.34		26.75	10.21	53.55		36.96	63.69	53.69	-10.14	-16.73	Р	
2	0.5060	28.72		19.20	10.39	39.11		29.59	56.00	46.00	-16.89	-16.41	Р	
3	1.0580	25.21		15.58	10.37	35.58		25.95	56.00	46.00	-20.42	-20.05	Р	
4	2.7460	27.98		15.57	10.49	38.47		26.06	56.00	46.00	-17.53	-19.94	Р	
5	4.1020	26.84		12.96	10.38	37.22		23.34	56.00	46.00	-18.78	-22.66	Р	
6	16.6020	24.14		11.54	10.12	34.26		21.66	60.00	50.00	-25.74	-28.34	Р	

Power:

Humidity: 60 %



EUT:	Bluetooth Speaker	Model Name. :	
Temperature :	<b>23</b> ℃	Relative Humidity:	50%
Pressure:	1010hPa	Phase :	N
Test Voltage:	DC3.7V	Test Mode:	keeping TX



Limit: FCC Class B Conduction(QP)

EUT:Bluetooth Stereo headset

M/N:BH02

Mode: Keeping TX

Note:

No.	Freq.	Reading_Level Correct (dBuV) Factor			asuren (dBuV)	ırement Limit uV) (dBuV)			Mai (d	rgin IB)	P/F	Comment		
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1620	41.47		26.53	10.17	51.64		36.70	65.36	55.36	-13.72	-18.66	Р	
2	0.5020	30.14		21.73	10.40	40.54		32.13	56.00	46.00	-15.46	-13.87	Р	
3	1.8180	31.25		21.38	10.28	41.53		31.66	56.00	46.00	-14.47	-14.34	Р	
4	3.3060	31.62		18.95	10.53	42.15		29.48	56.00	46.00	-13.85	-16.52	Р	
5	4.0939	30.67		15.11	10.39	41.06		25.50	56.00	46.00	-14.94	-20.50	Р	
6	16.6340	22.70		10.76	10.12	32.82		20.88	60.00	50.00	-27.18	-29.12	Р	

Power:



#### 3.2RADIATED EMISSION LIMITS

#### 3.2.1Radiated Emission Limits

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15247&205(a), then the Part 15 247&209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (30MHz - 1000MHz)

		,
Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

# LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

	Class B (dB	uV/m) (at 3M)		
FREQUENCY (MHz)	PEAK	AVERAGE		
Above 1000	74	54		

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting				
Attenuation	Auto				
Detector	Peak				
Start Frequency	1000 MHz(Peak/AV)				
Stop Frequency	10th carrier harmonic(Peak/AV)				
RB / VB (emission in restricted	RBW 1MHz / VBW 1MHz Peak detector for Pk value				
band)	RBW 1MHz / VBW 10Hz Peak detector for AV value				

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 3.3 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then QuasiPeak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.4 DEVIATION FROM TEST STANDARD No deviation




### 3.5 TESTSETUP

# (A) Radiated Emission Test-Up Frequency Below 30MHz




# (B) Radiated Emission Test-Up Frequency 30MHz~1GHz





# (C) Radiated Emission Test-Up Frequency Above 1GHz



#### 3.6EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**REMARK**: GFSK(1Mbps),  $\pi/4$ -DQPSK(2Mbps),8-DPSK(3Mbps) all have been tested ,GFSK(1Mbps) is found as worst case and only reported



# 3.7 TEST RESULTS(WORST CASE:GFSK)

Below 30 MHz

EUT:	Bluetooth stereo headset	Model Name. :	BH02
Temperature:	23 ℃	Relative Humidity:	50%
Pressure:	1010hPa	Polarization :	
Test Voltage:	DC 3.7V		
Test Mode :	TX Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



### Between 30MHz - 1000 MHz

# RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo headset

M/N: BH02

Mode: Low Channel TX

Note:


Polarization: Horizontal Temperature: 26
Power: Humidity: 60 %

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	m dB	cm	degree		
1		80.1167	4.62	9.80	14.42	40.00	-25.58	peak			
2		114.0667	13.37	11.45	24.82	43.50	-18.68	peak			
3		128.6167	12.51	13.30	25.81	43.50	-17.69	peak			
4		225.6167	17.52	12.97	30.49	46.00	-15.51	peak			
5	*	257.9500	26.08	14.14	40.22	46.00	-5.78	peak			
6		353.3333	6.81	18.76	25.57	46.00	-20.43	peak			



### RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo headset

M/N: BH02

Mode: Low Channel TX

Note:

Polarization: Vertical

Power:

Distance: 3m

Temperature: 26

Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	38.0833	19.80	6.39	26.19	40.00	-13.81	peak			
2		131.8500	10.72	11.80	22.52	43.50	-20.98	peak			
3		190.0500	13.10	11.52	24.62	43.50	-18.88	peak			
4		251.4833	17.39	13.94	31.33	46.00	-14.67	peak			
5		358.1833	4.06	18.79	22.85	46.00	-23.15	peak			
6		799.5333	1.64	27.31	28.95	46.00	-17.05	peak			


#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor+ Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



### RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo headset

M/N: BH02

Mode: Middle Channel TX

Note:

Polarization: Horizontal

forizontal Temperature: 26 Humidity: 60 %


Distance: 3m

Power:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		38.0833	7.14	9.43	16.57	40.00	-23.43	peak			
2		128.6167	12.75	13.30	26.05	43.50	-17.45	peak			
3		251.4833	25.43	13.94	39.37	46.00	-6.63	peak			
4	*	264.4166	25.14	14.34	39.48	46.00	-6.52	peak			
5		408.3000	3.16	19.32	22.48	46.00	-23.52	peak			
6		713.8500	0.73	25.59	26.32	46.00	-19.68	peak			



### RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo headset M/N: BH02

Mode: Middle Channel TX

Note:

Polarization: Vertical

Temperature: 26 Power: Humidity: 60 %

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	38.0833	20.84	6.39	27.23	40.00	-12.77	peak			
2		131.8500	10.54	11.80	22.34	43.50	-21.16	peak			
3		190.0500	13.67	11.52	25.19	43.50	-18.31	peak			
4		251.4833	16.67	13.94	30.61	46.00	-15.39	peak			
5		346.8667	5.75	18.53	24.28	46.00	-21.72	peak			
6		799.5333	3.76	27.31	31.07	46.00	-14.93	peak			


### **RESULT: PASS**

Note: 1. Factor=Antenna Factor+ Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



### RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1

Limit: FCC Class B 3M Radiation

EUT: Bluetooth Stereo headset

M/N: BH02

Mode: High Channel TX

Note:

Polarizat	tion: <i>Horizontal</i>	Temperature: :	26
_			


Power: Humidity: 60 %

Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		78.5000	15.90	2.17	18.07	40.00	-21.93	peak			
2		131.8500	14.27	11.80	26.07	43.50	-17.43	peak			
3		215.9167	20.90	10.56	31.46	43.50	-12.04	peak			
4	*	264.4166	26.19	14.34	40.53	46.00	-5.47	peak			
5		346.8667	8.50	18.53	27.03	46.00	-18.97	peak			
6		401.8333	6.97	19.13	26.10	46.00	-19.90	peak			



### RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1

Limit: FCC Class B 3M Radiation EUT: Bluetooth Stereo headset

M/N: BH02

Mode: High Channel TX

Note:

Polarization:	Vertical	Temperature:	26
_			

Power: Humidity: 60 % Distance: 3m

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1	*	38.0833	22.22	6.39	28.61	40.00	-11.39	peak			
2		130.2332	16.63	11.13	27.76	43.50	-15.74	peak			
3		199.7500	19.59	9.06	28.65	43.50	-14.85	peak			
4		251.4833	18.01	13.94	31.95	46.00	-14.05	peak			
5		345.2500	6.93	18.42	25.35	46.00	-20.65	peak			
6		406.6833	7.21	19.27	26.48	46.00	-19.52	peak			


#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor+ Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



# RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics)-LOW CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2402.000	90.57	10.32	100.89	74.00	26.89	peak			
2		3391.667	25.58	12.01	37.59	74.00	-36.41	peak			
3		4808.333	30.36	7.70	38.06	74.00	-35.94	peak			-



# RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics)-LOW CHANNEL -VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02


Mode: Low Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2402.000	90.70	10.32	101.02	74.00	27.02	peak			
2		3425.000	24.71	12.04	36.75	74.00	-37.25	peak			
3		4341.667	28.00	9.52	37.52	74.00	-36.48	peak			



# RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2441.000	91.11	10.36	101.47	74.00	27.47	peak			
2		3958.333	22.32	14.93	37.25	74.00	-36.75	peak			
3		4583.333	29.18	7.11	36.29	74.00	-37.71	peak			



# RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics)- MIDDLE CHANNEL -VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02


Mode: Middle Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1	*	2441.000	91.41	10.36	101.77	74.00	27.77	peak			
2		3575.000	25.02	12.57	37.59	74.00	-36.41	peak			
3		4891.667	29.75	7.92	37.67	74.00	-36.33	peak			



# RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics)-HIGH CHANNEL-HORIZONTAL



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02


Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	91.39	10.41	101.80	74.00	27.80	peak			
2		4208.333	23.47	11.73	35.20	74.00	-38.80	peak			
3		5725.000	38.12	-1.71	36.41	74.00	-37.59	peak			



# RADIATED EMISSION ABOVE 1GHZ (1-10<sup>th</sup> Harmonics)-HIGH CHANNEL -VERTICAL



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	91.26	10.41	101.67	74.00	27.67	peak			
2		3808.333	24.48	14.01	38.49	74.00	-35.51	peak			
3		4391.667	28.02	8.69	36.71	74.00	-37.29	peak			

### **RESULT: PASS**


Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor+ Cable loss-Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



# TEST PLOT OF BAND EDGE FOR LOW CHANNEL (1Mbps)-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:


M/N: BH02

Mode: Low Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2238.950	36.20	10.14	46.34	74.00	-27.66	peak			
2		2390.000	32.50	10.31	42.81	74.00	-31.19	peak			
3	*	2402.000	90.72	10.32	101.04	74.00	27.04	peak			



# TEST PLOT OF BAND EDGE FOR LOW CHANNEL (1Mbps)-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:


M/N: BH02

Mode: Low Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		2305.917	35.68	10.22	45.90	74.00	-28.10	peak			
2		2390.000	34.71	10.31	45.02	74.00	-28.98	peak			
3	*	2402.000	90.59	10.32	100.91	74.00	26.91	peak			



### TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (1Mbps)-Horizontal



Site: site #1 Polarization: Horizontal Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:


M/N: BH02

Mode: High Channel TX

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1	*	2480.000	91.55	10.41	101.96	74.00	27.96	peak			
2		2483.500	33.69	10.41	44.10	74.00	-29.90	peak			
3		2488.193	34.48	10.42	44.90	74.00	-29.10	peak			



## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL (1Mbps)-Vertical



Site: site #1 Polarization: Vertical Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %

EUT: Bluetooth stereo headset Distance:

M/N: BH02

Mode: High Channel TX

Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1	*	2480.000	91.32	10.41	101.73	74.00	27.73	peak			
2		2483.500	35.26	10.41	45.67	74.00	-28.33	peak			
3		2492.667	34.77	10.42	45.19	74.00	-28.81	peak			

## **RESULT: PASS**

Note: 1. Factor=Antenna Factor+ Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



#### 4. CONDUCTED SPURIOUS EMISSIONS

#### 4.1 REQUIREMENT


According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### 4 2TEST PROCEDURE

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/100 KHz
Trace-Mode:	Max hold

## 4.3 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 500hm; the path loss as the factor is calibrated to correct the reading. Make the measurement with the spectrum analyzer's resolution bandwidth(RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.


## 4.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**REMARK:** GFSK(1Mbps),  $\pi/4$ -DQPSK(2Mbps),8-DPSK(3Mbps) all have been tested  $\sigma$  GFSK(1Mbps) is found as worst case and only reported




EUT:	Bluetooth stereo headset	Model Name :	BH02
Temperature :	<b>25</b> ℃	Relative Humidity:	50%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	Low Channel(GFSK)	_	









EUT:	Bluetooth stereo headset	Model Name :	BH02
Temperature:	<b>25</b> ℃	Relative Humidity:	50%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	Middle(GFSK)		








EUT:	Bluetooth stereo headset	Model Name :	BH02
Temperature :	25℃	Relative Humidity:	50%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	High(GFSK)		








## CONDUCTED TEST RESULT FOR BANDEDGE

Mode	Channel	Carrier Frequency [MHz]	Frequenc y Hopping
GFSK	LCH	2402	Off
GFSK	LON	2402	On
GFSK	HCH	2480	Off
GFSK	псп	2400	On
π/4DQPSK	LCH	2402	Off
π/4DQPSK	HCH	2480	Off
8DPSK	LCH	2402	Off
8DPSK	HCH	2480	Off
















## 5. NUMBER OF HOPPING CHANNEL

## 5.1APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C							
Section	Test Item	Limit	FrequencyRange (MHz)	Result			
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS			

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating FrequencyRange
RB	100KHz
VB	300KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

## 5.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100K, VBW=300K, Sweep time = Auto.

## 5.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER


## 5.4 EUT OPERATION CONDITIONS



EUT:	Bluetooth stereo headset	Model Name :	BH02
Temperature:	25℃	Relative Humidity:	60%
Pressure:	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode		

Number of Hopping Channel	79
---------------------------	----

## **Hopping channel**



Note:All modes(3 modulation) have been tested, the test result was pass



## 6. AVERAGE TIME OF OCCUPANCY

#### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C							
Section Test Item Limit FrequencyRange (MHz)							
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS			

#### 6.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to e. zero span
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum 1600/79/6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- j. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds.
- k. DH1 Packet permit maximum 1600 / 79 /2 = 10.12 hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds.

## 6.3 TEST SETUP


EUT	SPECTRUM
	ANALYZER

## **6.4 EUT OPERATION CONDITIONS**




EUT:	Bluetooth Speaker	Model Name :	ES-56556BT
Temperature:	<b>25</b> ℃	Relative Humidity:	50%
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	8DPSK(3Mbps)DH5 (Worst c	ase)	

Data Packet	Frequen cy	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2402 MHz	2.899	0.31	0.4
DH5	2441 MHz	2.899	0.31	0.4
DH5	2480 MHz	2.899	0.31	0.4











## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

## 7.1 APPLIED PROCEDURES / LIMIT


Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 7.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- b. The resolution bandwidth of 30 kHz and the video bandwidth of 30 kHz were utilised for 20 dB bandwidth measurement.
- c. The resolution bandwidth of 30 kHz and the video bandwidth of 30 kHz were utilised for channel separation measurement.

## 7.3 TEST SETUP



## 7.4 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.



Mode	Channel.	Carrier Frequency Separation [MHz]	Verdict
8DPSK	Нор	1.115	PASS

Note:All modes were tested, only the worst case record in the report.

## **Test Graph**





## 8. BANDWIDTH TEST

## 8.1APPLIED PROCEDURES / LIMIT

## FCC Part15 (15.247) , Subpart C

Section	Test Item	Limit	FrequencyRange (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time Auto	

## 8.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW= 30KHz, VBW ≥ RBW, Sweep time = Auto.

## 8.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

## 8.4 EUT OPERATION CONDITIONS




Mode	Channel.	20dBBW [MHz]	99%BW [MHz]	Verdict
GFSK	LCH	0.947	0.866	PASS
GFSK	MCH	0.938	0.858	PASS
GFSK	HCH	0.933	0.873	PASS
π/4DQPSK	LCH	1.237	1.179	PASS
π/4DQPSK	MCH	1.320	1.194	PASS
π/4DQPSK	HCH	1.226	1.177	PASS
8DPSK	LCH	1.262	1.180	PASS
8DPSK	MCH	1.346	1.201	PASS
8DPSK	HCH	1.265	1.196	PASS


**Test Graph** 













## 9. OUTPUT POWER TEST

## 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	FrequencyRange (MHz)	Result
	Peak	1 W or 0.125W		
15.247 (b)(i)	Output Power	Or if channel separation > 2/3 bandwidthprovidedthesystem soperatewith an output power no greater than125 mW(20.96dBm)	2400-2483.5	PASS

## 9.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting :GFSK(1Mbps):RBW= 1.5MHz, VBW= 1.5MHz, Sweep time = Auto.
- c. Spectrum Setting :π/4-DQPSK(2Mbps):RBW= 1.5MHz, VBW= 1.5MHz, Sweep time = Auto.
- d. Spectrum Setting :8-DPSK(3Mbps):RBW= 1.5MHz, VBW= 1.5MHz, Sweep time = Auto.

#### 9.3 TEST SETUP

EUT	SPECTRUM
	ANALYZER

## 9.4 EUT OPERATION CONDITIONS



# PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION

Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	3.35	21	Pass
2.441	4.11	21	Pass
2.480	4.27	21	Pass


## PEAK OUTPUT POWER MEASUREMENT RESULT FOR $\, {\rm II} \,$ /4-DQPSK MODULATION

Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	2.2	21	Pass
2.441	2.68	21	Pass
2.480	2.53	21	Pass


## PEAK OUTPUT POWER MEASUREMENT RESULT FOR 8-DPSK MODULATION

Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	2.43	21	Pass
2.441	2.98	21	Pass
2.480	2.84	21	Pass
















## 10. ANTENNA REQUIREMENT

## 10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## 10.2 EUT ANTENNA

The EUT antenna is PCB Antenna. It comply with the standard requirement.






## **APPENDIX-PHOTOS OF TEST SETUP**

## **Radiated Measurement Photos**







**Conduction Measurement Photos** 

