



TEST REPORT

APPLICANT : NiceRF Wireless Technology Co., Ltd.

PRODUCT NAME : LoRa Wireless Module

MODEL NAME : Lora1262-915

BRAND NAME : N/A

FCC ID : 2AD66-1262

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2019-09-19

TEST DATE : 2019-10-10 to 2019-10-21

ISSUE DATE : 2019-10-25

Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1. Technical Information	4
1.1. Applicant and Manufacturer Information	4
1.2. Equipment Under Test (EUT) Description	4
1.3. The Channel Number and Frequency	5
1.4. Test Standards and Results	6
1.5. Environmental Conditions	7
2. 47 CFR Part 15C Requirements	8
2.1. Antenna Requirement	8
2.2. Duty Cycle Of Test Signal	9
2.3. Maximum Peak Conducted Output Power	10
2.4. Maximum Average Conducted Output Power	13
2.5. 6 dB Bandwidth	14
2.6. Conducted Spurious Emissions and Band Edge	17
2.7. Power Spectral Density (PSD)	21
2.8. Conducted Emission	24
2.9. Radiated Emission	30
Annex A Test Uncertainty	40
Annex B Testing Laboratory Information	41



Change History		
Version	Date	Reason for change
1.0	2019-10-25	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	NiceRF Wireless Technology Co., Ltd.
Applicant Address:	309-314, 3/F, Bldg A, Hongdu business building, Zone 43, Baoan Dist, Shenzhen, China
Manufacturer:	NiceRF Wireless Technology Co., Ltd.
Manufacturer Address:	309-314, 3/F, Bldg A, Hongdu business building, Zone 43, Baoan Dist, Shenzhen, China

1.2. Equipment Under Test (EUT) Description

Product Name:	LoRa Wireless Module
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	v1.0
Software Version:	v1.0
Equipment Type:	LoRa™
Modulation Type:	GFSK
Data Transfer Rate:	0.018-62.5kbps
Bandwidth:	500kHz
Operating Frequency Range:	902.8MHz – 927.3MHz
Antenna Type:	ANT1: Wire Antenna; ANT2: Loop Antenna
Antenna Gain:	ANT1: 2.0dBi; ANT2: 2.0dBi

Note 1: The EUT supports two kinds of antenna, Loop Antenna and Wire Antenna. All radiation test items for both of the two antennas were tested separately and recorded in this report.

Note 2: We use the dedicated software to control the EUT continuous transmission.

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3. The Channel Number and Frequency

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	902.8	12	911.6	24	921.2
2	903.6	13	912.4	25	922.0
3	904.4	14	913.2	26	922.8
4	905.2	15	914.0	27	923.6
5	906.0	16	914.8	28	924.4
6	906.8	17	915.6	29	925.2
7	907.6	18	916.4	30	926.0
8	908.4	19	917.2	31	926.8
9	909.2	20	918.0	32	927.3
10	910.0	21	918.8		
11	910.8	23	919.6		

Note: The lowest channel 1, middle channel 16 and highest channel 32 were selected for test in the report.



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle Of Test Signal	Oct 21, 2019	Zhou Chuang	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Oct 21, 2019	Zhou Chuang	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Oct 21, 2019	Zhou Chuang	PASS	No deviation
5	15.247(a)	Bandwidth	Oct 21, 2019	Zhou Chuang	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Oct 21, 2019	Zhou Chuang	PASS	No deviation
7	15.247(e)	Power spectral density (PSD)	Oct 21, 2019	Zhou Chuang	PASS	No deviation
8	15.207	Conducted Emission	Oct 10, 2019	Lin Jiayong	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Oct 10, 2019	Peng Xuewei	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB558074 D01 v05r02.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The Ref offset 2.0dB means the cable loss is 2.0dB.

Note 3: Additions to, deviation, or exclusions from the method should be judged in the "method



"determination" column of add, deviate or exclude from the specific method should be explained in the "Remark" of the above table.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Power Level Setting	4
Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2.47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle Of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

2.2.3. Test Result

Test Mode	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
GFSK	96.88	0.14

2.3. Maximum Peak Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3. Test Procedure

The measured output power was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for Peak Output Power test on the spectrum analyzer:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 1MHz
- c) Set VBW to 3MHz
- d) Set span to 3MHz
- e) Sweep time = auto couple
- f) Detector = peak
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use peak marker function to determine the peak amplitude level

2.3.4. Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	902.8	8.81	0.008	30	1	PASS
16	914.8	8.52	0.007			PASS
32	927.3	8.19	0.007			PASS

B. Test Plots:



(Channel 1, 902.8MHz)



(Channel 16, 914.8MHz)



(Channel 32, 927.3MHz)

2.4. Maximum Average Conducted Output Power


2.4.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

2.4.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.4.3. Test Procedure

KDB 558074 Section 8.3.2 was used in order to prove compliance.

2.4.4. Test Result

Channel	Frequency (MHz)	Average Power				Limit		Verdict			
		Measured dBm	Duty Factor	Duty factor Calculated							
				dBm	W						
1	902.8	8.50	0.14	8.64	0.007	30	1	PASS			
16	914.8	8.12		8.26	0.007			PASS			
32	927.3	7.59		7.73	0.006			PASS			


2.5.6 dB Bandwidth

2.5.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100 kHz
- c) Set VBW to 300 kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW \geq 3 \times RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be \geq 6 dB.

2.5.4. Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the module.

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	902.8	0.641	\geq 500	PASS
16	914.8	0.641	\geq 500	PASS
32	927.3	0.641	\geq 500	PASS

B. Test Plots:



(Channel 1, 902.8MHz)



(Channel 16, 914.8MHz)



(Channel 32, 927.3MHz)


2.6. Conducted Spurious Emissions and Band Edge

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.6.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.


2.6.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	902.8	-46.80	8.81	-11.19	PASS
16	914.8	-47.74	8.53	-11.47	PASS
32	927.3	-48.50	8.19	-11.81	PASS


B. Test Plots:




(Channel = 1, 30MHz to 25GHz)




(Band Edge, Channel = 1)



(Channel = 16, 30MHz to 25GHz)



(Channel = 32, 30MHz to 25GHz)



(Band Edge, Channel = 32)


2.7. Power Spectral Density (PSD)

2.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.7.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.7.3. Test Procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3 kHz
- d) Set VBW to 10 kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

2.7.4. Test Result

The lowest, middle and highest channels are tested.


A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	902.8	6.61	8	PASS
16	914.8	5.04	8	PASS
32	927.3	6.03	8	PASS


B. Test Plots:



(Channel = 1, 902.8MHz)



(Channel = 16, 914.8MHz)



(Channel = 32, 927.3MHz)

2.8. Conducted Emission

2.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.8.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



2.8.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

Test Setup:

Test Mode: EUT +Adaptor + TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V}] = U_R + L_{\text{Cable loss}} [\text{dB}] + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

ANT1



(L Phase)


NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2266	34.02	24.86	62.57	52.57	Line	PASS
2	0.2802	33.86	24.33	60.81	50.81		PASS
3	0.7792	32.47	24.50	56.00	46.00		PASS
4	0.9650	32.01	22.24	56.00	46.00		PASS
5	1.2443	31.57	21.96	56.00	46.00		PASS
6	1.5260	30.68	21.21	56.00	46.00		PASS



(N Phase)


NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1502	42.40	27.03	65.99	55.99	Neutral	PASS
2	0.1682	36.13	26.09	65.05	55.05		PASS
3	0.2807	32.53	24.62	60.79	50.79		PASS
4	0.4654	30.73	23.09	56.60	46.60		PASS
5	1.0144	30.55	22.45	56.00	46.00		PASS
6	1.4637	29.90	21.75	56.00	46.00		PASS

ANT2



(L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1636	35.18	25.56	65.28	55.28	Line	PASS
2	0.2041	34.62	25.13	63.44	53.44		PASS
3	0.2984	33.35	24.13	60.29	50.29		PASS
4	0.3747	32.86	23.47	58.40	48.40		PASS
5	0.6949	31.80	22.46	56.00	46.00		PASS
6	1.0915	31.72	22.15	56.00	46.00		PASS



(N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1503	42.67	26.95	65.99	55.99	Neutral	PASS
2	0.3166	32.15	24.27	59.79	49.79		PASS
3	0.6178	30.36	22.73	56.00	46.00		PASS
4	0.8568	30.58	22.54	56.00	46.00		PASS
5	1.1717	30.17	22.32	56.00	46.00		PASS
6	1.3866	30.16	22.11	56.00	46.00		PASS



2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dB_{AV}/m@3m (AV) and 74dB_{PK}/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.9.2. Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10:2013. For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10:2013.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant



emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading


G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

ANT1
Plot for Channel = 1


Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
53.280	24.84	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
903.000	42.23	N/A	N/A	N/A	46.00	N/A	Horizontal	N/A
1804.800	49.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2709.520	44.73	N/A	31.78	74.00	N/A	54.00	Horizontal	PASS
4515.120	48.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5972.920	47.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 10GHz)



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
38.730	25.58	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
903.000	32.82	N/A	N/A	N/A	46.00	N/A	Vertical	N/A
1805.300	53.74	N/A	48.10	74.00	N/A	54.00	Vertical	PASS
2708.040	48.64	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3610.840	49.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4513.500	51.44	N/A	42.75	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 10GHz)

Plot for Channel = 16



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
48.430	25.17	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
914.640	61.24	N/A	N/A	N/A	46.00	N/A	Horizontal	N/A
1829.867	49.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2743.560	48.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3658.200	48.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4572.840	49.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 10GHz)



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
38.730	25.11	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
914.640	46.21	N/A	N/A	N/A	46.00	N/A	Vertical	N/A
1829.700	52.63	N/A	47.41	74.00	N/A	54.00	Vertical	PASS
2743.560	48.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3659.900	52.50	N/A	43.01	74.00	N/A	54.00	Vertical	PASS
4573.400	55.97	N/A	46.04	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 10GHz)

Plot for Channel = 32




Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
53.280	25.30	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
927.250	72.80	N/A	N/A	N/A	46.00	N/A	Horizontal	N/A
1853.333	48.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3710.000	45.66	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4635.000	48.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
6189.000	45.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 10GHz)




Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
54.250	25.58	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
927.250	79.88	N/A	N/A	N/A	46.00	N/A	Vertical	N/A
1855.000	54.69	N/A	47.15	74.00	N/A	54.00	Vertical	PASS
2780.560	47.45	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3709.300	51.64	N/A	42.23	74.00	N/A	54.00	Vertical	PASS
4635.800	57.64	N/A	47.70	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 10GHz)

ANT2
Plot for Channel = 1


Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
49.400	24.78	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
1804.800	45.17	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2708.040	46.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4512.160	48.12	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5756.840	46.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8308.360	46.50	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 10GHz)



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
43.580	26.08	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
1804.800	46.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2708.040	49.89	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3610.840	49.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4513.900	57.90	N/A	47.88	74.00	N/A	54.00	Vertical	PASS
8465.240	47.19	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 10GHz)

Plot for Channel = 16



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
48.430	25.53	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
914.640	37.01	N/A	N/A	N/A	46.00	N/A	Horizontal	N/A
1829.333	46.71	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
2743.560	48.49	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3658.200	48.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4571.360	49.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 10GHz)



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
43.580	26.02	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
914.640	35.00	N/A	N/A	N/A	46.00	N/A	Vertical	N/A
1829.333	48.44	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2745.040	48.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3658.200	49.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4575.200	56.88	N/A	42.99	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 10GHz)

Plot for Channel = 32



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
43.580	26.21	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
927.250	61.91	N/A	N/A	N/A	46.00	N/A	Horizontal	N/A
1854.400	48.59	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3708.520	48.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4636.200	53.46	N/A	47.89	74.00	N/A	54.00	Horizontal	PASS
6535.320	45.23	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 10GHz)



Fre. (MHz)	Pk (dB μ V/m)	QP (dB μ V/m)	AV (dB μ V/m)	Limit-PK (dB μ V/m)	Limit-QP (dB μ V/m)	Limit-AV (dB μ V/m)	Antenna	Verdict
54.250	25.92	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
927.250	67.35	N/A	N/A	N/A	46.00	N/A	Vertical	N/A
1854.400	50.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2782.040	46.73	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
3708.520	49.57	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4636.600	57.20	N/A	51.02	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 10GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	±2.22dB
Power spectral density (PSD)	±2.22dB
Bandwidth	±5%
Conducted Spurious Emission	±2.77 dB
Radiated Emission	±2.95dB
Conducted Emission	±2.44dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2019.04.09	2020.04.08
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY56400093	N9038A	KEYSIGHT	2019.05.08	2020.05.09
LISN	812744	NSLK 8127	Schwarzbeck	2019.05.08	2020.05.09
Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2019.05.08	2020.05.09
Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A
Adaptor	N/A	GPE248-1 20200-2	GPE	N/A	N/A
LORA1262 DEMO Note	N/A	DEMO Board	NiceRF Wireless Technology Co., Ltd.	N/A	N/A

Note: The equipment is provided by manufacturer.

4.3 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V 1.0



4.4 Radiated Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2019.07.26	2020.07.25
Test Antenna - Bi-Log	9163-520	VULB 9163	Schwarzbeck	2019.05.08	2020.05.09
Test Antenna - Loop	1520-022	FMZB1520	Schwarzbeck	2019.02.15	2020.02.14
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2020.07.25
Test Antenna - Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2019.07.26	2020.07.25
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2018.12.01	2019.11.30
Anechoic Chamber	N/A	9m*6m*6m	CRT	2017.11.19	2020.11.18
LORA1262 DEMO Note	N/A	DEMO Board	NiceRF Wireless Technology Co., Ltd.	N/A	N/A

Note: The equipment is provided by manufacturer.

END OF REPORT