



REPORT No.: SZ24110310W01

TEST REPORT

APPLICANT : NiceRF Wireless Technology LTD.

PRODUCT NAME : Wireless module

MODEL NAME : LoRa1121

BRAND NAME : G-NiceRF

FCC ID : 2AD66-LORA1121

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2024-11-29


TEST DATE : 2024-12-04 to 2024-12-27

ISSUE DATE : 2025-01-10

Edited by:


Zeng Xiaoying (Rapporteur)

Approved by:


Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	5
1.2. Test Equipment List	6
1.3. Measurement Uncertainty	8
1.4. Testing Laboratory	8
2. General Description	9
2.1. Information of Applicant and Manufacturer	9
2.2. Information of EUT	9
2.3. Channel List of EUT	10
2.4. Operation and Transmitter Power Level Setting	10
2.5. Test Configuration of EUT	11
2.6. Test Conditions	11
2.7. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak Conducted Output Power	16
3.4. Maximum Average Conducted Output Power	17
3.5. 6 dB Bandwidth	18
3.6. Conducted Spurious Emissions and Band Edge	19
3.7. Power Spectral Density	20
3.8. Conducted Emission	21
3.9. Radiated Emission	22
Annex A Test Data and Result	24



REPORT No.: SZ24110310W01

Change History		
Version	Date	Reason for change
1.0	2025-01-10	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Dec. 19, 2024	Lin Haoyang	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Dec. 19, 2024	Lin Haoyang	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Dec. 19, 2024	Lin Haoyang	PASS	No deviation
5	15.247(a)	Bandwidth	Dec. 13&19, 2024	Lin Haoyang	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Dec. 19, 2024	Lin Haoyang	PASS	No deviation
7	15.247(e)	Power Spectral Density	Dec. 13&19, 2024	Lin Haoyang	PASS	No deviation
8	15.207	Conducted Emission	N/A	N/A	N/A _{Note1}	N/A
9	15.209, 15.247(d)	Radiated Emission	Dec. 06&10, 2024	Yang Lian	PASS	No deviation

Note 1: Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2013 and KDB 558074 D01 v05r02.

Note 2: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2024.02.19	2025.02.18
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
TS+ -[JS32-RE]	Tonscend	V2.5.0.6

**1.2.3 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2024.05.30	2025.05.29
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2024.06.03	2025.06.02
Test Antenna - Horn	01774	BBHA 9120D	Schwarzbeck	2024.06.22	2025.06.21
Test Antenna - Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2024.06.22	2025.06.21
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2024.05.30	2025.05.29
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2024.05.30	2025.05.29
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	N/A	N/A
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	N/A	N/A
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone	+86 755 36698555
Facsimile	+86 755 36698525
FCC Designation Number	CN1192
FCC Test Firm Registration Number	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant	NiceRF Wireless Technology LTD.
Applicant Address	309-314, Bldg A, Hongdu business building, Xin'an street, Zone 43, Baoan Dist, Shenzhen 518101, China
Manufacturer	NiceRF Wireless Technology LTD.
Manufacturer Address	309-314, Bldg A, Hongdu business building, Xin'an street, Zone 43, Baoan Dist, Shenzhen 518101, China

2.2. Information of EUT

Product Name:	Wireless module
Sample No.:	1#, 3#
Hardware Version:	V1.0
Software Version:	V1.0
Modulation Type:	LoRa
Transmitter Bandwidth:	500kHz
Operating Frequency Range:	902.92MHz– 926.92MHz
Antenna Type:	Rod Antenna
Antenna Gain:	-2.90dBi

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

2.3.Channel List of EUT

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	902.92	14	915.92
2	903.92	15	916.92
3	904.92	16	917.92
4	905.92	17	918.92
5	906.92	18	919.92
6	907.92	19	920.92
7	908.92	20	921.92
8	909.92	21	922.92
9	910.92	22	923.92
10	911.92	23	924.92
11	912.92	24	925.92
12	913.92	25	926.92
13	914.92		

Note 1: The black bold channels were selected for test.

2.4.Operation and Transmitter Power Level Setting

The EUT was tested while in a continues transmitter/receiver mode under the control of tool which is provided by manufacturer, all the items of transmitter were tested under the power setting as below:

Modulation	Power Setting
LoRa	8

2.5. Test Configuration of EUT


Test mode is used to control the EUT under the maximum power level during test.

2.6. Test Conditions

Temperature (°C)	15-35
Relative Humidity (%)	30-60
Atmospheric Pressure (kPa)	86-106

2.7. Test Setup Layout Diagram

2.7.1. Conducted Measurement




2.7.2. Conducted Emission Measurement




2.7.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☐ Internal ☒ External	☐ FPC Antenna ☐ Spring Antenna ☐ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☒ Rod Antenna	☐ I-PEX Connector ☐ SMA Connector ☒ RP-SMA Connector ☐ Metal Shrapnel ☐ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

KDB 558074 Section 8.3.1 was used in order to prove compliance.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 in this report.



3.4. Maximum Average Conducted Output Power

3.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

3.4.2. Test Procedures

KDB 558074 Section 8.3.2 was used in order to prove compliance.

3.4.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.4. Test Result

Refer to Annex A.3 in this report.



3.5.6 dB Bandwidth

3.5.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.5.1.Test Procedures

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak.
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100\text{ kHz}$, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq 6\text{ dB}$.

3.5.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.3.Test Result

Refer to Annex A.4 in this report.



3.6. Conducted Spurious Emissions and Band Edge

3.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.6.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.7. Power Spectral Density

3.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.7.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW

3.7.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.7.4. Test Result

Refer to Annex A.7 in this report.

3.8. Conducted Emission

3.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.8.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.

3.8.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.8.4. Test Result

This test case does not apply this kind of EUT.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4.Test Result

Refer to Annex A.8 in this report.



Annex A Test Data and Result

A.1. Duty Cycle of Test Signal

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	LoRa 500K	902.92	Ant1	91.31	0.39	0.1
NVNT	LoRa 500K	914.92	Ant1	91.13	0.4	0.1
NVNT	LoRa 500K	926.92	Ant1	91.13	0.4	0.1





Test Graphs

Duty Cycle NVNT LoRa 500K 902.92MHz Ant1



Duty Cycle NVNT LoRa 500K 914.92MHz Ant1






**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit (dBm)	Verdict
NVNT	LoRa 500K	902.92	Ant1	18.54	0	18.54	0.07145	30	Pass
NVNT	LoRa 500K	914.92	Ant1	17.73	0	17.73	0.05929	30	Pass
NVNT	LoRa 500K	926.92	Ant1	18.27	0	18.27	0.06714	30	Pass


Test Graphs

Peak Power NVNT LoRa 500K 902.92MHz Ant1



Peak Power NVNT LoRa 500K 914.92MHz Ant1






**A.3. Maximum Average Conducted Output Power**

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit (dBm)	Verdict
NVNT	LoRa 500K	902.92	Ant1	18.03	0.39	18.42	0.0695	30	Pass
NVNT	LoRa 500K	914.92	Ant1	16.99	0.4	17.39	0.05483	30	Pass
NVNT	LoRa 500K	926.92	Ant1	17.69	0.4	18.09	0.06442	30	Pass





Test Graphs

Average Power NVNT LoRa 500K 902.92MHz Ant1



Average Power NVNT LoRa 500K 914.92MHz Ant1






**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	LoRa 500K	902.92	Ant1	0.573	0.5	Pass
NVNT	LoRa 500K	914.92	Ant1	0.5679	0.5	Pass
NVNT	LoRa 500K	926.92	Ant1	0.629	0.5	Pass





Test Graphs

-6dB Bandwidth NVNT LoRa 500K 902.92MHz Ant1



-6dB Bandwidth NVNT LoRa 500K 914.92MHz Ant1






**A.5. Conducted Spurious Emissions**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	LoRa 500K	902.92	Ant1	-48.33	-20	Pass
NVNT	LoRa 500K	914.92	Ant1	-48.49	-20	Pass
NVNT	LoRa 500K	926.92	Ant1	-48.46	-20	Pass




Test Graphs

Tx. Spurious NVNT LoRa 500K 902.92MHz Ant1 Ref




Tx. Spurious NVNT LoRa 500K 902.92MHz Ant1 Emission







Tx. Spurious NVNT LoRa 500K 914.92MHz Ant1 Ref




Tx. Spurious NVNT LoRa 500K 914.92MHz Ant1 Emission



Tx. Spurious NVNT LoRa 500K 926.92MHz Ant1 Ref



Tx. Spurious NVNT LoRa 500K 926.92MHz Ant1 Emission





REPORT No.: SZ24110310W01


A.6. Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	LoRa 500K	902.92	Ant1	-54.80	-20	Pass
NVNT	LoRa 500K	926.92	Ant1	-48.45	-20	Pass




Test Graphs

Band Edge NVNT LoRa 500K 902.92MHz Ant1 Ref




Band Edge NVNT LoRa 500K 902.92MHz Ant1 Emission






Band Edge NVNT LoRa 500K 926.92MHz Ant1 Ref



Band Edge NVNT LoRa 500K 926.92MHz Ant1 Emission




**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	LoRa 500K	902.92	Ant1	5.85	0	5.85	8	Pass
NVNT	LoRa 500K	914.92	Ant1	5.31	0	5.31	8	Pass
NVNT	LoRa 500K	926.92	Ant1	5.97	0	5.97	8	Pass




Test Graphs

PSD NVNT LoRa 500K 902.92MHz Ant1




PSD NVNT LoRa 500K 914.92MHz Ant1





PSD NVNT LoRa 500K 926.92MHz Ant1





A.8. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


Note 3: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.

Plot for Channel 1




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
34.8549	27.32	-38.50	40.00	Horizontal	PASS
65.9259	14.51	-31.57	40.00	Horizontal	PASS
104.7648	20.76	-31.03	43.50	Horizontal	PASS
164.9650	21.28	-34.52	43.50	Horizontal	PASS
239.7297	20.57	-30.65	46.00	Horizontal	PASS
360.1301	25.34	-27.24	46.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
1806.5807	41.85	-22.86	74.00	Horizontal	PASS
2709.1709	46.70	-18.99	74.00	Horizontal	PASS
5417.9418	49.88	-10.19	74.00	Horizontal	PASS
7224.1224	43.57	-3.46	74.00	Horizontal	PASS
10657.6658	46.53	2.80	74.00	Horizontal	PASS
13041.1041	48.59	6.83	74.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
34.8549	26.66	-38.50	40.00	Vertical	PASS
106.7067	22.30	-31.04	43.50	Vertical	PASS
149.4294	21.20	-35.29	43.50	Vertical	PASS
248.4685	30.11	-30.46	46.00	Vertical	PASS
360.1301	28.28	-27.24	46.00	Vertical	PASS
507.7177	25.79	-24.17	46.00	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
1805.5806	41.04	-22.85	74.00	Vertical	PASS
2709.1709	47.46	-18.99	74.00	Vertical	PASS
3791.7792	44.66	-15.06	74.00	Vertical	PASS
5548.4548	48.07	-8.25	74.00	Vertical	PASS
8981.0981	44.11	-0.98	74.00	Vertical	PASS
13395.1395	49.15	6.50	74.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)




Plot for Channel 13




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
34.8549	26.90	-38.50	40.00	Horizontal	PASS
86.3163	20.62	-33.79	40.00	Horizontal	PASS
104.7648	26.49	-31.03	43.50	Horizontal	PASS
194.0941	23.01	-32.06	43.50	Horizontal	PASS
228.0781	22.01	-31.12	46.00	Horizontal	PASS
360.1301	25.31	-27.24	46.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
1830.0830	41.75	-23.27	74.00	Horizontal	PASS
2745.6746	45.77	-18.57	74.00	Horizontal	PASS
3780.7781	43.44	-15.25	74.00	Horizontal	PASS
5490.4490	49.64	-9.84	74.00	Horizontal	PASS
7243.3243	42.51	-3.03	74.00	Horizontal	PASS
10650.4650	46.92	3.02	74.00	Horizontal	PASS
14638.4638	49.59	7.56	74.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
34.8549	24.54	-38.50	40.00	Vertical	PASS
85.3453	22.53	-33.98	40.00	Vertical	PASS
106.7067	29.15	-31.04	43.50	Vertical	PASS
165.9359	22.47	-34.22	43.50	Vertical	PASS
240.7007	30.40	-30.63	46.00	Vertical	PASS
360.1301	28.22	-27.24	46.00	Vertical	PASS


(Antenna Vertical, 30MHz to 1GHz)



Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
1829.5830	37.97	-23.26	74.00	Vertical	PASS
3770.2770	43.64	-15.44	74.00	Vertical	PASS
4573.3573	46.21	-12.03	74.00	Vertical	PASS
5490.4490	50.61	-9.84	74.00	Vertical	PASS
10555.6556	47.04	3.09	74.00	Vertical	PASS
14651.6652	49.45	7.78	74.00	Vertical	PASS


(Antenna Vertical, 1GHz to 18GHz)

Plot for Channel 25




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
34.8549	27.45	-38.50	40.00	Horizontal	PASS
64.9550	17.27	-31.13	40.00	Horizontal	PASS
104.7648	17.65	-31.03	43.50	Horizontal	PASS
128.0681	22.78	-34.62	43.50	Horizontal	PASS
265.9459	20.97	-30.09	46.00	Horizontal	PASS
360.1301	25.63	-27.24	46.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 1GHz)




Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
1853.5854	46.28	-23.57	74.00	Horizontal	PASS
2780.6781	44.01	-18.71	74.00	Horizontal	PASS
5549.4549	48.23	-8.23	74.00	Horizontal	PASS
7227.7228	41.42	-3.38	74.00	Horizontal	PASS
10560.4560	46.43	2.93	74.00	Horizontal	PASS
14055.2055	48.78	7.04	74.00	Horizontal	PASS

(Antenna Horizontal, 1GHz to 18GHz)



Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
33.8839	24.94	-38.23	40.00	Vertical	PASS
52.3323	17.81	-29.42	40.00	Vertical	PASS
98.9389	20.92	-31.10	43.50	Vertical	PASS
135.8358	24.11	-34.90	43.50	Vertical	PASS
243.6136	28.61	-30.61	46.00	Vertical	PASS
360.1301	28.35	-27.24	46.00	Vertical	PASS

(Antenna Vertical, 30MHz to 1GHz)



Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Antenna	Verdict
1853.0853	43.97	-23.58	74.00	Vertical	PASS
2780.1780	43.96	-18.71	74.00	Vertical	PASS
4963.8964	46.79	-10.86	74.00	Vertical	PASS
7254.1254	41.22	-3.02	74.00	Vertical	PASS
10639.6640	45.94	2.74	74.00	Vertical	PASS
13608.7609	48.26	7.16	74.00	Vertical	PASS

(Antenna Vertical, 1GHz to 18GHz)

END OF REPORT