FCC 47 CFR PART 15 SUBPART C

for

EM3586 ZigBee Module with PA Model: ZiP E2.1-PSLB

Brand: N/A

Test Report Number: C150126Z06-RP1

Issued for

Starfield Electronic Limited
Room 1304-5, Hang Seng North Point Bldg.,339 King's Road, North Point,
HK

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1, Mingkeda Logistics Park, No.18 Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

> TEL: 86-755-28055000 FAX: 86-755-28055221

Issued Date: February 9, 2015







Report No.: C150126Z06-RP1

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST or any government agencies. The test results in the report only apply to the tested sample.



Revision History

Report No.: C150126Z06-RP1

Rev.	Issue Date.	Revisions	Effect Page	Revised By
00	February 9, 2015	Initial Issue	ALL	Sinphy Xie



IC. Report No.: C150126Z06-RP1

TABLE OF CONTENTS

1 T	EST CERTIFICATION	4
2 T	EST RESULT SUMMARY	5
3 E	UT DESCRIPTION	6
	EST METHODOLOGY	
	DESCRIPTION OF TEST MODES	
	ETUP OF EQUIPMENT UNDER TEST	
5.1.	DESCRIPTION OF SUPPORT UNITS	. 8
	CONFIGURATION OF SYSTEM UNDER TEST	
6 F	ACILITIES AND ACCREDITATIONS	9
	FACILITIES	
	ACCREDITATIONS	
	MEASUREMENT UNCERTAINTY	
	CC PART 15.247 REQUIREMENTS 1	
	POWER LINE CONDUCTED EMISSIONS MEASUREMENT	
	SPURIOUS EMISSIONS MEASUREMENT	
	6dB BANDWIDTH MEASUREMENT	
	PEAK OUTPUT POWER	
7.5.	BAND EDGES MEASUREMENT	32
7.6	PEAK POWER SPECTRAL DENSITY MEASUREMENT	38



1 TEST CERTIFICATION

Product	EM3586 ZigBee Module with PA
Model	ZiP E2.1-PSLB
Brand	N/A
Tested	January 26~February 6, 2015
Applicant	Starfield Electronic Limited Room 1304-5, Hang Seng North Point Bldg.,339 King's Road, North Point, HK
Manufacturer	Intercel Group Limited Unit 1706, 17/F, Vanta Industrial Centre, 21-33 Tai Lin Pai Road, Kwai Chung, NT Hong Kong SAR Hong Kong

Report No.: C150126Z06-RP1

APPLICABLE STANDARDS							
Standard	Test Type	Standard	Test Type				
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	Spurious EmissionsConducted MeasurementRadiated Emissions				
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement				
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density				

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2009** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by: Reviewed by:

Sunday Hu

Supervisor of EMC Dept.

Compliance Certification Service Inc.

Ruby Zhang

Supervisor of Report Dept.

Compliance Certification Service Inc.



2 TEST RESULT SUMMARY

APPLICABLE STANDARDS						
Standard	Test Type	Result	Remark			
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.			
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.			
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.			
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.			
15.247(d) 15.209(a)	Spurious EmissionsConducted MeasurementRadiated Emissions	Pass	Meet the requirement of limit.			
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.			

Report No.: C150126Z06-RP1

Note: 1. The statements of test result on the above are decided by the request of test standard only; the measurement uncertainties are not factored into this compliance determination.

^{2.} The information of measurement uncertainty is available upon the customer's request.



3 EUT DESCRIPTION

Product	EM3586 ZigBee Module with PA
Model	ZiP E2.1-PSLB
Brand	N/A
Model Discrepancy	N/A
Identify Number	C150126Z06-RP1
Received Date	January 26, 2015
Power Supply	DC 5V
Frequency Range	2405-2475 MHz
Transmit Power	18.57dBm
Modulation Technique	O-QFSK
Number of Channels	15 Channels
Antenna Specification	Chip antenna with 0.5dBi gain(Max)
Temperature Range	-40°C ~+85°C
Hardware Version	V0.1.4

Report No.: C150126Z06-RP1

Note: 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

^{2.} This submittal(s) (test report) is intended for <u>FCC ID</u>: <u>2AD69ZIPE21PSLB</u> filing to comply with Section 15.207, 15.209 and 15.247of the FCC Part 15, Subpart C Rules.



Compliance Certification Services Inc. Report No.: C150126Z06-RP1

4 TEST METHODOLOGY

4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

•	J. a. i. i. i. a. i.						
Test Item		Test mode	Worse mode				
	Conducted Emission	Mode 1: TX					
	Radiated Emission	Mode 1: TX					

After verification, all tests were carried out with the worst case test modes as shown below.

5 SETUP OF EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Report No.: C150126Z06-RP1

N	. Equipment	Equipment Model No. Serial No.		DOC	Trade Name	Data Cable	Power Cord	
1	Notebook	B475	WB04861612	Yes	LENOVO	Shielded 1.00m	Unshielded 2.50m	
2	Console panel	ISA3	N/A	N/A	ember	Shielded 1.70m	N/A	

Note:

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



6 FACILITIES AND ACCREDITATIONS

6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

No.10-1, Mingkeda Logistics Park, No.18, Huanguan South Rd., Guan Lan Town, Baoan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.4, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

Report No.: C150126Z06-RP1

6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

USA A2LA China CNAS

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

USA FCC

Japan VCCI(C-3478, R-3135, T-652, G-624)

Canada INDUSTRY CANADA

Taiwan BSMI

Copies of granted accreditation certificates are available for downloading from our web site, http://www.ccsrf.com

6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.

7 FCC PART 15.247 REQUIREMENTS

7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Report No.: C150126Z06-RP1

Frequency Range	Limits (dΒμV)				
(MHz)	Quasi-peak	Average			
0.15 to 0.50	66 to 56*	56 to 46*			
0.50 to 5	56	46			
5 to 30	60	50			

NOTE:

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site									
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration				
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015				
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	04/20/2014	04/19/2015				
LISN	EMCO	3825/2	8901-1459	03/09/2014	03/08/2015				
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/17/2014	03/17/2015				
Test S/W	FARAD		EZ-EMC/ CCS-3A	1-CE					

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. N.C.R = No Calibration Request.




Compliance Certification Services Inc. Report No.: C150126Z06-RP1

7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration.

7.1.5. DATA SAMPLE

Frequency (MHz)		Average Reading (dBuV)		QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Margin	Remark (Pass/Fail)
X.XXXX	34.99	19.33	10.15	45.14	29.48	65.99	56.00	-20.85	-26.52	Pass

Factor = Insertion loss of LISN + Cable Loss

Result = Quasi-peak Reading/ Average Reading + Factor

Limit = Limit stated in standard
Margin = Result (dBuV) – Limit (dBuV)



7.1.6. TEST RESULTS


Test Data

Operation Mode: TX **Test Date:** February 6, 2015

Report No.: C150126Z06-RP1

Temperature: 26°C Humidity: 60% RH

Tested by: Sun Guo



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Line (L1/L2)
0.5020	23.82	21.98	9.68	33.50	31.66	56.00	46.00	-22.50	-14.34	L1
1.2180	24.58	13.43	9.71	34.29	23.14	56.00	46.00	-21.71	-22.86	L1
1.6180	25.67	14.73	9.72	35.39	24.45	56.00	46.00	-20.61	-21.55	L1
1.9700	26.24	16.46	9.73	35.97	26.19	56.00	46.00	-20.03	-19.81	L1
5.8900	26.36	14.39	9.72	36.08	24.11	60.00	50.00	-23.92	-25.89	L1
11.6140	23.53	11.47	9.88	33.41	21.35	60.00	50.00	-26.59	-28.65	L1

Note:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
- 3. "---" denotes the emission level was or more than 2dB below the Average limit.
- 4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
- 5. L1= Line One (Live Line)/ L2= Line Two (Neutral Line)




Operation Mode: TX **Test Date:** February 6, 2015

Report No.: C150126Z06-RP1

Temperature: 26°C **Humidity:** 60% RH

Tested by: Sun Guo



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Line (L1/L2)
0.5060	26.37	21.59	9.68	36.05	31.27	56.00	46.00	-19.95	-14.73	L2
1.0580	26.26	17.33	9.80	36.06	27.13	56.00	46.00	-19.94	-18.87	L2
1.9700	28.55	20.12	9.73	38.28	29.85	56.00	46.00	-17.72	-16.15	L2
2.4460	27.72	9.11	9.74	37.46	18.85	56.00	46.00	-18.54	-27.15	L2
4.1940	27.08	17.00	9.77	36.85	26.77	56.00	46.00	-19.15	-19.23	L2
11.2739	24.86	14.22	9.83	34.69	24.05	60.00	50.00	-25.31	-25.95	L2

Note:

- 1. Measuring frequencies from 0.15 MHz to 30MHz.
- 2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Peak detector, Quasi-peak detector and average detector.
- 3. "---" denotes the emission level was or more than 2dB below the Average limit.
- 4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
- 5. L1= Line One (Live Line)/ L2= Line Two (Neutral Line)

7.2. SPURIOUS EMISSIONS MEASUREMENT

7.2.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Report No.: C150126Z06-RP1

7.2.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY52221469	10/25/2014	10/24/2015

7.2.3. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


Measurements are made over the 30MHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels.

Report No.: C150126Z06-RP1


7.2.4. TEST RESULTS

Test Plot


CH Low (30MHz ~26.5GHz)




CH Low (2.31GHz ~2.41GHz)




CH Mid (30MHz ~26.5GHz)



CH High (30MHz ~26.5GHz)



CH High(2.47GHz ~2.5GHz)





7.2.4.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Report No.: C150126Z06-RP1

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)		
30-88	100	40		
88-216	150	43.5		
216-960	200	46		
Above 960	500	54		

NOTE: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dBuV/m) = 20 log Emission level (uV/m).



7.2.4.2. TEST INSTRUMENTS

	Radiated En	nission Test Si	te 966 (2)		
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/01/2014	03/01/2015
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2014	03/18/2015
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2014	03/18/2015
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/01/2014	03/01/2015
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/01/2014	03/01/2015
Board-Band Horn Antenna	SCHWARZBECK	BBHA9170	9170-497	07/10/2014	07/09/2015
Loop Antenna	A、R、A	PLA-1030/B	1029	03/19/2014	03/18/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	СТ	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2014	02/28/2015
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD		LZ-RF / CCS	S-SZ-3A2	

Report No.: C150126Z06-RP1

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The FCC Site Registration number is 101879.
- 3. N.C.R = No Calibration Required.



7.2.4.3. TEST PROCEDURE (please refer to measurement standard)

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

Report No.: C150126Z06-RP1

- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz:


RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

- (a) PEAK:RBW= 1MHz /VBW =3MHz / Sweep=AUTO
- (b) AV: RBW= 1MHz /VBW = 3MHz /RMS detector /Sweep= AUTO
- 7. Repeat above procedures until the measurements for all frequencies are complete.

7.2.4.4. TEST SETUP


Below 30MHz






Report No.: C150126Z06-RP1

Below 1 GHz



Above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



7.2.4.5. DATA SAMPLE

Below 1GHz

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	53.41	-18.63	34.78	43.50	-8.72	V	QP

Report No.: C150126Z06-RP1

Frequency (MHz) = Emission frequency in MHz

Reading (dBuV) = Uncorrected Analyzer / Receiver reading
Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain
Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

Q.P. = Quasi-peak Reading

Above 1GHz

	Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
	XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
ſ	XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz

Reading (dBuV) = Uncorrected Analyzer / Receiver reading Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)

Limit (dBuV/m) = Limit stated in standard

Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)

Peak = Peak Reading AVG = Average Reading

Calculation Formula

Margin (dB) = Result (dBuV/m) – Limits (dBuV/m) Result (dBuV/m) = Reading (dBuV) + Correction Factor



7.2.4.6. TEST RESULTS

Below 1 GHz

Operation Mode: TX Test Date: January 30, 2015

Report No.: C150126Z06-RP1

24°C Tested by: Sun Guo **Temperature: Humidity:** 52% RH Polarity: Ver. / Hor.

(The chart below shows the highest readings taken from the final data.)

Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
224.9700	47.99	-21.10	26.89	46.00	-19.11	V	QP
399.5700	40.84	-16.10	24.74	46.00	-21.26	V	QP
500.4500	48.47	-14.35	34.12	46.00	-11.88	V	QP
549.9200	38.83	-13.10	25.73	46.00	-20.27	V	QP
749.7400	38.69	-11.19	27.50	46.00	-18.50	V	QP
833.1600	34.32	-10.63	23.69	46.00	-22.31	V	QP
224.9700	61.97	-21.10	40.87	46.00	-5.13	Н	QP
275.4100	60.90	-20.44	40.46	46.00	-5.54	Н	QP
399.5700	51.74	-16.10	35.64	46.00	-10.36	Н	QP
500.4500	52.80	-14.35	38.45	46.00	-7.55	Н	QP
549.9200	44.00	-13.10	30.90	46.00	-15.10	Н	QP
749.7400	41.15	-11.19	29.96	46.00	-16.04	Н	QP

^{**}Remark: No emission found between lowest internal used/generated frequency to 30MHz.

Notes:

- 1. Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
- 2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.

4. Frequency (MHz). = Emission frequency in MHz

Reading (dBµV/m) = Receiver reading

= Antenna factor + Cable loss – Amplifier gain = Limit stated in standard Correction Factor (dB)

Limit (dBµV/m)

Margin (dB) = Measured (dBμV/m) – Limits (dBμV/m)

Antenna Pol e(H/V) = Current carrying line of reading



Above 1 GHz

Operation Mode: TX / CH Low Test Date: January 30, 2015

Report No.: C150126Z06-RP1

Temperature:24°CTested by:Sun GuoHumidity:52% RHPolarity:Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	51.19	-5.01	46.18	74.00	-27.82	V	Peak
3322.000	45.54	-0.82	44.72	74.00	-29.28	V	Peak
4807.000	48.53	4.35	52.88	74.00	-21.12	V	Peak
4807.000	42.78	4.35	47.13	54.00	-6.87	V	AVG
6427.000	39.06	6.77	45.83	74.00	-28.17	V	Peak
7795.000	39.30	9.25	48.55	74.00	-25.45	V	Peak
9622.000	47.16	10.89	58.05	74.00	-15.95	V	Peak
9622.000	40.57	10.89	51.46	54.00	-2.54	V	AVG
2566.000	45.23	-2.14	43.09	74.00	-30.91	Н	Peak
3583.000	44.19	-0.17	44.02	74.00	-29.98	Н	Peak
4807.000	47.41	4.35	51.76	74.00	-22.24	Н	Peak
6580.000	38.99	7.02	46.01	74.00	-27.99	Н	Peak
7210.000	43.37	8.11	51.48	74.00	-22.52	Н	Peak
9622.000	48.32	10.89	59.21	74.00	-14.79	Н	Peak
9622.000	38.21	10.89	49.10	54.00	-4.90	Н	AVG

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).



Operation Mode: TX / CH Mid **Test Date:** January 30, 2015

Report No.: C150126Z06-RP1

Temperature:24°CTested by:Sun GuoHumidity:52% RHPolarity:Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	52.29	-5.01	47.28	74.00	-26.72	V	Peak
4132.000	40.93	2.05	42.98	74.00	-31.02	V	Peak
4897.000	47.60	4.64	52.24	74.00	-21.76	V	Peak
4897.000	42.52	4.64	47.16	54.00	-6.84	V	AVG
6769.000	40.35	7.33	47.68	74.00	-26.32	V	Peak
8326.000	39.94	9.47	49.41	74.00	-24.59	V	Peak
9802.000	46.13	11.41	57.54	74.00	-16.46	V	Peak
9802.000	38.41	11.41	49.82	54.00	-4.18	V	AVG
1711.000	55.28	-6.46	48.82	74.00	-25.18	Н	Peak
1999.000	50.90	-5.01	45.89	74.00	-28.11	Н	Peak
3583.000	43.15	-0.17	42.98	74.00	-31.02	Н	Peak
4897.000	50.47	4.64	55.11	74.00	-18.89	Н	Peak
4897.000	43.69	4.64	48.33	54.00	-5.67	Н	AVG
6085.000	40.11	6.22	46.33	74.00	-27.67	Н	Peak
9802.000	47.97	11.41	59.38	74.00	-14.62	Н	Peak
9802.000	40.28	11.41	51.69	54.00	-2.31	Н	AVG

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).



Operation Mode: TX / CH High **Test Date:** January 30, 2015

Report No.: C150126Z06-RP1

Temperature:24°CTested by:Sun GuoHumidity:52% RHPolarity:Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1999.000	50.98	-5.01	45.97	74.00	-28.03	V	Peak
3322.000	44.94	-0.82	44.12	74.00	-29.88	V	Peak
4951.000	49.09	4.82	53.91	74.00	-20.09	V	Peak
4951.000	43.06	4.82	47.88	54.00	-6.12	V	AVG
6814.000	40.32	7.40	47.72	74.00	-26.28	V	Peak
7741.000	39.92	9.14	49.06	74.00	-24.94	V	Peak
9901.000	44.81	11.69	56.50	74.00	-17.50	V	Peak
9901.000	37.08	11.69	48.77	54.00	-5.23	V	AVG
2827.000	44.20	-1.67	42.53	74.00	-31.47	Н	Peak
4951.000	52.97	4.82	57.79	74.00	-16.21	Н	Peak
4951.000	47.47	4.82	52.29	54.00	-1.71	Н	AVG
5626.000	39.60	5.92	45.52	74.00	-28.48	Н	Peak
7651.000	40.42	8.97	49.39	74.00	-24.61	Н	Peak
8227.000	39.51	9.53	49.04	74.00	-24.96	Н	Peak
9901.000	43.94	11.69	55.63	74.00	-18.37	Н	Peak
9901.000	38.55	11.69	50.24	54.00	-3.76	Н	AVG

REMARKS:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
- 3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
- 4. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 6. Margin (dB) = Remark result (dBuV/m) Average limit (dBuV/m).

7.3. 6dB BANDWIDTH MEASUREMENT

7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: C150126Z06-RP1


7.3.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY52221469	10/25/2014	10/24/2015

7.3.3. TEST PROCEDURES (please refer to measurement standard)

- 1. Place the EUT on the table and set it in the transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW = 100kHz, VBW = 300kHz, Span = 5MHz, Sweep = auto.
- 4. Mark the peak frequency and -6dB (upper and lower) frequency.
- 5. Repeat until all the rest channels are investigated.

7.3.4. TEST SETUP



7.3.5. TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2405	1590		PASS
Mid	2450	1587	>500	PASS
High	2475	1606		PASS


Report No.: C150126Z06-RP1

Test Plot


6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)



6dB Bandwidth (CH High)



Report No.: C150126Z06-RP1

7.4. PEAK OUTPUT POWER

7.4.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

- 1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz: 1 Watt.
- 2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

7.4.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Power Meter	Anritsu	ML2495A	1204003	03/01/2014	03/01/2015
Power Sensor	Anritsu	MA2411B	1126150	03/01/2014	03/01/2015

7.4.3. TEST SETUP



7.4.4. TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2405	18.57	0.07194		PASS
Mid	2445	18.01	0.06324	1	PASS
High	2475	17.71	0.05902		PASS

7.5. BAND EDGES MEASUREMENT

7.5.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Report No.: C150126Z06-RP1

7.5.2. TEST INSTRUMENTS

Radiated Emission Test Site 966 (2)							
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration		
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/01/2014	03/01/2015		
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2014	03/08/2015		
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2014	03/18/2015		
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2014	03/18/2015		
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/01/2014	03/01/2015		
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/01/2014	03/01/2015		
Board-Band Horn Antenna	SCHWARZBECK	BBHA9170	9170-497	07/10/2014	07/09/2015		
Loop Antenna	A、R、A	PLA-1030/B	1029	03/19/2014	03/18/2015		
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R		
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R		
Controller	СТ	N/A	N/A	N.C.R	N.C.R		
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2014	02/28/2015		
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R		
Test S/W FARAD LZ-RF / CCS-SZ-3A2							

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The FCC Site Registration number is 101879.
- 3. N.C.R = No Calibration Required.




Compliance Certification Services Inc. Report No.: C150126Z06-RP1

7.5.3. TEST PROCEDURES (please refer to measurement standard)

- 1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
- 4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=3MHz/ Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO
- 5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are

7.5.4. TEST SETUP







Report No.: C150126Z06-RP1


7.5.5. TEST RESULTS


Test Plot

Band Edges (CH Low)












Report No.: C150126Z06-RP1


Band Edges (CH High)






Detector mode: Average Polarity: Vertical







7.6. PEAK POWER SPECTRAL DENSITY MEASUREMENT

7.6.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Report No.: C150126Z06-RP1

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


7.6.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY52221469	10/25/2014	10/24/2015

7.6.3. TEST PROCEDURES (please refer to measurement standard)

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the DTS bandwidth.
- 3. Set the RBW to: 3 kHz \leq RBW \leq 100 kHz.
- 4. Set the VBW \geq 3 RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.6.4. TEST SETUP





7.6.5. TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2405	-11.538		PASS
Mid	2450	-14.090	8.00	PASS
High	2475	-15.329		PASS

Report No.: C150126Z06-RP1

Test Plot

PPSD (CH Low)



PPSD (CH Mid)



PPSD (CH High)

