RF Exposure evaluation

According to KDB 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [\(\forall f(GHz) \)] \(\leq 3.0 \) for 1-g SAR and \(\leq 7.5 \) for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- $\boldsymbol{\cdot}$ Power and distance are rounded to the nearest mW and mm before calculation
- ${}^{\centerdot}$ The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt
```

Field strength = 94.04 dBuV/m @3m Ant gain OdBi; so Ant numeric gain=1

```
So pt={ [10^{(94.04/20)}/10^6 \text{ x3}]^2/30\text{X1} }x1000 mW =0.8 mW So ( 0.8mW/5mm)x \sqrt{2.480} GHz = 0.3 <3
```

Then SAR evaluation is not required