

ISED CABid: ES1909

Lab. Company Number: 4621A

Test Report No:
83024RRF.003

Partial Test Report

USA FCC Part 15.247, 15.209

CANADA RSS-247, RSS-Gen

(*) Identification of item tested	Wellness ring
(*) Trademark	ŌURA
(*) Model and /or type reference	OA11
Other identification of the product	FCC ID: 2AD7V-OURA2401 IC: 20635- OURA2401
(*) Features	Sleep Analysis, Activity Monitoring, Readiness Score, Bluetooth LE HW version: 02 SW version: 2.1.4
Applicant	Oura Health Oy Elektroniikkatie 10, 90590 Oulu, Finland
Test method requested, standard	USA FCC Part 15.247 (10-1-23 Edition): Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-23 Edition): Radiated emission limits; general requirements. CANADA RSS-247 Issue 3 (August 2023). CANADA RSS-Gen Issue 5 amendment 2 (February 2021). Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Approved by (name / position & signature)	José Manuel Gómez Galván EMC Consumer & RF Lab. Manager
Date of issue	2025-07-17
Report template No	FDT08_25 (*) "Data provided by the client"

Index

INDEX2

ACRONYMS3

COMPETENCES AND GUARANTEES3

GENERAL CONDITIONS3

UNCERTAINTY4

DATA PROVIDED BY THE CLIENT4

USAGE OF SAMPLES5

TEST SAMPLE DESCRIPTION6

IDENTIFICATION OF THE CLIENT8

TESTING PERIOD AND PLACE8

DOCUMENT HISTORY8

ENVIRONMENTAL CONDITIONS8

REMARKS AND COMMENTS9

TESTING VERDICTS10

SUMMARY11

APPENDIX A: TEST RESULTS. BLUETOOTH LOW ENERGY (1MBPS, 2MBPS)12

Acronyms

Acronym ID	Acronym Description
Detector	Detector used
Equipment	Equipment Type
Freq	Frequency
Freq Rng	Frequency Range
MP	Measurement Point
Mod	Modulation
Operation Band	Operation Band
Pol	Polarization
Port	Active Port
RU	Resource Unit
Unwanted Freq	Unwanted Emissions Frequency
Unwanted Lvl	Unwanted Emissions Level

Competences and guarantees

DEKRA Testing and Certification S.A.U. is a testing laboratory accredited by the National Accreditation Body (ENAC -Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification S.A.U. is an FCC-recognized accredited testing laboratory with appropriate scope of accreditation that covers the performed tests in this report.

DEKRA Testing and Certification S.A.U. is an ISED-recognized accredited testing laboratory, CABid: ES1909, Company Number: 4621A, with the appropriate scope of accreditation that covers the performed tests in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification S.A.U. at the time of performance of the test.

DEKRA Testing and Certification S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification S.A.U.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification S.A.U. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Testing and Certification S.A.U. internal document PODT000.

The total uncertainty of the measurement system for the radiated emissions of EUT from 30 MHz to 1 GHz is:
Measurement uncertainty $\leq \pm 5,35$ dB with factor ($k = 2$).

The total uncertainty of the measurement system for the radiated emissions of EUT from 1 GHz to 17 GHz is:
Measurement uncertainty $\leq \pm 4,32$ dB with factor ($k = 2$).

The total uncertainty of the measurement system for the radiated emissions of EUT from 17 GHz to 26 GHz is:
Measurement uncertainty $\leq \pm 5,51$ dB with factor ($k = 2$).

The total uncertainty of the measurement system for the conducted testing of EUT is:

RF Peak Output Power: Measurement uncertainty $\leq \pm 0,80$ dB

RF Average Output Power: Measurement uncertainty $\leq \pm 0,99$ dB

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample consists of a Wellness ring. OURA is a revolutionary wellness ring and app, designed to help user gets more restful sleep and performs better. It enables user to learn how the lifestyle choices affect user's sleep, and how the quality of the sleep affects user's ability to perform. The OURA ring can automatically tell when user is sleeping. When user goes to sleep, the OURA ring analyzes the quality of the rest and recovery by measuring the heart rate (optically), respiration rate, body temperature, and movement. While user is awake, it monitors the duration and intensity of the activities, and the time user spends sitting. The OURA app integrates and visualizes this data to identify patterns between the sleep quality and daily activities. By understanding how well user slept and recharged, it can determine the readiness to perform and help user adjust the intensity and duration of the day's activities. It can also uncover actionable insights for changes to the daily activities that can help user sleep better..

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results. The laboratory is not responsible for such information and it is not covered by accreditation.

Usage of samples

Samples undergoing test have been selected by: The client.

Id	Control Number	Description	Model	Serial N°	Date of Reception	Application
S/01	83024_2.1	Smart Ring			2025-05-16	Element Under Test
S/02	82380_9.1	OA11 Smart Ring Size 10 (Conducted)	OA11	--	2025-05-15	Element Under Test

Notes referenced to samples during the project:

Id	Type
S/01	Radiated
S/02	Conducted

Test sample description

Ports..... :	Port name and description	Cable					
		Specified max length [m]	Attached during test	Shielded	Coupled to patient ⁽³⁾		
			[]	[]	[]		
			[]	[]	[]		
			[]	[]	[]		
			[]	[]	[]		
			[]	[]	[]		
Supplementary information to the ports..... :							
Rated power supply	Voltage and Frequency		Reference poles				
			L1	L2	L3	N	PE
	[]	AC:	[]	[]	[]	[]	[]
	[]	AC:	[]	[]	[]	[]	[]
	[X]	DC: 3.7V					
[]	DC:						
Rated Power							
Clock frequencies.....							
Other parameters							
Software version	2.1.4						
Hardware version	02						
Dimensions in cm (W x H x D)							
Mounting position	[]	Table top equipment					
	[]	Wall/Ceiling mounted equipment					
	[]	Floor standing equipment					
	[X]	Hand-held equipment					
	[]	Other:					

Modules/parts.....:	Module/parts of test item	Type	Manufacturer
			
			
			
			
Accessories (not part of the test item)	Description	Type	Manufacturer
			
			
			
			
			
			
Documents as provided by the applicant	Description	File name	Issue date
			
			
			
			

(3) Only for Medical Equipment

Identification of the client

Oura Health Oy
Elektroniikkatie 10, 90590 Oulu, Finland

Testing period and place

Test Location	DEKRA Testing and Certification S.A.U.
Date (start)	2025-06-24
Date (finish)	2025-06-30

Document history

Report number	Date	Description
83024RRF.003	2025-07-17	First release.

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the semianechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 20 % Max. = 75 %

Remarks and comments

The tests have been performed by the technical personnel: Rubén Mora Fernandez.

Used instrumentation:

Control No.	Equipment	Model	Manufacturer	Next Calibration
10304	EMI TEST RECEIVER 2Hz-44GHz	ESW44	ROHDE AND SCHWARZ	2026-10-01
07763	HORN ANTENNA 1-18GHz	BBHA 9120D	SCHWARZBECK MESS-ELEKTRONIK	2026-01-16
06495	HORN ANTENNA 18-40GHz	BBHA 9170	SCHWARZBECK	2027-07-11
09968	HYBRID BILOG ANTENNA 30MHz-6GHz	3142E	ETS LINDGREN	2026-09-22
07862	PRE-AMPLIFIER G>30dB 18-40GHz	BLMA 1840-3G	BONN ELEKTRONIK	2026-07-09
07769	PREAMPLIFIER 30dB 500MHz-18GHz	BBV 9718 C	SCHWARZBECK	2026-03-17
08130	SEMIANECHOIC ABSORBER LINED CHAMBER	P29419	ALBATROSS	--
08134	SHIELDED ROOM	P29419	ALBATROSS PROJECTS GMBH	--
04848	SOFTWARE FOR EMC/RF TESTING	EMC32	ROHDE AND SCHWARZ	--
07550	TEMPERATURE AND HUMIDITY PROBE	HWg-STE	HW GROUP	2026-04-23
07549	TEMPERATURE AND HUMIDITY PROBE	HWg-STE	HW GROUP	2026-04-23
07798	WMS32	WMS32	ROHDE AND SCHWARZ	--
07552	TEMPERATURE AND HUMIDITY PROBE	HWg-STE	HW GROUP	2026-04-23
08661	SHIELDED ROOM	-	SIEPEL	--
04848	SOFTWARE FOR EMC/RF TESTING	EMC32	ROHDE AND SCHWARZ	--
07039	Rohde&Schwarz	OSP-B157W8	ROHDE & SCHWARZ	2025-05-25
07040	EXTENSION FOR OPEN SWITCH UNIT UP TO 40GHz	OSP-B157Wx	Rohde&Schwarz	2025-04-19
07702	DC POWER SUPPLY 30V/3A 90W	GPS-3030D	GW INSTEK	--
07755	DIGITAL MULTIMETER	175	FLUKE	2025-11-25
07794	SIGNAL AND SPECTRUM ANALYZER 10Hz-40GHz	FSV40	ROHDE AND SCHWARZ	2027-06-10

Testing verdicts

Fail	F
Inconclusive	I
Not applicable	N/A
Not measured	N/M
Pass	P

Summary

Bluetooth Low Energy (1Mbps, 2Mbps).

FCC PART 15 PARAGRAPH/ RSS-247			
Requirement – Test case		Verdict	Remark
FCC 15.247 (a)(2) / RSS-247 5.2. (a)	6 dB Bandwidth	N/M	(1)
FCC 15.247 (b) / RSS-247 5.4. (d)	Maximum output power and antenna gain	P	--
FCC 15.247 (d) / RSS-247 5.5.	Band-edge emissions compliance (Transmitter)	N/M	(1)
FCC 15.247 (e) / RSS-247 5.2. (b)	Power spectral density	N/M	(1)
FCC 15.247 (d) / RSS-247 5.5.	Emission limitations radiated (Transmitter)	P	--
<u>Supplementary information and remarks:</u>			
(1) Test not requested by the customer			

Appendix A: Test results. Bluetooth Low Energy (1Mbps, 2Mbps)

INDEX

TEST CONDITIONS	14
TEST CASES DETAILS	17
<i>RSS-247 5.4 (d) / FCC 15.247 (b) (3) Maximum Peak Conducted output power</i>	<i>17</i>
<i>RSS-247 5.5 / FCC 15.247 (d) [RSE] Emission limitations radiated (Transmitter)</i>	<i>25</i>

TEST CONDITIONS

(*): Data provided by the client.

POWER SUPPLY (*):

Vnominal: 3.7V DC
Type of Power Supply: Battery

ANTENNA (*):

Type of Antenna: Integral Antenna
Maximum Declared Antenna Gain: -11.1dBi

TEST FREQUENCIES (*):

Modulation	Data rates	Low Channel:	Middle Channel	High Channel
BTLE GFSK	1M 1 Mbit/s	2402 MHz	2440 MHz	2480 MHz
BTLE GFSK	2M 2 Mbit/s	2402 MHz	2440 MHz	2480 MHz

During transmitter test the EUT was controlled by a SW tool provided by the client to operate in a continuous transmit mode on the modulation schemes and test channels as required.

CONDUCTED MEASUREMENTS:

The equipment under test was set up in a shielded room and it is connected to the TS8997 using a low loss RF cable. The reading of the spectrum analyser is corrected taking into account the cable loss.



RADIATED MEASUREMENTS:

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna (Bilog antenna for the range between 30 MHz to 1000 MHz and 1 GHz-17 GHz Double ridge horn antenna) is situated at a distance of 3 m and at a distance of 1.5 m for the frequency range 17 GHz-26 GHz (17 GHz-40 GHz horn antenna).


For radiated emissions in the range 17 GHz-26 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height (Bilog antenna and Double ridge horn antenna) was varied from 1 to 4 meters to find the maximum radiated emission.


Measurements were made in both horizontal and vertical planes of polarization.

A resolution bandwidth/video bandwidth of 100 kHz / 300 kHz was used for frequencies below 1 GHz and 1 MHz / 3 MHz for frequencies above 1 GHz.


Radiated measurements setup from 30 MHz to 1 GHz:



Radiated measurements setup from 1 GHz to 17 GHz:



Radiated measurements setup $f > 17$ GHz:



TEST CASES DETAILS

RSS-247 5.4 (d) / FCC 15.247 (b) (3) Maximum Peak Conducted output power

Limits

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).

The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

The maximum peak conducted output power level in the fundamental emission was measured using the method according to point 11.9.1.1 "RBW ≥ DTS bandwidth" of ANSI C.63.10-2013.

Modulation: BTLE (GFSK 1 Mbit/s)

Results

Freq (MHz)	Peak Power (dBm)	Peak Power EIRP (dBm)
2402.00000	0.745	-10.355
2440.00000	1.045	-10.055
2480.00000	1.322	-9.778



Verdict

Pass

Attachments



Equipment Type = Digital Transmission System (DTS) Bandwidth MHz = 1
 Modulation = BTLE (GFSK 1 Mbit/s) Frequency MHz = 2402.00000
 MIMO Mode = SISO Active Port = 1

Images:





Equipment Type = Digital Transmission System (DTS) Bandwidth MHz = 1
Modulation = BTLE (GFSK 1 Mbit/s) Frequency MHz = 2440.00000
MIMO Mode = SISO Active Port = 1

Images:



Equipment Type = Digital Transmission System (DTS) Bandwidth MHz = 1
Modulation = BTLE (GFSK 1 Mbit/s) Frequency MHz = 2480.00000
MIMO Mode = SISO Active Port = 1

Images:



Modulation: BTLE (GFSK 2 Mbit/s)

Results

Freq (MHz)	Peak Power (dBm)	Peak Power EIRP (dBm)
2402.00000	1.016	-10,084
2440.00000	1.346	-9,754
2480.00000	1.572	-9,528



Verdict

Pass

Attachments



Equipment Type = Digital Transmission System (DTS) Bandwidth MHz = 2
Modulation = BTLE (GFSK 2 Mbit/s) Frequency MHz = 2402.00000
MIMO Mode = SISO Active Port = 1

Images:





Equipment Type = Digital Transmission System (DTS) Bandwidth MHz = 2
Modulation = BTLE (GFSK 2 Mbit/s) Frequency MHz = 2440.00000
MIMO Mode = SISO Active Port = 1

Images:



Equipment Type = Digital Transmission System (DTS) Bandwidth MHz = 2
Modulation = BTLE (GFSK 2 Mbit/s) Frequency MHz = 2480.00000
MIMO Mode = SISO Active Port = 1

Images:



RSS-247 5.5 / FCC 15.247 (d) [RSE] Emission limitations radiated (Transmitter)

Limits

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)/RSS-Gen):

Frequency Range (MHz)	Field strength ($\mu\text{V/m}$)	Field strength (dB $\mu\text{V/m}$)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	-	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
Above 960	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247: Attenuation below the general field strength limits specified in RSS-Gen is not required.

Frequency range tested for Radiated emissions:

Start frequency: no radiofrequency signal generated in the device found below 10th sub-harmonic, no further investigation required.

Stop frequency: it has been performed the radiated spurious emissions until 10th harmonic.

Modulation: BTLE 5.0 (GFSK 1 Mbit/s)

Results

Freq Rng (GHz)	Operation Band (MHz)	Equipment	Freq (MHz)	Unwanted Freq (MHz)	Unwanted Lvl (dBµV/m)	Pol	Detector
[3, 17]	[2400, 2483.5]	Digital Transmission System (DTS)	2402.00000	4804.500	43.09	V	PK
				7205.500	51.12	V	PK
				9607.000	50.80	V	PK
			2440.00000	4879.500	42.49	V	PK
				7320.500	51.91	V	PK
				9759.000	51.85	V	PK
			2480.00000	4960.500	42.85	V	PK
				7441.000	52.44	V	PK
				9921.500	51.82	H	PK

Verdict

Pass

Attachments

Frequency Range GHz = [0.03, 1]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2402.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	30 MHz - 1 GHz	48,5 kHz	PK+	100 kHz	1 s	20 dB

Frequency Range GHz = [0.03, 1]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2440.00000

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	30 MHz - 1 GHz	48,5 kHz	PK+	100 kHz	1 s	20 dB

Frequency Range GHz = [0.03, 1]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2480.00000

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	30 MHz - 1 GHz	48,5 kHz	PK+	100 kHz	1 s	20 dB

Frequency Range GHz = [1, 3]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2402.00000

Active Port = 1


Modulation = BTLE 5.0 (GFSK 1 Mbit/s)


Resource Unit Tone/Index = -

Images:



Full Spectrum





Tables:
Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	1 GHz - 3 GHz	66,667 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [1, 3]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2440.00000

Active Port = 1


Modulation = BTLE 5.0 (GFSK 1 Mbit/s)


Resource Unit Tone/Index = -

Images:



Full Spectrum





Tables:
Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	1 GHz - 3 GHz	66,667 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [1, 3]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2480.00000

Active Port = 1


Modulation = BTLE 5.0 (GFSK 1 Mbit/s)


Resource Unit Tone/Index = -

Images:



Full Spectrum





Tables:
Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	1 GHz - 3 GHz	66,667 kHz	PK+ ; AVG	1 MHz	1 s	0 dB


Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2402.00000

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	3 GHz - 17 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [3, 17]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2440.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	3 GHz - 17 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [3, 17]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2480.00000

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	3 GHz - 17 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [17, 26]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2402.00000

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	17 GHz - 26 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [17, 26]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2440.00000

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	17 GHz - 26 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [17, 26]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2480.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 1 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	17 GHz - 26 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Modulation: BTLE 5.0 (GFSK 2 Mbit/s)

Results

Freq Rng (GHz)	Operation Band (MHz)	Equipment	Freq (MHz)	Unwanted Freq (MHz)	Unwanted Lvl (dBµV/m)	Pol	Detector
[3, 17]	[2400, 2483.5]	Digital Transmission System (DTS)	2402.00000	4803.500	42.45	V	PK
				7204.500	52.13	V	PK
				9610.000	50.51	V	PK
			2440.00000	4879.000	42.52	V	PK
				7318.500	52.25	V	PK
				9760.000	50.00	V	PK
			2480.00000	4959.500	42.47	V	PK
				7439.000	50.37	V	PK
				9919.000	52.07	V	PK

Verdict

Pass

Attachments

Frequency Range GHz = [0.03, 1]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2402.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	30 MHz - 1 GHz	48,5 kHz	PK+	100 kHz	1 s	20 dB

Frequency Range GHz = [0.03, 1]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2440.00000

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	30 MHz - 1 GHz	48,5 kHz	PK+	100 kHz	1 s	20 dB

Frequency Range GHz = [0.03, 1]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2480.00000

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	30 MHz - 1 GHz	48,5 kHz	PK+	100 kHz	1 s	20 dB

Frequency Range GHz = [1, 3]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2402.00000

Active Port = 1


Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Resource Unit Tone/Index = -

Images:



Full Spectrum





Tables:
Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	1 GHz - 3 GHz	66,667 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [1, 3]

Operation Band MHz = [2400, 2483.5]


Equipment Type = Digital Transmission System (DTS) Frequency MHz = 2440.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Resource Unit Tone/Index = -

Images:



Full Spectrum





Tables:
Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	1 GHz - 3 GHz	66,667 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [1, 3]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2480.00000

Active Port = 1


Modulation = BTLE 5.0 (GFSK 2 Mbit/s)


Resource Unit Tone/Index = -

Images:



Full Spectrum





Tables:
Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	1 GHz - 3 GHz	66,667 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [3, 17]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2402.00000

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	3 GHz - 17 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [3, 17]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2440.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Resource Unit Tone/Index = -

Images:




Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	3 GHz - 17 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	3 GHz - 17 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [17, 26]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2402.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	17 GHz - 26 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [17, 26]

Operation Band MHz = [2400, 2483.5]

Equipment Type = Digital Transmission System (DTS)


Frequency MHz = 2440.00000

Active Port = 1

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Resource Unit Tone/Index = -

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	17 GHz - 26 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB

Frequency Range GHz = [17, 26]

Equipment Type = Digital Transmission System (DTS)

Active Port = 1


Resource Unit Tone/Index = -

Operation Band MHz = [2400, 2483.5]

Frequency MHz = 2480.00000

Modulation = BTLE 5.0 (GFSK 2 Mbit/s)

Images:



Tables:

Spectrum Analyzer Parameters

	Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
	Receiver: [ESW 44]					
	17 GHz - 26 GHz	500 kHz	PK+ ; AVG	1 MHz	1 s	0 dB