

**ERON ELEKTRONIK BILGISAYAR VE  
YAZILIM SANAYI TIC. LTD. STI.  
Esensehir Mah. Kurkuler Cad. Kanuni Sok. White Side Sit.  
F Blok D:33 Umraniye ISTANBUL Turkey**

Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

**Applicant's declaration concerning RF Radiation Exposure**

We hereby indicate that the product  
Product description: MIOPS BTM  
Model No: MIOPS BTM

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the  
Product: MIOPS BTM  
will be integrated in the user's manual to provide end-users with transmitter operating  
conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21711-17579-C-1  
and the accompanying calculations.

Company: ERON ELEKTRONIK BILGISAYAR VE YAZILIM SANAYI TIC. LTD. STI.

Address: Esensehir Mah. Kurkuler Cad. Kanuni Sok. White Side Sit. F Blok D:33 Umraniye  
ISTANBUL Turkey

Date: 2017-12-04

Signature

  
**ERON ELEKTRONIK**  
BİLGİSAYAR ve YAZILIM SANAYİ LTD. STİ.  
Esensehir Mah. Kurkuler Cad. Kanuni Sok. White Side Sit.  
F Blok D:33 Umraniye - İSTANBUL  
İzmit İlçesi: 360 600 7236 İmzalı BİL: No: 86431



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M21711-17579-C-1

FCC ID: 2AD8MMBTM37

## **3.2 RF Exposure Compliance Requirements**

FCC Rule: 15.247(b)(3)

Test exclusion = max. conducted output power

Test exclusion = 2.65 dBm

## **3.3 RF Exposure Compliance Requirements**

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{P G}{4 \pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	1.8408	Peak value
D	dB		
AG	dBi	2	
G		1.5849	Calculated Value
R	cm	20	Assumed value
S	mW/cm <sup>2</sup>	0.0006	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm <sup>2</sup> )
1500 – 100.000	1.0