



■ Report No.: DDT-R21041902-1E06

■ Issued Date: May 28, 2021

RF EXPOSURE REPORT

FOR

Applicant	:	JL Audio, Inc.
Address	:	10369 North Commerce Pkwy, Miramar, FL 33025 USA.
Equipment under Test	:	GAUGE RADIO WITH BT MUSIC
Model No.	:	CMM-20
Trade Mark	:	/
FCC ID	:	2AD9E-CMM20
Manufacturer	:	JL Audio, Inc.
Address	:	10369 North Commerce Pkwy, Miramar, FL 33025 USA.

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,

Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

Test report declares.....	3
1. General Information	5
1.1. Description of equipment	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC	5

Test Report Declare

Applicant	:	JL Audio, Inc.
Address	:	10369 North Commerce Pkwy, Miramar, FL 33025 USA.
Equipment under Test	:	GAUGE RADIO WITH BT MUSIC
Model No.	:	CMM-20
Trade mark	:	/
Manufacturer	:	JL Audio, Inc.
Address	:	10369 North Commerce Pkwy, Miramar, FL 33025 USA.

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above.

The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R21041902-1E06	
Date of Receipt:	May 19, 2021	Date of Test: May 19, 2021 ~ May 25, 2021

Prepared By:


Sam Li

Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	May 28, 2021	

1. General Information

1.1. Description of equipment

EUT* Name	: GAUGE RADIO WITH BT MUSIC
Model Number	: CMM-20
EUT function description	: Please reference user manual of this device
Power Supply	: DC 12V
Radio Specification	: Bluetooth V5.0
Operation Frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: Integral PCB antenna, maximum PK gain: 0 dBi
Serial Number	: N/A

Note: EUT is the abbreviation of equipment under test.

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

BT Manufacturing Tolerance

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	-2	-5
Tolerance \pm (dB)	1	1	1
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	-2	-5
Tolerance \pm (dB)	1	1	1
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	0	-2	-5
Tolerance \pm (dB)	1	1	1

BLE Manufacturing Tolerance

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	-4	-7	-9
Tolerance \pm (dB)	1	1	1

Estimation Result

Worse case is as below: [2402 MHz, 1 dBm, 1.26 mW] output power]

$$(1.26/5) \cdot [\sqrt{2.402(\text{GHz})}] = 0.39 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required

END OF REPORT