

RF EXPOSURE REPORT



Report No.: 16070480-FCC-H2

Supersede Report No.: N/A

Applicant	MOBIWIRE MOBILES (NINGBO) CO.,LTD	
Product Name	Mobile phone	
Model No.	öwn SMART VALUE	
Serial No.	N/A	
Test Standard	FCC 2.1093:2015	
Test Date	April 28 to May 10, 2016	
Issue Date	May 20, 2016	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
Winnie Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16070480-FCC-H2
Page	3 of 10

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.8	
5.1 RF EXPOSURE.....	8
5.2 TEST RESULT	9

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070480-FCC-H2	NONE	Original	May 11, 2016
16070480-FCC-H2	V1	Update trademark	May 20, 2016

2. Customer information

Applicant Name	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Applicant Add	No.999,Dacheng East Road,Fenghua City,Zhejiang
Manufacturer	MOBIWIRE MOBILES (NINGBO) CO.,LTD
Manufacturer Add	No.999,Dacheng East Road,Fenghua City,Zhejiang

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Mobile phone

Main Model: **öwn** SMART VALUE

Serial Model: N/A

Date EUT received: April 27, 2016

Test Date(s): April 28 to May 10, 2016

GSM850: -3dBi

PCS1900: -1dBi

UMTS-FDD Band V: -3dBi

UMTS-FDD Band II: -1dBi

Bluetooth/BLE/WIFI: -2dBi

LTE Band IV: -3dBi

LTE Band VII: -2dBi

GPS:-2dBi

GSM / GPRS: GMSK

EGPRS: GMSK,8PSK

UMTS-FDD: QPSK, 16QAM

802.11b/g/n: DSSS, OFDM

Bluetooth: GFSK, π /4DQPSK, 8DPSK

BLE: GFSK

LTE Band: QPSK, 16QAM

GPS:BPSK

Type of Modulation:

Test Report	16070480-FCC-H2
Page	7 of 10

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
 PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
 UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
 UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
 RX: 1932.4 ~ 1987.6 MHz

RF Operating Frequency (ies):
 WIFI: 802.11b/g/n(20M): 2412-2462 MHz
 WIFI: 802.11n(40M): 2422-2452 MHz
 Bluetooth & BLE: 2402-2480 MHz
 LTE Band IV TX: 1712.5 ~ 1752.5 MHz; RX: 2112.5 ~ 2152.5 MHz
 LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX: 2622.5 ~ 2687.5 MHz
 GPS RX: 1575.42 MHz

GSM 850: 124CH
 PCS1900: 299CH
 UMTS-FDD Band V: 102CH
 UMTS-FDD Band II: 277CH
 Number of Channels:
 WIFI: 802.11b/g/n(20M): 11CH
 WIFI: 802.11n(40M): 7CH
 Bluetooth: 79CH
 BLE: 40CH
 GPS: 1CH

Port: Power Port, Earphone Port, USB Port

Adapter:
 Model: OWN SMART VALUE
 Input: AC 100-240V; 50/60Hz; 0.2A
 Output: DC 5.0V, 1A
 Input Power:
 Battery:
 Model: OWN SMART VALUE
 Spec: 3.8V, 2100mAh, 7.98Wh
 Limited charger voltage: 4.35V

Trade Name :



GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2ADA4VALUE

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	3.005	3.5±1	4.5	2.818	0.87	3
	Mid	2441	3.988	3.5±1	4.5	2.818	0.88	3
	High	2480	3.658	3.5±1	4.5	2.818	0.89	3
$\pi/4$ DQPSK	Low	2402	2.189	2.7±1	3.7	2.344	0.73	3
	Mid	2441	3.330	2.7±1	3.7	2.344	0.73	3
	High	2480	2.691	2.7±1	3.7	2.344	0.74	3
8-DPSK	Low	2402	2.365	2.7±1	3.7	2.344	0.73	3
	Mid	2441	3.447	2.7±1	3.7	2.344	0.73	3
	High	2480	2.955	2.7±1	3.7	2.344	0.74	3

WIFI Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	8.23	8.5±1	9.5	8.913	2.77	3
	Mid	2437	9.08	8.5±1	9.5	8.913	2.78	3
	High	2462	9.41	8.5±1	9.5	8.913	2.80	3
802.11g	Low	2412	9.18	8.5±1	9.5	8.913	2.77	3
	Mid	2437	9.64	8.7±1	9.7	9.333	2.91	3
	High	2462	9.29	8.5±1	9.5	8.913	2.80	3
802.11n (20M)	Low	2412	8.90	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.87	8.5±1	9.5	8.913	2.78	3
	High	2462	8.72	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	7.65	7.5±1	8.5	7.079	2.20	3
	Mid	2437	9.21	8.5±1	9.5	8.913	2.78	3
	High	2452	7.43	7.5±1	8.5	7.079	2.22	3

BLE Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-4.302	-4±1	-3	0.501	0.16	3
	Mid	2440	-2.381	-2±1	-1	0.794	0.25	3
	High	2480	-3.989	-3±1	-2	0.631	0.20	3

Result: Compliance

No SAR measurement is required.