





EMC TEST REPORT FCC 47 CFR Part 15B Industry Canada RSS-Gen Electromagnetic compatibility - Unintentional radiators	
Report Reference No.	G0M-1409-4154-EF0515B-V01
Testing Laboratory	Eurofins Product Service GmbH
Address	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	<div style="text-align: center;">   </div> <p>A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A</p>
Applicant's name	Amor Gummiwaren GmbH
Address	August-Rost-Straße 4 99310 Arnstadt GERMANY
Test specification:	
Standard.....	47 CFR Part 15 Subpart B RSS-Gen, Issue 3, 2010-12 ANSI C63.4:2009
Equipment under test (EUT):	
Product description	electric device
Model No.	Sette
Additional Models	None
Hardware version	V2.0
Firmware / Software version	BLE-Stack SD110 V6.0.0
	FCC-ID: 2ADAR504007 IC: 12372A-504007
Test result	Passed

Possible test case verdicts:	
- not applicable to test object	N/A
- test object does meet the requirement.....	P (Pass)
- test object does not meet the requirement.....	F (Fail)
Testing:	
Date of receipt of test item	2015-02-18
Date (s) of performance of tests	2015-02-24
Compiled by	Steffen Zunke
Tested by (+ signature).....	Steffen Zunke 
Approved by (+ signature)	Marcus Klein 
Date of issue.....	2015-02-25
Total number of pages.....	34
General remarks:	
<p>The test results presented in this report relate only to the object tested.</p> <p>The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.</p> <p>This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.</p>	
Additional comments:	

Version History

Version	Issue Date	Remarks	Revised by
V01	2015-02-25	Initial Release	


REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Photos – Equipment external	6
1.2	Photos – Equipment internal	8
1.3	Photos – Test setup	9
1.4	Supporting Equipment Used During Testing	10
1.5	Input / Output Ports	10
1.6	Operating Modes and Configurations	11
1.7	Sample emission level calculation	12
2	RESULT SUMMARY	13
3	TEST CONDITIONS AND RESULTS	14
3.1	Test Conditions and Results – Radiated emissions	14
3.2	Test Conditions and Results – AC power line conducted emissions	31

1 Equipment (Test item) Description


Description	electric device
Model	Sette
Additional Models	None
Serial number	None
Hardware version	V2.0
Software / Firmware version	BLE-Stack SD110 V6.0.0
FCC-ID	2ADAR504007
IC-ID	12372A-504007
Power supply	3.7 VDC (accu)
AC/DC-Adaptor	Model : FW7713 Manufacturer : FRIWO Gerätebau GmbH Input : 100-240VAC / 50-60Hz Output : 5VDC / 1.0A
Manufacturer	Amor Gummiwaren GmbH August-Rost-Straße 4 99310 Arnstadt GERMANY
Highest emission frequency	Fmax [MHz] = 2540
Device classification	Class B
Equipment type	Tabletop
Number of tested samples	1

1.1 Photos – Equipment external







1.2 Photos – Equipment internal



1.3 Photos – Test setup



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
AE	smart phone	LG	G2	-
<p>*Note: Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

1.5 Input / Output Ports

No ports available

1.6 Operating Modes and Configurations

Mode #	Description
1	vibrating + Bluetooth communication to a smartphone
2	charging + Bluetooth communication to a smartphone

Configuration #	EUT Configuration
1	EUT in normal operation mode

1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB μ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB μ V/m). The FCC limits are given in units of μ V/m. The following formula is used to convert the units of μ V/m to dB μ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 * \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

2 Result Summary

FCC 47 CFR Part 15B, Industry Canada RSS-Gen				
Product Specific Standard	Requirement – Test	Reference Method	Result	Remarks
47 CFR 15.109 RSS-Gen 4.9 & 4.10	Radiated emissions	ANSI C 63.4	PASS	-
47 CFR 15.107 RSS-Gen 7.2.4	AC power line conducted emissions	ANSI C63.4	PASS	-
Remarks:				

3 Test Conditions and Results

3.1 Test Conditions and Results – Radiated emissions


Radiated emissions acc. FCC 47 CFR 15.109 / IC RSS-Gen		Verdict: PASS				
Laboratory Parameters:	Required prior to the test	During the test				
Ambient Temperature	15 to 35 °C	21°C				
Relative Humidity	30 to 60 %	32%				
Test according referenced standards	Reference Method					
	ANSI C63.4					
Sample is tested with respect to the requirements of the equipment class	Equipment class					
	Class B					
Test frequency range determined from highest emission frequency	Highest emission frequency					
	Fmax [MHz] = 2540					
Fully configured sample scanned over the following frequency range	Frequency range					
	30 MHz to 13 GHz					
Operating mode and configuration	mode 1 / 2, configuration 1					
Limits and results Class B						
Frequency [MHz]	Quasi-Peak [dBµV/m]	Result	Average [dBµV/m]	Result	Peak [dBµV/m]	Result
30 – 88	40	PASS	-		-	-
88 – 216	43.5	PASS	-		-	-
216 – 960	46	PASS	-		-	-
960 – 1000	54	PASS	-		-	-
> 1000	-	-	54	PASS	74	PASS
Comments:						

Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 55




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 56




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 57



Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 58




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 59




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 60




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 69




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC via AC/DC Adapter
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	charging + BT link to a smartphone
Test Date:	2015-02-24
Note:	SETTE

Index 70




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 65




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 66




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 63




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 64




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 62




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 61




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 68




Spurious emissions under normal conditions according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	SETTE
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Zunke
Test Conditions:	Tnom: 23°C, Unom: 3.7 VDC (accu)
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3m
Mode:	vibrating + BT link to a smartphone
Test Date:	2015-02-24
Note:	

Index 67



3.2 Test Conditions and Results – AC power line conducted emissions

Conducted emissions acc. FCC 47 CFR 15.107 / IC RSS-Gen			Verdict: PASS	
Laboratory Parameters:	Required prior to the test	During the test		
Ambient Temperature	15 to 35 °C	21°C		
Relative Humidity	30 to 60 %	32%		
Test according referenced standards	Reference Method			
	ANSI C63.4			
Fully configured sample scanned over the following frequency range	Frequency range			
	0.15 MHz to 30 MHz			
Sample is tested with respect to the requirements of the equipment class	Equipment class			
	Class B			
Points of Application	Application Interface			
AC Mains	LISN			
Operating mode and configuration	mode 2, configuration 1			
Limits and results Class B				
Frequency [MHz]	Quasi-Peak [dB μ V]	Result	Average [dB μ V]	Result
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS
0.5 to 5	56	PASS	46	PASS
5 to 30	60	PASS	50	PASS
Comments:				
* Limit decreases linearly with the logarithm of the frequency.				

Test Procedure:


- 1) The EUT was placed on a non conductive table 0.8 m above the reference ground plane and 0.4 m away from the vertical conducting plane (ANSI C63.4: 2009 item 7.3.1)
- 2) The power cord that is normally supplied or recommended by the manufacturer was connected to the LISN.
- 3) The distance between the outer edge of the EUT and the LISN shall be set to 0.8 m. A longer power cord shall be bundled to this length (bundling shall not exceed 40 cm in length).
- 4) The LISN measurement port was connected to a measurement receiver
- 5) I/O cables were bundled not longer than 0.4 m
- 6) Measurement was performed in the frequency range 0.15 – 30MHz on each current-carrying conductor

EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	Sette
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pflug
Test Conditions:	Tnom: 24°C, Unom: 3.0VDC (accu)
LISN:	ESH2-Z5 N
Mode:	charging
Test Date:	2015-02-24
Note:	

Index 214



EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1409-4154

Manufacturer:	Amor Gummiwaren GmbH
EUT Name:	electric device
Model:	Sette
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Pflug
Test Conditions:	Tnom: 24°C, Unom: 3.0VDC (accu)
LISN:	ESH2-Z5 L
Mode:	charging
Test Date:	2015-02-24
Note:	

Index 215

