

Test of HBM T12 type S6 to 47 CFR 15.225 and RSS-210 Issue 9

ANNEX 1 TO TEST REPORT # EMCC-040197MAE, 2016-09-29

PHOTOGRAPHS OF TEST SET-UP

EQUIPMENT UNDER TEST:

Trade Name: T12
Type Designation(s): S6
Serial Number: 201130140 (Rotor); none (Stator)
Equipment Class: Low Power Transceiver
Manufacturer: Hottinger Baldwin Messtechnik GmbH
Address: Im Tiefen See 45
64293 Darmstadt
Germany
Phone: +49 6151 803-681
Fax: +49 6151 803-98790

RELEVANT STANDARD(S): 47 CFR 15.225; RSS-210 Issue 9

MEASUREMENT PROCEDURE:

RSS-Gen Issue 4 ANSI C63.10-2013 Other

CONTENTS	Page
1 Radiated and conducted Emissions test.....	2
2 Carrier frequency stability.....	3

Test of HBM T12 type S6 to 47 CFR 15.225 and RSS-210 Issue 9


1 RADIATED AND CONDUCTED EMISSIONS TEST



Radiated emissions measurement at 3 m distance
9 kHz – 30 MHz



Radiated emissions measurement at 3 m distance at open
area test site 9 kHz – 30 MHz



Radiated emissions measurement at 3 m distance,
30 MHz – 150 MHz



Conducted emissions measurement
9 kHz – 30 MHz

Test of HBM T12 type S6 to 47 CFR 15.225 and RSS-210 Issue 9

2 CARRIER FREQUENCY STABILITY



Test setup



Detailed view inside climatic chamber