

Yamaha Motor Co.,Ltd.  
2500 Shingai, Iwata-shi, Shizuoka-ken, Japan

Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

**Applicant's declaration concerning RF Radiation Exposure**

We hereby indicate that the product

Product description: X2Y Meter

Model No: X2Y

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the

Product: X2Y Meter

will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M22102-20660-C-1 and the accompanying calculations.


Company: Yamaha Motor Co.,Ltd.

Address: 2500 Shingai, Iwata-shi, Shizuoka-ken, Japan

Date: 2021/02/08

Signature

A handwritten signature in black ink, appearing to read "H. Arai".



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22102-20660-C-1

FCC ID: 2ADBKX2Y

## **3.2 Equivalent Isotropic Radiated Power (EIRP)**

FCC Rule: 15.247(b)(3)

BLE

EIRP = max. conducted output power + antenna gain

EIRP = 4.36 dBm + (-5.43 dBi [antenna gain claimed by manufacturer]) = -1.07 dBm = 0.7816 mW

ANT+

EIRP = max. conducted output power + antenna gain

EIRP = -2.20 dBm + (-5.43 dBi [antenna gain claimed by manufacturer]) = -7.63 dBm = 0.1726 mW

## **3.3 Exemption Limits for Routine Evaluation according to FCC KDB Publication**

**RESULT:**

Test standard : FCC KDB Publication  
447498 D01 General RF Exposure Guidance v06

According to 447498 D01 General RF Exposure Guidance v06:

SAR evaluation, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### **3.3.1 Exemption Limits for Routine Evaluation – SAR Evaluation**

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table .

Table: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance

MHz	5	10	15	20	25	mm
2402	10.09	19.26	29.35	38.52	48.52	SAR Test Exclusion Threshold (mW)
2457	9.99	18.98	28.97	37.96	47.95	SAR Test Exclusion Threshold (mW)

MHz	30	35	40	45	50	mm
2402	57.70	67.79	77.87	87.05	97.13	SAR Test Exclusion Threshold (mW)
2457	56.94	66.93	76.91	85.91	95.90	SAR Test Exclusion Threshold (mW)

Output power level shall be the higher of the maximum conducted or equivalent isotropically radiated power (e.i.r.p.) source-based, time-averaged output power.



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22102-20660-C-1

FCC ID: 2ADBKX2Y

BLE

Established separation distance is 5 mm.

Operating frequency band : 2402-2480 MHz

Max. output power level at 5 mm separation distance at 2402 MHz according to table is: 10.09 mW

The product is exempt from SAR Evaluation/Testing because the output power of 0.7816 mW is below the exemption limit of 10.09 mW.

ANT+

Established separation distance is 5 mm.

Operating frequency band : 2457 MHz

Max. output power level at 5 mm separation distance at 2457 MHz according to table is: 9.99 mW

The product is exempt from SAR Evaluation/Testing because the output power of 0.1726 mW is below the exemption limit of 9.99 mW.