

TEST REPORT

**ACCORDING TO: FCC 47CFR part 15 subpart C § 15.247(DTS) and subpart B;
RSS-247 issue 1, RSS-Gen issue 4 section 7**

FOR:

**Pixie Technology Ltd.
PixiePoint Tag
Model: P1000
FCC ID:2ADBO-P1000**

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested. This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.



Table of contents

1	Applicant information.....	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details	3
5	Tests summary.....	4
6	EUT description.....	5
6.1	General information.....	5
6.2	Test configuration.....	5
6.3	Changes made in EUT	5
6.4	Transmitter characteristics	6
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements.....	7
7.1	Minimum 6 dB bandwidth	7
7.2	Peak output power	11
7.3	Field strength of spurious emissions	17
7.4	Band edge radiated emissions	35
7.5	Peak spectral power density	39
7.6	Antenna requirements	44
8	Unintentional emissions	45
8.1	Radiated emission measurements	45
9	APPENDIX A Test equipment and ancillaries used for tests.....	53
10	APPENDIX B Measurement uncertainties.....	54
11	APPENDIX C Test laboratory description	55
12	APPENDIX D Specification references	55
13	APPENDIX E Test equipment correction factors.....	56
14	APPENDIX F Abbreviations and acronyms.....	63



1 Applicant information

Client name: Pixie Technology Ltd.
Address: 8 Hamada street, Bld. B, 3rd floor, Herzliya 46733, Israel
Telephone: +972 77 921 5815
Fax: +972 77 921 5833
E-mail: tsachs@getpixie.com
Contact name: Mr. Tsach Shwartz

2 Equipment under test attributes

Product name: PixiePoint tag
Product type: Transceiver
Model(s): P1000
Hardware version: Rev D
Software release: 001
Receipt date 17-May-15

3 Manufacturer information

Manufacturer name: Pixie Technology Ltd.
Address: 8 Hamada street, Bld. B, 3rd floor, Herzliya 46733, Israel
Telephone: +972 77 921 5815
Fax: +972 77 921 5833
E-Mail: tsachs@getpixie.com
Contact name: Mr. Tsach Shwartz

4 Test details

Project ID: 26451
Location: Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel
Test started: 17-May-15
Test completed: 28-May-15
Test specification(s): FCC Part 15 subpart C §15.247 (DTS), subpart B §15.109;
RSS-247 issue 1, RSS-Gen issue 4 section 7, ICES-003 issue 5:2012



5 Tests summary

Test	Status
Transmitter characteristics	
FCC Section 15.247(a)2 / RSS-247 section 5.2(1), 6 dB bandwidth	Pass
FCC Section 15.247(b)3/ RSS-247 section 5.4(4), Peak output power	Pass
FCC section 15.247(i) / RSS-102 section 2.5.1, RF exposure	Pass, the exhibit to the application of certification is provided
FCC Section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions	Pass
FCC Section 15.247(d)/ RSS-247 section 5.5, Emissions at band edges	Pass
FCC Section 15.247(e) / RSS-247 section 5.2(2), Peak power density	Pass
FCC section 15.203 / RSS-Gen section 8.3, Antenna requirement	Pass
FCC section 15.207(a) / RSS-Gen section 8.8, Conducted emission	Not required
Unintentional emissions	
FCC section 15.107/ RSS-Gen section 8.8, Conducted emission at AC power port	Not required
FCC section 15.109, RSS-Gen section 7, Radiated emission	Pass

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.

The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

	Name and Title	Date	Signature
Tested by:	Mr. V. Einem, test engineer	June 25, 2015	
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	July 7, 2015	
Approved by:	Mr. M. Nikishin, EMC and Radio group manager	August 23, 2015	




6 EUT description

6.1 General information

The EUT, PixiePoint tag, is a very low power wireless device utilizing 2 wireless technologies: BLE (Bluetooth) to communicate with smartphones and UWB to measure distance between the tags. The tag is working in very low duty cycle. Most of the time the tag is advertising (sends BLE standard "existing" message). Advertise is done every 2 sec for 3 msec. The UWB radio is set to deep sleep. Once the smartphone responses the tag can communicate with the smartphone and via smartphone can communicate with other similar tags and measure Tag to Tag range using the UWB radio. The UWB radio is active for minimal time that is needed for range measurement – about 2 -3 msec. After the measurement sequence, the UWB is set to deep sleep again. The BLE (Bluetooth) and UWB radio do not work at the same time. There is one built-in antenna for UWB and BLE.

6.2 Test configuration



6.3 Changes made in EUT

No changes were performed in the EUT during testing.



6.4 Transmitter characteristics

Type of equipment							
V	Stand-alone (Equipment with or without its own control provisions)						
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)						
	Plug-in card (Equipment intended for a variety of host systems)						
Assigned frequency range		2400 -2483.5 MHz					
Operating frequencies		2402-2480 MHz					
Maximum rated output power		Peak output power 4.12 dBm					
Is transmitter output power variable?		V	No	continuous variable			
				stepped variable with stepsize			
		Yes		minimum RF power	dBm		
				maximum RF power	dBm		
Antenna connection							
unique coupling	standard connector		V	Integral	with temporary RF connector		
			V		without temporary RF connector		
Antenna/s technical characteristics							
Type	Manufacturer		Model number		Gain		
Printed Omni	Pixie		P1000		0 dBi		
Transmitter aggregate data rate/s		1 Mbps					
Type of modulation		GFSK					
Modulating test signal (baseband)		PRBS					
Transmitter power source							
V	Battery	Nominal rated voltage	3.0 V	Battery type	Lithium Manganese Dioxide		
	DC	Nominal rated voltage					
	AC mains	Nominal rated voltage		Frequency	Hz		



HERMON LABORATORIES

Test specification:	FCC section 15.247(a)(2) / RSS-247 section 5.2(1), 6 dB bandwidth		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22 °C	Air Pressure: 1005 hPa	Relative Humidity: 46 %	Power Supply: Battery
Remarks:			

7 Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements

7.1 Minimum 6 dB bandwidth

7.1.1 General

This test was performed to measure 6 dB bandwidth of the EUT carrier frequency. Specification test limit is given in Table 7.1.1.

Table 7.1.1 The 6 dB bandwidth limits

Assigned frequency, MHz	Modulation envelope reference points*, dBc	Minimum bandwidth, kHz
2400.0 – 2483.5	6.0	500.0

* - Modulation envelope reference points provided in terms of attenuation below the peak of modulated carrier.

7.1.2 Test procedure

7.1.2.1 The EUT was set up as shown in Figure 7.1.1, energized and its proper operation was checked.

7.1.2.2 The EUT was set to transmit modulated carrier.

7.1.2.3 The transmitter minimum 6 dB bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.1.2 and the associated plots.

Figure 7.1.1 The 6 dB bandwidth test setup





HERMON LABORATORIES

Test specification:	FCC section 15.247(a)(2) / RSS-247 section 5.2(1), 6 dB bandwidth		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	28-May-15		
Temperature: 22 °C	Air Pressure: 1005 hPa	Relative Humidity: 46 %	Power Supply: Battery
Remarks:			

Table 7.1.2 The 6 dB bandwidth test results

ASSIGNED FREQUENCY BAND: 2400-2483.5 MHz
 DETECTOR USED: Peak
 SWEEP MODE: Max Hold
 SWEEP TIME: Auto
 RESOLUTION BANDWIDTH: 100 kHz
 VIDEO BANDWIDTH: 300 kHz
 MODULATION ENVELOPE REFERENCE POINTS: 6.0 dBc
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps

Carrier frequency, MHz	6 dB bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
Low frequency 2402	686.2	500	-186.2	Pass
Mid frequency 2440	684.3	500	-184.3	Pass
High frequency 2480	665.2	500	-165.2	Pass

Carrier frequency, MHz	99% bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
Low frequency 2402	1065.2	500	-565.2	Pass
Mid frequency 2440	1064.5	500	-564.5	Pass
High frequency 2480	1081.1	500	-581.1	Pass

- Margin, kHz = Occupied bandwidth, kHz - Limit, kHz

Reference numbers of test equipment used


HL 1984	HL 4353	HL 4575	HL 4722				
---------	---------	---------	---------	--	--	--	--

Full description is given in Appendix A.



HERMON LABORATORIES

Test specification:	FCC section 15.247(a)(2) / RSS-247 section 5.2(1), 6 dB bandwidth		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22 °C	Air Pressure: 1005 hPa	Relative Humidity: 46 %	Power Supply: Battery
Remarks:			


Plot 7.1.1 The 6 dB bandwidth test result at low frequency**Plot 7.1.2 The 6 dB bandwidth test result at mid frequency**



HERMON LABORATORIES

Test specification:	FCC section 15.247(a)(2) / RSS-247 section 5.2(1), 6 dB bandwidth		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22 °C	Air Pressure: 1005 hPa	Relative Humidity: 46 %	Power Supply: Battery
Remarks:			

Plot 7.1.3 The 6 dB bandwidth test result at high frequency





HERMON LABORATORIES

Test specification:	FCC section 15.247(b)3 / RSS-247 section 5.4(4) ,Peak output power		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

7.2 Peak output power

7.2.1 General

This test was performed to measure the maximum peak output power radiated by transmitter. Specification test limits are given in Table 7.2.1.

Table 7.2.1 Peak output power limits

Assigned frequency range, MHz	Maximum antenna gain, dBi	Peak output power*		Equivalent field strength limit @ 3m, dB(µV/m)**
		W	dBm	
2400.0 – 2483.5	6.0	1.0	30.0	131.2

*- The limit is provided in terms of conducted RF power at the antenna connector. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value as follows:

by 1 dB for every 3 dB that the directional gain of antenna exceeds 6 dBi for fixed point-to-point transmitters operate in 2400-2483.5 MHz band;

without any corresponding reduction for fixed point-to-point transmitters operate in 5725-5850 MHz band;

by the amount in dB that the directional gain of antenna exceeds 6 dBi for the rest of transmitters.

**- Equivalent field strength limit was calculated from the peak output power as follows: $E = \sqrt{30 \times P \times G} / r$, where P is peak output power in Watts, r is antenna to EUT distance in meters and G is transmitter antenna gain in dBi.

7.2.2 Test procedure

7.2.2.1 The EUT was set up as shown in Figure 7.2.1, energized and its proper operation was checked.

7.2.2.2 The EUT was adjusted to produce maximum available to end user RF output power.

7.2.2.3 The resolution bandwidth of spectrum analyzer was set wider than 6 dB bandwidth of the EUT and the field strength of the EUT carrier frequency was measured with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.

7.2.2.4 The maximum field strength of the EUT carrier frequency was measured as provided in Table 7.2.2 and associated plots.

7.2.2.5 The maximum peak output power was calculated from the field strength of carrier as follows:

$$P = (E \times d)^2 / (30 \times G),$$

where P is the peak output power in W, E is the field strength in V/m, d is the test distance and G is the transmitter numeric antenna gain over an isotropic radiator.

The above equation was converted in logarithmic units for 3 m test distance:

$$\text{Peak output power in dBm} = \text{Field strength in dB}(\mu\text{V}/\text{m}) - \text{Transmitter antenna gain in dBi} - 95.2 \text{ dB}$$


7.2.2.6 The worst test results (the lowest margins) were recorded in Table 7.2.2.



HERMON LABORATORIES

Test specification:	FCC section 15.247(b)3 / RSS-247 section 5.4(4) ,Peak output power		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Figure 7.2.1 Setup for carrier field strength measurements





HERMON LABORATORIES

Test specification:	FCC section 15.247(b)3 / RSS-247 section 5.4(4) ,Peak output power		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.2.2 Peak output power test results

ASSIGNED FREQUENCY:	2400-2483.5 MHz
TEST DISTANCE:	3 m
TEST SITE:	Semi anechoic chamber
EUT HEIGHT:	0.8 m
DETECTOR USED:	Peak
TEST ANTENNA TYPE:	Biconilog (30 MHz – 1000 MHz) Double ridged guide (above 1000 MHz)
MODULATION:	GFSK
MODULATING SIGNAL:	PRBS
BIT RATE:	1 Mbps
DETECTOR USED:	Peak
EUT 6 dB BANDWIDTH:	1.081 MHz
RESOLUTION BANDWIDTH:	1 MHz
VIDEO BANDWIDTH:	3 MHz

Frequency, MHz	Field strength, dB(µV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	EUT antenna gain, dBi	Peak output power, dBm**	Limit, dBm	Margin, dB***	Verdict
2402.2105	99.317	Horizontal	1.5	350	0	4.12	30.00	-25.88	Pass
2440.2900	98.275	Horizontal	1.9	4	0	3.08	30.00	-26.93	Pass
2480.2420	99.315	Horizontal	1.8	46	0	4.11	30.00	-25.89	Pass

*- EUT front panel refer to 0 degrees position of turntable.

**- Peak output power was calculated from the field strength of carrier as follows: $P = (E \times d)^2 / (30 \times G)$, where P is the peak output power in W, E is the field strength in V/m, d is the test distance in meters and G is the transmitter numeric antenna gain over an isotropic radiator. The above equation was converted in logarithmic units for 3 m test distance: *Peak output power in dBm = Field strength in dB(µV/m) - Transmitter antenna gain in dBi - 95.2 dB*

***- Margin = Peak output power – specification limit.

Reference numbers of test equipment used

HL 1984	HL 4353	HL 4575	HL 4722				
---------	---------	---------	---------	--	--	--	--

Full description is given in Appendix A.



HERMON LABORATORIES

Test specification:	FCC section 15.247(b)3 / RSS-247 section 5.4(4) ,Peak output power		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.2.1 Field strength of carrier at low frequency

TEST SITE:

Semi anechoic chamber

TEST DISTANCE:


3 m

ANTENNA POLARIZATION:


Horizontal

Vertical


EUT POSITION:




X-axis



EUT POSITION:



Y-axis





HERMON LABORATORIES

Test specification:	FCC section 15.247(b)3 / RSS-247 section 5.4(4) ,Peak output power		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.2.1 Field strength of carrier at low frequency (continued)

TEST SITE:

Semi anechoic chamber

TEST DISTANCE:


3 m

ANTENNA POLARIZATION:


Horizontal

Vertical

EUT POSITION:



Z-axis






HERMON LABORATORIES

Test specification:	FCC section 15.247(b)3 / RSS-247 section 5.4(4) ,Peak output power		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.2.2 Field strength of carrier at mid frequency


TEST SITE:
TEST DISTANCE:
EUT POSITION:
ANTENNA POLARIZATION:
Vertical




Semi anechoic chamber
3 m
X,Y,Z-axes

Horizontal**Plot 7.2.3 Field strength of carrier at high frequency**

TEST SITE:
TEST DISTANCE:
EUT POSITION:
ANTENNA POLARIZATION:
Vertical



Semi anechoic chamber
3 m
X,Y,Z-axes

Horizontal



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

7.3 Field strength of spurious emissions

7.3.1 General

This test was performed to measure field strength of spurious emissions from the EUT. Specification test limits are given in Table 7.3.1.

Table 7.3.1 Radiated spurious emissions limits

Frequency, MHz	Field strength at 3 m within restricted bands, dB(µV/m)*			Attenuation of field strength of spurious versus carrier outside restricted bands, dBc***	
	Peak	Quasi Peak	Average		
0.009 – 0.090	148.5 – 128.5	NA	128.5 – 108.5**	20.0	
0.090 – 0.110	NA	108.5 – 106.8**	NA		
0.110 – 0.490	126.8 – 113.8	NA	106.8 – 93.8**		
0.490 – 1.705	NA	73.8 – 63.0**	NA		
1.705 – 30.0*		69.5			
30 – 88		40.0			
88 – 216		43.5			
216 – 960		46.0			
960 - 1000		54.0			
1000 – 10 th harmonic	74.0	NA	54.0		

*- The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows:

$$\text{Lim}_{S_2} = \text{Lim}_{S_1} + 40 \log (S_1/S_2)$$

where S_1 and S_2 – standard defined and test distance respectively in meters.

**- The limit decreases linearly with the logarithm of frequency.

*** - The field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.

7.3.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized and the performance check was conducted.

7.3.2.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna was rotated around its vertical axis.

7.3.2.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.

7.3.3 Test procedure for spurious emission field strength measurements above 30 MHz

7.3.3.1 The EUT was set up as shown in Figure 7.3.2, energized and the performance check was conducted.

7.3.3.2 The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.

7.3.3.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Figure 7.3.1 Setup for spurious emission field strength measurements below 30 MHz





Figure 7.3.2 Setup for spurious emission field strength measurements above 30 MHz





HERMON LABORATORIES

Report ID: PIXRAD_FCC.26451_BLE.docx

Date of Issue: 23-Aug-15

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.3.2 Field strength of emissions outside restricted bands

ASSIGNED FREQUENCY:	2400-2483.5 MHz
INVESTIGATED FREQUENCY RANGE:	0.009 – 25000 MHz
TEST DISTANCE:	3 m
MODULATION:	GFSK
MODULATING SIGNAL:	PRBS
BIT RATE:	1 Mbps
DUTY CYCLE:	99.3 %
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	100 kHz
VIDEO BANDWIDTH:	300 kHz
TEST ANTENNA TYPE:	Active loop (9 kHz – 30 MHz) Biconilog (30 MHz – 1000 MHz) Double ridged guide (above 1000 MHz)

Frequency, MHz	Field strength of spurious, dB(µV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	Field strength of carrier, dB(µV/m)	Attenuation below carrier, dBc	Limit, dBc	Margin, dB**	Verdict
No emissions were found									

*- EUT front panel refers to 0 degrees position of turntable.

**- Margin = Attenuation below carrier – specification limit.



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.3.3 Field strength of spurious emissions above 1 GHz within restricted bands

ASSIGNED FREQUENCY: 2400-2483.5 MHz
 INVESTIGATED FREQUENCY RANGE: 1000 – 25000 MHz
 TEST DISTANCE: 3 m
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 DUTY CYCLE: 99.3 %
 DETECTOR USED: Peak
 RESOLUTION BANDWIDTH: 1000 kHz
 TEST ANTENNA TYPE: Double ridged guide

Frequency, MHz	Antenna		Azimuth, degrees*	Peak field strength(VBW=3 MHz)			Average field strength(VBW=10 Hz)			Verdict	
	Polarization	Height, m		Measured, dB(µV/m)	Limit, dB(µV/m)	Margin, dB**	Measured, dB(µV/m)	Calculated, dB(µV/m)	Limit, dB(µV/m)		
Low carrier frequency	No emissions were found									Pass	
Mid carrier frequency	No emissions were found									Pass	
High carrier frequency	No emissions were found									Pass	

*- EUT front panel refers to 0 degrees position of turntable.

**- Margin = Measured field strength - specification limit.

***- Margin = Calculated field strength - specification limit,

where Calculated field strength = Measured field strength + average factor.

Table 7.3.4 Average factor calculation

Transmission pulse		Transmission burst		Transmission train duration, ms	Average factor, dB
Duration, ms	Period, ms	Duration, ms	Period, ms		
		NA			

*- Average factor was calculated as follows

$$\text{for pulse train shorter than 100 ms: } \text{Average factor} = 20 \times \log_{10} \left(\frac{\text{Pulse duration}}{\text{Pulse period}} \times \frac{\text{Burst duration}}{\text{Train duration}} \times \text{Number of bursts within pulse train} \right)$$

$$\text{for pulse train longer than 100 ms: } \text{Average factor} = 20 \times \log_{10} \left(\frac{\text{Pulse duration}}{\text{Pulse period}} \times \frac{\text{Burst duration}}{100 \text{ ms}} \times \text{Number of bursts within 100 ms} \right)$$



HERMON LABORATORIES

Report ID: PIXRAD_FCC.26451_BLE.docx

Date of Issue: 23-Aug-15

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.3.5 Field strength of spurious emissions below 1 GHz within restricted bands

ASSIGNED FREQUENCY:	2400-2483.5 MHz
INVESTIGATED FREQUENCY RANGE:	0.009 – 1000 MHz
TEST DISTANCE:	3 m
MODULATION:	GFSK
MODULATING SIGNAL:	PRBS
BIT RATE:	1 Mbps
DUTY CYCLE:	99.3 %
RESOLUTION BANDWIDTH:	1.0 kHz (9 kHz – 150 kHz) 9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz) > Resolution bandwidth
VIDEO BANDWIDTH:	
TEST ANTENNA TYPE:	Active loop (9 kHz – 30 MHz) Biconical (30 MHz – 200 MHz) Log periodic (200 MHz – 1000 MHz) Biconilog (30 MHz – 1000 MHz)

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict			
Low carrier frequency											
No emissions were found											
Mid carrier frequency											
No emissions were found											
High carrier frequency											
No emissions were found											

*- Margin = Measured emission - specification limit.

**- EUT front panel refer to 0 degrees position of turntable.

Reference numbers of test equipment used

HL 0446	HL 0604	HL 0768	HL 1984	HL 2780	HL 3818	HL 3901	HL 4114
HL 4224	HL 4353	HL 4575	HL 4722	HL 4932			

Full description is given in Appendix A.



HERMON LABORATORIES

Report ID: PIXRAD_FCC.26451_BLE.docx

Date of Issue: 23-Aug-15

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.3.6 Restricted bands according to FCC section 15.205

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	Above 38.6

Table 7.3.7 Restricted bands according to RSS-Gen

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.291 - 8.294	16.80425 - 16.80475	399.9 - 410	3260 - 3267	10.6 - 12.7
2.1735 - 2.1905	8.362 - 8.366	25.5 - 25.67	608 - 614	3332 - 3339	13.25 - 13.4
3.020 - 3.026	8.37625 - 8.38675	37.5 - 38.25	960 - 1427	3345.8 - 3358	14.47 - 14.5
4.125 - 4.128	8.41425 - 8.41475	73 - 74.6	1435 - 1626.5	3500 - 4400	15.35 - 16.2
4.17725 - 4.17775	12.29 - 12.293	74.8 - 75.2	1645.5 - 1646.5	4500 - 5150	17.7 - 21.4
4.20725 - 4.20775	12.51975 - 12.52025	108 - 138	1660 - 1710	5350 - 5460	22.01 - 23.12
5.677 - 5.683	12.57675 - 12.57725	156.52475 - 156.52525	1718.8 - 1722.2	7250 - 7750	23.6 - 24
6.215 - 6.218	13.36 - 13.41	156.7 - 156.9	2200 - 2300	8025 - 8500	31.2 - 31.8
6.26775 - 6.26825	16.42 - 16.423	240 - 285	2310 - 2390	9000 - 9200	36.43 - 36.5
6.31175 - 6.31225	16.69475 - 16.69525	322 - 335.4	2655 - 2900	9300 - 9500	Above 38.6




HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.3.1 Radiated emission measurements at the low carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.2 Radiated emission measurements at the mid carrier frequency

TEST SITE: Semi anechoic chamber
TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical and Horizontal






HERMON LABORATORIES


Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.3 Radiated emission measurements at the high carrier frequency

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal

**Plot 7.3.4 Radiated emission measurements from 9 to 150 kHz at the low carrier frequency**

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 CARRIER FREQUENCY: Low, Mid, High





HERMON LABORATORIES


Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.5 Radiated emission measurements from 0.15 to 30 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical
 CARRIER FREQUENCY: Low, Mid, High




ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 160 kHz
 58.14 dB μ V/m

**Plot 7.3.6 Radiated emission measurements from 30 to 1000 MHz at the low carrier frequency**

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal
 Carrier Frequency: Low, Mid, High



ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 1.0000 GHz
 27.92 dB μ V/m






HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.7 Radiated emission measurements from 1000 to 4000 MHz at the low carrier frequency

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal









HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.8 Radiated emission measurements from 1000 to 4000 MHz at the mid carrier frequency

TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal









HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.9 Radiated emission measurements from 1000 to 4000 MHz at the high carrier frequency



TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal





HERMON LABORATORIES



Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.10 Radiated emission measurements from 4000 to 10000 MHz at the low carrier frequency**Plot 7.3.11 Radiated emission measurements from 4000 to 10000 MHz at the mid carrier frequency**



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			


Plot 7.3.12 Radiated emission measurements from 4000 to 10000 MHz at the high carrier frequency**Plot 7.3.13 Radiated emission measurements from 10000 to 18000 MHz at the low carrier frequency**

10.5 GHz – is ambient signal.




HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.14 Radiated emission measurements from 10000 to 18000 MHz at the mid carrier frequency

10.5 GHz – is ambient signal.


Plot 7.3.15 Radiated emission measurements from 10000 to 18000 MHz at the high carrier frequency

10.5G Hz – is ambient signal.




HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.16 Radiated emission measurements from 18000 to 25000 MHz at the low carrier frequency

21.9 GHz, 22 GHz, 23.01 GHz, 23.07 GHz – are ambient signals.

Plot 7.3.17 Radiated emission measurements from 18000 to 25000 MHz at the mid carrier frequency


21.9 GHz, 22 GHz, 23.01 GHz, 23.07 GHz – are ambient signals.



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.18 Radiated emission measurements from 18000 to 25000 MHz at the high carrier frequency




21.9 GHz, 22 GHz, 23.01 GHz, 23.07 GHz – are ambient signals.



HERMON LABORATORIES


Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1008 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.3.19 Transmission pulse duration



Duty cycle = 99.3%

Plot 7.3.20 Transmission pulse period





HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Band edge emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

7.4 Band edge radiated emissions

7.4.1 General

This test was performed to measure emissions, radiated from the EUT at the assigned frequency band edges. Specification test limits are given in Table 7.4.1.

Table 7.4.1 Band edge emission limits

Output power	Assigned frequency, MHz	Attenuation below carrier*, dBc	Field strength at 3 m within restricted bands, dB(µV/m)	
			Peak	Average
Peak	2400.0 – 2483.5	20.0	74.0	54.0
Averaged over a time interval	2400.0 – 2483.5	30.0	74.0	54.0

* - Band edge emission limit is provided in terms of attenuation below the peak of modulated carrier measured with the same resolution bandwidth.

7.4.2 Test procedure


- 7.4.2.1 The EUT was set up as shown in energized normally modulated at the maximum data rate and its proper operation was checked.
- 7.4.2.2 The EUT was adjusted to produce maximum available to end user RF output power at the lowest carrier frequency.
- 7.4.2.3 The spectrum analyzer span was set to capture the carrier frequency and associated modulation products. The resolution bandwidth was set wider than 1 % of the frequency span.
- 7.4.2.4 The spectrum analyzer was set in max hold mode and allowed trace to stabilize. The highest emission level within the authorized band was measured.
- 7.4.2.5 The maximum band edge emission and modulation product outside of the band were measured as provided in Table 7.4.2 and associated plots and referenced to the highest emission level measured within the authorized band.
- 7.4.2.6 The above procedure was repeated with the EUT adjusted to produce maximum RF output power at the highest carrier frequency.
- 7.4.2.7 The above procedure was repeated with the frequency hopping function enabled.



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Band edge emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Figure 7.4.1 Band edge emission test setup





HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Band edge emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict: PASS	
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.4.2 Band edge emission test results

ASSIGNED FREQUENCY RANGE: 2400-2483.5MHz
 DETECTOR USED: Peak
 MODULATION: GFSK
 MODULATING SIGNAL: PRBS
 BIT RATE: 1 Mbps
 TRANSMITTER OUTPUT POWER: dBm at low carrier frequency
 dBm at high carrier frequency
 RESOLUTION BANDWIDTH: $\geq 1\%$ of the span
 VIDEO BANDWIDTH: \geq RBW

Frequency, MHz	Band edge emission, dBuV/m	Emission at carrier, dBuV/m	Attenuation below carrier, dBc	Limit, dBc	Margin, dB*	Verdict
2402	54.974	95.905	40.931	20.0	-20.931	Pass

*- Margin = Attenuation below carrier – specification limit.

Frequency, MHz	Peak field strength(VBW=3 MHz)			Average field strength(VBW=10 Hz)				Verdict
	Measured, dB(μ V/m)	Limit, dB(μ V/m)	Margin, dB*	Measured, dB(μ V/m)	Calculated, dB(μ V/m)	Limit, dB(μ V/m)	Margin, dB*	
2480	61.505	74.0	-12.50	49.424	49.424	54.0	-4.58	Pass

*- Margin = Measured emission – specification limit.

Reference numbers of test equipment used



HL 1984	HL 2780	HL 3818	HL 3901	HL 4114	HL 4224	HL 4353	HL 4575
HL 4722	HL 4932						

Full description is given in Appendix A.



HERMON LABORATORIES

Test specification:	FCC section 15.247(d) / RSS-247 section 5.5, Band edge emissions		
Test procedure:	558074 D01 DTS Meas Guidance v03r01		
Test mode:	Compliance	Verdict:	PASS
Date(s):	17-May-15 - 27-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.4.1 The highest emission level within the assigned band at low carrier frequency**Plot 7.4.2 The highest emission level within the assigned band at high carrier frequency**



HERMON LABORATORIES

Test specification:	FCC section 15.247(e) / RSS-247 section 5.2(2), Peak power density		
Test procedure:	558074 D01 DTS Meas Guidance v03r01, Method 10.2		
Test mode:	Compliance	Verdict: PASS	
Date(s):	26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

7.5 Peak spectral power density

7.5.1 General

This test was performed to measure the peak spectral power density radiated by the transmitter RF antenna. Specification test limits are given in Table 7.5.1.

Table 7.5.1 Peak spectral power density limits

Assigned frequency range, MHz	Measurement bandwidth, kHz	Peak spectral power density, dBm	Equivalent field strength limit @ 3m, dB(μV/m)*
2400.0 – 2483.5	3.0	8.0	103.2

* - Equivalent field strength limit was calculated from the peak spectral power density as follows: $E = \sqrt{30 \times P} / r$, where P is peak spectral power density and r is antenna to EUT distance in meters.

7.5.2 Test procedure for field strength measurements

- 7.5.2.1 The EUT was set up as shown in Figure 7.5.1, energized and its proper operation was checked.
- 7.5.2.2 The EUT was adjusted to produce maximum available to end user RF output power.
- 7.5.2.3 The field strength of the EUT carrier frequency was measured with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360° and the measuring antenna height was swept in both vertical and horizontal polarizations.
- 7.5.2.4 The maximum power spectral density was measured using a peak detector with resolution bandwidth set to 100 kHz, $VBW \geq 300$ kHz, sweep time = auto couple, trace mode=max hold.
- 7.5.2.5 The maximum power level was determined in any 100 kHz band within the fundamental EBW. The measured value did not exceed the limit.
- 7.5.2.6 The test results provided in Table 7.5.2 and the associated plots.




HERMON LABORATORIES

Report ID: PIXRAD_FCC.26451_BLE.docx

Date of Issue: 23-Aug-15

Test specification:	FCC section 15.247(e) / RSS-247 section 5.2(2), Peak power density		
Test procedure:	558074 D01 DTS Meas Guidance v03r01, Method 10.2		
Test mode:	Compliance	Verdict:	PASS
Date(s):	26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Figure 7.5.1 Setup for carrier field strength measurements





HERMON LABORATORIES

Test specification:	FCC section 15.247(e) / RSS-247 section 5.2(2), Peak power density		
Test procedure:	558074 D01 DTS Meas Guidance v03r01, Method 10.2		
Test mode:	Compliance	Verdict: PASS	
Date(s):	26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Table 7.5.2 Field strength measurement of peak spectral power density

ASSIGNED FREQUENCY:	2440-2483.5 MHz
TEST DISTANCE:	3 m
TEST SITE:	Semi anechoic chamber
EUT HEIGHT:	0.8 m
DETECTOR USED:	Peak
RESOLUTION BANDWIDTH:	100 kHz
VIDEO BANDWIDTH:	300 kHz
TEST ANTENNA TYPE:	Double ridged guide (above 1000 MHz)
MODULATION:	GFSK
MODULATING SIGNAL:	PRBS
BIT RATE:	1 Mbps

Frequency, MHz	Field strength, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*	Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
2401.9982	95.909	103.2	-7.291	Horizontal	1.5	350	Pass
2439.9262	97.131	103.2	-6.069	Horizontal	1.9	4	Pass
2479.9797	98.186	103.2	-5.014	Horizontal	1.8	46	Pass

*- Margin = Field strength - EUT antenna gain - calculated field strength limit.

**- EUT front panel refer to 0 degrees position of turntable.

Reference numbers of test equipment used

HL 1984	HL 4353	HL 4575	HL 4722				
---------	---------	---------	---------	--	--	--	--


Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:	FCC section 15.247(e) / RSS-247 section 5.2(2), Peak power density		
Test procedure:	558074 D01 DTS Meas Guidance v03r01, Method 10.2		
Test mode:	Compliance	Verdict:	PASS
Date(s):	26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.5.1 Peak spectral power density at low frequency zoomed at the peak



Plot 7.5.2 Peak spectral power density at mid frequency zoomed at the peak






HERMON LABORATORIES

Test specification:	FCC section 15.247(e) / RSS-247 section 5.2(2), Peak power density		
Test procedure:	558074 D01 DTS Meas Guidance v03r01, Method 10.2		
Test mode:	Compliance	Verdict:	PASS
Date(s):	26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

Plot 7.5.3 Peak spectral power density at high frequency zoomed at the peak





HERMON LABORATORIES

Test specification:	Section 15.203 / RSS-Gen section 7.1.4, Antenna requirements		
Test procedure:	Visual inspection		
Test mode:	Compliance	Verdict:	PASS
Date(s):	26-May-15		
Temperature: 22 °C	Air Pressure: 1014 hPa	Relative Humidity: 44 %	Power Supply: Battery
Remarks:			

7.6 Antenna requirements


The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters.

The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.6.1.

Table 7.6.1 Antenna requirements

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	Comply
The transmitter employs a unique antenna connector	NA	
The transmitter requires professional installation	NA	

Photograph 7.6.1 Antenna assembly





HERMON LABORATORIES

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict: PASS	
Date(s):	28-May-15	Temperature: 22.3 °C	Air Pressure: 1019 hPa
Remarks:		Relative Humidity: 43 %	Power Supply: Battery

8 Unintentional emissions

8.1 Radiated emission measurements

8.1.1 General

This test was performed to measure radiated emissions from the EUT enclosure. Specification test limits are given in Table 8.1.1, Table 8.1.2.

Table 8.1.1 Radiated emission test limits according to FCC Part 15 Section 15.109 and ICES-003, Section 6.2

Frequency, MHz	Class B limit, dB(µV/m)		Class A limit, dB(µV/m)	
	10 m distance	3 m distance	10 m distance	3 m distance
30 - 88	29.5*	40.0	39.0	49.5*
88 - 216	33.0*	43.5	43.5	54.0*
216 - 960	35.5*	46.0	46.4	56.9*
Above 960	43.5*	54.0	49.5	60.0*

* The limit for test distance other than specified was calculated using the inverse linear distance extrapolation factor as follows: $Lim_{S_2} = Lim_{S_1} + 20 \log (S_1/S_2)$, where S_1 and S_2 – standard defined and test distance respectively in meters.

Table 8.1.2 Radiated emission limits according to RSS-Gen, Section 7.1.2

Frequency, MHz	Field strength limit at 3 m test distance, dB(µV/m)
30 - 88	40.0
88 - 216	43.5
216 - 960	46.0
960 - 3 rd harmonic**	54.0

** - harmonic of the highest frequency the EUT generates, uses, operates or tunes to.

8.1.2 Test procedure


- 8.1.2.1 The EUT was set up as shown in Figure 8.1.1, Figure 8.1.2 and the associated photographs, energized and the EUT performance was checked.
- 8.1.2.1 The measurements were performed in the anechoic chamber and at the open area test site at 3 m test distance. The specified frequency range was investigated with the antenna connected to the EMI receiver. To find the highest emission the turntable was rotated 360° and the measuring antenna height was swept from 1 to 4 m in both, vertical and horizontal polarizations. The EUT cables position was varied to maximize emission.
- 8.1.2.2 The worst test results with respect to the limits were recorded in Table 8.1.3 and shown in the associated plots.



HERMON LABORATORIES

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22.3 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Figure 8.1.1 Setup for radiated emission measurements in anechoic chamber, table-top equipment





HERMON LABORATORIES

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22.3 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Photograph 8.1.1 Setup for radiated emission measurements in the anechoic chamber



Photograph 8.1.2 Setup for radiated emission measurements in the anechoic chamber






HERMON LABORATORIES

Report ID: PIXRAD_FCC.26451_BLE.docx

Date of Issue: 23-Aug-15

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22.3 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Figure 8.1.2 Setup for radiated emission measurements at OATS, table-top EUT





HERMON LABORATORIES

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22.3 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Photograph 8.1.3 Setup for final radiated emission measurements at the OATS



Photograph 8.1.4 Setup for final radiated emission measurements at the OATS





HERMON LABORATORIES

Report ID: PIXRAD_FCC.26451_BLE.docx

Date of Issue: 23-Aug-15

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict: PASS	
Date(s):	28-May-15	Temperature: 22.3 °C	Air Pressure: 1019 hPa
Remarks:	Relative Humidity: 43 % Power Supply: Battery		

Table 8.1.3 Radiated emission test results

EUT SET UP: TABLE-TOP
 TEST SITE: SEMI ANECHOIC CHAMBER
 TEST DISTANCE: 3 m
 DETECTORS USED: PEAK / QUASI-PEAK
 FREQUENCY RANGE: 30 MHz – 1000 MHz
 RESOLUTION BANDWIDTH: 120 kHz

Frequency, MHz	Peak emission, dB(µV/m)	Quasi-peak			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
		Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
No emissions were found								

TEST SITE: OATS / SEMI ANECHOIC CHAMBER
 TEST DISTANCE: 3 m
 DETECTORS USED: PEAK / AVERAGE
 FREQUENCY RANGE: 1000 MHz – 18000 MHz
 RESOLUTION BANDWIDTH: 1000 kHz

Frequency, MHz	Peak			Average			Antenna polarization	Antenna height, m	Turn-table position**, degrees	Verdict
	Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*	Measured emission, dB(µV/m)	Limit, dB(µV/m)	Margin, dB*				
No emissions were found										

*- Margin = Measured emission - specification limit.

**- EUT front panel refers to 0 degrees position of turntable.

Reference numbers of test equipment used


HL 0446	HL 0604	HL 0768	HL 1984	HL 2780	HL 3818	HL 3901	HL 4114
HL 4224	HL 4353	HL 4575	HL 4722	HL 4932			

Full description is given in Appendix A.




HERMON LABORATORIES

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict:	PASS
Date(s):	28-May-15		
Temperature: 22.3 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Plot 8.1.1 Radiated emission measurements in 30 - 1000 MHz range**Plot 8.1.2 Radiated emission measurements from 1000 to 6000 MHz**



TEST SITE: Semi anechoic chamber
 TEST DISTANCE: 3 m
 ANTENNA POLARIZATION: Vertical and Horizontal





HERMON LABORATORIES

Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Class B, Radiated emission		
Test procedure:	ANSI C63.4, Sections 11.6 and 12.1.4		
Test mode:	Compliance	Verdict: PASS	
Date(s):	28-May-15		
Temperature: 22.3 °C	Air Pressure: 1019 hPa	Relative Humidity: 43 %	Power Supply: Battery
Remarks:			

Plot 8.1.3 Radiated emission measurements from 4000 to 10000 MHz**Plot 8.1.4 Radiated emission measurements from 10000 to 18000 MHz**

10.5 GHz – is ambient signal.



HERMON LABORATORIES

9 APPENDIX A Test equipment and ancillaries used for tests

HL No	Description	Manufacturer	Model	Ser. No.	Last Cal./Check	Due Cal./Check
0446	Antenna, Loop, Active, 10 kHz - 30 MHz	EMCO	6502	2857	13-Jan-15	13-Jan-16
0604	Antenna BiconiLog Log-Periodic/T Bow-TIE, 26 - 2000 MHz	EMCO	3141	9611-1011	15-May-15	15-May-16
0768	Antenna Standard Gain Horn, 18-26.5 GHz, WR-42, 25 dB gain	Quinstar Technology	QWH-4200-BA	110	25-Dec-14	25-Dec-15
1984	Antenna, Double-Ridged Waveguide Horn, 1-18 GHz, 300 W	EMC Test Systems	3115	9911-5964	17-Apr-15	17-Apr-16
2780	EMC analyzer, 100 Hz to 26.5 GHz	Agilent Technologies	E7405A	MY451024 62	02-Sep-14	02-Sep-15
3818	PSA Series Spectrum Analyzer, 3 Hz- 44 GHz	Agilent Technologies	E4446A	MY482502 88	29-Apr-15	29-Apr-16
3901	Microwave Cable Assembly, 40.0 GHz, 3.5 m, SMA/SMA	Huber-Suhner	SUCOFLE X 102A	1225/2A	10-Feb-15	10-Feb-16
4114	Antenna, Double-Ridged Waveguide Horn, 1-18 GHz	ETS Lindgren	3117	00123515	19-Dec-14	19-Dec-15
4224	Precision Fixed Attenuator, 50 Ohm, 5W, 10dB, DC to 18000 MHz	Mini-Circuits	BW-N10W5+	NA	09-Mar-14	09-Mar-15
4353	Low Loss Armored Test Cable, DC - 18 GHz, 6.2 m, N type-M/N type-M	MegaPhase	NC29-N1N1-244 003	12025101	15-Mar-15	15-Mar-16
4575	EXA Signal Analyzer, 9 kHz - 26.5 GHz	Agilent Technologies	N9010A	MY480301 10	05-Feb-15	05-Feb-16
4722	Low Loss Armored Test Cable, DC - 18 GHz, 6.2 m, N type-M/N type-M	MegaPhase	NC29-N1N1-244 001	51228701	26-Aug-14	26-Aug-15
4932	Microwave preamplifier, 500 MHz to 18 GHz, 40 dB Gain	Com-Power Corporation	PAM-118A	551029	18-Nov-14	18-Nov-15



HERMON LABORATORIES

10 APPENDIX B Measurement uncertainties

Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted carrier power at RF antenna connector	Below 12.4 GHz: ± 1.7 dB 12.4 GHz to 40 GHz: ± 2.3 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB 2.9 GHz to 6.46 GHz: ± 3.5 dB 6.46 GHz to 13.2 GHz: ± 4.3 dB 13.2 GHz to 22.0 GHz: ± 5.0 dB 22.0 GHz to 26.8 GHz: ± 5.5 dB 26.8 GHz to 40.0 GHz: ± 4.8 dB
Occupied bandwidth	± 8.0 %
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Conducted emissions with LISN	9 kHz to 150 kHz: ± 3.9 dB 150 kHz to 30 MHz: ± 3.8 dB
Radiated emissions at 3 m measuring distance Horizontal polarization	Biconilog antenna: ± 5.3 dB Biconical antenna: ± 5.0 dB Log periodic antenna: ± 5.3 dB Double ridged horn antenna: ± 5.3 dB
Vertical polarization	Biconilog antenna: ± 6.0 dB Biconical antenna: ± 5.7 dB Log periodic antenna: ± 6.0 dB Double ridged horn antenna: ± 6.0 dB

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.



HERMON LABORATORIES

11 APPENDIX C Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility.

Hermon Laboratories is listed by the Federal Communications Commission (USA) for all parts of Code of Federal Regulations 47 (CFR 47), Registration Numbers 90624 for OATS and 90623 for the anechoic chamber; by Industry Canada for electromagnetic emissions (file numbers IC 2186A-1 for OATS), certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, C-845 for conducted emissions site, T-1606 for conducted emissions at telecommunication ports), has a status of a Telefication - Listed Testing Laboratory, Certificate No. L138/00. The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01). The FCC Designation Number is US1003.

Address: P.O. Box 23, Binyamina 30500, Israel.
Telephone: +972 4628 8001
Fax: +972 4628 8277
e-mail: mail@hermonlabs.com
website: www.hermonlabs.com

Person for contact: Mr. Alex Usoskin, CEO.

12 APPENDIX D Specification references

FCC 47CFR part 15: 2014	Radio Frequency Devices
558074 D01 DTS Meas Guidance v03r01, 4/09/2013	FCC Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
ANSI C63.2: 1996	American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications
ANSI C63.4: 2009	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
RSS-247 Issue 1: 2015	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence- Exempt Local Area Network (LE-LAN) Devices
RSS-Gen Issue 4: 2014	General Requirements and Information for the Certification of Radiocommunication Equipment



HERMON LABORATORIES

13 APPENDIX E Test equipment correction factors

Antenna factor
Active loop antenna
Model 6502, S/N 2857, HL 0446

Frequency, MHz	Magnetic antenna factor, dB	Electric antenna factor, dB
0.009	-32.8	18.7
0.010	-33.8	17.7
0.020	-38.3	13.2
0.050	-41.1	10.4
0.075	-41.3	10.2
0.100	-41.6	9.9
0.150	-41.7	9.8
0.250	-41.6	9.9
0.500	-41.8	9.8
0.750	-41.9	9.7
1.000	-41.4	10.1
2.000	-41.5	10.0
3.000	-41.4	10.2
4.000	-41.4	10.1
5.000	-41.5	10.1
10.000	-41.9	9.6
15.000	-41.9	9.6
20.000	-42.2	9.3
25.000	-42.8	8.7
30.000	-44.0	7.5

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).

Antenna factor
Standard gain horn antenna
Quinstar Technology
Model QWH
Ser.No.112, HL 0768, 0769, 0770, 0771, 0772

Frequency min, GHz	Frequency max, GHz	Antenna factor, dB(1/m)
18.000	26.500	32.01
26.500	40.000	35.48
40.000	60.000	39.03
60.000	90.000	42.55
90.000	140.000	46.23
140.000	220.000	50.11

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).



HERMON LABORATORIES

**Antenna factor
Biconilog antenna EMCO Model 3141
Ser.No.1011, HL 0604**

Frequency, MHz	Antenna factor, dB(1/m)	Frequency, MHz	Antenna factor, dB(1/m)	Frequency, MHz	Antenna factor, dB(1/m)
26	7.8	580	20.6	1320	27.8
28	7.8	600	21.3	1340	28.3
30	7.8	620	21.5	1360	28.2
40	7.2	640	21.2	1380	27.9
60	7.1	660	21.4	1400	27.9
70	8.5	680	21.9	1420	27.9
80	9.4	700	22.2	1440	27.8
90	9.8	720	22.2	1460	27.8
100	9.7	740	22.1	1480	28.0
110	9.3	760	22.3	1500	28.5
120	8.8	780	22.6	1520	28.9
130	8.7	800	22.7	1540	29.6
140	9.2	820	22.9	1560	29.8
150	9.8	840	23.1	1580	29.6
160	10.2	860	23.4	1600	29.5
170	10.4	880	23.8	1620	29.3
180	10.4	900	24.1	1640	29.2
190	10.3	920	24.1	1660	29.4
200	10.6	940	24.0	1680	29.6
220	11.6	960	24.1	1700	29.8
240	12.4	980	24.5	1720	30.3
260	12.8	1000	24.9	1740	30.8
280	13.7	1020	25.0	1760	31.1
300	14.7	1040	25.2	1780	31.0
320	15.2	1060	25.4	1800	30.9
340	15.4	1080	25.6	1820	30.7
360	16.1	1100	25.7	1840	30.6
380	16.4	1120	26.0	1860	30.6
400	16.6	1140	26.4	1880	30.6
420	16.7	1160	27.0	1900	30.6
440	17.0	1180	27.0	1920	30.7
460	17.7	1200	26.7	1940	30.9
480	18.1	1220	26.5	1960	31.2
500	18.5	1240	26.5	1980	31.6
520	19.1	1260	26.5	2000	32.0
540	19.5	1280	26.6		
560	19.8	1300	27.0		

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).



HERMON LABORATORIES

Antenna factor
Double-ridged wave guide horn antenna
Model 3115, S/N 9911-5964, HL1984

Frequency, MHz	Antenna factor, dB(1/m)
1000.0	24.7
1500.0	25.7
2000.0	27.6
2500.0	28.9
3000.0	31.2
3500.0	32.0
4000.0	32.5
4500.0	32.7
5000.0	33.6
5500.0	35.1
6000.0	35.4
6500.0	34.9
7000.0	36.1
7500.0	37.8
8000.0	38.0
8500.0	38.1
9000.0	39.1
9500.0	38.3
10000.0	38.6
10500.0	38.2
11000.0	38.7
11500.0	39.5
12000.0	40.0
12500.0	40.4
13000.0	40.5
13500.0	41.1
14000.0	41.6
14500.0	41.7
15000.0	38.7
15500.0	38.2
16000.0	38.8
16500.0	40.5
17000.0	42.5
17500.0	45.9
18000.0	49.4

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).



HERMON LABORATORIES

Antenna factor
Double-ridged waveguide horn antenna
ETS Lindgren, Model 3117, serial number: 00123515, HL 4114

Frequency, MHz	Antenna factor, dB/m		
	Measured	Manufacturer	Deviation
1000	28.0	28.4	-0.4
1500	28.0	27.4	0.6
2000	31.2	30.9	0.3
2500	32.5	33.4	-0.9
3000	32.9	32.6	0.3
3500	32.7	32.8	-0.1
4000	33.1	33.4	-0.3
4500	33.8	33.9	-0.1
5000	33.8	34.1	-0.3
5500	34.4	34.5	-0.1
6000	35.0	35.2	-0.2
6500	35.4	35.5	-0.1
7000	35.7	35.7	0.0
7500	35.9	35.7	0.2
8000	35.8	35.8	0.0
8500	35.9	35.8	0.1
9000	36.3	36.2	0.1
9500	36.6	36.6	0.0
10000	37.1	37.1	0.0
10500	37.6	37.5	0.1
11000	37.9	37.7	0.2
11500	38.5	38.1	0.4
12000	39.2	38.7	0.5
12500	39.0	38.9	0.1
13000	39.1	39.1	0.0
13500	38.9	38.8	0.1
14000	39.0	38.8	0.2
14500	39.6	39.9	-0.3
15000	39.9	39.7	0.2
15500	39.9	40.1	-0.2
16000	40.7	40.8	-0.1
16500	41.3	41.8	-0.5
17000	42.5	42.1	0.4
17500	41.3	41.2	0.1
18000	41.4	40.9	0.5

Antenna factor is to be added to receiver meter reading in dB(μ V) to convert to field strength in dB(μ V/meter)



HERMON LABORATORIES

Cable loss
Microwave Cable Assembly, Huber-Suhner, 40 GHz, 3.5 m, SMA-SMA, S/N 1225/2A
HL 3901

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.09	9500	4.29	21000	6.67
100	0.41	10000	4.40	22000	6.92
500	0.93	10500	4.52	23000	7.00
1000	1.33	11000	4.64	24000	7.18
1500	1.63	11500	4.76	25000	7.29
2000	1.90	12000	4.87	26000	7.55
2500	2.12	12500	4.99	27000	7.70
3000	2.33	13000	5.11	28000	7.88
3500	2.50	13500	5.20	29000	8.02
4000	2.67	14000	5.31	30000	8.15
4500	2.82	14500	5.42	31000	8.35
5000	2.99	15000	5.51	32000	8.40
5500	3.16	15500	5.58	33000	8.62
6000	3.32	16000	5.68	34000	8.73
6500	3.51	16500	5.78	35000	8.78
7000	3.65	17000	5.91	36000	8.94
7500	3.79	17500	5.99	37000	9.21
8000	3.92	18000	6.07	38000	9.37
8500	4.04	19000	6.36	39000	9.45
9000	4.18	20000	6.49	40000	9.52



HERMON LABORATORIES

Cable loss
Low Loss Armored Test Cable, MegaPhase, 18 GHz, 6.2 m, N type-M/N type-M,
NC29-N1N1-244S/N 12025101 003,
HL 4353

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
50	0.20	9000	2.71
100	0.27	9500	2.81
300	0.47	10000	2.90
500	0.61	10500	2.97
1000	0.87	11000	3.06
1500	1.07	11500	3.13
2000	1.24	12000	3.20
2500	1.39	12500	3.26
3000	1.53	13000	3.34
3500	1.65	13500	3.39
4000	1.77	14000	3.47
4500	1.89	14500	3.54
5000	1.99	15000	3.62
5500	2.07	15500	3.69
6000	2.20	16000	3.76
6500	2.30	16500	3.83
7000	2.39	17000	3.86
7500	2.51	17500	3.94
8000	2.58	18000	4.02
8500	2.65		



HERMON LABORATORIES

Cable loss
Low Loss Armored Test Cable, MegaPhase, 18 GHz, 6.2 m, N type-M/N type-M,
NC29-N1N1-244, S/N 51228701001
HL 4722

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
50	0.22	9000	2.93
100	0.30	9500	3.06
300	0.52	10000	3.16
500	0.66	10500	3.20
1000	0.93	11000	3.34
1500	1.15	11500	3.39
2000	1.33	12000	3.48
2500	1.49	12500	3.55
3000	1.64	13000	3.66
3500	1.77	13500	3.75
4000	1.90	14000	3.76
4500	2.03	14500	3.87
5000	2.17	15000	3.98
5500	2.30	15500	4.01
6000	2.39	16000	4.14
6500	2.51	16500	4.15
7000	2.59	17000	4.32
7500	2.67	17500	4.36
8000	2.76	18000	4.38
8500	2.84		



HERMON LABORATORIES

14 APPENDIX F Abbreviations and acronyms

A	ampere
AC	alternating current
AM	amplitude modulation
AVRG	average (detector)
cm	centimeter
dB	decibel
dBm	decibel referred to one milliwatt
dB(µV)	decibel referred to one microvolt
dB(µV/m)	decibel referred to one microvolt per meter
dB(µA)	decibel referred to one microampere
DC	direct current
EIRP	equivalent isotropically radiated power
ERP	effective radiated power
EUT	equipment under test
F	frequency
GHz	gigahertz
GND	ground
H	height
HL	Hermon laboratories
Hz	hertz
k	kilo
kHz	kilohertz
LO	local oscillator
m	meter
MHz	megahertz
min	minute
mm	millimeter
ms	millisecond
µs	microsecond
NA	not applicable
NB	narrow band
OATS	open area test site
Ω	Ohm
PM	pulse modulation
PS	power supply
ppm	part per million (10^{-6})
QP	quasi-peak
RE	radiated emission
RF	radio frequency
rms	root mean square
Rx	receive
s	second
T	temperature
Tx	transmit
V	volt
WB	wideband

END OF DOCUMENT