

Acuity Brands Lighting Inc. RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Wireless LED Light Model: RSDGR

REPORT NUMBER

104317434MPK-002

ISSUE DATE

May 11, 2020

REVISED DATE

August 12, 2020

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 104317434MPK-002

Project Number: G104317434

Original Report Issue Date: May 11, 2020

Revision Report Issue Date: August 12, 2020

Product Designation: Wireless LED Light

Model Tested: RSDGR

FCC ID: 2ADCB-RMODIT

IC: 6715C-RMODIT

to

47CFR 2.1091

RSS-102 Issue 5

for

Acuity Brands Lighting Inc.

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

Acuity Brands Lighting Inc.
One Lithonia Way
Conyers, GA 30012 USA

Report prepared by:



Aaron Chang / Project Engineer

Report reviewed by:



Krishna Vemuri / EMC Manager

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Report No. 104317434MPK-002	
Equipment Under Test:	Wireless LED Light
Trade Name:	Acuity Brands Lighting Inc.
Model(s) Tested:	RSDGR
Applicant:	Acuity Brands Lighting Inc.
Contact:	Sanjana Dhankani
Address:	Acuity Brands Lighting Inc. One Lithonia Way Conyers, GA 30012 USA
Country:	USA
Tel. Number:	(770) 922-9000
Email:	Sanjana.Dhankani@AcuityBrands.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

<i>Acuity Brands Lighting Inc.....</i>	<i>1</i>
<i>1.0 RF Exposure Summary.....</i>	<i>5</i>
<i>2.0 RF Exposure Limits</i>	<i>5</i>
<i>3.0 Test Results (Mobile Configuration)</i>	<i>7</i>
<i>4.0 Document History</i>	<i>10</i>

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	$0.73/f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142/f^{0.3417}$	$0.008335/f^{0.3417}$	$0.02619/f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158/f^{0.5}$	$4.21 \times 10^{-4}/f^{0.5}$	$6.67 \times 10^{-5}/f$	$616000/f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Wireless LED Light, Model: rSDGR consists of two radios: Bluetooth Low Energy and SubGHz..

3.3 Maximum RF Power

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
904 - 926	18.88	0.8	Conducted power measurements were taken from Report # 103986369ATL-001.

¹As declared by the manufacturer.

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2402-2480	9.55	3.0	Conducted power measurements were taken from original filing, FCC ID: 2ADCB-RMODIT. Antenna gain information was taken from operational description of rSDGR.

¹As declared by the manufacturer.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for Bluetooth Low Energy & SubGHz.

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (W/m ²) @20 cm	RSS Limit (W/m ²)	MPE Ratio	Sum of MPE Ratios
2402-2480	12.55	17.989	0.0358	5.469	0.0065	0.0727
904 - 926	19.68	92.897	0.1848	2.789	0.0662	

Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20 cm	FCC Limit (mW/cm ²)	MPE Ratio	Sum of MPE Ratios
2402-2480	12.55	17.989	0.00358	1	0.00358	0.03353
904 - 926	19.68	92.897	0.01848	0.617	0.02995	

¹Note: Antenna gains below 0 are considered as 0dBi.

The summation of the MPE ratio is less than 1, therefore, the EUT complies for the MPE requirement of simultaneous transmission.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewer Initials	Date	Change
1.0/ G104317434	AC	KV	May 11, 2020	Original document
2.0/ G104317434	AC	KV	August 12, 2020	Revised section 3.4 with 2.4GHz radio information