



RF TEST REPORT



Report No.: 18070631-FCC-R1

Supersede Report No.: N/A

Applicant	Monoprice, Inc.	
Product Name	Bluetooth Speaker System	
Model No.	33394	
Serial No.	33393, Soundstage3 (Note: All models have same circuits diagram, PCB Layout, construction and rated power, only different was model name and appearance color.)	
Test Standard	FCC Part 15.247, ANSI C63.10: 2013	
Test Date	June 23 to July 01, 2018	
Issue Date	July 02, 2018	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Aaron Liang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	18070631-FCC-R1
Page	3 of 50

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH	14
6.4 PEAK OUTPUT POWER	18
6.5 NUMBER OF HOPPING CHANNEL	22
6.6 TIME OF OCCUPANCY (DWEIL TIME)	24
6.7 BAND EDGE & RESTRICTED BAND	28
6.8 AC POWER LINE CONDUCTED EMISSIONS	33
6.9 RADIATED EMISSIONS & RESTRICTED BAND	39
ANNEX A. TEST INSTRUMENT	45
ANNEX B. TEST SETUP AND SUPPORTING EQUIPMENT	46
ANNEX C. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST/ DECLARATION OF SIMILARITY	50

1. Report Revision History

Report No.	Report Version	Description	Issue Date
18070631-FCC-R1	NONE	Original	July 02, 2018

2. Customer information

Applicant Name	Monoprice, Inc.
Applicant Add	11701 6th St., Rancho Cucamonga, CA 91730, United State
Manufacturer	Monoprice, Inc.
Manufacturer Add	11701 6th St., Rancho Cucamonga, CA 91730, United State

3. Test site information

Test Lab A:

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

Test Lab B:

Lab performing tests	SIEMIC (Nanjing-China) Laboratories
Lab Address	2-1 Longcang Avenue Yuhua Economic and Technology Development Park, Nanjing, China
FCC Test Site No.	694825
IC Test Site No.	4842B-1
Test Software	EZ_EMG(ver.lcp-03A1)

Note: We just perform Radiated Spurious Emission above 18GHz in the test Lab. B.

4. Equipment under Test (EUT) Information

Description of EUT:	Bluetooth Speaker System
Main Model:	33394
Serial Model:	33393, Soundstage3 (Note: All models have same circuits diagram, PCB Layout, construction and rated power, only different was model name and appearance color.)
Date EUT received:	June 22, 2018
Test Date(s):	June 23 to July 01, 2018
Equipment Category :	DSS
Antenna Gain:	Bluetooth/BLE: 0dBi
Antenna Type:	PCB antenna
Type of Modulation:	Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK
RF Operating Frequency (ies):	Bluetooth& BLE: 2402-2480 MHz
Max. Output Power:	3.996dBm
Number of Channels:	Bluetooth: 79CH BLE: 40CH
Port:	Please refer to the user' s manual
Input Power:	N/A
Trade Name :	Monoprice, IIIP

Test Report	18070631-FCC-R1
Page	7 of 50

FCC ID:

2ADDH-SOUNDSTAGE3

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge& Restricted Band	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions& Restricted Band	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge& Restricted Band and Radiated Emissions& Restricted Band	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:

A permanently attached PCB antenna for Bluetooth/BLE, the gain is 0dBi for Bluetooth/BLE.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span - Video (or Average) Bandwidth (VBW) $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.		

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Channel Separation measurement result

Type/ Modulation	CH	CH Frequency (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.000	0.906	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	0.998	0.888	Pass
	Adjacency Channel	2441			
	High Channel	2480	0.998	0.888	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	0.994	0.815	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.000	0.813	Pass
	Adjacency Channel	2441			
	High Channel	2480	0.996	0.813	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	0.992	0.806	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.008	0.804	Pass
	Adjacency Channel	2441			
	High Channel	2480	0.996	0.805	Pass
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result





8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.3 20dB Bandwidth

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Use the following spectrum analyzer settings: - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW $\geq$ 1% of the 20 dB bandwidth - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Measurement result

Modulation	CH	CH Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	0.9062	0.8376
	Mid	2441	0.8877	0.8421
	High	2480	0.8883	0.8435
$\pi/4$ DQPSK	Low	2402	1.223	1.687
	Mid	2441	1.219	1.160
	High	2480	1.219	1.159
8-DPSK	Low	2402	1.209	1.151
	Mid	2441	1.206	1.146
	High	2480	1.207	1.140


Test Plots

20dB Bandwidth measurement result





8DPSK - Low Channel



8DPSK - Middle Channel




8DPSK - High Channel

6.4 Peak Output Power

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☒
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☒
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & < 50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☐

Test Setup	
------------	--

Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW $>$ the 20 dB bandwidth of the emission being measured - VBW $\geq$ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize.
----------------	---

	- Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A


Peak Output Power measurement result

Type	Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	2.898	1000	Pass
		Mid	2441	3.379	1000	Pass
		High	2480	3.110	1000	Pass
	$\pi/4$ DQPSK	Low	2402	2.105	125	Pass
		Mid	2441	3.169	125	Pass
		High	2480	2.739	125	Pass
	8-DPSK	Low	2402	2.308	125	Pass
		Mid	2441	3.459	125	Pass
		High	2480	3.996	125	Pass


Test Plots

Output Power measurement result





8DPSK Output power - Mid CH 2441




8DPSK Output power - High CH 2480

6.5 Number of Hopping Channel

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	FHSS in 2400-2483.5MHz ≥ 15 channels	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer settings:</u> The EUT must have its hopping function enabled. - Span = the frequency band of operation - RBW ≥ 1% of the span - VBW ≥ RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow trace to fully stabilize. - It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).		
Remark			
Result	☒ Pass ☐ Fail		


Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):


Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	☒
Test Setup			
Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. <u>Use the following spectrum analyzer</u> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW ≥ RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.96	315.733	400	Pass
		Mid	2.95	314.667	400	Pass
		High	2.97	316.800	400	Pass
	π /4 DQPSK	Low	2.99	318.933	400	Pass
		Mid	2.96	315.733	400	Pass
		High	2.98	317.867	400	Pass
	8-DPSK	Low	3.00	320.000	400	Pass
		Mid	2.97	316.800	400	Pass
		High	2.99	318.933	400	Pass
Note: Dwell time=Pulse Time (ms) $\times$ (1600 $\div$ 6 $\div$ 79) $\times$ 31.6						

Test Plots


Dwell Time measurement result



GFSK - Low CH 2402




GFSK - Mid CH 2441




GFSK - High CH 2402




$\pi/4$ DQPSK - Low CH 2402




$\pi/4$ DQPSK - Mid CH 2441




$\pi/4$ DQPSK - High CH 2480



8DPSK - Low CH 2402



8DPSK - Mid CH 2441




8DPSK - High CH 2480

6.7 Band Edge & Restricted Band

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. □	☒

Test Setup	
------------	--


Test Procedure	The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range,
----------------	--

	and make sure the instrument is operated in its linear range. - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail


Test Data ☐ Yes ☒ N/A
Test Plot ☒ Yes (See below) ☐ N/A

Test Plots


GFSK Mode:



GFSK-Hopping Left Side



GFSK-Hopping Right Side




GFSK-Left Side




GFSK-Right Side

$\pi/4$ DQPSK-Right Side


8-DPSK Mode:



8DPSK-Hopping Left Side



8DPSK-Hopping Right Side



8DPSK-Left Side



8DPSK-Right Side

6.8 AC Power Line Conducted Emissions

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
		0.5 ~ 5		56	46												
5 ~ 30	60	50															

Test Setup	Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	--

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report	18070631-FCC-R1
Page	34 of 50

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2670	29.24	QP	10.03	39.27	61.21	-21.94
2	L1	0.2670	20.40	AVG	10.03	30.43	51.21	-20.78
3	L1	0.6336	21.40	QP	10.03	31.43	56.00	-24.57
4	L1	0.6336	12.26	AVG	10.03	22.29	46.00	-23.71
5	L1	0.9378	20.80	QP	10.03	30.83	56.00	-25.17
6	L1	0.9378	11.33	AVG	10.03	21.36	46.00	-24.64
7	L1	1.4253	19.99	QP	10.04	30.03	56.00	-25.97
8	L1	1.4253	10.47	AVG	10.04	20.51	46.00	-25.49
9	L1	3.8697	18.99	QP	10.07	29.06	56.00	-26.94
10	L1	3.8697	9.66	AVG	10.07	19.73	46.00	-26.27
11	L1	9.3726	20.08	QP	10.14	30.22	60.00	-29.78
12	L1	9.3726	12.44	AVG	10.14	22.58	50.00	-27.42

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2670	29.22	QP	10.03	39.25	61.21	-21.96
2	N	0.2670	20.03	AVG	10.03	30.06	51.21	-21.15
3	N	0.6921	20.21	QP	10.03	30.24	56.00	-25.76
4	N	0.6921	9.96	AVG	10.03	19.99	46.00	-26.01
5	N	1.2357	18.79	QP	10.03	28.82	56.00	-27.18
6	N	1.2357	8.81	AVG	10.03	18.84	46.00	-27.16
7	N	3.4992	17.50	QP	10.06	27.56	56.00	-28.44
8	N	3.4992	7.21	AVG	10.06	17.27	46.00	-28.73
9	N	9.4974	21.34	QP	10.14	31.48	60.00	-28.52
10	N	9.4974	12.43	AVG	10.14	22.57	50.00	-27.43
11	N	27.3399	12.04	QP	10.44	22.48	60.00	-37.52
12	N	27.3399	6.91	AVG	10.44	17.35	50.00	-32.65

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	L1	0.2787	32.85	QP	10.02	42.87	60.85	-17.98
2	L1	0.2787	24.17	AVG	10.02	34.19	50.85	-16.66
3	L1	0.8091	25.26	QP	10.03	35.29	56.00	-20.71
4	L1	0.8091	16.03	AVG	10.03	26.06	46.00	-19.94
5	L1	1.3005	24.41	QP	10.03	34.44	56.00	-21.56
6	L1	1.3005	15.41	AVG	10.03	25.44	46.00	-20.56
7	L1	2.9658	23.80	QP	10.05	33.85	56.00	-22.15
8	L1	2.9658	15.93	AVG	10.05	25.98	46.00	-20.02
9	L1	10.2891	23.52	QP	10.14	33.66	60.00	-26.34
10	L1	10.2891	16.24	AVG	10.14	26.38	50.00	-23.62
11	L1	27.3399	13.79	QP	10.38	24.17	60.00	-35.83
12	L1	27.3399	4.26	AVG	10.38	14.64	50.00	-35.36

Test Mode: Bluetooth Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
		(MHz)	(dBuV)		(dB)	(dBuV)	(dBuV)	(dB)
1	N	0.2787	32.15	QP	10.02	42.17	60.85	-18.68
2	N	0.2787	22.95	AVG	10.02	32.97	50.85	-17.88
3	N	0.7974	24.59	QP	10.03	34.62	56.00	-21.38
4	N	0.7974	14.80	AVG	10.03	24.83	46.00	-21.17
5	N	1.6671	21.51	QP	10.04	31.55	56.00	-24.45
6	N	1.6671	13.05	AVG	10.04	23.09	46.00	-22.91
7	N	3.0585	23.56	QP	10.05	33.61	56.00	-22.39
8	N	3.0585	14.09	AVG	10.05	24.14	46.00	-21.86
9	N	9.4818	25.03	QP	10.13	35.16	60.00	-24.84
10	N	9.4818	17.36	AVG	10.13	27.49	50.00	-22.51
11	N	28.4631	13.84	QP	10.40	24.24	60.00	-35.76
12	N	28.4631	2.27	AVG	10.40	12.67	50.00	-37.33


6.9 Radiated Emissions & Restricted Band

Temperature	23°C
Relative Humidity	52%
Atmospheric Pressure	1020mbar
Test date :	June 26, 2018
Tested By :	Aaron Liang

Requirement(s):

Spec	Item	Requirement	Applicable																
47CFR§15.205, §15.209, §15.247(d)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	☒																
		<table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>0.009~0.490</td><td>2400/F(KHz)</td></tr><tr><td>0.490~1.705</td><td>24000/F(KHz)</td></tr><tr><td>1.705~30.0</td><td>30</td></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>		Frequency range (MHz)	Field Strength (µV/m)	0.009~0.490	2400/F(KHz)	0.490~1.705	24000/F(KHz)	1.705~30.0	30	30 – 88	100	88 – 216	150	216 960	200	Above 960	500
		Frequency range (MHz)		Field Strength (µV/m)															
		0.009~0.490		2400/F(KHz)															
		0.490~1.705		24000/F(KHz)															
		1.705~30.0		30															
		30 – 88		100															
		88 – 216		150															
		216 960		200															
		Above 960		500															

Test Setup	 The diagram illustrates the test setup for radiated emissions. It shows an Equipment Under Test (EUT) placed on a stand that is 0.8 meters high. A Loop Antenna is positioned 3 meters away from the EUT. The entire setup is on a Ground Plane. An RF Test Receiver is connected to the antenna.
------------	---

	
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. - The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Result:

Test Mode:	Transmitting Mode
------------	-------------------

Frequency range: 9KHz - 30MHz

Freq.	Detection	Factor	Reading	Result	Limit@3m	Margin
(MHz)	value	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dB)
--	--	--	--	--	--	>20
--	--	--	--	--	--	>20

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.

Test Mode: Bluetooth Mode

30MHz -1GHz

80.0 dBuV/m




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()
1	H	156.4578	46.79	QP	12.60	22.29	1.37	38.47	43.50	-5.03	100	19
2	H	400.4319	39.92	peak	15.71	22.01	2.01	35.63	46.00	-10.37	100	349
3	H	247.6819	44.23	peak	11.43	22.29	1.69	35.06	46.00	-10.94	100	133
4	H	316.5890	39.44	peak	13.95	22.24	1.87	33.02	46.00	-12.98	100	39
5	H	112.5244	37.33	peak	12.59	22.35	1.17	28.74	43.50	-14.76	100	348
6	H	151.0666	43.49	peak	12.60	22.33	1.35	35.11	43.50	-8.39	100	86

30MHz -1GHz

80.0 dBuV/m



Test Data

Vertical Polarity Plot @3m

N o.	P/ L	Frequency (MHz)	Reading (dBuV/m)	Detect or	Ant_F (dB/m)	PA_G (dB)	Cab_L (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degr ee ()
1	V	158.6677	44.37	peak	12.60	22.28	1.38	36.07	43.50	-7.43	100	93
2	V	111.7380	43.63	peak	12.45	22.34	1.17	34.91	43.50	-8.59	100	274
3	V	440.1963	39.05	peak	16.50	21.93	2.11	35.73	46.00	-10.27	100	255
4	V	316.5890	28.76	peak	13.95	22.24	1.87	22.34	46.00	-23.66	100	10
5	V	252.0627	34.23	peak	11.49	22.29	1.70	25.13	46.00	-20.87	100	312
6	V	30.9619	32.91	peak	20.66	22.27	0.65	31.95	40.00	-8.05	100	284

Above 1GHz

Test Mode:	Transmitting Mode
-------------------	--------------------------

Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector	Polarity
(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	(PK/AV)	(H/V)
Low Channel:8DPSK Mode(Worst Case)-2402MHz									
2393	35.11	28.72	3.36	26.32	40.87	74	-33.13	peak	Vertical
4808	30.02	32.94	3.98	27.49	39.45	54	-14.55	Average	Vertical
4808	38.01	32.94	3.98	27.49	47.44	74	-26.56	peak	Vertical
7206	31.09	25.28	5.51	27.94	33.94	54	-20.06	Average	Vertical
7206	40.04	25.28	5.51	27.94	42.89	74	-31.11	peak	Vertical
2393	36.99	28.72	3.36	26.32	42.75	74	-31.25	peak	Horizontal
4808	31.65	32.94	3.98	27.49	41.08	54	-12.92	Average	Horizontal
4808	41.82	32.94	3.98	27.49	51.25	74	-22.75	peak	Horizontal
7206	31.99	25.28	5.51	27.94	34.84	54	-19.16	Average	Horizontal
7206	40.58	25.28	5.51	27.94	43.43	74	-30.57	peak	Horizontal
Middle Channel:8DPSK Mode(Worst Case)-2441MHz									
4883	31.69	32.11	4.04	27.53	40.31	54	-13.69	Average	Vertical
4883	36.95	32.11	4.04	27.53	45.57	74	-28.43	peak	Vertical
7326	30.99	24.33	5.58	27.96	32.94	54	-21.06	Average	Vertical
7326	39.19	24.33	5.58	27.96	41.14	74	-32.86	peak	Vertical
4883	30.06	32.11	4.04	27.53	38.68	54	-15.32	Average	Horizontal
4883	40.47	32.11	4.04	27.53	49.09	74	-24.91	peak	Horizontal
7326	33.91	24.33	5.58	27.96	35.86	54	-18.14	Average	Horizontal
7326	40.02	24.33	5.58	27.96	41.97	74	-32.03	peak	Horizontal
High Channel:8DPSK Mode(Worst Case)-2480MHz									
2483.6	38.65	28.79	3.48	26.34	44.58	74	-29.42	peak	Vertical
4959.9	31.25	31.32	4.12	27.58	39.11	54	-14.89	Average	Vertical
4959.9	39.68	31.32	4.12	27.58	47.54	74	-26.46	peak	Vertical
7434.5	30.02	24.38	5.68	27.99	32.09	54	-21.91	Average	Vertical
7434.5	41.78	24.38	5.68	27.99	43.85	74	-30.15	peak	Vertical
2483.6	40.03	28.79	3.48	26.34	45.96	74	-28.04	peak	Horizontal
4959.9	28.36	31.32	4.12	27.58	36.22	54	-17.78	Average	Horizontal
4959.9	39.89	31.32	4.12	27.58	47.75	74	-26.25	peak	Horizontal
7434.5	32.12	24.38	5.68	27.99	34.19	54	-19.81	Average	Horizontal
7434.5	42.01	24.38	5.68	27.99	44.08	74	-29.92	peak	Horizontal

NOTE:1.Absolute Level= ReadingLevel+antenna Factor+cable loss-preamp factor.

2.EUT Pre-scan X/Y/Z orientation, only the worst case is presented in the report (Z orientation)


Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/15/2017	09/14/2018	☒
Line Impedance	LI-125A	191106	09/23/2017	09/22/2018	☒
Line Impedance	LI-125A	191107	09/23/2017	09/22/2018	☒
ISN	ISN T800	34373	09/23/2017	09/22/2018	☐
Transient Limiter	LIT-153	531118	08/30/2017	08/29/2018	☐
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/15/2017	09/14/2018	☒
Power Splitter	1#	1#	08/30/2017	08/29/2018	☒
DC Power Supply	E3640A	MY40004013	09/15/2017	09/14/2018	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/15/2017	09/14/2018	☒
Positioning Controller	UC3000	MF780208282	11/17/2017	11/16/2018	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/30/2017	08/29/2018	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/22/2018	03/21/2019	☒
Horn Antenna	BBHA9170	3145226D1	09/27/2017	09/26/2018	☒
Active Antenna (9kHz-30MHz)	AL-130	121031	10/12/2017	10/11/2018	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/19/2017	09/18/2018	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/22/2017	09/21/2018	☒
Universal Radio Communication Tester	CMU200	121393	09/23/2017	09/22/2018	☒


Annex B. TEST SETUP AND SUPPORTING EQUIPMENT

Annex B.i. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex B. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Lenovo	Laptop	E40	LR-1EHRX
Huawei	Phone	Honor 9	N/A

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
Power Line	Un-shielding	No	0.8m	N/A

**Annex C. User Manual / Block Diagram / Schematics / Partlist/
DECLARATION OF SIMILARITY**

Please see the attachment