



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM170500490503  
Page: 1 of 59

## TEST REPORT

**Application No.:** SZEM1705004905CR  
**Applicant:** EMOI LIFESTYLE CO., LTD  
**Address of Applicant:** 3<sup>rd</sup> Floor, Block E-5, OCT LOFT, Shenzhen  
**Manufacturer:** EMOI LIFESTYLE CO., LTD  
**Address of Manufacturer:** 3rd Floor, Block E-5, OCT LOFT, Shenzhen  
**Factory:** Konig Electronics (HuiZhou) limited  
**Address of Factory:** 2-Plant East Lake Side, Qing Tang LianHe Village, ShuiKou, HuiCheng District, HuiZhou, GuangDong, China

**Equipment Under Test (EUT):**

**EUT Name:** Smart candle lamp speaker  
**Model No.:** H0042  
**Trade mark:** EMOI  
**FCC ID:** 2ADDJ-H0042  
**Standards:** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2017-05-23  
**Date of Test:** 2017-05-27 to 2017-06-02  
**Date of Issue:** 2017-06-13

<b>Test Result :</b>	Pass*
----------------------	-------

\* In the configuration tested, the EUT complied with the standards specified above.




Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

<b>Revision Record</b>				
<b>Version</b>	<b>Chapter</b>	<b>Date</b>	<b>Modifier</b>	<b>Remark</b>
01		2017-06-13		Original

Authorized for issue by:			
		Edison Li /Project Engineer	
		Eric Fu /Reviewer	

## 2 Test Summary

<b>Radio Spectrum Technical Requirement</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

<b>Radio Spectrum Matter Part</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Conducted Disturbance at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

### **3 Contents**

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>3</b>
<b>3 CONTENTS .....</b>	<b>4</b>
<b>4 GENERAL INFORMATION .....</b>	<b>6</b>
4.1 DETAILS OF E.U.T. .....	6
4.1.1 TEST ENVIRONMENT .....	7
4.2 DESCRIPTION OF SUPPORT UNITS .....	7
4.3 MEASUREMENT UNCERTAINTY .....	7
4.4 TEST LOCATION .....	8
4.5 TEST FACILITY .....	8
4.6 DEVIATION FROM STANDARDS .....	8
4.7 ABNORMALITIES FROM STANDARD CONDITIONS .....	8
<b>5 EQUIPMENT LIST .....</b>	<b>9</b>
<b>6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....</b>	<b>11</b>
6.1 ANTENNA REQUIREMENT .....	11
6.1.1 <i>Test Requirement:</i> .....	11
6.1.2 <i>Conclusion:</i> .....	11
<b>7 RADIO SPECTRUM MATTER TEST RESULTS .....</b>	<b>12</b>
7.1 CONDUCTED DISTURBANCE AT AC POWER LINE (150kHz-30MHz) .....	12
7.1.1 <i>E.U.T. Operation:</i> .....	12
7.1.2 <i>Test Setup Diagram:</i> .....	12
7.1.3 <i>Measurement Procedure and Data:</i> .....	13
7.2 MINIMUM 6dB BANDWIDTH .....	16
7.2.1 <i>E.U.T. Operation:</i> .....	16
7.2.2 <i>Test Setup Diagram:</i> .....	16
7.2.3 <i>Measurement Procedure and Data:</i> .....	16
7.3 CONDUCTED PEAK OUTPUT POWER .....	17
7.3.1 <i>E.U.T. Operation:</i> .....	18
7.3.2 <i>Test Setup Diagram:</i> .....	18
7.3.3 <i>Measurement Procedure and Data:</i> .....	18
7.4 POWER SPECTRUM DENSITY .....	19
7.4.1 <i>E.U.T. Operation:</i> .....	19
7.4.2 <i>Test Setup Diagram:</i> .....	19
7.4.3 <i>Measurement Procedure and Data:</i> .....	19
7.5 CONDUCTED BAND EDGES MEASUREMENT .....	20
7.5.1 <i>E.U.T. Operation:</i> .....	20
7.5.2 <i>Test Setup Diagram:</i> .....	20
7.5.3 <i>Measurement Procedure and Data:</i> .....	20
7.6 CONDUCTED SPURIOUS EMISSIONS .....	21
7.6.1 <i>E.U.T. Operation:</i> .....	21
7.6.2 <i>Test Setup Diagram:</i> .....	21
7.6.3 <i>Measurement Procedure and Data:</i> .....	21
7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS .....	22
7.7.1 <i>E.U.T. Operation:</i> .....	22
7.7.2 <i>Test Setup Diagram:</i> .....	22

7.7.3	<i>Measurement Procedure and Data</i> .....	23
7.8	RADIATED SPURIOUS EMISSIONS .....	28
7.8.1	<i>E.U.T. Operation</i> .....	29
7.8.2	<i>Test Setup Diagram</i> .....	29
7.8.3	<i>Measurement Procedure and Data</i> .....	30
<b>8</b>	<b>PHOTOGRAPHS .....</b>	<b>36</b>
8.1	CONDUCTED DISTURBANCE AT AC POWER LINE (150KHz-30MHz) TEST SETUP .....	36
8.2	RADIATED SPURIOUS EMISSIONS TEST SETUP.....	37
8.3	EUT CONSTRUCTIONAL DETAILS .....	38
<b>9</b>	<b>APPENDIX.....</b>	<b>39</b>
9.1	APPENDIX 15.247.....	39-59

## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 3.7V, 1200mAh rechargeable battery which charged by USB port
Cable:	USB Cable: 100cm unshielded
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.0 dual mode
Modulation Type:	GFSK
Number of Channel:	40
Antenna Type:	PCB Antenna
Antenna Gain:	1dBi

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz

#### 4.1 Test Environment

Operating Environment:	
Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	1010mbar

#### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Adapter	Apple	A1357 W010A051	REF. No. SEA0500

#### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10-8
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz) 4.8dB (above 1GHz)
8	Radiated Spurious emission test	4.5dB (30MHz-1GHz) 4.8dB (1GHz-18GHz)
9	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%

#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053      Fax: +86 755 2671 0594

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

## 5 Equipment List

<b>Conducted Disturbance at AC Power Line (150kHz-30MHz)</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2017-05-10	2018-05-10
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-14
8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
2 Line ISN	Fischer Custom	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28

<b>RF Conducted Test</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No</b>	<b>Inventory No</b>	<b>Cal Date</b>	<b>Cal Due Date</b>
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

<b>RE in Chamber</b>					
<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal. Date (yyyy-mm-dd)</b>	<b>Cal. Due date (yyyy-mm-dd)</b>
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2017-05-13	2018-05-13
EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2016-10-09	2017-10-09
BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01
Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24
Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2017-04-14	2018-04-14
Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13

**RE in Chamber**

Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2017-05-13	2018-05-13
EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24
Horn Antenna(26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2015-02-12	2018-02-12
Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

**General used equipment**

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2017-04-18	2018-04-18

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(c)


#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1dBi.

## 7 Radio Spectrum Matter Test Results

## 7.1 Conducted Disturbance at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


### 7.1.1 E.U.T. Operation

## Operating Environment:

Temperature: 25 °C      Humidity: 54 % RH      Atmospheric Pressure: 1015 mbar

c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.


### 7.1.2 Test Setup Diagram



### **7.1.3 Measurement Procedure and Data**

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 $\mu$ H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Mode:c; Line:Live Line



Site : Shielding Room


Condition : CE LINE

Job No. : 04905CR

Test Mode : c

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level			
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1	0.20614	0.02	9.64	19.45	29.11	53.36	-24.25 AVERAGE
2	0.20614	0.02	9.64	29.62	39.28	63.36	-24.08 QP
3 @	0.91842	0.03	9.65	32.22	41.90	46.00	-4.10 AVERAGE
4 @	0.91842	0.03	9.65	35.76	45.44	56.00	-10.56 QP
5 @	1.848	0.03	9.67	34.68	44.38	56.00	-11.62 QP
6 @	1.848	0.03	9.67	28.05	37.74	46.00	-8.26 AVERAGE
7 @	2.779	0.03	9.69	31.47	41.18	56.00	-14.82 QP
8 @	2.779	0.03	9.69	24.04	33.76	46.00	-12.24 AVERAGE
9 @	3.700	0.02	9.70	24.12	33.85	46.00	-12.15 AVERAGE
10 @	3.700	0.02	9.70	31.29	41.01	56.00	-14.99 QP
11 @	4.598	0.02	9.73	30.19	39.94	56.00	-16.06 QP
12 @	4.598	0.02	9.73	24.57	34.32	46.00	-11.68 AVERAGE

Mode:c; Line:Neutral Line



Site : Shielding Room

Condition : CE NEUTRAL

Job No. : 04905CR

Test Mode : c

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level			
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1	0.15160	0.02	9.64	31.88	41.54	65.91	-24.37 QP
2	0.15160	0.02	9.64	27.51	37.17	55.91	-18.74 AVERAGE
3	0.20505	0.02	9.63	29.66	39.31	63.40	-24.09 QP
4	0.20505	0.02	9.63	19.27	28.92	53.40	-24.48 AVERAGE
5	0.24165	0.02	9.63	17.14	26.79	52.04	-25.25 AVERAGE
6	0.24165	0.02	9.63	26.20	35.85	62.04	-26.19 QP
7	0.30348	0.02	9.63	23.60	33.25	60.15	-26.90 QP
8	0.30348	0.02	9.63	13.03	22.68	50.15	-27.47 AVERAGE
9	0.52654	0.02	9.63	13.82	23.47	46.00	-22.53 AVERAGE
10	0.52654	0.02	9.63	25.05	34.71	56.00	-21.29 QP
11	0.61400	0.02	9.63	14.28	23.93	46.00	-22.07 AVERAGE
12	0.61400	0.02	9.63	25.11	34.77	56.00	-21.23 QP

## 7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz


### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C      Humidity: 56 % RH      Atmospheric Pressure: 1010 mbar  
Pretest these mode to find the worst case: b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

The worst case for final test: b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

### 7.3 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(1)

Test Method: ANSI C63.10 (2013) Section 11.9.1.1


Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1w for $\geq 50$ hopping channels
	0.25w for $< 50$ hopping channels
	1w for digital modulation
2400-2483.5	1w for $\geq 75$ non-overlapping hopping channels
	0.125w for all other frequency hopping systems
	1w for digital modulation
5725-5850	1w for frequency hopping systems and digital modulation

**7.3.1 E.U.T. Operation**

Operating Environment:

Temperature: 23 °C      Humidity: 56 % RH      Atmospheric Pressure: 1010 mbar

Pretest these mode to find the worst case:  
b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.The worst case for final test:  
b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.**7.3.2 Test Setup Diagram****7.3.3 Measurement Procedure and Data**

The detailed test data see: Appendix 15.247

## 7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
Test Method: ANSI C63.10 (2013) Section 11.10.2  
Limit:  $\leq 8\text{dBm}$  in any 3 kHz band during any time interval of continuous transmission


### 7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C Humidity: 56 % RH Atmospheric Pressure: 1010 mbar  
Pretest these mode to find the worst case: b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

The worst case for final test: b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.

### 7.4.2 Test Setup Diagram



### 7.4.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.13.3.2

### 7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 23 °C Humidity: 56 % RH Atmospheric Pressure: 1010 mbar

Pretest these mode to find the worst case:  
b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

The worst case for final test:  
b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.11  
Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C      Humidity: 56 % RH      Atmospheric Pressure: 1010 mbar  
Pretest these mode to find the worst case: b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

The worst case for final test: b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.

### 7.6.2 Test Setup Diagram



### 7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix 15.247

## 7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

### 7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 23 °C Humidity: 54 % RH Atmospheric Pressure: 1010 mbar

Pretest these mode to find the worst case:  
b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

The worst case for final test:  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.


### 7.7.2 Test Setup Diagram



### **7.7.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Mode:c; Polarization:Horizontal; Modulation Type:GFSK; Channel:Low




Condition: 3m Horizontal

Job No: : 04905CR

Mode: : 2402 Band edge  
: BLE

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit	Over Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2321.386	5.28	28.87	38.14	51.76	47.77	74.00	-26.23	peak
2	2361.776	5.32	28.99	38.14	57.37	53.54	74.00	-20.46	peak
3	2390.000	5.34	29.08	38.14	49.77	46.05	74.00	-27.95	peak
4	pp 2401.610	5.35	29.11	38.15	104.65	100.96	74.00	26.96	Peak

Mode:c; Polarization:Vertical; Modulation Type: GFSK; Channel:Low




Condition: 3m Vertical

Job No: : 04905CR

Mode: : 2402 Band edge  
: BLE

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit	Over Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2321.573	5.28	28.87	38.14	49.25	45.26	74.00	-28.74	Peak
2	2361.966	5.32	28.99	38.14	56.58	52.75	74.00	-21.25	peak
3	2390.000	5.34	29.08	38.14	48.27	44.55	74.00	-29.45	peak
4	pp 2401.803	5.35	29.11	38.15	101.70	98.01	74.00	24.01	peak

Mode:c; Polarization:Horizontal; Modulation Type: GFSK; Channel:High




Condition: 3m Horizontal

Job No: : 04905CR

Mode: : 2480 Band edge  
: BLE

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit	Over Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp	2479.457	5.40	29.34	38.15	103.07	99.66	74.00	25.66 peak
2		2483.500	5.41	29.35	38.15	56.64	53.25	74.00	-20.75 peak

Mode:c; Polarization:Vertical; Modulation Type: GFSK; Channel:High



Condition: 3m Vertical  
Job No: : 04905CR  
Mode: : 2480 Band edge  
: BLE

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit	Remark
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp	2479.407	5.40	29.34	38.15	100.51	97.10	74.00	23.10 peak
2		2483.500	5.41	29.35	38.15	53.91	50.52	74.00	-23.48 peak

## 7.8 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 &amp; 15.209

Test Method: ANSI C63.10 (2013) Section 11.12

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.8.1 E.U.T. Operation


Operating Environment:

Temperature: 25 °C      Humidity: 55 % RH      Atmospheric Pressure: 1015 mbar

Pretest these mode to find the worst case:  
b: Tx mode, Keep the EUT in transmitting mode with GFSK modulation.  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

The worst case for final test:  
c: Tx mode+ Charging, Keep the EUT in transmitting mode with GFSK modulation and being charging with adapter.

### 7.8.2 Test Setup Diagram




### **7.8.3 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

**Radiated Emission below 1GHz**

Mode:c; Polarization:Horizontal




Condition: 3m HORIZONTAL

Job No. : 04905CR

Test mode: c

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.86	0.60	17.10	27.35	34.82	25.17	40.00	-14.83
2	82.36	1.10	7.94	27.23	39.86	21.67	40.00	-18.33
3	182.56	1.37	9.95	26.77	42.69	27.24	43.50	-16.26
4 pp	250.30	1.68	12.31	26.54	44.75	32.20	46.00	-13.80
5	399.03	2.20	16.29	27.13	39.78	31.14	46.00	-14.86
6	993.01	3.69	24.02	26.33	26.43	27.81	54.00	-26.19

Mode:c; Polarization:Vertical



Condition: 3m VERTICAL

Job No. : 04905CR

Test mode: c

Freq	Cable	Ant	Preamp	Read	Limit	Over	Remark	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	32.98	0.60	17.03	27.34	42.45	32.74	40.00	-7.26
2	55.22	0.80	7.92	27.28	43.13	24.57	40.00	-15.43
3	79.52	1.08	7.66	27.23	50.91	32.42	40.00	-7.58
4	129.92	1.28	7.70	27.01	49.55	31.52	43.50	-11.98
5	182.56	1.37	9.95	26.77	49.72	34.27	43.50	-9.23
6 pp	254.73	1.70	12.39	26.52	51.36	38.93	46.00	-7.07

**Transmitter Emission above 1GHz**

Test mode:		GFSK(DH1)		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
3610.398	32.53	7.67	38.52	46.10	47.78	74.00	-26.22	Vertical		
4804.000	34.16	8.87	39.03	47.67	51.67	74.00	-22.33	Vertical		
6069.413	34.76	10.47	38.96	46.08	52.35	74.00	-21.65	Vertical		
7206.000	36.42	10.68	38.18	42.84	51.76	74.00	-22.24	Vertical		
9608.000	37.52	12.50	36.99	38.06	51.09	74.00	-22.91	Vertical		
12676.420	38.86	14.65	38.99	37.55	52.07	74.00	-21.93	Vertical		
3759.672	32.95	7.73	38.59	46.44	48.53	74.00	-25.47	Horizontal		
4804.000	34.16	8.87	39.03	54.03	58.03	74.00	-15.97	Horizontal		
6393.941	35.02	10.06	38.75	47.49	53.82	74.00	-20.18	Horizontal		
7206.000	36.42	10.68	38.18	47.26	56.18	74.00	-17.82	Horizontal		
9608.000	37.52	12.50	36.99	37.00	50.03	74.00	-23.97	Horizontal		
12639.790	38.87	14.55	38.95	39.01	53.48	74.00	-20.52	Horizontal		

Test mode:		GFSK(DH1)		Test channel:		Lowest		Remark:		Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
4804.000	34.15	8.86	39.03	45.81	49.79	54.00	-4.21	Horizontal		
7206.000	36.42	10.68	38.18	40.19	49.11	54.00	-4.89	Horizontal		

Test mode:		GFSK(DH1)		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit (dB)	Polarization		
3589.562	32.46	7.66	38.51	46.12	47.73	74.00	-26.27	Vertical		
4880.000	34.29	8.97	39.06	49.62	53.82	74.00	-20.18	Vertical		
6087.002	34.77	10.45	38.94	46.61	52.89	74.00	-21.11	Vertical		
7320.000	36.37	10.72	38.07	43.27	52.29	74.00	-21.71	Vertical		
9760.000	37.55	12.58	36.92	40.01	53.22	74.00	-20.78	Vertical		
12713.160	38.86	14.75	39.02	38.43	53.02	74.00	-20.98	Vertical		
3825.521	33.13	7.75	38.62	45.85	48.11	74.00	-25.89	Horizontal		
4880.000	34.29	8.97	39.06	56.67	60.87	74.00	-13.13	Horizontal		
6140.076	34.82	10.38	38.91	46.25	52.54	74.00	-21.46	Horizontal		
7320.000	36.37	10.72	38.07	44.63	53.65	74.00	-20.35	Horizontal		
9760.000	37.55	12.58	36.92	40.13	53.34	74.00	-20.66	Horizontal		
12603.270	38.88	14.44	38.91	38.14	52.55	74.00	-21.45	Horizontal		

Test mode:		GFSK(DH1)		Test channel:		Middle		Remark:		Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Cable Loss (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit (dB)	Polarization		
4880.000	34.29	8.97	39.06	46.21	50.41	54.00	-3.59	Horizontal		

Test mode:		GFSK(DH1)		Test channel:		Highest		Remark:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit (dB)	Polarization	
3825.521	33.13	7.75	38.62	45.65	47.91	74.00	-26.09	Vertical	
4960.000	34.43	9.09	39.09	48.68	53.11	74.00	-20.89	Vertical	
6069.413	34.76	10.47	38.96	45.54	51.81	74.00	-22.19	Vertical	
7440.000	36.32	10.77	37.94	42.22	51.37	74.00	-22.63	Vertical	
9920.000	37.58	12.67	36.84	40.36	53.77	74.00	-20.23	Vertical	
12603.270	38.88	14.44	38.91	38.54	52.95	74.00	-21.05	Vertical	
3781.495	33.01	7.73	38.60	45.50	47.64	74.00	-26.36	Horizontal	
4960.000	34.43	9.09	39.09	54.14	58.57	74.00	-15.43	Horizontal	
6338.673	34.97	10.13	38.79	46.39	52.70	74.00	-21.30	Horizontal	
7440.000	36.32	10.77	37.94	42.78	51.93	74.00	-22.07	Horizontal	
9920.000	37.58	12.67	36.84	40.31	53.72	74.00	-20.28	Horizontal	
12639.790	38.87	14.55	38.95	38.41	52.88	74.00	-21.12	Horizontal	

Test mode:		GFSK(DH1)		Test channel:		Highest		Remark:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over limit (dB)	Polarization	
4960.000	34.43	9.09	39.09	44.8	49.23	54.00	-4.77	Horizontal	

**Remark:**

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

## 8 Photographs

### 8.1 Conducted Disturbance at AC Power Line (150kHz-30MHz) Test Setup



## 8.2 Radiated Spurious Emissions Test Setup



### **8.3 EUT Constructional Details**


Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1705004905CR.


## **9 Appendix**


### **9.1 Appendix 15.247**

#### **1.6dB Bandwidth**

Test Mode	Test Channel	EBW[MHz]	Limit	Verdict
BLE	2402	0.537	>=0.5	PASS
BLE	2440	0.537	>=0.5	PASS
BLE	2480	0.546	>=0.5	PASS










### 3. Maximum peak conducted output power

Test Mode	Test Channel	Power[dBm]	Limit[dBm]	Verdict
BLE	2402	-7.6	<30	PASS
BLE	2440	-7.15	<30	PASS
BLE	2480	-7.43	<30	PASS










#### **4. Maximum Peak power spectral density**

Test Mode	Test Channel	PSD[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	2402	-26.15	<8.00	PASS
BLE	2440	-25.69	<8.00	PASS
BLE	2480	-25.97	<8.00	PASS









**5. Band-edge for RF Conducted Emissions**

Test Mode	Test Channel	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	2402	-8.740	-54.327	<-28.74	PASS
BLE	2480	-8.590	-66.691	<-28.59	PASS





**6.RF Conducted Spurious Emissions**

Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref [dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BLE	2402	30	10000	1000	3000	-8.7	-52.980	<-28.7	PASS
BLE	2402	10000	25000	1000	3000	-8.7	-69.960	<-28.7	PASS
BLE	2440	30	10000	1000	3000	-8.25	-53.640	<-28.25	PASS
BLE	2440	10000	25000	1000	3000	-8.25	-69.970	<-28.25	PASS
BLE	2480	30	10000	1000	3000	-8.52	-53.920	<-28.52	PASS
BLE	2480	10000	25000	1000	3000	-8.52	-69.550	<-28.52	PASS

