

Certification Exhibit

FCC ID: 2ADDK360FLY4K IC: 12404A-360FLY4K

FCC Rule Part: 15.247 IC Radio Standards Specification: RSS-247

ACS Project Number: 16-2006

Manufacturer: 360fly, Inc. Model: 360FLY4K

RF Exposure

General Information:

Applicant: 360fly, Inc.
ACS Project: 16-2006
Device Category: Mobile

Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Loop Antenna

Antenna Gain: 0.03 dBi (2.4 GHz), 1.9 dBi (5 GHz)

Maximum Transmitter Conducted Power (2.4 GHz): 14.93 dBm, 31.117 mW

Maximum Transmitter Conducted Power (5 GHz): 12.28 dBm, 16.904 mW

Maximum System EIRP (2.4 GHz): 14.96 dBm, 31.333 mW

Maximum System EIRP (5 GHz): 14.18 dBm, 26.182 mW

Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: FCC Maximum Permissible Exposure

Table 111 of maximum 1 of models appears											
MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*											
Radio	Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)			
BLE	2402	1.03	1.00	1.27	0.03	1.007	20	0.000			
BT	2402	10.8	1.00	12.02	0.03	1.007	20	0.002			
2.4 GHz WLAN	2412	14.93	1.00	31.12	0.03	1.007	20	0.006			
5 GHz WLAN	5180	12.28	1.00	16.90	1.9	1.549	20	0.005			

Table 2: Innovation Science Economic Development Canada Maximum Permissible Exposure

Table 2: Illiovation colonic Economic Development canada maximam i erimosible Exposure										
MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*										
Radio	Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (W/m2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (W/m^2)		
BLE	2402	1.03	5.35	1.27	0.03	1.007	20	0.003		
BT	2402	10.8	5.35	12.02	0.03	1.007	20	0.024		
2.4 GHz WLAN	2412	14.93	5.37	31.12	0.03	1.007	20	0.062		
5 GHz WLAN	5180	12.28	9.05	16.90	1.9	1.549	20	0.052		

Model: 360FLY4K FCC ID: 2ADDK360FLY4K IC: 12404A-360FLY4K

Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.