Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5647.420	15.45	38.33	53.78	68.20	-14.42	peak	
2		5674.300	15.15	38.40	53.55	86.22	-32.67	peak	
3		5704.300	14.91	38.48	53.39	106.41	-53.02	peak	
4		5724.820	16.90	38.53	55.43	121.79	-66.36	peak	
5		5745.000	57.05	38.58	95.63	122.20	-26.57	peak	No Limit
6	*	5745.000	46.15	38.58	84.73	54.00	30.73	AVG	No Limit

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11490.00	54.57	3.40	57.97	74.00	-16.03	peak	
2	*	11490.00	41.86	3.40	45.26	54.00	-8.74	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5645.335	15.95	38.31	54.26	68.20	-13.94	peak	
2		5683.300	16.12	38.42	54.54	92.88	-38.34	peak	
3		5714.200	15.03	38.50	53.53	109.18	-55.65	peak	
4		5723.190	16.24	38.53	54.77	118.07	-63.30	peak	
5		5745.000	49.64	38.58	88.22	122.20	-33.98	peak	No Limit
6	*	5745.000	38.96	38.58	77.54	54.00	23.54	AVG	No Limit

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11490.00	53.62	3.40	57.02	74.00	-16.98	peak	
2	*	11490.00	39.82	3.40	43.22	54.00	-10.78	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5697.210	15.22	38.46	53.68	103.14	-49.46	peak	
2		5712.260	15.51	38.50	54.01	108.64	-54.63	peak	
3		5723.235	15.27	38.53	53.80	118.18	-64.38	peak	
4		5785.000	62.87	38.70	101.57	122.20	-20.63	peak	No Limit
5	*	5785.000	52.90	38.70	91.60	54.00	37.60	AVG	No Limit
6		5854.050	15.46	38.89	54.35	112.97	-58.62	peak	
7		5869.120	15.42	38.92	54.34	106.84	-52.50	peak	
8		5884.310	14.70	38.96	53.66	98.29	-44.63	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11570.00	54.33	3.28	57.61	74.00	-16.39	peak	
2	*	11570.00	42.54	3.28	45.82	54.00	-8.18	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5698.365	14.51	38.46	52.97	104.00	-51.03	peak	
2		5705.260	14.06	38.48	52.54	106.67	-54.13	peak	
3		5722.315	15.86	38.53	54.39	116.08	-61.69	peak	
4		5785.000	54.31	38.70	93.01	122.20	-29.19	peak	No Limit
5	*	5785.000	43.81	38.70	82.51	54.00	28.51	AVG	No Limit
6		5854.780	16.13	38.89	55.02	111.30	-56.28	peak	
7		5864.440	14.98	38.91	53.89	108.15	-54.26	peak	
8		5880.510	14.64	38.96	53.60	101.11	-47.51	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11570.00	53.95	3.28	57.23	74.00	-16.77	peak	
2	*	11570.00	39.93	3.28	43.21	54.00	-10.79	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5805MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5715.635	15.15	38.51	53.66	109.58	-55.92	peak	
2		5723.309	15.88	38.53	54.41	118.35	-63.94	peak	
3		5805.000	61.14	38.75	99.89	122.20	-22.31	peak	No Limit
4	*	5805.000	52.18	38.75	90.93	54.00	36.93	AVG	No Limit
5		5850.655	15.83	38.87	54.70	120.71	-66.01	peak	
6		5871.160	14.40	38.93	53.33	106.27	-52.94	peak	
7		5883.220	14.75	38.96	53.71	99.10	-45.39	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5805MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11610.00	53.94	3.21	57.15	74.00	-16.85	peak	
2	*	11610.00	40.82	3.21	44.03	54.00	-9.97	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5805MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5714.210	14.82	38.50	53.32	109.18	-55.86	peak	
2		5724.884	16.47	38.53	55.00	121.94	-66.94	peak	
3		5805.000	51.97	38.75	90.72	122.20	-31.48	peak	No Limit
4	*	5805.000	42.91	38.75	81.66	54.00	27.66	AVG	No Limit
5		5853.480	15.94	38.89	54.83	114.26	-59.43	peak	
6		5858.060	14.17	38.89	53.06	109.94	-56.88	peak	
7		5879.470	14.77	38.96	53.73	101.88	-48.15	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX A Mode 5805MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11610.00	54.08	3.21	57.29	74.00	-16.71	peak	
2	*	11610.00	40.18	3.21	43.39	54.00	-10.61	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5649.170	15.61	38.33	53.94	68.20	-14.26	peak	
2		5662.400	14.19	38.36	52.55	77.41	-24.86	peak	
3		5710.760	14.82	38.50	53.32	108.22	-54.90	peak	
4		5724.305	16.05	38.53	54.58	120.62	-66.04	peak	
5		5745.000	54.56	38.58	93.14	122.20	-29.06	peak	No Limit
6	*	5745.000	44.93	38.58	83.51	54.00	29.51	AVG	No Limit

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5745MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11490.00	54.92	3.40	58.32	74.00	-15.68	peak	
2	*	11490.00	42.63	3.40	46.03	54.00	-7.97	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5645.575	15.45	38.31	53.76	68.20	-14.44	peak	
2		5664.200	15.31	38.36	53.67	78.74	-25.07	peak	
3		5709.880	15.82	38.50	54.32	107.97	-53.65	peak	
4		5721.175	15.75	38.52	54.27	113.48	-59.21	peak	
5		5745.000	45.75	38.58	84.33	122.20	-37.87	peak	No Limit
6	*	5745.000	36.07	38.58	74.65	54.00	20.65	AVG	No Limit

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5745MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11490.00	54.43	3.40	57.83	74.00	-16.17	peak	
2	*	11490.00	41.79	3.40	45.19	54.00	-8.81	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5686.095	15.46	38.43	53.89	94.94	-41.05	peak	
2		5704.920	15.50	38.48	53.98	106.58	-52.60	peak	
3		5722.995	15.50	38.53	54.03	117.63	-63.60	peak	
4		5785.000	61.11	38.70	99.81	122.20	-22.39	peak	No Limit
5	*	5785.000	51.84	38.70	90.54	54.00	36.54	AVG	No Limit
6		5850.505	16.20	38.87	55.07	121.05	-65.98	peak	
7		5860.980	14.87	38.90	53.77	109.12	-55.35	peak	
8		5882.080	13.69	38.96	52.65	99.94	-47.29	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5785MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11570.00	54.52	3.28	57.80	74.00	-16.20	peak	
2	*	11570.00	42.94	3.28	46.22	54.00	-7.78	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5697.630	15.14	38.46	53.60	103.45	-49.85	peak	
2		5709.620	15.00	38.49	53.49	107.90	-54.41	peak	
3		5721.455	15.22	38.52	53.74	114.12	-60.38	peak	
4		5785.000	51.92	38.70	90.62	122.20	-31.58	peak	No Limit
5	*	5785.000	42.38	38.70	81.08	54.00	27.08	AVG	No Limit
6		5852.290	15.56	38.87	54.43	116.98	-62.55	peak	
7		5855.540	14.69	38.89	53.58	110.65	-57.07	peak	
8		5875.080	14.33	38.94	53.27	105.14	-51.87	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5785MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11570.00	54.15	3.28	57.43	74.00	-16.57	peak	
2	*	11570.00	39.97	3.28	43.25	54.00	-10.75	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5805MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5710.850	14.80	38.50	53.30	108.24	-54.94	peak	
2		5722.710	16.14	38.53	54.67	116.98	-62.31	peak	
3		5805.000	61.92	38.75	100.67	122.20	-21.53	peak	No Limit
4	*	5805.000	52.42	38.75	91.17	54.00	37.17	AVG	No Limit
5		5852.265	16.07	38.87	54.94	117.03	-62.09	peak	
6		5862.900	16.20	38.91	55.11	108.59	-53.48	peak	
7		5881.810	14.61	38.96	53.57	100.14	-46.57	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5805MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11610.00	53.92	3.21	57.13	74.00	-16.87	peak	
2	*	11610.00	40.80	3.21	44.01	54.00	-9.99	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5805MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5712.020	14.11	38.50	52.61	108.57	-55.96	peak	
2		5722.820	15.43	38.53	53.96	117.23	-63.27	peak	
3		5805.000	54.10	38.75	92.85	122.20	-29.35	peak	No Limit
4	*	5805.000	44.97	38.75	83.72	54.00	29.72	AVG	No Limit
5		5851.500	15.43	38.87	54.30	118.78	-64.48	peak	
6		5856.440	14.71	38.89	53.60	110.40	-56.80	peak	
7		5890.750	14.82	38.99	53.81	93.51	-39.70	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N20 Mode 5805MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11610.00	53.92	3.21	57.13	74.00	-16.87	peak	
2	*	11610.00	40.17	3.21	43.38	54.00	-10.62	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5755MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5640.785	14.24	38.31	52.55	68.20	-15.65	peak	
2		5688.550	15.02	38.43	53.45	96.76	-43.31	peak	
3		5719.100	16.16	38.52	54.68	110.55	-55.87	peak	
4		5724.090	19.18	38.53	57.71	120.13	-62.42	peak	
5		5755.000	57.24	38.62	95.86	122.20	-26.34	peak	No Limit
6	*	5755.000	46.98	38.62	85.60	54.00	31.60	AVG	No Limit
7		5850.805	16.07	38.87	54.94	120.36	-65.42	peak	
8		5862.060	16.71	38.91	55.62	108.82	-53.20	peak	
9		5910.000	13.97	39.04	53.01	79.27	-26.26	peak	
10		5928.030	14.31	39.08	53.39	68.20	-14.81	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5755MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11510.00	54.65	3.40	58.05	74.00	-15.95	peak	
2	*	11510.00	42.32	3.40	45.72	54.00	-8.28	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5755MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5641.355	14.72	38.31	53.03	68.20	-15.17	peak	
2		5658.550	14.32	38.35	52.67	74.55	-21.88	peak	
3		5710.860	15.30	38.50	53.80	108.24	-54.44	peak	
4		5720.670	16.38	38.52	54.90	112.33	-57.43	peak	
5		5755.000	49.60	38.62	88.22	122.20	-33.98	peak	No Limit
6	*	5755.000	39.83	38.62	78.45	54.00	24.45	AVG	No Limit
7		5852.540	15.91	38.87	54.78	116.41	-61.63	peak	
8		5866.260	14.13	38.92	53.05	107.64	-54.59	peak	
9		5917.250	13.46	39.06	52.52	73.91	-21.39	peak	
10		5926.500	14.21	39.08	53.29	68.20	-14.91	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5755MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11510.00	55.02	3.40	58.42	74.00	-15.58	peak	
2	*	11510.00	42.33	3.40	45.73	54.00	-8.27	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5795MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5645.765	14.03	38.31	52.34	68.20	-15.86	peak	
2		5664.850	14.00	38.36	52.36	79.22	-26.86	peak	
3		5715.460	14.80	38.50	53.30	109.53	-56.23	peak	
4		5723.050	16.00	38.53	54.53	117.76	-63.23	peak	
5		5795.000	58.81	38.72	97.53	122.20	-24.67	peak	No Limit
6	*	5795.000	48.40	38.72	87.12	54.00	33.12	AVG	No Limit
7		5852.845	15.79	38.88	54.67	115.71	-61.04	peak	
8		5871.840	15.27	38.93	54.20	106.08	-51.88	peak	
9		5896.350	14.51	38.99	53.50	89.36	-35.86	peak	
10		5929.080	15.18	39.09	54.27	68.20	-13.93	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5795MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11590.00	54.94	3.25	58.19	74.00	-15.81	peak	
2	*	11590.00	42.77	3.25	46.02	54.00	-7.98	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5795MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5632.290	15.40	38.28	53.68	68.20	-14.52	peak	
2		5693.500	14.55	38.45	53.00	100.41	-47.41	peak	
3		5712.840	14.48	38.50	52.98	108.80	-55.82	peak	
4		5723.820	16.86	38.53	55.39	119.51	-64.12	peak	
5		5795.000	48.44	38.72	87.16	122.20	-35.04	peak	No Limit
6	*	5795.000	38.22	38.72	76.94	54.00	22.94	AVG	No Limit
7		5850.295	15.56	38.87	54.43	121.53	-67.10	peak	
8		5870.120	14.89	38.92	53.81	106.56	-52.75	peak	
9		5909.950	14.05	39.04	53.09	79.30	-26.21	peak	
10		5931.540	14.30	39.09	53.39	68.20	-14.81	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX N40 Mode 5795MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11590.00	54.10	3.25	57.35	74.00	-16.65	peak	
2	*	11590.00	40.24	3.25	43.49	54.00	-10.51	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX AC80 Mode 5210MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5049.900	14.87	37.43	52.30	74.00	-21.70	peak	
2		5049.900	1.16	37.43	38.59	54.00	-15.41	AVG	
3	X	5210.000	50.57	37.61	88.18	74.00	14.18	peak	No Limit
4	*	5210.000	41.51	37.61	79.12	54.00	25.12	AVG	No Limit
5		5409.760	13.31	37.83	51.14	74.00	-22.86	peak	
6		5409.760	0.50	37.83	38.33	54.00	-15.67	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX AC80 Mode 5210MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	10420.00	53.16	1.95	55.11	68.20	-13.09	peak	

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX AC80 Mode 5210MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5149.580	13.90	37.54	51.44	74.00	-22.56	peak	
2		5149.580	0.65	37.54	38.19	54.00	-15.81	AVG	
3	X	5210.000	48.37	37.61	85.98	74.00	11.98	peak	No Limit
4	*	5210.000	38.90	37.61	76.51	54.00	22.51	AVG	No Limit
5		5351.680	14.03	37.76	51.79	74.00	-22.21	peak	
6		5351.680	0.42	37.76	38.18	54.00	-15.82	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-1/ TX AC80 Mode 5210MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	10420.00	53.94	1.95	55.89	68.20	-12.31	peak	

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX AC80 Mode 5290MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5130.200	14.36	37.52	51.88	74.00	-22.12	peak	
2		5130.200	1.26	37.52	38.78	54.00	-15.22	AVG	
3	X	5290.000	46.62	37.69	84.31	74.00	10.31	peak	No Limit
4	*	5290.000	37.12	37.69	74.81	54.00	20.81	AVG	No Limit
5		5370.160	13.80	37.78	51.58	74.00	-22.42	peak	
6		5370.160	1.33	37.78	39.11	54.00	-14.89	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX AC80 Mode 5290MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		10580.00	54.27	2.11	56.38	68.20	-11.82	peak	
2	*	10580.00	41.30	2.11	43.41	54.00	-10.59	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX AC80 Mode 5290MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5104.520	14.11	37.49	51.60	74.00	-22.40	peak	
2		5104.520	1.17	37.49	38.66	54.00	-15.34	AVG	
3	X	5290.000	43.15	37.69	80.84	74.00	6.84	peak	
4	*	5290.000	33.54	37.69	71.23	54.00	17.23	AVG	
5		5482.020	13.82	37.90	51.72	74.00	-22.28	peak	
6		5482.020	1.19	37.90	39.09	54.00	-14.91	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2A/ TX AC80 Mode 5290MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		10580.00	53.18	2.11	55.29	68.20	-12.91	peak	
2	*	10580.00	39.19	2.11	41.30	54.00	-12.70	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5530MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5449.990	13.55	37.87	51.42	74.00	-22.58	peak	
2		5449.990	2.15	37.87	40.02	54.00	-13.98	AVG	
3		5461.590	14.77	37.88	52.65	68.20	-15.55	peak	
4	X	5530.000	47.77	38.00	85.77	74.00	11.77	peak	No Limit
5	*	5530.000	39.05	38.00	77.05	54.00	23.05	AVG	No Limit
6		5729.410	15.89	38.55	54.44	68.20	-13.76	peak	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5530MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11060.00	55.02	2.92	57.94	74.00	-16.06	peak	
2	*	11060.00	43.69	2.92	46.61	54.00	-7.39	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5530MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5449.990	13.16	37.87	51.03	74.00	-22.97	peak	
2		5449.990	1.75	37.87	39.62	54.00	-14.38	AVG	
3		5460.880	14.85	37.88	52.73	68.20	-15.47	peak	
4	X	5530.000	41.17	38.00	79.17	74.00	5.17	peak	No Limit
5	*	5530.000	32.19	38.00	70.19	54.00	16.19	AVG	No Limit
6		5725.670	15.90	38.53	54.43	68.20	-13.77	peak	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5530MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11060.00	54.80	2.92	57.72	74.00	-16.28	peak	
2	*	11060.00	43.29	2.92	46.21	54.00	-7.79	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5610MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5450.050	13.28	37.87	51.15	74.00	-22.85	peak	
2		5450.050	1.98	37.87	39.85	54.00	-14.15	AVG	
3		5462.570	15.25	37.88	53.13	68.20	-15.07	peak	
4	X	5610.000	53.58	38.22	91.80	74.00	17.80	peak	No Limit
5	*	5610.000	44.02	38.22	82.24	54.00	28.24	AVG	No Limit
6		5768.775	14.17	38.65	52.82	68.20	-15.38	peak	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5610MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11220.00	54.71	3.10	57.81	74.00	-16.19	peak	
2	*	11220.00	43.19	3.10	46.29	54.00	-7.71	AVG	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5610MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5448.500	12.50	37.87	50.37	74.00	-23.63	peak	
2		5448.500	1.67	37.87	39.54	54.00	-14.46	AVG	
3		5464.450	14.74	37.88	52.62	68.20	-15.58	peak	
4	X	5610.000	43.96	38.22	82.18	74.00	8.18	peak	No Limit
5	*	5610.000	34.34	38.22	72.56	54.00	18.56	AVG	No Limit
6		5787.220	14.38	38.70	53.08	68.20	-15.12	peak	

Orthogonal Axis :	X
Test Mode :	UNII-2C/ TX AC80 Mode 5610MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11220.00	54.77	3.10	57.87	74.00	-16.13	peak	
2	*	11220.00	42.73	3.10	45.83	54.00	-8.17	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX AC80 Mode 5775MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5622.375	13.82	38.26	52.08	68.20	-16.12	peak	
2		5674.300	14.71	38.40	53.11	86.22	-33.11	peak	
3		5716.540	15.54	38.51	54.05	109.83	-55.78	peak	
4		5720.800	16.17	38.52	54.69	112.62	-57.93	peak	
5		5775.000	53.67	38.67	92.34	122.20	-29.86	peak	No Limit
6	*	5775.000	44.52	38.67	83.19	54.00	29.19	AVG	No Limit
7		5854.940	16.40	38.89	55.29	110.94	-55.65	peak	
8		5856.780	15.03	38.89	53.92	110.30	-56.38	peak	
9		5892.750	13.57	38.99	52.56	92.03	-39.47	peak	
10		5925.700	14.25	39.08	53.33	68.20	-14.87	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX AC80 Mode 5775MHz

Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11550.00	54.65	3.32	57.97	74.00	-16.03	peak	
2	*	11550.00	42.83	3.32	46.15	54.00	-7.85	AVG	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX AC80 Mode 5775MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		5581.875	13.17	38.14	51.31	68.20	-16.89	peak	
2		5682.650	14.77	38.41	53.18	92.40	-39.22	peak	
3		5703.060	14.86	38.47	53.33	106.06	-52.73	peak	
4		5722.540	16.27	38.53	54.80	116.59	-61.79	peak	
5		5775.000	45.36	38.67	84.03	122.20	-38.17	peak	No Limit
6	*	5775.000	35.50	38.67	74.17	54.00	20.17	AVG	No Limit
7		5854.720	15.79	38.89	54.68	111.44	-56.76	peak	
8		5855.160	14.56	38.89	53.45	110.76	-57.31	peak	
9		5910.400	13.91	39.04	52.95	78.97	-26.02	peak	
10		5984.600	14.73	39.24	53.97	68.20	-14.23	peak	

Orthogonal Axis:	X
Test Mode:	UNII-3/TX AC80 Mode 5775MHz

Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		11550.00	53.69	3.32	57.01	74.00	-16.99	peak	
2	*	11550.00	40.09	3.32	43.41	54.00	-10.59	AVG	

APPENDIX E - BANDWIDTH

Test Mode: UNII-1/TX A Mode_CH36/CH40/CH48

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH36	5180	23.19	17.10
CH40	5200	21.39	17.00
CH48	5240	21.49	17.00

TX CH36



Date: 17.JAN.2018 13:17:30

TX CH40



Date: 17.JAN.2018 13:19:23

TX CH48



Date: 17.JAN.2018 13:20:46

Test Mode: UNII-1/TX N20 Mode_CH36/CH40/CH48

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH36	5180	22.29	18.00
CH40	5200	22.39	18.00
CH48	5240	22.29	18.00

TX CH36



Date: 17.JAN.2018 13:42:48

TX CH40



Date: 17.JAN.2018 13:44:22

TX CH48



Date: 17.JAN.2018 13:45:35

Test Mode: UNII-1/TX N40 Mode_CH38/CH46			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH38	5190	46.59	37.80
CH46	5230	45.99	37.60

TX CH38



Date: 17.JAN.2018 15:46:03

TX CH46



Date: 17.JAN.2018 15:47:17

Test Mode: UNII-2A/TX A Mode_CH52/CH60/CH64

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH52	5260	21.35	16.90
CH60	5300	21.39	17.00
CH64	5320	21.40	17.00

TX CH52



Date: 17.JAN.2018 13:22:07

TX CH60



Date: 17.JAN.2018 13:23:58

TX CH64



Date: 17.JAN.2018 13:25:34

Test Mode: UNII-2A/TX N20 Mode_CH52/CH60/CH64

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH52	5260	22.15	18.00
CH60	5300	22.09	18.00
CH64	5320	22.31	18.00

TX CH52



Date: 17.JAN.2018 13:47:07

TX CH60



Date: 17.JAN.2018 13:48:25

TX CH64



Date: 17.JAN.2018 13:49:46

Test Mode: UNII-2A/TX N40 Mode_CH54/CH62

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH54	5270	46.10	37.60
CH62	5310	46.10	37.60

TX CH54



Date: 17.JAN.2018 17:03:10

TX CH62



Date: 17.JAN.2018 17:04:41

Test Mode: UNII-2C/TX A Mode_CH100/CH116/CH140

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH100	5500	21.49	17.00
CH116	5580	21.20	16.90
CH140	5700	21.30	17.00

TX CH100



Date: 17.JAN.2018 13:27:09

TX CH116



Date: 17.JAN.2018 13:29:50

TX CH140



Date: 17.JAN.2018 13:31:10

Test Mode: UNII-2C/TX N20 Mode_CH100/CH116/CH140

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH100	5500	22.29	18.00
CH116	5580	22.19	18.00
CH140	5700	22.19	18.00

TX CH100



Date: 17.JAN.2018 13:51:37

TX CH116



Date: 17.JAN.2018 13:52:50

TX CH140



Date: 17.JAN.2018 13:54:03

Test Mode: UNII-2C/TX N40 Mode_CH102/CH110/CH134			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH102	5510	45.99	37.60
CH110	5550	45.99	37.60
CH134	5670	45.80	37.60

TX CH102



Date: 17.JAN.2018 17:06:21

TX CH110



Date: 17.JAN.2018 17:07:48

TX CH134



Date: 17.JAN.2018 17:09:09

Test Mode: UNII-3/ TX A Mode_CH149/CH157/CH161				
Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
CH149	5745	16.65	16.60	>=500
CH157	5785	16.70	16.60	>=500
CH161	5805	16.61	16.50	>=500

TX CH 149



Date: 17.JAN.2018 13:32:33

TX CH 157



Date: 17.JAN.2018 13:33:54

TX CH 161



Date: 17.JAN.2018 13:35:14

Test Mode: UNII-3/ TX N20 Mode_CH149/CH157/CH161

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
CH149	5745	17.85	17.70	>=500
CH157	5785	17.75	17.70	>=500
CH161	5805	17.86	17.70	>=500

TX CH 149



Date: 17.JAN.2018 13:55:23

TX CH 157



Date: 17.JAN.2018 13:57:43

TX CH 161



Date: 17.JAN.2018 13:59:02

Test Mode: UNII-3/ TX N40 Mode_CH151/CH159

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
CH151	5755	36.70	36.60	>=500
CH159	5795	36.60	36.20	>=500

TX CH 151



Date: 17.JAN.2018 17:10:36

TX CH 159



Date: 17.JAN.2018 17:12:14

Test Mode: UNII-1/TX AC20 Mode_CH36/CH40/CH48			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH36	5180	22.29	18.00
CH40	5200	22.29	18.00
CH48	5240	22.30	18.00

TX CH36



Date: 17.JAN.2018 14:42:30

TX CH40



Date: 17.JAN.2018 14:45:07

TX CH48



Date: 17.JAN.2018 14:48:00

Test Mode: UNII-1/TX AC40 Mode_CH38/CH46

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH38	5190	46.39	37.60
CH46	5230	46.00	37.40

TX CH38



Date: 17.JAN.2018 17:23:18

TX CH46



Date: 17.JAN.2018 17:24:41

Test Mode: UNII-1/TX AC80 Mode_CH42

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH42	5210	83.59	75.60

TX CH42



Date: 17.JAN.2018 18:53:42

Test Mode: UNII-2A/TX AC20 Mode_CH52/CH60/CH64

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH52	5260	22.29	18.00
CH60	5300	22.19	18.00
CH64	5320	22.19	17.90

TX CH52



Date: 17.JAN.2018 14:49:12

TX CH60



Date: 17.JAN.2018 14:50:33

TX CH64



Date: 17.JAN.2018 14:51:47

Test Mode: UNII-2A/TX AC40 Mode_CH54/CH62			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH54	5270	45.99	37.60
CH62	5310	46.19	37.80

TX CH54



Date: 17.JAN.2018 17:26:08

TX CH62



Date: 17.JAN.2018 17:27:29

Test Mode: UNII-2A/TX AC80 Mode_CH58

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH58	5290	83.60	75.60

TX CH58



Date: 17.JAN.2018 18:55:11

Test Mode: UNII-2C/TX AC20 Mode_CH100/CH116/CH140

Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH100	5500	22.19	18.00
CH116	5580	22.19	18.00
CH140	5700	22.29	18.00

TX CH100



Date: 17.JAN.2018 14:53:06

TX CH116



Date: 17.JAN.2018 14:54:18

TX CH140



Date: 17.JAN.2018 14:55:44

Test Mode: UNII-2C/TX AC40 Mode_CH102/CH110/CH134			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH102	5510	45.60	37.60
CH110	5550	46.31	37.60
CH134	5670	45.79	37.60

TX CH102



Date: 17.JAN.2018 17:29:01

TX CH110



Date: 17.JAN.2018 17:30:33

TX CH134



Date: 17.JAN.2018 17:33:20

Test Mode: UNII-2C/TX AC80 Mode_CH106/CH122			
Channel	Frequency (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
CH106	5530	83.40	75.60
CH122	5610	83.00	75.60

TX CH106



Date: 17.JAN.2018 18:56:37

TX CH122



Date: 17.JAN.2018 18:58:16

Test Mode: UNII-3/ TX AC20 Mode_CH149/CH157/CH161

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
CH149	5745	17.85	17.70	>=500
CH157	5785	17.75	17.70	>=500
CH161	5805	17.90	17.80	>=500

TX CH 149



Date: 17.JAN.2018 14:57:06

TX CH 157



Date: 17.JAN.2018 14:58:23

TX CH 161



Date: 17.JAN.2018 14:59:51

Test Mode: UNII-3/ TX AC40 Mode_CH151/CH159

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
CH151	5755	36.70	36.60	>=500
CH159	5795	36.60	36.20	>=500

TX CH 151



Date: 17.JAN.2018 17:34:54

TX CH 159



Date: 17.JAN.2018 17:36:40

Test Mode: UNII-3/ TX AC80 Mode_CH155

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
CH155	5775	76.41	75.60	>=500

TX CH 155



Date: 17.JAN.2018 19:00:12

APPENDIX F - MAXIMUM OUTPUT POWER

Test Mode: UNII-1/TX A Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH36	5180	10.65	24.00	1.00
CH40	5200	11.28	24.00	1.00
CH48	5240	11.30	24.00	1.00

Test Mode: UNII-1/TX N20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH36	5180	11.05	24.00	1.00
CH40	5200	11.42	24.00	1.00
CH48	5240	11.45	24.00	1.00

Test Mode: UNII-1/TX N40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH38	5190	10.56	24.00	1.00
CH46	5230	10.54	24.00	1.00

Test Mode: UNII-2A/TX A Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH52	5260	10.74	24.00	0.25
CH60	5300	11.37	24.00	0.25
CH64	5320	11.30	24.00	0.25

Test Mode: UNII-2A/TX N20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH52	5260	11.13	24.00	0.25
CH60	5300	11.43	24.00	0.25
CH64	5320	11.15	24.00	0.25

Test Mode: UNII-2A/TX N40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH54	5270	10.31	24.00	0.25
CH62	5310	10.36	24.00	0.25

Test Mode: UNII-2C/TX A Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH100	5500	11.22	23.42	0.25
CH116	5580	11.37	23.42	0.25
CH140	5700	11.30	23.42	0.25

Test Mode: UNII-2C/TX N20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH100	5500	11.25	23.42	0.25
CH116	5580	11.16	23.42	0.25
CH140	5700	11.28	23.42	0.25

Test Mode: UNII-2C/TX N40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH102	5510	10.73	23.42	0.25
CH110	5550	10.74	23.42	0.25
CH134	5670	10.56	23.42	0.25

Test Mode: UNII-3/ TX A Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH149	5745	11.13	29.42	1.00
CH157	5785	11.19	29.42	1.00
CH161	5805	11.08	29.42	1.00

Test Mode: UNII-3/TX N20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH149	5745	11.26	29.42	1.00
CH157	5785	11.33	29.42	1.00
CH161	5805	11.37	29.42	1.00

Test Mode: UNII-3/ TX N40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH151	5755	10.66	29.42	1.00
CH159	5795	10.69	29.42	1.00

Test Mode: UNII-1/TX AC20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH36	5180	9.38	24.00	1.00
CH40	5200	9.58	24.00	1.00
CH48	5240	9.75	24.00	1.00

Test Mode: UNII-1/TX AC40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH38	5190	9.95	24.00	1.00
CH46	5230	9.88	24.00	1.00

Test Mode: UNII-1/TX AC80 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH42	5210	9.93	24.00	1.00

Test Mode: UNII-2A/TX AC20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH52	5260	9.76	24.00	0.25
CH60	5300	9.67	24.00	0.25
CH64	5320	9.80	24.00	0.25

Test Mode: UNII-2A/TX AC40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH54	5270	9.77	24.00	0.25
CH62	5310	9.89	24.00	0.25

Test Mode: UNII-2A/TX AC80 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH58	5290	9.72	24.00	0.25

Test Mode: UNII-2C/TX AC20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH100	5500	9.71	23.42	0.25
CH116	5580	9.89	23.42	0.25
CH140	5700	9.76	23.42	0.25

Test Mode: UNII-2C/TX AC40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH102	5510	9.89	23.42	0.25
CH110	5550	9.63	23.42	0.25
CH134	5670	9.83	23.42	0.25

Test Mode: UNII-2C/TX AC80 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH106	5530	9.87	23.42	0.25
CH122	5610	9.56	23.42	0.25

Test Mode: UNII-3/TX AC20 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH149	5745	9.93	29.42	1.00
CH157	5785	9.69	29.42	1.00
CH161	5805	9.74	29.42	1.00

Test Mode: UNII-3/ TX AC40 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH151	5755	9.70	29.42	1.00
CH159	5795	9.88	29.42	1.00

Test Mode: UNII-3/TX AC80 Mode				
Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)	Limit (Watt)
CH155	5775	9.63	29.42	1.00

APPENDIX G - POWER SPECTRAL DENSITY

Test Mode: UNII-1/ TX A Mode_CH36/CH40/CH48					
Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH36	5180	1.45	0.00	1.45	11.00
CH40	5200	-0.03	0.00	-0.03	11.00
CH48	5240	0.38	0.00	0.38	11.00

CH36



Date: 17.JAN.2018 13:17:43

CH40



Date: 17.JAN.2018 13:19:37

CH48



Date: 17.JAN.2018 13:20:59

Test Mode: UNII-1/TX N20 Mode_CH36/CH40/CH48					
Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH36	5180	-0.07	0.00	-0.07	11.00
CH40	5200	0.57	0.00	0.57	11.00
CH48	5240	0.76	0.00	0.76	11.00

CH36



Date: 17.JAN.2018 13:43:02

CH40



Date: 17.JAN.2018 13:44:35

CH48



Date: 17.JAN.2018 13:45:49

Test Mode: UNII-1/TX N40 Mode_CH38/CH46					
Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH38	5190	-1.43	0.00	-1.43	11.00
CH46	5230	-1.98	0.00	-1.98	11.00

CH38



Date: 17.JAN.2018 15:46:19

CH46



Date: 17.JAN.2018 15:47:33

Test Mode: UNII-2A/ TX A Mode_CH52/CH60/CH64

Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH52	5260	-0.95	0.00	-0.95	11.00
CH60	5300	0.50	0.00	0.50	11.00
CH64	5320	0.79	0.00	0.79	11.00

CH52



Date: 17.JAN.2018 13:22:20

CH60



Date: 17.JAN.2018 13:24:11

CH64



Date: 17.JAN.2018 13:25:48

Test Mode: UNII-2A/TX N20 Mode_CH52/CH60/CH64

Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH52	5260	0.24	0.00	0.24	11.00
CH60	5300	0.27	0.00	0.27	11.00
CH64	5320	0.44	0.00	0.44	11.00

CH52



Date: 17.JAN.2018 13:47:20

CH60



Date: 17.JAN.2018 13:48:38

CH64



Date: 17.JAN.2018 13:49:59

Test Mode: UNII-2A/TX N40 Mode_CH54/CH62					
Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH54	5270	-3.74	0.00	-3.74	11.00
CH62	5310	-3.53	0.00	-3.53	11.00

CH54



Date: 17.JAN.2018 17:03:28

CH62



Date: 17.JAN.2018 17:04:57

Test Mode: UNII-2C/ TX A Mode_CH100/CH116/CH140

Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH100	5500	1.04	0.00	1.04	10.42
CH116	5580	1.14	0.00	1.14	10.42
CH140	5700	-0.65	0.00	-0.65	10.42

CH100



Date: 17.JAN.2018 13:27:22

CH116



Date: 17.JAN.2018 13:30:03

CH140



Date: 17.JAN.2018 13:31:23

Test Mode: UNII-2C/TX N20 Mode_CH100/CH116/CH140

Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH100	5500	0.79	0.00	0.79	10.42
CH116	5580	-0.13	0.00	-0.13	10.42
CH140	5700	-1.11	0.00	-0.13	10.42

CH100



Date: 17.JAN.2018 13:51:50

CH116



Date: 17.JAN.2018 13:53:03

CH140



Date: 17.JAN.2018 13:54:17

Test Mode: UNII-2C/TX N40 Mode_CH102/CH110/CH134

Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH102	5510	-2.93	0.00	-2.93	10.42
CH110	5550	-3.44	0.00	-3.44	10.42
CH134	5670	-4.57	0.00	-4.57	10.42

CH102



Date: 17.JAN.2018 17:06:37

CH110



Date: 17.JAN.2018 17:08:05

CH134



Date: 17.JAN.2018 17:09:25

Test Mode: UNII-3/TX A Mode_CH149/CH157/CH161

Channel	Frequency (MHz)	Power Density (dBm/500kHz)	Duty Factor	Power Density + Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)
CH149	5745	-3.40	0.00	-3.40	29.42
CH157	5785	-3.05	0.00	-3.05	29.42
CH161	5805	-2.71	0.00	-2.71	29.42

TX CH149



Date: 17.JAN.2018 13:32:46

TX CH157



Date: 17.JAN.2018 13:34:07

TX CH161



Date: 17.JAN.2018 13:35:28

Test Mode: UNII-3/ TX N20 Mode_CH149/CH157/CH161

Channel	Frequency (MHz)	Power Density (dBm/500kHz)	Duty Factor	Power Density + Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)
CH149	5745	-3.94	0.00	-3.94	29.42
CH157	5785	-3.58	0.00	-3.58	29.42
CH161	5805	-3.21	0.00	-3.21	29.42

TX CH149



Date: 17.JAN.2018 13:55:37

TX CH157



Date: 17.JAN.2018 13:57:56

TX CH161



Date: 17.JAN.2018 13:59:16

Test Mode: UNII-3/ TX N40 Mode_CH151/CH159

Channel	Frequency (MHz)	Power Density (dBm/500kHz)	Duty Factor	Power Density + Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)
CH151	5755	-7.46	0.00	-7.46	29.42
CH159	5795	-7.14	0.00	-7.14	29.42

TX CH151



Date: 17.JAN.2018 17:10:53

TX CH159



Date: 17.JAN.2018 17:12:31

Test Mode: UNII-1/TX AC80 Mode_CH42					
Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH42	5210	-3.74	0.00	-3.74	11.00

CH42



Date: 17.JAN.2018 18:53:58

Test Mode: UNII-2A/TX AC80 Mode_CH58					
Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH58	5290	-4.87	0.00	-4.87	11.00

CH58



Date: 17.JAN.2018 18:55:28

Test Mode: UNII-2C/TX AC80 Mode_CH106/CH122

Channel	Frequency (MHz)	Power Density (dBm/MHz)	Duty Factor	Power Density + Duty Factor (dBm/MHz)	Limit (dBm/MHz)
CH106	5530	-4.83	0.00	-4.83	10.42
CH122	5610	-6.40	0.00	-6.40	10.42

CH106



Date: 17.JAN.2018 18:56:54

CH122



Date: 17.JAN.2018 18:58:32

Test Mode: UNII-3/ TX AC80 Mode_CH155

Channel	Frequency (MHz)	Power Density (dBm/500kHz)	Duty Factor	Power Density + Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)
CH155	5775	-10.21	0.00	-10.21	29.42

TX CH155



Date: 17.JAN.2018 19:00:29

APPENDIX H - FREQUENCY STABILITY

Test Mode:	UNII-1

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5180.0000
132	5180.0020
120	5180.0008
108	5180.0000
Max. Deviation (MHz)	0.0020
Max. Deviation (ppm)	0.3861

Temperature vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(℃)	5180.0000
0	5179.9996
10	5179.9996
20	5179.9988
30	5179.9988
40	5179.9984
50	5179.9980
Max. Deviation (MHz)	0.0020
Max. Deviation (ppm)	0.3861

Test Mode:	UNII-2A

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5260.0000
132	5259.9980
120	5259.9988
108	5259.9992
Max. Deviation (MHz)	0.0020
Max. Deviation (ppm)	0.3802

Temperature vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(℃)	5260.0000
0	5259.9996
10	5260.0000
20	5260.0000
30	5260.0004
40	5260.0008
50	5260.0008
Max. Deviation (MHz)	0.0008
Max. Deviation (ppm)	0.1521

Test Mode:	UNII-2C

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5500.0000
132	5500.0048
120	5500.0056
108	5500.0060
Max. Deviation (MHz)	0.0060
Max. Deviation (ppm)	1.0909

Temperature vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(℃)	5500.0000
0	5500.0068
10	5500.0072
20	5500.0072
30	5500.0076
40	5500.0080
50	5500.0100
Max. Deviation (MHz)	0.0100
Max. Deviation (ppm)	1.8182

Test Mode:	UNII-3

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5745.0000
132	5745.0108
120	5745.0108
108	5745.0112
Max. Deviation (MHz)	0.0112
Max. Deviation (ppm)	1.9495

Temperature vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(℃)	5745.0000
0	5745.0116
10	5745.0120
20	5745.0128
30	5745.0128
40	5745.0128
50	5745.0132
Max. Deviation (MHz)	0.0132
Max. Deviation (ppm)	2.2977