Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Report No: CCISE200406403

RF Exposure Evaluation Report

Applicant: Shenzhen Tengwei Video Technology Co., Ltd

Room 505, Rujun Building, Banxuegang Road, Longgang **Address of Applicant:**

District Shenzhen, China

Equipment Under Test (EUT)

Product Name: IP CAMERA

T3801D, T3801F, TH661D, TH661F, T3812D, T3812F, Model No.:

T3815D, T3815F, T3818D, T3818F

Trade mark: **TENVIS**

FCC ID: 2ADGP-TVS200

Applicable standards: FCC CFR Title 47 Part 2 Subpart J Section 2.1091

Date of sample receipt: 20 Apr., 2020

Date of Test: 21 Apr., to 27 May, 2020

Date of report issue: 27 May, 2020

Test Result: PASS*

Authorized Signature:



Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





Version

Version No.	Date	Description
00	27 May, 2020	Original

Tested by:

Test Engineer

Reviewed by:

Project Engineer **Date:** 27 May, 2020

Date: 27 May, 2020 **Project Engineer**



3 Contents

			Page
1	CO	VER PAGE	1
2	VEF	RSION	2
3	CO	NTENTS	3
4		NERAL INFORMATION	
	4.1	CLIENT INFORMATION	4
	4.2	GENERAL DESCRIPTION OF E.U.T.	4
	4.3	OPERATING MODES	4
	4.4	LABORATORY FACILITY	
	4.5	LABORATORY LOCATION	4
5	TEC	CHNICAL REQUIREMENTS SPECIFICATION IN FCC CFR TITLE 47 PART 2.1091	5
	5.1	LIMITS	
	5.2	Test Procedure	
	5.3	RESULT	
	5.4	CONCLUSION	6



4 General Information

4.1 Client Information

Applicant:	Shenzhen Tengwei Video Technology Co., Ltd		
Address:	Room 505, Rujun Building, Banxuegang Road, Longgang District Shenzhen, China		
Manufacturer:	TENVIS Technology Co., Ltd		
Address:	14F, Building B1, Nanshan Park, No. 1001 Xueyuan Road, Nanshan District, Shenzhen, 518000, China.		
Factory:	TENVIS Technology Co., Ltd		
Address:	TENVIS Technology Industrial Park, NO.10 Jixiang 3rd Road, Pingdi Town, Longgang District, Shenzhen, 518117, China.		

4.2 General Description of E.U.T.

Product Name:	IP CAMERA
Model No.:	T3801D, T3801F, TH661D, TH661F, T3812D, T3812F, T3815D, T3815F, T3818D, T3818F
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(HT20));2422MHz~2452MHz (802.11n(HT40))
Modulation technology:	802.11b: DSSS, 802.11g/nH20/nH40: OFDM
Antenna Type:	External Antenna
Antenna gain:	Wi-Fi: 5.0 dBi
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

4.3 Operating Modes

Operating mode	Detail description
2.4G WIFI mode	Keep the EUT in continuously transmitting in 2.4G WIFI mode

4.4 Additions to, deviations, or exclusions from the method

No

4.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Designation No.: CN1211

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

• ISED - CAB identifier.: CN0021

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

4.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

Shenzhen Zhongjian Nanfang Testing Co., Ltd. No.110~116, Building B, Jinyuan Business Building, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China Telephone: +86 (0) 755 23118282 Fax: +86 (0) 755 23116366



5 Technical Requirements Specification in FCC CFR Title 47 Part 2.1091

5.1 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)			
(A) Limits for Occupational/Controlled Exposures							
0.3–3.0 614 1.63 *(100) 6							
3.0–30	1842/f	4.89/f	*(900/f ²)	6			
30–300	61.4	0.163	1.0	6			
300–1500			f/300	6			
1500–100,000			5	6			
(B) Limits for General Population/Uncontrolled Exposure							
0.3–1.34	614	1.63	*(100)	30			
1.34–30	824/f	2.19/f	*(180/f ²)	30			
30–300	27.5	0.073	0.2	30			
300–1500			f/1500	30			
1500–100,000			1.0	30			

5.2 Test Procedure

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna





5.3 Result

Frequency (MHz)	Maximum Output power (dBm)	Maximum Output power (mW)	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm²)	Limits for General Population/ Uncontrolled Exposure (mW/cm²)
2.4G Wi-Fi							
2462	16.11	40.83	5	3.16	20.00	0.0257	1.0

Note: Just the worst case mode was shown in report.

5.4 Conclusion

The device is exempt from the RF exposure evaluation.

-----End of report-----