

TEST REPORT

Report Number: 102960041MPK-004 Project Numbers: G102960041, G1029966706 July 13, 2017

Testing performed on the Wireless Load Controllers: Genius Control 10, Genius Pro Control 10, Genius Dimmer 15, Genius Pro Dimmer 15 & Genius Pro Control 20

Models: GC10, GPC10, GDT15, GPDT15 & GPC20

FCC ID: 2ADH9-G2CF IC: 12453A-G2CF

to

FCC Part 15 Subpart C (15.247) Industry Canada RSS-247 Issue 2

For

Levven Automation Inc.

Test Performed by: Intertek 1365 Adams Court Menlo Park, CA 94025 USA Test Authorized by: Levven Automation Inc. 9741 54 Avenue Edmonton, AB T6E 5J4 Canada

| Prepared by: | Anderson Soungpanya | Date: | July 13, 2017 | |
|--------------|---------------------|-------|---------------|--|
| Reviewed by: | Krishna K Vemuri | Date: | July 13, 2017 | |

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004



Equipment Under Test:

Report No. 102960041MPK-004

Wireless Load Controllers

| Model Name & Number(s): | Genius Control 10; GC10 Genius Pro Control 10; GPC10 Genius Dimmer 15; GDT15 Genius Pro Dimmer 15; GPDT15 |
|---|--|
| | Genius Pro Control 20; GPC20 |
| Applicant: Contact: Address: Country | Levven Automation Inc. Jim Qualie Levven Automation Inc. 9741 54 Avenue Edmonton, AB T6E 5J4 Canada |
| Tel. Number: Email: | +1 780-391-3004 Jqualie@levven.com |
| Applicable Regulation: | FCC Part 15 Subpart C (15.247) Industry Canada RSS-247 Issue 2 |
| Date of Test: | March 21 - June 27, 2017 |
| We attest to the accuracy of this report: | (2) shove |
| Anderson Soungpanya | Krishna K Vemuri |
| Project Engineer | Engineering Team Lead |



TABLE OF CONTENTS

| 1.0 | Sumi | mary of ' | Tests | 5 |
|-----|-------|-----------|---|----|
| 2.0 | Gene | ral Infor | rmation | 6 |
| | 2.1 | | ct Description | |
| | 2.2 | | ed Submittal(s) Grants | |
| | 2.3 | | Methodology | |
| | 2.4 | | Pacility | |
| | 2.5 | | rement Uncertainty | |
| 3.0 | Syste | m Test (| Configuration | 8 |
| | 3.1 | Suppo | ort Equipment and description | 8 |
| | 3.2 | Block | Diagram of Test Setup | 8 |
| | 3.3 | Justifi | cation | 9 |
| | 3.4 | Mode | of Operation During Test | 9 |
| | 3.5 | Modif | ications Required for Compliance | 9 |
| | 3.6 | Additi | ions, Deviations and Exclusions from Standards | 9 |
| 4.0 | Meas | urement | t Results | 10 |
| 7.0 | 4.1 | | Bandwidth and 99% Occupied Bandwidth | |
| | 7.1 | 4.1.1 | Requirement | |
| | | 4.1.2 | Procedure | |
| | | 4.1.3 | Test Result | |
| | 4.2 | | num Conducted Output Power at Antenna Terminals | |
| | 7.2 | 4.2.1 | Requirement | |
| | | 4.2.2 | Procedure | |
| | | 4.2.3 | Test Result | |
| | 4.3 | | Spectral Density | |
| | 4.5 | 4.3.1 | Requirement | |
| | | 4.3.2 | Procedure | |
| | | 4.3.3 | Test Result | |
| | 4.4 | | f-Band Conducted Emissions | |
| | | 4.4.1 | Requirement | |
| | | 4.4.2 | Procedure | |
| | | 4.4.3 | Test Result | |
| | 4.5 | | mitter Radiated Emissions | |
| | 1.5 | 4.5.1 | Requirement | |
| | | 4.5.2 | Procedure – Radiated Emissions | |
| | | 4.5.3 | Field Strength Calculation | |
| | | 4.5.4 | Test Results | |
| | | 4.5.5 | Test Setup Photographs | |
| | 4.6 | | ine Conducted Emission | |
| | | 4.6.1 | Requirement | |
| | | 4.6.2 | Procedure | |
| | | 4.6.3 | Test Results | |
| | | 4.6.4 | Test Configuration Photographs | |
| | | 1.0.7 | 1 201 201111601 miles 1 1101061 mpile | |



| 5.0 | List o | of Test Equipment | 70 |
|------|----------|-----------------------|------------|
| 6.0 | Docu | ıment History | 7 1 |
| Anne | x A - Dı | uty Cycle Measurement | 72 |
| | A.1 | Procedure | 72 |
| | A 2 | Test Results | 73 |



1.0 Summary of Tests

| Test | Reference | Reference | Result |
|---|------------------------------|------------------------|---------------------------------|
| | FCC | Industry Canada | |
| RF Output Power | 15.247(b)(3) | RSS-247, 5.4 | Complies |
| 6 dB Bandwidth | 15.247(a)(2) | RSS-247, 5.2 | Complies |
| Power Density | 15.247(e) | RSS-247, 5.2 | Complies |
| Out of Band Antenna Conducted Emission | 15.247(d) | RSS-247, 5.5 | Complies |
| Transmitter Radiated Emissions | 15.247(d), 15.209, 15.205 | RSS-247, 5.5 | Complies |
| AC Line Conducted Emission | 15.207 | RSS-GEN | Complies |
| Antenna Requirement | 15.203 | RSS-GEN | Complies (Permanently attached) |
| RF Exposure | 15.247(i), 2.1093(d) | RSS-102 | Complies |

EUT receive date: March 21, 2017

EUT receive condition: The pre-production version of the EUT was received in good condition

with no apparent damage. As declared by the Applicant, it is identical to

the production units.

Test start date: March 21, 2017

Test completion date: June 27, 2017

The test results in this report pertain only to the item tested.

Page 5 of 75



2.0 General Information

2.1 Product Description

Levven Automation Inc. supplied the following description of the EUT:

The product covered by this report is a permanently connected wireless controller for lighting system. It is intended for household / commercial, indoor dry locations; and installed inside a junction box that supports light fixtures. All products covered in this report must be installed in accordance with local electrical codes.

This test report covers only the 903-927MHz radio.

| Applicant | Levven Automation Inc. |
|---|---|
| Model Number | GC10, GPC10, GDT15, GPDT15 & GPC20 |
| FCC Identifier | 2ADH9-G2CF |
| IC Identifier | 12453A-G2CF |
| Modulation Technique | Digital Transmission System (DTS) |
| Rated RF Output | 13.97 dBm |
| Frequency Range | 903 – 927 MHz |
| Type of modulation | 2GFSK |
| Number of Channel(s) | 33 |
| Antenna(s) & Gain •Antenna is single wire quarter wave monopole | |
| | •Antenna gain theoretical maximum will have a gain of 5.19 dBi (3db |
| | higher than a theoretical dipole 2.19 dBi). |
| Applicant Name & | Levven Automation Inc. |
| Address | 9741 54 Avenue |
| | Edmonton, AB T6E 5J4 |
| | Canada |



2.2 Related Submittal(s) Grants

None.

2.3 Test Methodology

Antenna conducted measurements were performed according to the FCC documents "Guidance for Performing Compliance Measurement on Digital Transmission Systems (DTS) Operating under §15.247" (KDB 558074 D01 DTS MEAS GUIDANCE V04), and RSS-247, RSS-GEN, and

Radiated emissions and AC mains conducted emissions measurements were performed according to the procedures in ANSI C63.10: 2013. Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Data Sheet" of this report.

2.4 Test Facility

The test site used to collect the radiated data is site 1 (10-m semi-anechoic chamber). This test facility and site measurement data have been fully placed on file with the FCC, IC and A2LA accredited.

2.5 Measurement Uncertainty

Compliance with the limits was based on the results of the measurements and doesn't take into account the measurement uncertainty.

Estimated Measurement Uncertainty

| Estimated Wedsdrenient Sheertainty | | | | |
|--|----------------------------|--------------------|-----------|--|
| Measurement | Expanded Uncertainty (k=2) | | | |
| | 0.15 MHz – 1 GHz | 1 GHz – 2.5 GHz | > 2.5 GHz | |
| RF Power and Power Density – antenna conducted | - | 0.7 dB | - | |
| Unwanted emissions - antenna conducted | 1.1 dB | 1.3 dB | 1.9 dB | |
| Bandwidth – antenna conducted | - | 30 Hz | - | |

| Measurement | | Expanded Un | certainty (k=2) | |
|------------------------------|------------|-------------|-----------------|------------|
| | 0.15 MHz – | 30 - 200 | 200 MHz - | 1 GHz – 18 |
| | 30MHz | MHz | 1 GHz | GHz |
| Radiated emissions | - | 4.7 | 4.6 | 5.1 dB |
| AC mains conducted emissions | 2.1 dB | - | - | - |



3.0 System Test Configuration


3.1 Support Equipment and description

None

3.2 Block Diagram of Test Setup

| Equipment Under Test | | | |
|-----------------------|-----------------|--|--|
| Product Name | Product Model # | Serial Number | |
| Genius Control 10 | GC10 | MPK1703211148-003 (Conducted) | |
| Genius Pro Control 10 | GPC10 | MPK1703211148-004 (Radiated) | |
| Genius Dimmer 15 | GDT15 | MPK1703211148-005 (Conducted) | |
| Genius Pro Dimmer 15 | GPDT15 | MPK1703211148-006(Radiated | |
| Genius Pro Control 20 | GPC20 | MPK1703211148-001 (Conducted) MPK1703211148-002(Radiated) | |

Antenna was removed and co-axial connector with a cable was installed for Conducted Measurements.



| S = Shielded | F = With Ferrite |
|----------------|-------------------------------|
| U = Unshielded | $\mathbf{M} = \mathbf{Meter}$ |

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004



3.3 Justification

Testing was performed for all modulation/data rate modes.

Unless otherwise stated in this report, measurements made for Power Density, Bandwidth, Conducted Spurious, Radiated Spurious were made with the worst case power setting

Genius Control 10 and Genius Pro Control 10 are same design and components, the differences are Genius Control 10 is single voltage and Genius Pro Control 10 is dual voltage.

Genius Dimmer 15 and Genius Pro Dimmer 15 are same design and components, the differences are Genius Dimmer 15 is single voltage and Genius Pro Dimmer 15 is dual voltage.

Genius Control 10, Genius Pro Control 10, Genius Dimmer 15, Genius Pro Dimmer 15 & Genius Pro Control 20 use the same 903-927MHz Radio. Transmitter Output power, Radiated Spurious and AC Line Emissions were conducted on each model.

3.4 Mode of Operation During Test

During transmitter testing, the transmitter was setup to transmit at maximum RF power on low, middle and high frequencies/channels.

During transmitter testing, the transmitter was setup to transmit using the maximum RF power setting provided by the manufacturer. Their corresponding output power in dBm can be found in section 4.2 of this report.

3.5 Modifications Required for Compliance

No modifications were made by the manufacturer or Intertek to the EUT in order to bring the EUT into compliance.

3.6 Additions, Deviations and Exclusions from Standards

No additions, deviations or exclusions from the standard were made.



4.0 Measurement Results

4.1 6-dB Bandwidth and 99% Occupied Bandwidth FCC Rule: 15.247(a)(2); RSS-247 A8.2 and RSS-GEN;

4.1.1 Requirement

The minimum 6-dB bandwidth shall be at least 500 kHz

4.1.2 Procedure

A spectrum analyzer was connected to the antenna port of the transmitter.

For FCC 6dB Channel Bandwidth the Procedure described in the FCC Publication 558074 D01 DTS Meas Guidance v04 was used to determine the DTS occupied bandwidth. Section 8.1 Option 1 was used.

- 1. Set RBW = 100 kHz.
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

For 99% power bandwidth measurement, the bandwidth was determined by using the built-in 99% occupied bandwidth function of the spectrum analyzer. The resolution bandwidth is set to 1% of the selected span as is without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth.

Test Date: March 27, 2017

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004




4.1.3 Test Result

| Frequency MHz | 6 dB FCC Bandwidth, kHz | Plot # | 99% Bandwidth, kHz | Plot # |
|------------------|----------------------------|-----------|-----------------------|-----------|
| 903 | 524.43 | 1.1 | 523.50 | 1.4 |
| 915 | 524.04 | 1.2 | 523.13 | 1.5 |
| 927 | 526.44 | 1.3 | 523.88 | 1.6 |




Plot 1.1 – 6dB Bandwidth (FCC)



Date: 27.MAR.2017 10:59:38




Plot 1.2 – 6dB Bandwidth (FCC)



Date: 27.MAR.2017 11:01:07




Plot 1 3 – 6dB Bandwidth (FCC)



Date: 27.MAR.2017 10:57:49




Plot 1.4 – 6dB Bandwidth (FCC)



Date: 27.MAR.2017 11:04:08




Plot 1.5 – 6dB Bandwidth (FCC)



Date: 27.MAR.2017 11:02:27



Plot 1.6 – 6dB Bandwidth (FCC)



Date: 27.MAR.2017 11:03:24



4.2 Maximum Conducted Output Power at Antenna Terminals FCC Rule 15.247(b)(3)

4.2.1 Requirement

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased appropriately, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.2.2 Procedure

The antenna port of the EUT was connected to the input of a spectrum analyzer to measure the Maximum Conducted Transmitter Output Power. The offset programmed on the analyzer is corrected to include cable loss & attenuator.

The procedure described in FCC Publication 558074 D01 DTS Meas Guidance v04 was used. Specifically, section <u>9.1.1 RBW ≥ DTS Bandwidth</u> was utilized as the spectrum analyzer's resolution bandwidth was greater than the DTS bandwidth.

- 1. Set the RBW ≥ DTS Bandwidth
- 2. Set the VBW \geq 3 x RBW
- 3. Set the span \geq 3 x RBW
- 4. Sweep time = Auto couple
- 5. Detector = Peak
- 6. Trace mode = Max Hold
- 7. Allow trace to fully stabilize
- 8. Use peak marker function to determine the peak amplitude level.

A spectrum analyzer was connected to the antenna port of the transmitter.

| Total Date: | Manual 21 April 2 0 Inno 7 2017 |
|-------------|----------------------------------|
| Test Date: | March 21, April 3 & June 7, 2017 |

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004




4.2.3 Test Result

Refer to the following plots for the test result:

| Model Number | Frequency MHz | Conducted Peak Power dBm | Conducted Peak Power mW | Plot # |
|----------------|------------------|--------------------------------|-------------------------------|-----------|
| | 903 | 13.97 | 24.946 | 2.1 |
| GC10 & GPC10 | 915 | 13.82 | 24.099 | 2.2 |
| | 927 | 13.60 | 22.909 | 2.3 |
| | 903 | 13.00 | 19.953 | 2.4 |
| GDT15 & GPDT15 | 915 | 12.68 | 18.535 | 2.5 |
| | 927 | 12.60 | 18.197 | 2.6 |
| | 903 | 13.44 | 22.080 | 2.7 |
| GPC20 | 915 | 13.25 | 21.135 | 2.8 |
| | 927 | 13.06 | 20.230 | 2.9 |




Plot 2.1



Date: 7.JUN.2017 12:24:00




Plot 2.2



Date: 7.JUN.2017 12:24:53




Plot 2.3



Date: 7.JUN.2017 12:25:22




Plot 2.4



Date: 21.MAR.2017 07:21:30




Plot 2.5



Date: 21.MAR.2017 07:23:19




Plot 2.6



Date: 21.MAR.2017 07:48:57




Plot 2.7



Date: 3.APR.2017 09:28:28




Plot 2.8



Date: 3.APR.2017 09:29:21



Plot 2.9



Date: 3.APR.2017 09:30:00



4.3 Power Spectral Density FCC 15.247 (e)

4.3.1 Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna should not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2 Procedure

The antenna port of the EUT was connected to the input of a spectrum analyzer to measure the Transmitter Power Density (PSD). The offset programmed on the analyzer is corrected to include cable loss, attenuator.

The procedure described in FCC Publication 558074 D01 DTS Meas Guidance, specifically section 10.2 Method PKPSD (peak PSD).

- 1. Set analyzer center frequency to DTS channel center frequency.
- 2. Set the span to 1.5 times the *DTS bandwidth*.
- 3. Set the RBW to: $3 \text{ kHz} \le \text{RBW} \le 100 \text{ kHz}$.
- 4. Set the VBW \geq 3 x RBW.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

| Test Date: | June 7, 2017 |
|------------|--------------|

EMC Report for Levven Automation Inc. on the Wireless Load Controller
File: 102960041MPK-004 Page 29 of 75




4.3.3 Test Result

Refer to the following plots for the test result:

| Frequency MHz | PSD (Peak) dBm | Margin to 8dBm Limit dB | Plot # |
|------------------|----------------------|-------------------------------|-----------|
| 903 | 5.54 | -2.46 | 3.1 |
| 915 | 5.43 | -2.57 | 3.2 |
| 927 | 5.36 | -2.64 | 3.3 |




Plot 3. 1



Date: 7.JUN.2017 12:27:18




Plot 3. 2



Date: 7.JUN.2017 12:28:49



Plot 3. 3



Date: 7.JUN.2017 12:26:21



4.4 Out-of-Band Conducted Emissions FCC 15.247(d)

4.4.1 Requirement

In any 100 kHz bandwidths outside the EUT pass-band, the RF power shall be at least 20dB (peak) or 30 dB (average) below that of the maximum in-band 100 kHz emissions.

4.4.2 Procedure

A spectrum analyzer was connected to the antenna port of the transmitter. Analyzer Resolution Bandwidth was set to 100 kHz. For each channel investigated, the in-band and out-of-band emission measurements were performed. The out-of-band emissions were measured from 30 MHz to 10 GHz.

4.4.3 Test Result


Refer to the following plots 4.1 - 4.5 for unwanted conducted emissions. The plot shows -20dB attenuation limit line.

| Test Date: | March 21, 2017 |
|------------|----------------|
|------------|----------------|


| Results Complies |
|------------------|
|------------------|



Plot 4.1 **Tx** @ **903MHz**




Plot 4.2 **Tx @ 915MHz**






Plot 4.3 **Tx @ 927MHz**






Plot 4.4 **Conducted Band Edge, Tx @ 903MHz**



Date: 21.MAR.2017 08:44:25



Plot 4.5 Conducted Band Edge, Tx @ 927MHz



Date: 21.MAR.2017 08:46:04



4.5 Transmitter Radiated Emissions FCC Rule 15.247(d), 15.209, 15.205; RSS-247

4.5.1 Requirement

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

For out of band radiated emissions (except for frequencies in restricted bands), in any 100 kHz bandwidths outside the EUT pass-band, the RF power shall be at least 20dB (peak) or 30 dB (average) below that of the maximum in-band 100 kHz emissions.

4.5.2 Procedure – Radiated Emissions

Radiated emission measurements were performed from 30 MHz to 10 GHz according to the procedure described in ANSI C64.10. Spectrum Analyzer Resolution Bandwidth is 100 kHz or greater for frequencies 30 MHz to 1000 MHz, 1 MHz for frequencies above 1000 MHz. Above 1000 MHz Peak and Average measurements were performed.

The EUT is placed on a plastic turntable that is 80 cm in height for below 1000MHz and 1.5m in height for above 1GHz. If the EUT attaches to peripherals, they are connected and operational (as typical as possible). During testing, all cables were manipulated to produce worst-case emissions. The signal is maximized through rotation. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters.

Radiated emissions are taken at 3 meters for frequencies above 1 GHz and at 10 meters for frequencies below 1 GHz.

Measurements made from 30MHz to 1GHz had a notch filter in place. Measurements made from 1 GHz to 10GHz had a high pass filter in place. A preamp was used from 30MHz to 10GHz.

All measurements were made with a Peak Detector and compared to QP limits for 30MHz - 1GHz and Average limits for 1GHz - 10GHz.

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels).

EMC Report for Levven Automation Inc. on the Wireless Load Controller

File: 102960041MPK-004 Page 39 of 75



4.5.3 Field Strength Calculation

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

 $FS = RA + AF + CF - AG - \delta$ (for average measurement only); if measurement is performed at a distance other than specified in the rule, a Distance Correction Factor (DCF) shall be added.

Where $FS = Field Strength in dB(\mu V/m)$

 $RA = Receiver Amplitude (including preamplifier) in dB(<math>\mu V$)

AF = Antenna Factor in dB(1/m)

CF = Cable Attenuation Factor in dB

AG = Amplifier Gain in dB

 δ = Duty cycle correction factor, see Annex A

Assume a receiver reading of $52.0 \, dB(\mu V)$ is obtained. The antennas factor of $7.4 \, dB(1/m)$ and cable factor of $1.6 \, dB$ is added. The amplifier gain of 29 dB is subtracted, giving field strength of $32 \, dB(\mu V/m)$. This value in $dB(\mu V/m)$ was converted to its corresponding level in $\mu V/m$.

 $RA = 52.0 dB(\mu V)$

AF = 7.4 dB(1/m)

CF = 1.6 dB

AG = 29.0 dB

 $\delta = 20.0 \text{ dB}$

 $FS = 52.0 + 7.4 + 1.6 - 29.0 = 32 dB(\mu V/m) Peak.$

 $FS = 52.0+7.4+1.6-29.0-20.0= 12 dB(\mu V/m)$ Average.

| t Date: March 24 – June 14, 2017 |
|------------------------------------|
| t Date: March 24 = Line 14 20 |

| Result: | Complies by 0.31dB | |
|---------|--------------------|--|
| Result: | Combiles by 0.510b | |

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004




4.5.4 Test Results

GC10 & GPC10

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 903MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/29/2017 07:07



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)
× Peak (Peak Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizonta
 Peak (Peak /Lim. Peak) (Vertical)



| Model: ; Clie | ent:; Commen | ts:; Test D | Date: 06/07/2 | 017 08:33 |
|---------------|--------------|-------------|---------------|-----------|

| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1805.8 | 61.66 | 74 | -12.34 | 41.66 | 54 | -12.34 | Н | 1.98 | 294 |
| 2708.5 | 60.82 | 74 | -13.18 | 40.82 | 54 | -13.18 | Н | 1.48 | 141 |
| 5418.3 | 62.67 | 74 | -11.33 | 42.67 | 54 | -11.33 | Н | 1.01 | 95 |
| 5418.3 | 59.80 | 74 | -14.20 | 39.80 | 54 | -14.20 | V | 1.99 | 37 |
| 6322.7 | 63.16 | 74 | -10.84 | 43.16 | 54 | -10.84 | Н | 1.48 | 155 |
| 6322.7 | 64.48 | 74 | -9.52 | 44.48 | 54 | -9.52 | V | 1.52 | 223 |
| 7222.0 | 61.73 | 74 | -12.27 | 41.73 | 54 | -12.27 | V | 1.02 | 260 |
| 8128.1 | 68.76 | 74 | -5.24 | 48.76 | 54 | -5.24 | Н | 1.98 | 154 |
| 8128.1 | 71.83 | 74 | -2.17 | 51.83 | 54 | -2.17 | V | 1.02 | 246 |
| 9027.4 | 61.50 | 74 | -12.50 | 41.50 | 54 | -12.50 | V | 1.02 | 161 |
| Test Result | : Pass at 903 | MHz | | | | | | | |




Test Results: 15.209 Radiated Spurious Emissions Mid Channel, Tx at 915MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz








Model: ; Client: ; Comments: ; Test Date: 03/29/2017 07:13



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)

× Peak (Peak /Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizontal
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/07/2017 08:43


| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1829.6 | 63.18 | 74 | -10.82 | 43.18 | 54 | -10.82 | Н | 1.48 | 111 |
| 1829.6 | 60.23 | 74 | -13.77 | 40.23 | 54 | -13.77 | V | 1.02 | 83 |
| 5490.0 | 62.10 | 74 | -11.90 | 42.10 | 54 | -11.90 | Н | 1.01 | 79 |
| 5490.0 | 62.08 | 74 | -11.92 | 42.08 | 54 | -11.92 | V | 1.99 | 226 |
| 6406.0 | 61.99 | 74 | -12.01 | 41.99 | 54 | -12.01 | Н | 1.98 | 153 |
| 6406.0 | 63.91 | 74 | -10.09 | 43.91 | 54 | -10.09 | V | 1.52 | 236 |
| 7320.6 | 60.16 | 74 | -13.84 | 40.16 | 54 | -13.84 | Н | 1.48 | 153 |
| 7320.6 | 60.66 | 74 | -13.34 | 40.66 | 54 | -13.34 | V | 1.02 | 267 |
| 8233.5 | 66.15 | 74 | -7.85 | 46.15 | 54 | -7.85 | Н | 1.48 | 280 |
| 8233.5 | 69.13 | 74 | -4.87 | 49.13 | 54 | -4.87 | V | 1.02 | 267 |
| 9151.5 | 59.99 | 74 | -14.01 | 39.99 | 54 | -14.01 | Н | 1.48 | 209 |
| 9151.5 | 61.90 | 74 | -12.10 | 41.90 | 54 | -12.10 | V | 1.52 | 164 |
| Test Result | : Pass at 915 | MHz | | | | | | | |



Test Results: 15.209 Radiated Spurious Emissions High Channel, Tx at 927MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/29/2017 07:18



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)
× Peak (Peak /Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizonta
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/07/2017 08:55

| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1853.4 | 65.70 | 74 | -8.30 | 45.70 | 54 | -8.30 | Н | 1.48 | 110 |
| 1853.4 | 61.84 | 74 | -12.16 | 41.84 | 54 | -12.16 | V | 1.02 | 81 |
| 5562.8 | 63.02 | 74 | -10.98 | 43.02 | 54 | -10.98 | Н | 1.01 | 79 |
| 5562.8 | 63.82 | 74 | -10.18 | 43.82 | 54 | -10.18 | V | 1.02 | 9 |
| 6489.3 | 63.82 | 74 | -10.18 | 43.82 | 54 | -10.18 | V | 1.99 | 222 |
| 6489.3 | 61.83 | 74 | -12.17 | 41.83 | 54 | -12.17 | Н | 1.48 | 138 |
| 7416.5 | 61.27 | 74 | -12.73 | 41.27 | 54 | -12.73 | V | 1.99 | 222 |
| 7416.5 | 60.47 | 74 | -13.53 | 40.47 | 54 | -13.53 | Н | 1.01 | 79 |
| 8344.0 | 66.44 | 74 | -7.56 | 46.44 | 54 | -7.56 | V | 1.02 | 110 |
| 8344.0 | 62.89 | 74 | -11.11 | 42.89 | 54 | -11.11 | Н | 1.98 | 140 |
| 9272.2 | 59.92 | 74 | -14.08 | 39.92 | 54 | -14.08 | Н | 1.01 | 65 |
| Test Result | : Pass at 927 | MHz | | | | | | | |




GDT15 & GPDT15

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 903MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/24/2017 08:20



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)
× Peak (Peak Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizontal
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/14/2017 12:19


| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1805.8 | 66.44 | 74 | -7.56 | 46.44 | 54 | -7.56 | Н | 1.81 | 194 |
| 1805.8 | 62.89 | 74 | -11.11 | 42.89 | 54 | -11.11 | V | 1.41 | 110 |
| 3611.2 | 60.22 | 74 | -13.78 | 40.22 | 54 | -13.78 | Н | 1.52 | 286 |
| 3611.2 | 65.50 | 74 | -8.50 | 45.50 | 54 | -8.50 | V | 1.51 | 198 |
| 4515.6 | 66.04 | 74 | -7.96 | 46.04 | 54 | -7.96 | V | 1.80 | 261 |
| 4515.6 | 65.46 | 74 | -8.54 | 45.46 | 54 | -8.54 | Н | 1.74 | 166 |
| 5416.6 | 70.16 | 74 | -3.84 | 50.16 | 54 | -3.84 | Н | 1.81 | 347 |
| 5416.6 | 73.69 | 74 | -0.31 | 53.69 | 54 | -0.31 | V | 1.85 | 231 |
| Test Result | : Pass at 903 | MHz | · | _ | | | · | | |



Test Results: 15.209 Radiated Spurious Emissions Mid Channel, Tx at 915MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/24/2017 08:37



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)

× Peak (Peak /Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizonta
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/14/2017 12:29

| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1829.6 | 61.88 | 74 | -12.12 | 41.88 | 54 | -12.12 | Н | 1.75 | 133 |
| 1829.6 | 65.17 | 74 | -8.83 | 45.17 | 54 | -8.83 | V | 1.84 | 107 |
| 3660.5 | 63.47 | 74 | -10.53 | 43.47 | 54 | -10.53 | V | 1.64 | 107 |
| 4575.1 | 64.92 | 74 | -9.08 | 44.92 | 54 | -9.08 | Н | 1.75 | 282 |
| 4575.1 | 67.23 | 74 | -6.77 | 47.23 | 54 | -6.77 | V | 1.66 | 197 |
| 5488.0 | 69.01 | 74 | -4.99 | 49.01 | 54 | -4.99 | Н | 1.51 | 251 |
| 5488.0 | 72.25 | 74 | -1.75 | 52.25 | 54 | -1.75 | V | 1.44 | 167 |
| 7318.9 | 59.70 | 74 | -14.30 | 39.70 | 54 | -14.30 | V | 1.91 | 18 |
| 9151.5 | 60.17 | 74 | -13.83 | 40.17 | 54 | -13.83 | V | 1.97 | 0 |
| Test Result | : Pass at 915 | MHz | | • | | | • | • | |




Test Results: 15.209 Radiated Spurious Emissions High Channel, Tx at 927MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz

FCC Part 15/FCC Part 15.205/15.209, 30MHz-1GHz - QPeak/10.0m/ Meas.Peak (Horizontal)

- Meas.Peak (Vertical)
- Peak (Peak /Lim. QPeak) (Horizontal) Peak (Peak /Lim. QPeak) (Vertical) FS (Final QP) (Horizontal)



Model: ; Client: ; Comments: ; Test Date: 03/24/2017 08:43

| Frequency | QP Field Strength | QP Limit | QP Margin | Azimuth | Height | Polarity | RA | Correction |
|-----------|----------------------|-------------|--------------|---------|--------|------------|-------|------------|
| MHz | dBµV/m | dB(uV/m) | dB | 0 | m | | dBuV | (dB |
| 968.653 | 37.78 | 43.5 | -5.72 | 84.5 | 1.00 | Horizontal | 32.74 | 5.04 |


EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)

× Peak (Peak /Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizontal
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/14/2017 12:32

| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1853.4 | 63.58 | 74 | -10.42 | 43.58 | 54 | -10.42 | Н | 1.80 | 148 |
| 1853.4 | 66.14 | 74 | -7.86 | 46.14 | 54 | -7.86 | V | 1.81 | 104 |
| 3706.4 | 63.67 | 74 | -10.33 | 43.67 | 54 | -10.33 | V | 1.75 | 104 |
| 4634.6 | 64.27 | 74 | -9.73 | 44.27 | 54 | -9.73 | Н | 1.53 | 248 |
| 4634.6 | 64.99 | 74 | -9.01 | 44.99 | 54 | -9.01 | V | 1.94 | 195 |
| 5561.1 | 66.11 | 74 | -7.89 | 46.11 | 54 | -7.89 | Н | 1.77 | 311 |
| 5561.1 | 71.69 | 74 | -2.31 | 51.69 | 54 | -2.31 | V | 1.75 | 165 |
| 7417.5 | 60.83 | 74 | -13.17 | 40.83 | 54 | -13.17 | V | 1.92 | 17 |
| 9268.8 | 60.81 | 74 | -13.19 | 40.81 | 54 | -13.19 | V | 1.64 | 17 |
| Test Result | : Pass at 927 | MHz | | | | | | | |




GPC20

Test Results: 15.209 Radiated Spurious Emissions Low Channel, Tx at 903MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/28/2017 07:56



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)
× Peak (Peak Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizonta
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/14/2017 11:45

| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1805.8 | 63.17 | 74 | -10.83 | 43.17 | 54 | -10.83 | Н | 1.82 | 131 |
| 1805.8 | 62.40 | 74 | -11.60 | 42.40 | 54 | -11.60 | V | 1.81 | 197 |
| 5416.6 | 67.29 | 74 | -6.71 | 47.29 | 54 | -6.71 | Н | 1.72 | 299 |
| 5418.3 | 71.72 | 74 | -2.28 | 51.72 | 54 | -2.28 | V | 1.74 | 274 |
| 6319.3 | 59.09 | 74 | -14.91 | 39.09 | 54 | -14.91 | V | 1.61 | 260 |
| Test Result | : Pass at 903 | MHz | | | | | | | |

Note: The peaks showed are compliant with 15.209 Average limit (54dBuV/m) by applying Duty Cycle Correction Factor of 20dB (See Annex A for Duty Cycle calculation).


EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004



Test Results: 15.209 Radiated Spurious Emissions Mid Channel, Tx at 915MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/28/2017 08:04



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)

× Peak (Peak /Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizontal
 Peak (Peak /Lim. Peak) (Vertical)



Model: ; Client: ; Comments: ; Test Date: 06/14/2017 12:05


| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|----------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1829.6 | 65.12 | 74 | -8.88 | 45.12 | 54 | -8.88 | Н | 1.75 | 138 |
| 1829.6 | 62.68 | 74 | -11.32 | 42.68 | 54 | -11.32 | V | 1.82 | 192 |
| 5489.7 | 70.48 | 74 | -3.52 | 50.48 | 54 | -3.52 | V | 1.69 | 75 |
| 5489.7 | 68.35 | 74 | -5.65 | 48.35 | 54 | -5.65 | Н | 1.77 | 318 |
| Test Result | : Pass at 915 | MHz | | | | | | | · |



Test Results: 15.209 Radiated Spurious Emissions High Channel, Tx at 927MHz

Out-of-Band Radiated Spurious Emissions - 30 MHz to 1000 MHz






Model: ; Client: ; Comments: ; Test Date: 03/28/2017 08:09



FCC Part 15/FCC Part 15.109 Peak 1GHz to 40GHz B - Peak/3.0m/
Meas.Peak (Horizontal)
Meas.Peak (Vertical)

× Peak (Peak /Lim. Peak) (Horizontal)

Peak (Peak /Lim. Peak) (Horizonta
 Peak (Peak /Lim. Peak) (Vertical)




Model: ; Client: ; Comments: ; Test Date: 06/14/2017 12:08

| Frequency | Peak Amplitude | Peak Limit | Peak Margin | Avg Amplitude | Avg Limit | Avg Margin | Polarity | Height | Angle |
|-------------|--------------------------------------|---------------|----------------|------------------|--------------|---------------|----------|--------|-------|
| MHz | dBμV/m | dBμV/m | dB | dBμV/m | dBμV/m | dB | H/V | m | 0 |
| 1853.4 | 65.94 | 74 | -8.06 | 45.94 | 54 | -8.06 | Н | 1.75 | 135 |
| 1853.4 | 63.20 | 74 | -10.80 | 43.20 | 54 | -10.80 | V | 1.74 | 196 |
| 5561.1 | 67.66 | 74 | -6.34 | 47.66 | 54 | -6.34 | Н | 1.82 | 308 |
| 5562.8 | 72.99 | 74 | -1.01 | 52.99 | 54 | -1.01 | V | 1.81 | 77 |
| 6487.6 | 62.85 | 74 | -11.15 | 42.85 | 54 | -11.15 | V | 1.61 | 284 |
| 6489.3 | 59.47 | 74 | -14.53 | 39.47 | 54 | -14.53 | Н | 1.69 | 340 |
| Test Result | Test Result : Pass at 927 MHz | | | | | | | | |



4.5.5 Test Setup Photographs








4.5.8 Test Setup Photographs (Continued)








4.5.8 Test Setup Photographs (Continued)







4.5.8 Test Setup Photographs (Continued)







4.6 AC Line Conducted Emission

FCC: 15.207

4.6.1 Requirement

| Frequency Band MHz | FCC 15.207 Limit dB(μV) | | | | | |
|--------------------|-------------------------|------------|--|--|--|--|
| | Quasi-Peak | Average | | | | |
| 0.15-0.50 | 66 to 56 * | 56 to 46 * | | | | |
| 0.50-5.00 | 56 | 46 | | | | |
| 5.00-30.00 | 60 | 50 | | | | |

Note: *Decreases linearly with the logarithm of the frequency at the transition frequency the lower limit applies.

4.6.2 Procedure

Measurements are carried out using quasi-peak and average detector receivers in accordance with CISPR 16. An AMN is required to provide a defined impedance at high frequencies across the power feed at the point of measurement of terminal voltage and also to provide isolation of the circuit under test from the ambient noise on the power lines. An AMN as defined in CISPR 16 shall be used.

The EUT is located so that the distance between the boundary of the EUT and the closest surface of the AMN is 0.8m.

Where a flexible mains cord is provided by the manufacturer, this shall be 1m long or if in excess of 1m, the excess cable is folded back and forth as far as possible so as to form a bundle not exceeding 0.4m in length.

The EUT is arranged and connected with cables terminated in accordance with the product specification.

Conducted disturbance is measured between the phase lead and the reference ground, and between the neutral lead and the reference ground. Both measured values are reported.

The EUT, where intended for tabletop use, is placed on a table whose top is 0.8m above the ground plane. A vertical, metal reference plane is placed 0.4m from the EUT. The vertical metal reference-plane is at least 2m by 2m. The EUT shall be kept at least 0.8m from any other metal surface or other ground plane not being part of the EUT. The table is constructed of non-conductive materials. Its dimensions are 1m by 1.5m, but may be extended for larger EUT.

Floor standing EUT are placed on a horizontal metal ground plane and isolated from the ground plane by resting on an insulating material. The metal ground plane extends at least 0.5m beyond the boundaries of the EUT and has minimum dimensions of 2m by 2m.

Equipment setup for conducted disturbance tests followed the guidelines of ANSI C63.4:2014.

| Tested By: Anderson Soungpanya | |
|--------------------------------|----------------|
| Test Date: | March 30, 2017 |

File: 102960041MPK-004 Page 63 of 75




4.6.3 **Test Results**

The EUT met the conducted disturbance requirement of FCC 15.207 with the transmitter on. GC10 & GPC10

FCC Part 15/FCC Part 15.107 B - Average/ FCC Part 15/FCC Part 15.107 B - QPeak/ Meas.Peak (Phase 1) Meas.Peak (Neutral)

- Ave Level (dBuV) (Final QP and Ave) (Phase 1)
- Ave Level (dBuV) (Final QP and Ave) (Neutral)
- QP Level (dBuV) (Final QP and Ave) (Phase 1)
- QP Level (dBuV) (Final QP and Ave) (Neutral)



| | | 1 | 1 | 1 | 1 | | | |
|-----------------|------------------|-----------------|------------------|-----------------|-----------------|-------------------|---------|-----------------|
| Frequency (MHz) | Ave Level (dBuV) | QP Level (dBuV) | Ave Limit (dBuV) | QP Limit (dBuV) | Ave Margin (dB) | QP Margin (dB) | Line | Correction (dB) |
| (IVIIIE) | (ubu t) | (dBu) | (dBd 1) | (ubu i) | (ub) | (ub) | | (ub) |
| 0.263 | 32.19 | 42.72 | 51.32 | 61.32 | -19.13 | -18.60 | Phase 1 | 11.07 |
| 0.328 | 30.28 | 41.00 | 49.49 | 59.49 | -19.21 | -18.49 | Phase 1 | 11.10 |
| 0.394 | 28.34 | 38.83 | 47.97 | 57.97 | -19.63 | -19.14 | Phase 1 | 11.10 |
| 0.197 | 35.53 | 44.75 | 53.70 | 63.70 | -18.17 | -18.96 | Neutral | 11.05 |
| 0.263 | 33.24 | 42.36 | 51.32 | 61.32 | -18.08 | -18.96 | Neutral | 11.07 |
| 0.339 | 31.88 | 40.34 | 49.20 | 59.20 | -17.33 | -18.87 | Neutral | 11.10 |

Complies by 17.33 dB at 120V 60Hz **Results:**




4.6.3 Test Results (Continued)

GDT15 & GPDT15

FCC Part 15/FCC Part 15.107 B - Average/ FCC Part 15/FCC Part 15.107 B - QPeak/ Meas.Peak (Phase 1) Meas.Peak (Neutral)

- Ave Level (dBuV) (Final QP and Ave) (Phase 1)
- Ave Level (dBuV) (Final QP and Ave) (Neutral)
- QP Level (dBuV) (Final QP and Ave) (Neutral)
 QP Level (dBuV) (Final QP and Ave) (Neutral)



| Model: ; | Client: ; | Comments: ; | Test Date: | 03/30/2017 | 08:11 |
|----------|-----------|-------------|------------|------------|-------|

| Frequency (MHz) | Ave Level (dBuV) | QP Level (dBuV) | Ave Limit (dBuV) | QP Limit (dBuV) | Ave Margin (dB) | QP Margin (dB) | Line | Correction (dB) |
|-----------------|------------------|-----------------|------------------|-----------------|-----------------|-------------------|---------|-----------------|
| 0.150 | 39.79 | 63.62 | 56.00 | 66.00 | -16.21 | -2.38 | Phase 1 | 11.02 |
| 0.151 | 39.76 | 62.92 | 55.97 | 65.97 | -16.21 | -3.05 | Phase 1 | 11.02 |
| 0.151 | 39.75 | 62.92 | 55.96 | 65.96 | -16.21 | -3.05 | Phase 1 | 11.02 |
| 0.151 | 39.71 | 63.47 | 55.95 | 65.95 | -16.24 | -2.48 | Phase 1 | 11.02 |
| 0.161 | 38.40 | 61.89 | 55.43 | 65.43 | -17.03 | -3.55 | Phase 1 | 11.03 |
| 0.162 | 38.25 | 61.66 | 55.36 | 65.36 | -17.11 | -3.70 | Phase 1 | 11.03 |
| 0.176 | 36.67 | 59.72 | 54.69 | 64.69 | -18.02 | -4.97 | Phase 1 | 11.03 |
| 0.178 | 36.48 | 59.48 | 54.56 | 64.56 | -18.08 | -5.08 | Phase 1 | 11.03 |
| 0.184 | 35.89 | 58.73 | 54.31 | 64.31 | -18.42 | -5.58 | Phase 1 | 11.04 |
| 0.192 | 34.91 | 57.73 | 53.93 | 63.93 | -19.02 | -6.20 | Phase 1 | 11.05 |
| 0.196 | 34.39 | 57.14 | 53.76 | 63.76 | -19.37 | -6.62 | Phase 1 | 11.05 |
| 0.198 | 34.29 | 56.75 | 53.71 | 63.71 | -19.42 | -6.96 | Phase 1 | 11.05 |
| 0.220 | 31.98 | 54.21 | 52.82 | 62.82 | -20.84 | -8.61 | Phase 1 | 11.06 |

EMC Report for Levven Automation Inc. on the Wireless Load Controller

File: 102960041MPK-004 Page 65 of 75



| 0.248 29.68 0.264 28.45 | 51.45 | 51.84 | 61.84 | -22.16 | -10.39 | Phase 1 | 11.06 |
|---------------------------------------|-------|-------|-------|--------|--------|----------|-------|
| 0.264 28.45 | 40.0- | | 01.01 | -22.10 | -10.57 | T Hase I | 11.06 |
| | 49.87 | 51.31 | 61.31 | -22.87 | -11.44 | Phase 1 | 11.07 |
| 0.284 26.90 | 47.88 | 50.71 | 60.71 | -23.81 | -12.83 | Phase 1 | 11.09 |
| 0.301 25.56 | 46.25 | 50.23 | 60.23 | -24.67 | -13.98 | Phase 1 | 11.10 |
| 0.340 21.99 | 42.88 | 49.21 | 59.21 | -27.23 | -16.34 | Phase 1 | 11.10 |
| 0.380 17.72 | 40.61 | 48.27 | 58.27 | -30.55 | -17.66 | Phase 1 | 11.10 |
| 0.416 13.80 | 37.81 | 47.52 | 57.52 | -33.73 | -19.72 | Phase 1 | 11.10 |
| 0.150 39.46 | 63.59 | 56.00 | 66.00 | -16.54 | -2.41 | Neutral | 11.02 |
| 0.150 39.36 | 63.50 | 55.98 | 65.98 | -16.62 | -2.48 | Neutral | 11.02 |
| 0.152 38.93 | 63.07 | 55.88 | 65.88 | -16.95 | -2.81 | Neutral | 11.02 |
| 0.156 38.47 | 62.47 | 55.67 | 65.67 | -17.20 | -3.20 | Neutral | 11.02 |
| 0.160 38.10 | 61.96 | 55.45 | 65.45 | -17.36 | -3.50 | Neutral | 11.03 |
| 0.164 37.67 | 61.34 | 55.28 | 65.28 | -17.61 | -3.94 | Neutral | 11.03 |
| 0.170 36.80 | 60.29 | 54.95 | 64.95 | -18.15 | -4.66 | Neutral | 11.03 |
| 0.183 35.76 | 58.81 | 54.36 | 64.36 | -18.60 | -5.56 | Neutral | 11.04 |
| 0.197 34.22 | 56.83 | 53.74 | 63.74 | -19.52 | -6.92 | Neutral | 11.05 |
| 0.204 33.52 | 55.95 | 53.45 | 63.45 | -19.94 | -7.50 | Neutral | 11.06 |
| 0.225 31.62 | 53.42 | 52.61 | 62.61 | -20.99 | -9.19 | Neutral | 11.06 |
| 0.243 30.53 | 51.71 | 52.00 | 62.00 | -21.48 | -10.29 | Neutral | 11.06 |
| 0.262 29.25 | 49.78 | 51.36 | 61.36 | -22.11 | -11.58 | Neutral | 11.07 |
| 0.286 27.78 | 47.43 | 50.64 | 60.64 | -22.86 | -13.21 | Neutral | 11.09 |
| 0.296 27.27 | 46.48 | 50.35 | 60.35 | -23.08 | -13.87 | Neutral | 11.10 |
| 0.311 26.46 | 45.06 | 49.96 | 59.96 | -23.50 | -14.89 | Neutral | 11.10 |
| 0.341 24.57 | 42.77 | 49.19 | 59.19 | -24.62 | -16.42 | Neutral | 11.10 |
| 0.367 23.01 | 41.26 | 48.57 | 58.57 | -25.55 | -17.30 | Neutral | 11.10 |
| 0.394 21.07 | 39.68 | 47.98 | 57.98 | -26.91 | -18.30 | Neutral | 11.10 |
| 0.419 19.36 | 37.55 | 47.48 | 57.48 | -28.11 | -19.93 | Neutral | 11.10 |

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004




4.6.3 Test Results (Continued)

GPC20

FCC Part 15/FCC Part 15.107 B - Average/
FCC Part 15/FCC Part 15.107 B - QPeak/
Meas.Peak (Phase 1)

- Meas.Peak (Neutral)
- × Ave Level (dBuV) (Final QP and Ave) (Phase 1)
- Ave Level (dBuV) (Final QP and Ave) (Neutral)
- QP Level (dBuV) (Final QP and Ave) (Phase 1)
- QP Level (dBuV) (Final QP and Ave) (Neutral)



Model: ; Client: ; Comments: ; Test Date: 03/30/2017 07:26

| Frequency (MHz) | Ave Level (dBuV) | QP Level (dBuV) | Ave Limit (dBuV) | QP Limit (dBuV) | Ave Margin (dB) | QP Margin (dB) | Line | Correction (dB) |
|-----------------|------------------|-----------------|------------------|--------------------|-----------------|-------------------|---------|-----------------|
| 0.647 | 20.14 | 27.6 | 46 | 56 | -25.86 | -28.40 | Phase 1 | 11.10 |
| 0.980 | 20.74 | 28.24 | 46 | 56 | -25.26 | -27.76 | Phase 1 | 11.14 |
| 4.116 | 18.99 | 24.19 | 46 | 56 | -27.01 | -31.81 | Phase 1 | 11.27 |
| 0.648 | 18.35 | 28.41 | 46 | 56 | -27.65 | -27.59 | Neutral | 11.10 |
| 0.981 | 19.88 | 29.98 | 46 | 56 | -26.12 | -26.02 | Neutral | 11.14 |
| 1.079 | 18.50 | 28.18 | 46 | 56 | -27.50 | -27.82 | Neutral | 11.14 |

Results: Complies by 25.26 at 120V 60Hz



4.6.4 Test Configuration Photographs





AC Mains Line-Conducted Disturbance Setup Photograph



4.6.4 Test Configuration Photographs (Continued)





5.0 List of Test Equipment

Measurement equipment used for emission compliance testing utilized the equipment on the following list:

| Equipment | Manufacturer | Manufacturer Model/Type | | Cal Int | Cal Due |
|-------------------------|-------------------|-------------------------|------------|---------|----------|
| Spectrum Analyzer | Rohde and Schwarz | FSU | ITS 00913 | 12 | 01/12/18 |
| Pre-Amplifier (1-18GHz) | Miteq | AMF-4D-001180-24-10P | ITS 00526 | 12 | 09/29/17 |
| Horn Antenna | ETS-Lindgren | 3117 | ITS 01325 | 12 | 09/07/17 |
| High Pass Filter | Reactel | 7HS-1.5G/15G-S11 | ITS 001416 | 12 | 05/03/18 |
| Notch Filter | Micro-Tronics | BRM50722 | ITS 01170 | 12 | 01/19/18 |
| EMI Receiver | Rohde and Schwarz | ESU | ITS 00961 | 12 | 07/07/17 |
| BI-Log Antenna | Antenna Research | LPB-2513 | ITS 00355 | 12 | 09/09/17 |
| Pre-Amplifier | Sonoma Instrument | 310 | ITS 01493 | 12 | 09/28/17 |
| LISN | FCC | FCC-LISN-50-50-M-H | ITS 00551 | 12 | 09/14/17 |
| RE Cable | TRU Corporation | TRU CORE 300 | ITS 1462 | 12 | 08/24/17 |
| RE Cable | TRU Corporation | TRU CORE 300 | ITS 1465 | 12 | 08/24/17 |
| RE Cable | TRU Corporation | TRU CORE 300 | ITS 1470 | 12 | 08/24/17 |
| Attenuator | Mini Circuits | BW-N3W5+ | ITS 1315 | 12 | 10/19/17 |
| Notch Filter | MICRO-TRONICS | BRM50702 | ITS 1166 | 12 | 12/08/18 |
| Attenuator | Weinschel | 50-10 | ITS 1224 | 12 | 11/08/17 |
| RE Cable | Megaphase | EMC1-K1K1-236 | IT 1538 | 12 | 06/13/18 |
| RE Cable | Megaphase | EMC1-K1K1-19 | ITS 1482 | 12 | 08/25/17 |
| RE Cable | Megaphase | TM40-K1K1-19 | ITS 1154 | 12 | 01/26/18 |
| Transient Limiter | COM-POWER | LIT-153A | ITS 1452 | 12 | 06/19/18 |
| RE Cable | TRU Corporation | TRU CORE 300 | ITS 1462 | 12 | 08/24/17 |

Software used for emission compliance testing utilized the following:

| Name | Manufacturer | Version | Template/Profile |
|--------------|----------------|-----------|---------------------------------|
| Tile | Quantum Change | 3.4.K.22 | Conducted Spurious_30M-26GHz |
| BAT-EMC | Nexio | 3.16.0.64 | 102960041_Levven.bpp |
| RS Commander | Rohde Schwarz | 1.6.4 | Not Applicable (Screen grabber) |



6.0 Document History

| Revision/ Job Number | Writer Initials | Reviewers Initials | Date | Change |
|-------------------------|--------------------|-----------------------|---------------|-------------------|
| 1.0 / G102960041 | AS | KV | July 13, 2017 | Original document |



Annex A - Duty Cycle Measurement

A.1 Procedure

ANSI C63.10:2013; Section 7.5

Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s (100 ms). In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval. The following procedure is an example of how the average value may be determined. The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in Equation:

 δ (dB) = 20 log (Δ)

where

 δ is the duty cycle correction factor (dB) Δ is the duty cycle (dimensionless)

This correction factor may then be subtracted from the peak pulse amplitude (in dB) to find the average emission. This correction may be applied to all emissions that demonstrate the same pulse timing characteristics as the fundamental emission (e.g., the fundamental and harmonic emissions). In cases where the pulse train is truly random or pseudo random, some regulatory agencies may accept a declaration by the manufacturer of the worst-case value of $t_{\rm ON}$.


When the duty cycle correction factor is calculated to be less than -20.0 dB, -20.0 dB is used to find the average emission.

EMC Report for Levven Automation Inc. on the Wireless Load Controller File: 102960041MPK-004



A.2 Test Results

GC10 & GPC10




Date: 27.JUN.2017 09:42:37

Duty Cycle: DC = 9.86/100 = 0.0986 or 9.86%

Duty Cycle Correction Factor δ (dB) = 20 log (0.0986) = -20.1 dB



GDT15 & GPDT15




Date: 27.JUN.2017 10:32:33

Duty Cycle: DC = 9.86/100 = 0.0986 or 9.86%

Duty Cycle Correction Factor δ (dB) = 20 log (0.0986) = -20.1 dB



GPC20



Date: 27.JUN.2017 10:30:10

Duty Cycle: DC = 9.62/100 = 0.0962 or 9.62%

Duty Cycle Correction Factor δ (dB) = 20 log (0.0962) = -20.3 dB