

Prüfbericht-Nr.: <i>Test report no.:</i>	CN24B2MM 001	Auftrags-Nr.: <i>Order no.:</i>	48218246	Seite 1 von 31 Page 1 of 31												
Kunden-Referenz-Nr.: <i>Client reference no.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	2023-04-19													
Auftraggeber: <i>Client:</i>	Microchip Technology Inc. 2355 West Chandler Blvd. Chandler, Arizona 85224-6199, United States															
Prüfgegenstand: <i>Test item:</i>	Wireless MCU Module with IEEE®802.11 b/g/n															
Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i>	WINCS02UC, WINCS02UE, RNWF02UC, RNWF02UE, WILCS02UE, WIUBS02UE															
Auftrags-Inhalt: <i>Order content:</i>	FCC Part 15C Test report (WiFi 2.4GHz)															
Prüfgrundlage: <i>Test specification:</i>	FCC 47CFR Part 15: Subpart C Section 15.247															
Wareneingangsdatum: <i>Date of sample receipt:</i>	2023-05-16															
Prüfmuster-Nr.: <i>Test sample no.:</i>	A003476526-003 A003476526-009															
Prüfzeitraum: <i>Testing period:</i>	2023-08-14 - 2024-04-24															
Ort der Prüfung: <i>Place of testing:</i>	EMC/RF Taipei Testing Site															
Prüflaboratorium: <i>Testing laboratory:</i>	Taipei Testing Laboratories															
Prüfergebnis*: <i>Test result*:</i>	Pass															
überprüft von: <i>compiled by:</i>	genehmigt von: <i>authorized by:</i>															
Datum: <i>Date:</i>	2024-04-29	Ausstellungsdatum: <i>Issue date:</i>	2024-04-29													
Stellung / Position:	David Huang Project Manager	Stellung / Position:	Ryan Chen Senior Project Manager													
Sonstiges / Other:																
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>														
<table><tr><td>* Legende:</td><td>1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)</td><td>2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)</td><td>3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)</td><td>4 = ausreichend N/A = nicht anwendbar</td><td>5 = mangelhaft N/T = nicht getestet</td></tr><tr><td>* Legend:</td><td>1 = very good P(ass) = passed a.m. test specification(s)</td><td>2 = good F(ail) = failed a.m. test specification(s)</td><td>3 = satisfactory F(ail) = failed a.m. test specification(s)</td><td>4 = sufficient N/A = not applicable</td><td>5 = poor N/T = not tested</td></tr></table>					* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar	5 = mangelhaft N/T = nicht getestet	* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable	5 = poor N/T = not tested
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar	5 = mangelhaft N/T = nicht getestet											
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable	5 = poor N/T = not tested											
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>																

Prüfbericht-Nr.: CN24B2MM 001
Test report no.:

Seite 2 von 31
Page 2 of 31

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

TEST SUMMARY

Report Section	FCC Clause	Test Item	Result
5.1.1	15.247(b) & 15.203	Antenna Requirement	Pass
5.1.2	15.247(b)(3)	Peak Output Power	Pass
5.1.3	15.247(a)(2)	6 dB Bandwidth	Pass
5.1.3	2.1049	99% Occupied Bandwidth	Pass
5.1.4	15.247(e)	Power Spectral Density	Pass
5.1.5	15.247(d)	Conducted Spurious Emissions and Band Edges	Pass
5.1.6	15.247(d) & 15.205 & 15.209	Radiated Spurious Emissions and Band Edges	Pass
5.2.1	15.207	Mains Conducted Emission	Pass

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Contents

HISTORY OF THIS TEST REPORT	6
1. GENERAL REMARKS.....	7
1.1 COMPLEMENTARY MATERIALS	7
1.2 DECISION RULE OF CONFORMITY.....	7
2. TEST SITES.....	8
2.1 TEST LABORATORY.....	8
2.2 TEST FACILITY	8
2.3 TRACEABILITY.....	9
2.4 CALIBRATION.....	9
2.5 MEASUREMENT UNCERTAINTY	9
3. GENERAL PRODUCT INFORMATION	10
3.1 PRODUCT FUNCTION AND INTENDED USE.....	10
3.2 SYSTEM DETAILS AND RATINGS	10
3.3 NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	12
3.4 SUBMITTED DOCUMENTS.....	12
4. TEST SET-UP AND OPERATION MODES.....	13
4.1 PRINCIPLE OF CONFIGURATION SELECTION.....	13
4.2 CARRIER FREQUENCY AND CHANNEL.....	13
4.3 TEST OPERATION AND TEST SOFTWARE.....	14
4.4 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	15
4.5 TEST SETUP DIAGRAM.....	15
4.6 DUTY CYCLE OF TEST SIGNAL	17
5. TEST RESULTS.....	18
5.1 TRANSMITTER REQUIREMENT & TEST SUITES.....	18
5.1.1 Antenna Requirement.....	18
5.1.2 Peak Output Power	19
5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth	22
5.1.4 Power Spectral Density.....	23
5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100 kHz Bandwidth.....	24
5.1.6 Radiated Spurious Emissions and Band Edges	25
5.2 MAINS EMISSION	30
5.2.1 Mains Conducted Emission.....	30

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.

Seite 5 von 31
Page 5 of 31

APPENDIX B - TEST RESULT OF RADIATED EMISSIONS & MAINS CONDUCTED EMISSION

APPENDIX SP - PHOTOGRAPHS OF TEST SETUP

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.

Seite 6 von 31
Page 6 of 31

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
R01	Original Release	2024-04-29

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.Seite 7 von 31
Page 7 of 31

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A - Test Result of Conducted

Appendix B - Test Result of Radiated Emissions & Mains Conducted Emission

Appendix SP - Photographs of Test Setup

Appendix EP - Photographs of EUT

Applied Standard and Test Levels

Radio
FCC 47CFR Part 15: Subpart C Section 15.247
FCC 47CFR Part 2: Subpart J Section 2.1049
ANSI C63.10:2013
KDB 558074 D01 15.247 Meas Guidance v05r02

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2. Test Sites

2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)
FCC Registration No.: 180491
ISED Registration No.: 25563

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

All measurement uncertainty values are shown with a coverage factor of k=2 to indicate a 95% level of confidence.

Emission Measurement Uncertainty

Parameter	Uncertainty
Radiated Emission (9 kHz ~ 30 MHz)	± 1.15 dB
Radiated Emission (30 MHz ~ 200 MHz)	± 1.32 dB
Radiated Emission (200 MHz ~ 1 GHz)	± 1.31 dB
Radiated Emission (1 GHz ~ 18 GHz)	± 1.53 dB
Radiated Emission (18 GHz ~ 40 GHz)	± 2.50 dB
Mains Conducted Emission	± 1.65 dB

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless MCU Module with IEEE®802.11 b/g/n. It contains a WLAN compatible module enabling the user to communicate data through a Wireless interface.

For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Basic Information of EUT

Item	EUT information
Kind of Equipment/Test Item	Wireless MCU Module with IEEE®802.11 b/g/n
Type Identification	WINCS02UC, WINCS02UE, RNWF02UC, RNWF02UE, WILCS02UE, WIUBS02UE
FCC ID	2ADHKWIXCS02U

Technical Specification of EUT

Item	EUT information
Operating Frequency	2412 MHz ~ 2462 MHz
Channel Number	802.11b/g/n HT20: 11
Data Rate	802.11b: 11.0 / 5.5 / 2.0 / 1.0 Mbps 802.11g: 54.0 / 48.0 / 36.0 / 24.0 / 18.0 / 12.0 / 9.0 / 6.0 Mbps 802.11n: up to MCS7
Operation Voltage	VDD = 3.0 ~ 3.6V, and VDDIO = 1.8 ~ 3.6V
Modulation	DSSS (DBPSK, DQPSK, CCK) OFDM (BPSK, QPSK, 16QAM, 64QAM)
Maximum Output Power (mW)	802.11b: 257.04 802.11g: 263.63 802.11n HT20: 272.9
Antenna Information	Refer to 5.1.1
Accessory Device	Refer to 4.4

Note:

1. All models are listed as below.

Main Model	Series Model	Difference
WINCS02UC	WINCS02UE	Network Controller, SPI interface. Main model: with Trust&GO ECC chip ; series model: without Trust&GO ECC chip
RNWF02UC	RNWF02UE	Network Controller, UART interface. Main model: with Trust&GO ECC chip ; series model: without Trust&GO ECC chip
WILCS02UE	--	Link Controller, SDIO/SPI host interface, Non-ECC chip
WIUBS02UE	--	Link Controller, USB host interface, Non-ECC chip

2. Antenna List:

Ant No.	Part Number	Manufacturer	Antenna Gain	Antenna Type	Cable Length
1	RFA-02-L2H1	Aristotle	2	Dipole	150 mm
2	RFA-02-C2H1-D034	Alead	2	Dipole	150 mm
3	RFA-02-D3	Aristotle	2	Dipole	150 mm
4	RFDPA870920IMLB301	Walsin	1.84	Dipole	200 mm
5	RFDPA870920IMAB302	Walsin	1.82	Dipole	200 mm
6	RFDPA870920IMAB305	Walsin	1.82	Dipole	200 mm
7	RFDPA870910IMAB308	Walsin	2	Dipole	100 mm
8	RFA-02-C2M2	Aristotle	2	Dipole	100 mm
9	RFA-02-C2M2-D034	Alead	2	Dipole	100 mm
10	RN-SMA-S-RP	Microchip	0.56	Dipole	100 mm
11	W1049B030	Pulse	2	Dipole	76 mm
12	RN-SMA4-RP	Microchip	2.2	Dipole	100 mm
13	ANT-2.4-CW-RCL-RPS	TE Connectivity / Linx Technologies	2.3	Dipole	100 mm
14	WXE2400	TE Connectivity / Laird External Antennas	3	Dipole	100 mm

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.

Seite 12 von 31
Page 12 of 31

3.3 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.4 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The test modes were adapted accordingly in reference to the instructions for use.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output expected by the customer and is going to be fixed on the firmware of the final end product.

Table for Parameters of Test Software Setting

802.11b		802.11g		802.11n HT20	
Channel	Power Setting	Channel	Power Setting	Channel	Power Setting
1	52.400.15	1	60.1500.15	1	51.1500.15
6	71.400.15	2	75.1500.15	2	79.1500.15
11	50.400.15	6	95.1500.15	6	91.1500.15
		9	76.1500.15	9	72.1500.15
		10	69.1500.15	10	61.1500.15
		11	49.1500.15	11	47,1500,15

4.2 Carrier Frequency and Channel

802.11b, 802.11g and 802.11n HT20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

4.3 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed as below.

Test Software	MCHPRT3_Setup_v1.0.1.6936
---------------	---------------------------

The samples were used as follows:

A003476526-003

A003476526-009

Full test was applied on all test modes, but only worst case was shown.

EUT Configure Mode	Applicable To				Description
	Antenna Port Conducted Measurement	Radiated Spurious Emissions above 1 GHz	Radiated Spurious Emissions below 1 GHz	Mains Conducted Emission	
-	√	√	√	√	-

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when position on **Z-plane**.
2. "-" means no effect.
3. The worst antenna No.14 (WXE2400) has been chosen and evaluated.

Antenna Port Conducted Measurement

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
ECC	802.11b	1 to 11	1, 6, 11	1.0
	802.11g	1 to 11	1, 2, 6, 9, 10, 11 (Power only)	6.0
			1, 6, 11 (All other conducted)	
	802.11n HT20	1 to 11	1, 2, 6, 9, 10, 11 (Power only)	MCS0
			1, 6, 11 (All other conducted)	

Radiated Spurious Emissions (Above 1 GHz)

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
ECC	802.11b	1 to 11	1, 6, 11	1.0
	802.11g	1 to 11	1, 6, 11	6.0
	802.11n HT20	1 to 11	1, 6, 11	MCS0
Non-ECC	802.11b	1 to 11	11	1.0
	802.11g	1 to 11	11	6.0
	802.11n HT20	1 to 11	11	MCS0

Radiated Spurious Emissions (Below 1 GHz)

☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
ECC	802.11b	1 to 11	1	1.0

Prüfbericht - Nr.: CN24B2MM 001
Test Report No.

 Seite 15 von 31
 Page 15 of 31

Mains Conducted Emission

- ☒ Pre-Scan full test was applied on all test modes, but only worst case was shown.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Available Channel	Tested Channel	Date Rate (Mbps)
ECC	802.11b	1 to 11	1	1.0

Test Condition

Test Item	Ambient Temperature	Relative Humidity	Tested by
Conducted Measurement	22.5-24.5 °C	56-65 %	Nick Guan / Zeke Wang
Radiated Spurious Emissions above 1 GHz	23.7-24.6 °C	52-55 %	Ray Huang
Radiated Spurious Emissions below 1 GHz	23.7-24.6 °C	52-55 %	Ray Huang
Mains Conducted Emission	21.2 °C	59 %	Chuan Chu

4.4 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Accessory of EUT


None

Support Unit


Support Unit								
No	Description	Brand	Model	S/N	Shielded	Ferrite Core (Qty)	Length (cm)	Remark
A	Antenna	TE / Laird	WXE2400	N/A	-	-	10	Radiated
1	USB to USB	TUV	TUV-01	N/A	NO	NO	300	
2	Notebook	HP	15-da1046TX	CND9111RJB	-	-	-	
3	USB to TYPEC	TUV	TUV-02	NO	NO	NO	180	
A	Antenna	TE / Laird	WXE2400	N/A	-	-	10	Mains Conducted
1	Adapter	HP	HSTNN-DA40	N/A	-	-	-	
2	Notebook	HP	15s-du0007TX	CND93662VF	-	-	-	
3	USB Cable	TUV	TUV-01	N/A	NO	NO	100	

4.5 Test Setup Diagram

<Radiated Spurious Emissions mode>




<Mains Conducted Emission mode>



4.6 Duty Cycle of Test Signal

Mode	On + Off Time (ms)	On Time (ms)	Duty Cycle (%)	Duty Factor (dB)
802.11b	3.42	3.39	99.30	0.03
802.11g	2.05	2.03	98.78	0.05
802.11n HT20	1.92	1.89	98.69	0.06



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

Requirement Use of approved antennas only

According to the manufacturer declaration, the antenna information is as listed below. The antenna is with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Ant No.	Part Number	Manufacturer	Antenna Gain	Antenna Type	Cable Length
1	RFA-02-L2H1	Aristotle	2	Dipole	150 mm
2	RFA-02-C2H1-D034	Alead	2	Dipole	150 mm
3	RFA-02-D3	Aristotle	2	Dipole	150 mm
4	RFDPA870920IMLB301	Walsin	1.84	Dipole	200 mm
5	RFDPA870920IMAB302	Walsin	1.82	Dipole	200 mm
6	RFDPA870920IMAB305	Walsin	1.82	Dipole	200 mm
7	RFDPA870910IMAB308	Walsin	2	Dipole	100 mm
8	RFA-02-C2M2	Aristotle	2	Dipole	100 mm
9	RFA-02-C2M2-D034	Alead	2	Dipole	100 mm
10	RN-SMA-S-RP	Microchip	0.56	Dipole	100 mm
11	W1049B030	Pulse	2	Dipole	76 mm
12	RN-SMA4-RP	Microchip	2.2	Dipole	100 mm
13	ANT-2.4-CW-RCL-RPS	TE Connectivity / Linx Technologies	2.3	Dipole	100 mm
14	WXE2400	TE Connectivity / Laird External Antennas	3	Dipole	100 mm

Refer to EUT photo for details.

Prüfbericht - Nr.: CN24B2MM 001
Test Report No.

Seite 19 von 31
 Page 19 of 31

5.1.2 Peak Output Power

Limit 1 watt (30 dBm)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Power Meter	Anritsu	ML2495A	1901008	2023/03/17	2024/03/16	2023/11/13	2024/3/8
Power Sensor	Anritsu	MA2411B	1725269	2023/03/17	2024/03/16	2023/11/13	2024/3/8

Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

Test Result

Peak Output Power

<802.11b>

Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
		(dBm)	(mW)	
1	2412	23.24	210.86	30
6	2437	24.10	257.04	30
11	2462	22.69	185.78	30

<802.11g>

Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
		(dBm)	(mW)	
1	2412	18.93	78.16	30
2	2417	22.59	181.55	30
6	2437	24.21	263.63	30
9	2452	22.31	170.22	30
10	2457	20.98	125.31	30
11	2462	16.06	40.36	30

<802.11n HT20>

Channel	Channel Frequency (MHz)	Peak Output Power		Limit (dBm)
		(dBm)	(mW)	
1	2412	17.67	58.48	30
2	2417	23.81	240.44	30
6	2437	24.36	272.90	30
9	2452	22.48	177.01	30
10	2457	20.16	103.75	30
11	2462	16.73	47.10	30

Average Power

<802.11b>

Channel	Channel Frequency (MHz)	Average Power	
		(dBm)	(mW)
1	2412	20.44	110.66
6	2437	22.65	184.08
11	2462	19.84	96.38

<802.11g>

Channel	Channel Frequency (MHz)	Average Power	
		(dBm)	(mW)
1	2412	14.59	28.77
2	2417	18.46	70.15
6	2437	21.87	153.82
9	2452	18.27	67.14
10	2457	16.71	46.88
11	2462	11.80	15.14

<802.11n HT20>

Channel	Channel Frequency (MHz)	Average Power	
		(dBm)	(mW)
1	2412	13.04	20.14
2	2417	19.82	95.94
6	2437	21.85	153.11
9	2452	17.83	60.67
10	2457	15.09	32.28
11	2462	12.09	16.18

Prüfbericht - Nr.: CN24B2MM 001
Test Report No.


Seite 22 von 31
 Page 22 of 31

5.1.3 6 dB Bandwidth and 99% Occupied Bandwidth

Limit The minimum 6 dB bandwidth shall be at least 500 kHz.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2023/05/11	2024/05/10	2023/11/13	2024/3/8

Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- For 99% occupied bandwidth measurement, the transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

Test Results

Please refer to Appendix A.

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.

Seite 23 von 31
 Page 23 of 31


5.1.4 Power Spectral Density

Limit

The power spectral density shall not be greater than 8 dBm in any 3 kHz band.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2023/05/11	2024/05/10	2023/11/13	2024/3/8

Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

Test Results

Please refer to Appendix A.

Prüfbericht - Nr.: CN24B2MM 001
Test Report No.

Seite 24 von 31
 Page 24 of 31


5.1.5 Conducted Spurious Emissions and Frequency Band Edges Measured in 100 kHz Bandwidth

Limit

20 dB (below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.)

Kind of Test Site Shielded room

Test Setup



Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date	Test Date	
						From	Until
Spectrum Analyzer	R&S	FSV	101513	2023/05/11	2024/05/10	2023/11/13	2024/3/8

Test Procedure

Measurement procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement procedure OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

Test Results

Please refer to Appendix A.

5.1.6 Radiated Spurious Emissions and Band Edges


Limit

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must comply with the radiated emission limits specified in §15.209(a).
Emissions radiated outside the restricted and authorized frequency bands must either comply with the radiated emission limits specified for the restricted bands or in §15.247(d).


Kind of Test Site 3m Semi-Anechoic Chamber

Test Setup


<Radiated Emissions below 30 MHz>



<Radiated Emissions 30 MHz to 1 GHz>



<Radiated Emissions above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Prüfbericht - Nr.: CN24B2MM 001
Test Report No.

Seite 27 von 31
Page 27 of 31

Test Instruments

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Above 1 GHz (Tested Period: 2023-08-14 ~ 2024-04-24)					
Signal Analyzer	R&S	FSV40	101509	2023/4/26	2024/4/24
Horn Antenna	ETS-Lindgren	3117	00218929	2023/11/17 2022/11/17	2024/11/15 2023/11/16
Horn Antenna	SCHWARZBECK	BBHA 9170	00890	2023/5/4	2024/5/2
HF-AMP + AC source	EMCI	EMC051845SE	980633	2024/1/24 2023/2/22	2025/1/22 2024/2/21
HF-AMP + AC source	EMCI	EMC051845SE	980656	2024/1/18 2023/1/6	2025/1/16 2024/1/5
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
30 MHz ~ 1 GHz (Tested Period: 2024-03-08)					
Receiver	R&S	ESR7	102109	2024/2/22	2025/2/20
Bilog Antenna	SCHWARZBECK	VULB-9168	00951	2023/3/31	2024/3/29
LF-AMP	Agilent	8447D	2944A107722	2023/3/22	2024/3/20
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A
Below 30 MHz (Tested Period: 2024-03-08)					
Receiver	R&S	ESR7	102109	2024/2/22	2025/2/20
Loop Antenna	SCHWARZBECK	FMZB 1519B	00215	2024/1/4	2025/1/2
Test Software	Audix E3	15914a_20191106 tuv	PK-001087	N/A	N/A

Test Procedures**For Radiated Emissions below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel (OPEN), perpendicular (CLOSE), and ground-parallel (GROUND) orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated Emissions above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The Radiated Emissions testing was performed in the X(E1), Y(H) and Z(E2) axis orientation. The worst-case Axis orientation is recorded in this test report.
6. The emission levels of other frequencies (including the 10th harmonic of the highest fundamental frequency) are very lower than the limit and are not shown in the test report.

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.

Seite 29 von 31
Page 29 of 31

Test Results

Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) – Amplifier (dB)

Level (dBuV/m) = Reading (dBuV) + Factor (dB/m)

Please refer to Appendix B.

5.2 Mains Emission


5.2.1 Mains Conducted Emission

Limit

Mains Conducted Emission as defined in §15.207 must comply with the mains conducted emission limits.

Kind of Test Site Shielded room

Test Setup



Test Instruments

Test Period: 2024-03-21

Kind of Equipment	Manufacturer	Type	S/N	Calibration Date	Calibration Due Date
Two-Line V-Network	Rohde & Schwarz	ENV216	101938	2023/10/23	2024/10/21
EMI Test Receiver	R&S	ESCI	101094	2023/11/27	2024/11/25

Prüfbericht - Nr.: **CN24B2MM 001**
Test Report No.

Seite 31 von 31
Page 31 of 31

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz – 30 MHz.

Test Results

Please refer to Appendix B.