UNITS STANDARD 6. PACKAGING REQUIREMENTS **TOLERANCES** mm PARTS ARE TO BE PACKAGED SO AS TO PREVENT DAMAGE IN SHIPMENT AND HANDLING. INTERPRET ALL DIMENSIONS AND **DRAWING NOTES: TOLERANCES PER ASME Y14.5M-1994** LABELS ARE TO BE PROVIDED ON A ROLL WITH AN INNER CORE DIAMETER OF THREE(3) INCHES. THE ROLLS SHALL CONTAIN A MINIMUM OF 1000 LABELS PER ROLL AND MAXIMUM **TOLERANCES UNLESS OTHERWISE** 1. DESCRIPTION & APPLICATION OF 12,000 LABELS PER ROLL. SPLICES ARE REEL SHALL NOT EXCEED THREE(3). IN THE SPECIFIED ON THIS DOCUMENT LABEL COMPONENT DESIGNED FOR USE IN MOBILE DEVICES PRODUCTS OVER EVENT OF A SPICE, ALL LABELS SHALL BE REMOVED FROM THE SPLICED REGION. BAR A TEMPERATURE RANGE OF -20°C TO +70°C IN AN INDOOR / OUTDOOR ENVIRONMENT. ONE PLACE CODE NUMBERS SHALL BE CONSECUTIVE WITHIN A REEL AND MISSING BAR CODE \pm 0.3 NUMBERS SHALL BE IDENTIFIED ON THE OUTSIDE OF EACH SHRINK-WRAPPED ROLL TWO PLACE X.XX ±0.13 2. APPLICABLE DOCUMENTS 6.C LABELS SHALL BE PLACED ON TRANSLUCENT LINER AND SHALL BE SEPARATED AS SHOWN HSDC-RD-ME-001 CONTROLLED AND REPORTABLE MATERIALS DISCLOSURE \pm 0.5 $^{\circ}$ **ANGULAR DIM** HSDC-RD-ME-003 RECEIVING BAR CODE SPECIFICATION ALL TRAY DESIGNS MUST BE APPROVED BY DEVELOPMENT ENGINEERING. X.X HOLE DIA. VARIATION \pm 0.1 HSDC-RD-ME-004 COSMETIC SPECIFICATION FOR HANDHELD PRODUCTS 6.E ROLLS SHALL BE DATE CODED AND ROLL PACKAGED IN A BOX. REFERENCE HSDC-RD-ME-005 SUPPLIER CORRECTIVE ACTION REQUEST PROCEDURE (X.XX) REF ASTM D1238 STANDARD TEST METHOD FOR MELT FLOW RATES OF THERMOPLASTICS BY EXTRUSION PLASTOMETER 7. GENERAL REQUIREMENTS ASME Y14.5M-1994 AMERICAN STANDARD ON GEOMETRIC DIMENSIONING AND 7.A FOR ALL INITIAL DRAWING DETAILS AND SUBSEQUENT REVISIONS TO THIS TOLERANCING (GD&T), VERSION 1994 DRAWING, THE SUPPLIER MUST COMPLETE AND RETURN A SIGNED "PRINT ACCEPTANCE FORM". 3. MATERIALS 7.B NO CHANGES SHALL BE ALLOWED TO THE DESIGN, PRODUCTION MATERIAL. 3.A LABEL: FASSON WHITE PET, 72825T, THICKNESS 0.05mm. PRODUCTION PROCESSES, MANUFACTURING SITES/LINES, TOOLING, OR TO ANY 3.B LABEL BACKGROUND COLOR: WHITE OTHER FACTORS AFFECTING PART QUALITY, COST, OR PERFORMANCE, WITHOUT LABEL MARKING COLOR: BLACK PRIOR EXPLICIT WRITTEN APPROVAL BY DEVELOPMENT ENGINEERING, QUALITY ENGINEERING, AND SOURCING DEPARTMENTS. 4. TOLERANCE / APPEARANCE 7.C ALL NON-CONFORMING MATERIAL MUST BE DISPOSITIONED WITH A SCAR PER THE 4.A ALL DIMENSIONS IN mm UNLESS OTHERWISE SPECIFIED. SUPPLIER CORRECTIVE ACTION REQUEST SPECIFICATION. ALL NOMINAL PART GEOMETRY IS DEFINED BY THE PRO/ENGINEER DATABASE. 7.D IT IS THE SUPPLIER'S RESPONSIBILITY TO PROVIDE DEVELOPMENT ENGINEERING, ALL DIMENSIONS FOR THE LOCATION OF FEATURES (SURFACE, AXIS, OR QUALITY ENGINEERING WITH PROOF OF COMPLIANCE TO ALL DIMENSIONS, AND CENTERLINE) SHALL BE WITH RESPECT TO DATUMS "A", "B", AND "C" WITH A TO ALL SPECIFICATIONS CONTAINED IN THIS DRAWING. TOLERANCE OF ± 0.10 mm UNLESS OTHERWISE SPECIFIED. ALL DIMENSIONS FOR 7.E PRIOR TO PART QUALIFICATION, SUPPLIER MUST DISCLOSE ANY CONTROLLED FEATURES OF SIZE (HOLE, SLOT, PIN, ETC, WITH AN AXIS OR CENTERLINE) AND REPORTABLE MATERIALS IN THEIR PRODUCTS. SHALL BE IRRESPECTIVE OF DATUMS AND HAVE A TOLERANCE OF ± 0.10 mm UNLESS OTHERWISE SPECIFIED. DIMENSIONING AND TOLERANCE PER ASME Y14.5M. ALL POINTS IN THE DATABASE MUST BE HELD TO THE LINEAR TOLERANCE SHOWN IN THE TOLERANCE TABLE ON THIS DRAWING. **REMARKS: LABEL ON REEL FORM** 5. QUALITY CONTROL REQUIREMENTS WHERE THERE IS A CONFLICT BETWEEN THE DRAWING NOTES AND AN APPLICABLE DOCUMENT NOTE, THE DRAWING NOTES SHALL SUPERSEDE. BASE RELEASE (29.00)5.B SAMPLES PRODUCED FROM A PRODUCTION PROCESS FLOW SHALL BE SUBMITTED IMEI LABEL **LINER** FOR QUALIFICATION WITH DATA. (17.00)MINIMUM DATA REQUIREMENTS INCLUDE (i) MEASUREMENTS AND A PROCESS CAPABILITY STUDY (Cp>2.0/Cpk>1.5) ON THIRTY-FIVE (35) RANDOMLY SELECTED 11.00 SERIALIZED SAMPLES, FROM EACH CAVITY, FOR EACH PARAMETER DENOTED AS PROCESS CONTROL, (ii) MEASUREMENTS ON FIVE (5) SERIALIZED PARTS, FROM EACH CAVITY, FOR ALL OTHER PARAMETERS/DIMENSIONS DENOTED ON THE DRAWING, AND (iii) DOCUMENTATION OF CONFORMANCE TO ALL NOTES ON THIS DRAWING AS WELL AS ANY TESTS SPECIFIED IN SUPPORTING DOCUMENTS (e.g. PLATING LABEL THICKNESS, HARDNESS, GRAPHICS WEAR TEST, ETC.). MAY ADD (6.00)**BORDER** PROCESS CONTROL PARAMETERS LATER IF THE NEED ARISES. DIMENSIONS DENOTED WITH THE SYMBOL "<ST>" OR [X] REQUIRE Cp/Cpk DATA FOR ALL PART QUALIFICATION & FIRST ARTICLE SUBMISSIONS. 5.C PRODUCTION LOT DATA, SHALL BE PROVIDED WITH EACH PRODUCTION LOT UNTIL THREE (3) CONSECUTIVE SHIPMENTS DEMONSTRATE A **SCALE 1.000** Cp>2.0 AND Cpk>1.5 FOR ALL PROCESS CONTROL DIMENSIONS, AND THAT NO 4. SUPPLIER CORRECTIVE ACTION REQUESTS (SCARs) WERE ISSUED RELATING TO ANY CONCERNS WITH THIS PART. THEREAFTER, FUTURE LOTS WILL NO LONGER REQUIRE DATA TO BE SHIPPED WITH SUPPLIED MATERIAL. HOWEVER, SUPPLIER MUST CONTINUE TO GENERATE THE DATA AND MAINTAIN IT ON FILE FOR REVIEW FOR A MINIMUM OF TWO (2) YEARS. 5.D IF THE Cp/Cpk VALUES ON ANY DEFINED PROCESS CONTROL PARAMETER SHOULD FALL BELOW 2.0 AND 1.5, RESPECTIVELY, AT ANY TIME DURING THE FOR FACTORY PRINTING REFERENCES MANUFACTURE OF THIS PART, THEN SUPPLIER MUST 100% SCREEN ALL PARTS TO THOSE SPECIFIED PARAMETERS. QUALITY ENGINEERING IS TO BE NOTIFIED WHENEVER SUCH A CONDITION EXISTS. THIS SHOULD BE DONE BOLDED FONTS Yota 2.95 95 THROUGH THE USE OF A CORRECTIVE ACTION RESPONSE FORM USING THE 8D Devices ζi FORMAT. AN INITIAL NOTIFICATION SHOULD BE SUBMITTED NO MORE THAN TWELVE (12) HOURS AFTER A PROBLEM HAS BEEN IDENTIFIED, STATING THE FCC ID: IMMEDIATE CONTAINMENT ACTION TAKEN. AFTER ANALYSIS OF ROOT CAUSE OF DISCREPANCY, A PLAN DEFINING PERMANENT CORRECTIVE ACTION(S) SHALL BE 2ADHW201 3.00 SUBMITTED WITH SAMPLES AND SUPPORTING DATA FOR APPROVAL BY QUALITY ENGINEERING. LABEL OUTLINE -5.E ALL DIMENSIONS SHALL BE CONTROLLED BY A QUALITY CONTROL PLAN. SUPPLIER **KISSCUT** imei : MUST SUBMIT THIS DOCUMENT AS PART OF THEIR PART QUALIFICATION AABBBBBB PACKAGE. NO PRODUCTION LOTS SHOULD BE SUPPLIED PRIOR TO THAT SUBMITTAL AND APPROVAL BY SUPPLIER DEVELOPMENT ENGINEERING. CCCCCD -SUPPLIED ON **REEL FORM SCALE 4.000** LABEL BORDER D (WASTE REGION TO HELP IN PRINTING) PROJECT NAME PART NO. PART VER **UNREEL DIRECTION** HI-P CORPORATION **TITANIUM** DC1000103 PART NAME DRAWING NO. DRW. VER. LABEL, IMEI FCC (NO LOGO) **SIGNATURE** DATE DC1000103 MATERIAL UNIT DESIGNED LYE OCT-15-14 SCALE SHEET NEW RELEASED 4.000 MM 1 OF 1 Α OCT-15-14 LYE PAUL TAN CHECKED HH TEE OCT-15-14 SEE NOTES DRW.VER. ECN NO. DESCRIPTION DATE DESIGNED | APPROVED | APPROVED | PAUL TAN OCT-15-14 COPYRIGHT 2013 HI-P R&D CENTER CREATED BY PRO/E WILDFIRE SIZE:A2 CONFIDENTIAL 3 4 6

Yota Devices EHE IMEI: 00440260 0056976