

FCC LISTED, REGISTRATION  
NUMBER: 720267

Informe de ensayo nº:  
Test report No:

IC LISTED REGISTRATION  
NUMBER IC 4621A-1

**NIE: 43480RRF.002**

## Test report

USA FCC Part 15.247, 15.209  
CANADA RSS-210, RSS-Gen

Radio Frequency Devices. Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz.  
Licence-Exempt Radio Apparatus (All Frequency Bands): Category I Equipment.  
General Requirements and Information for the Certification of Radio Apparatus.

|                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Identificación del objeto ensayado.....:  | SmartPhone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Identification of item tested             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Marca .....                               | YotaPhone                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Trade                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Modelo y/o referencia tipo .....          | YD201                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Model and /or type reference              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Other identification of the product ..... | Commercial name: YOTAPHONE2<br>FCC ID: 2ADHW201<br>IC ID: 12469A-201                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Final HW version .....                    | P2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Final SW version .....                    | 3.9                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Serial number.....                        | 004402600038271 / 004402600038503                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Características .....                     | Bluetooth EDR+LE, WiFi b/g/n20, NFC and 2G/3G cellular                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Features                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Peticionario .....                        | YOTA DEVICES LTD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Applicant                                 | Arch. Makariou & Kalograion, 4, Nicolaides Sea View City, 9th Floor, Flat/Offices 903 -904, Block A-B, 6016, Larnaca, Cyprus.<br>Contact person: Jukka Ollila<br>Telephone: +358405433264<br>e-mail: jollila@yotadevices.com                                                                                                                                                                                                                                                                                                                                        |
| Método de ensayo solicitado, norma.....:  | USA FCC Part 15.247 10-1-13 Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.<br>USA FCC Part 15.209 10-1-13 Edition: Radiated emission limits; general requirements.<br>CANADA RSS-210 Issue 8 (December 2010).<br>CANADA RSS-Gen Issue 4 (November 2014).<br>Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 05/06/2014.<br>ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices. |
| Test method requested, standard           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Resultado.....                            | IN COMPLIANCE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Summary                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

|                                                                                                 |                              |
|-------------------------------------------------------------------------------------------------|------------------------------|
| <b>Aprobado por (nombre / cargo y firma) .....</b><br>Approved by (name / position & signature) | A. Llamas<br>RF Lab. Manager |
| <b>Fecha de realización .....</b><br>Date of issue                                              | 2014-12-04                   |
| <b>Formato de informe No. ....</b><br>Report template No                                        | FDT08_15                     |

# Index

|                                                               |     |
|---------------------------------------------------------------|-----|
| Competences and guarantees.....                               | 4   |
| General conditions.....                                       | 4   |
| Uncertainty .....                                             | 4   |
| Usage of samples.....                                         | 4   |
| Test sample description .....                                 | 5   |
| Test samples supplier .....                                   | 5   |
| Testing period.....                                           | 5   |
| Environmental conditions.....                                 | 6   |
| Remarks and comments.....                                     | 7   |
| Testing verdicts .....                                        | 8   |
| Appendix A – Test result “Bluetooth EDR” .....                | 10  |
| Appendix B – Test result “Bluetooth Low Energy” .....         | 80  |
| Appendix C – Test result “WiFi 2.4 GHz (802.11b/g/n20)” ..... | 111 |

## Competences and guarantees

AT4 wireless is a laboratory with a measurement facility in compliance with the requirements of Section 2.948 of the FCC rules and has been added to the list of facilities whose measurements data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Registration Number: 720267.

AT4 wireless is a laboratory with a measurement site in compliance with the requirements of RSS 212, Issue 1 (Provisional) and has been added to the list of filed sites of the Canadian Certification and Engineering Bureau. Reference File Number: IC 4621A-1.

In order to assure the traceability to other national and international laboratories, AT4 wireless has a calibration and maintenance program for its measurement equipment.

AT4 wireless guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at AT4 wireless at the time of performance of the test.

AT4 wireless is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of AT4 wireless.

## General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of AT4 wireless.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of AT4 wireless and the Accreditation Bodies.

## Uncertainty

Uncertainty (factor  $k=2$ ) was calculated according to the AT4 wireless internal document PODT000.

## Usage of samples

Samples undergoing test have been selected by: **the client**

Sample S/01 is composed of the following elements:

| Control N° | Description                      | Model | Serial N°                | Date of reception |
|------------|----------------------------------|-------|--------------------------|-------------------|
| 43116/027  | Smartphone with integral antenna | YD201 | IMEI:<br>004402600038271 | 2014-07-11        |

1. Sample S/01 has undergone following test(s).  
All radiated tests indicated in appendix A, appendix B and appendix C.

Sample S/02 is composed of the following elements:

| Control N° | Description                          | Model | Serial N°                | Date of reception |
|------------|--------------------------------------|-------|--------------------------|-------------------|
| 43116/010  | Smartphone with an antenna connector | YD201 | IMEI:<br>004402600038503 | 2014/07/08        |

1. Sample S/02 has undergone the test(s) specified in subclause “Test method requested”.

All conducted tests indicated in appendix A, appendix B and appendix C.

## Test sample description

The test sample consists of a smartphone with Bluetooth EDR+LE, WiFi b/g/n20, NFC and 2G/3G cellular.

## Test samples supplier

YOTA DEVICES LTD

Arch. Makariou & Kalograion, 4, Nicolaides Sea View City, 9th Floor, Flat/Offices 903 -904, Block A-B, 6016, Larnaca, Cyprus.

Contact person: Jukka Ollila

Telephone: +358405433264

e-mail: jollila@yotadevices.com

## Testing period

The performed test started on 2014-10-08 and finished on 2014-10-15.

The tests have been performed at AT4 wireless.

## Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

|                                      |                                  |
|--------------------------------------|----------------------------------|
| <b>Temperature</b>                   | Min. = 20.2 °C<br>Max. = 23.1 °C |
| <b>Relative humidity</b>             | Min. = 31.7 %<br>Max. = 43.0 %   |
| <b>Shielding effectiveness</b>       | > 100 dB                         |
| <b>Electric insulation</b>           | > 10 kΩ                          |
| <b>Reference resistance to earth</b> | < 0,5 Ω                          |

In the semianechoic chamber (21 meters x 11 meters x 8 meters), the following limits were not exceeded during the test.

|                                      |                                                                                             |
|--------------------------------------|---------------------------------------------------------------------------------------------|
| <b>Temperature</b>                   | Min. = 20.7 °C<br>Max. = 26.7 °C                                                            |
| <b>Relative humidity</b>             | Min. = 32.2 %<br>Max. = 41.7 %                                                              |
| <b>Air pressure</b>                  | Min. = 1008 mbar<br>Max. = 1013 mbar                                                        |
| <b>Shielding effectiveness</b>       | > 100 dB                                                                                    |
| <b>Electric insulation</b>           | > 10 kΩ                                                                                     |
| <b>Reference resistance to earth</b> | < 0,5 Ω                                                                                     |
| <b>Normal site attenuation (NSA)</b> | < ±4 dB at 10 m distance between item under test and receiver antenna, (30 MHz to 1000 MHz) |
| <b>Field homogeneity</b>             | More than 75% of illuminated surface is between 0 and 6 dB (26 MHz to 1000 MHz).            |

In the chamber for conducted measurements, the following limits were not exceeded during the test:

|                                      |                                      |
|--------------------------------------|--------------------------------------|
| <b>Temperature</b>                   | Min. = 23.6 °C<br>Max. = 25.1 °C     |
| <b>Relative humidity</b>             | Min. = 36.8 %<br>Max. = 46.4 %       |
| <b>Air pressure</b>                  | Min. = 1010 mbar<br>Max. = 1013 mbar |
| <b>Shielding effectiveness</b>       | > 100 dB                             |
| <b>Electric insulation</b>           | > 10 kΩ                              |
| <b>Reference resistance to earth</b> | < 0,5 Ω                              |

## Remarks and comments

### 1: Used instrumentation:

#### Conducted Measurements

|    |                                         | Last Cal. date | Cal. due date |
|----|-----------------------------------------|----------------|---------------|
| 1. | Spectrum analyser Rohde & Schwarz FSW50 | 2013/10        | 2015/10       |
| 2. | Spectrum analyser Agilent PSA E4440A    | 2014/06        | 2016/06       |

#### Radiated Measurements

|     |                                                                  | Last Cal. date | Cal. due date |
|-----|------------------------------------------------------------------|----------------|---------------|
| 1.  | Semianechoic Absorber Lined Chamber ETS FACT3 200STP             | N.A.           | N.A.          |
| 2.  | BiconicalLog antenna ETS LINDGREN 3142E                          | 2014/03        | 2017/03       |
| 3.  | Multi Device Controller EMCO 2090                                | N.A.           | N.A.          |
| 4.  | Double-ridge Guide Horn antenna 1-18 GHz SCHWARZBECK BBHA 9120 D | 2013/11        | 2016/11       |
| 5.  | Double-ridge Guide Horn antenna 18-40 GHz Agilent 119665J        | 2011/09        | 2014/09       |
| 6.  | EMI Test Receiver R&S ESU 26                                     | 2013/08        | 2015/08       |
| 7.  | Spectrum analyser Rohde & Schwarz FSW50                          | 2013/10        | 2015/10       |
| 8.  | RF pre-amplifier 10 MHz-6 GHz SCHWARZBECK BBV9743                | 2014/02        | 2015/02       |
| 9.  | RF pre-amplifier 1-18 GHz Schwarzbeck BBV 9718                   | 2014/02        | 2015/02       |
| 10. | RF pre-amplifier BONN BLMA 1840-1M 18-40 GHz.                    | 2014/02        | 2016/02       |

## Testing verdicts

|                      |     |
|----------------------|-----|
| Not applicable ..... | N/A |
| Pass .....           | P   |
| Fail .....           | F   |
| Not measured .....   | N/M |

### 1. Bluetooth EDR

| FCC PART 15 PARAGRAPH / RSS-210                            |                                                  | VERDICT |   |   |    |
|------------------------------------------------------------|--------------------------------------------------|---------|---|---|----|
|                                                            |                                                  | NA      | P | F | NM |
| FCC 15.247 Subclause (a) (1) / RSS-210 Clause A8.1 (b)     | 20 dB Bandwidth and Carrier frequency separation |         | P |   |    |
| FCC 15.247 Subclause (a)(1)(iii) / RSS-210 Clause A8.1 (d) | Number of hopping channels                       |         | P |   |    |
| FCC 15.247 Subclause (a)(1)(iii) / RSS-210 Clause A8.1 (d) | Time of occupancy (Dwell Time)                   |         | P |   |    |
| FCC 15.247 Subclause (b) / RSS-210, Clause A8.4 (2)        | Maximum peak output power and antenna gain       |         | P |   |    |
| FCC 15.247 Subclause (d) / RSS-210 Clause A8.5             | Emission limitations conducted (Transmitter)     |         | P |   |    |
| FCC 15.247 Subclause (d) / RSS-210 Clause A8.5             | Emission limitations radiated (Transmitter)      |         | P |   |    |

### 2. Bluetooth Low Energy

| FCC PART 15 PARAGRAPH / RSS-210                         |                                             | VERDICT |   |   |    |
|---------------------------------------------------------|---------------------------------------------|---------|---|---|----|
|                                                         |                                             | NA      | P | F | NM |
| Section 15.247 Subclause (a) (2) / RSS-210 A8.2. (a)    | 6 dB Bandwidth                              |         | P |   |    |
| Section 15.247 Subclause (b) / RSS-210 A8.4. (4)        | Maximum output power and antenna gain       |         | P |   |    |
| Section 15.247 Subclause (d) / RSS-210 A8.5. conducted  | Emission limitations (Transmitter)          |         | P |   |    |
| Section 15.247 Subclause (d) / RSS-210 A8.5. compliance | Band-edge emissions (Transmitter)           |         | P |   |    |
| Section 15.247 Subclause (e) / RSS-210 A8.2. (b)        | Power spectral density                      |         | P |   |    |
| Section 15.247 Subclause (d) / RSS-210 A8.5.            | Emission limitations radiated (Transmitter) |         | P |   |    |

### 3. WiFi 2.4 GHz (802.11b/g/n20)

| FCC PART 15 PARAGRAPH / RSS-210                                                           | VERDICT |   |   |    |
|-------------------------------------------------------------------------------------------|---------|---|---|----|
|                                                                                           | NA      | P | F | NM |
| Section 15.247 Subclause (a) (2) / RSS-210 A8.2. (a) 6 dB Bandwidth                       |         | P |   |    |
| Section 15.247 Subclause (b) / RSS-210 A8.4. (4) Maximum output power and antenna gain    |         | P |   |    |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations conducted (Transmitter) |         | P |   |    |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Band-edge emissions compliance (Transmitter) |         | P |   |    |
| Section 15.247 Subclause (e) / RSS-210 A8.2. (b) Power spectral density                   |         | P |   |    |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations radiated (Transmitter)  |         | P |   |    |

## Appendix A – Test result “Bluetooth EDR”

## INDEX

|                                                                                                                            |    |
|----------------------------------------------------------------------------------------------------------------------------|----|
| TEST CONDITIONS.....                                                                                                       | 12 |
| FCC Section 15.247 Subclause (a) (1) / RSS-210 Clause A8.1 (b). 20 dB Bandwidth and Carrier frequency separation..         | 13 |
| FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Number of hopping channels.....                      | 20 |
| FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Time of occupancy (Dwell Time).....                  | 26 |
| FCC Section 15.247 Subclause (b) / RSS-210 Clause A8.4 (2). Maximum peak output power and antenna gain .....               | 35 |
| FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Band-edge compliance of conducted emissions (Transmitter)<br>..... | 41 |
| FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Emission limitations conducted (Transmitter).....                  | 48 |
| FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Emission limitations radiated (Transmitter) .....                  | 53 |

## TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 3.8 \text{ Vdc}$$

Type of power supply = DC Voltage from rechargeable battery

Type of antenna = Integral antenna

Declared Gain for antenna (maximum) = 0 dBi

## TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2441 MHz

Highest channel: 2480 MHz

## CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyzer using a low loss RF cable. The reading in the spectrum analyser is corrected taking into account the cable loss.

## RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

## FCC Section 15.247 Subclause (a) (1) / RSS-210 Clause A8.1 (b). 20 dB Bandwidth and Carrier frequency separation

### SPECIFICATION

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### RESULTS

(See next plots)

Modulation: GFSK

|                                | Lowest frequency<br>2402 MHz | Middle frequency<br>2441 MHz | Highest frequency<br>2480 MHz |
|--------------------------------|------------------------------|------------------------------|-------------------------------|
| 20 dB Spectrum bandwidth (kHz) | 977.84                       | 995.37                       | 1012.00                       |
| Measurement uncertainty (kHz)  | ±11                          |                              |                               |

Modulation: Π/4-DQPSK (2Mbps)

|                                | Lowest frequency<br>2402 MHz | Middle frequency<br>2441 MHz | Highest frequency<br>2480 MHz |
|--------------------------------|------------------------------|------------------------------|-------------------------------|
| 20 dB Spectrum bandwidth (kHz) | 1311.00                      | 1293.00                      | 1308.00                       |
| Measurement uncertainty (kHz)  | ±11                          |                              |                               |


Modulation: 8-DPSK (3Mbps)

|                                | Lowest frequency<br>2402 MHz | Middle frequency<br>2441 MHz | Highest frequency<br>2480 MHz |
|--------------------------------|------------------------------|------------------------------|-------------------------------|
| 20 dB Spectrum bandwidth (kHz) | 1293.00                      | 1295.00                      | 1298.00                       |
| Measurement uncertainty (kHz)  | ±11                          |                              |                               |

## Modulation: GFSK


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation




The hopping channel carrier frequencies are separated by a minimum of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

## Modulation: $\Pi/4$ -DQPSK


20 dB BANDWIDTH.

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation




The hopping channel carrier frequencies are separated by a minimum of the two-thirds of the 20 dB bandwidth of the hopping channel

Verdict: PASS

## Modulation: 8-DPSK


20 dB BANDWIDTH

Lowest Channel: 2402 MHz.




20 dB BANDWIDTH

Middle Channel: 2441 MHz.




20 dB BANDWIDTH

Highest Channel: 2480 MHz.



Carrier frequency separation



The hopping channel carrier frequencies are separated by a minimum of the two-thirds of the 20 dB bandwidth of the hopping channel.

Verdict: PASS

## FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Number of hopping channels


### SPECIFICATION

Frequency hopping system in the 2400-2483.5 MHz band shall use at least 15 channels.


### RESULTS

The number of hopping channels is 79 for all three modes (see next plots).

### Modulation: GFSK



Number of hopping frequencies: 39




Number of hopping frequencies: 40


Total number of hopping frequencies: 79

Verdict: PASS

## Modulation: $\Pi/4$ -DQPSK



Number of hopping frequencies: 39




Number of hopping frequencies: 40


Total number of hopping frequencies: 79

Verdict: PASS

## Modulation: 8-DPSK



Number of hopping frequencies: 39



Number of hopping frequencies: 40

Total number of hopping frequencies: 79

Verdict: PASS

## FCC Section 15.247 Subclause (a) (1) (iii) / RSS-210 Clause A8.1 (d). Time of occupancy (Dwell Time)

### SPECIFICATION

The average time of occupancy on any channel shall not be greater than 0.4 seconds (400 ms) within a period of 0.4 seconds multiplied by the number of hopping channels employed =  $0.4 \times 79 = 31.6$  seconds.

### RESULTS


#### Modulation: GFSK

##### 1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of  $625 \mu\text{s}$  with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/2 = 800$  hops per second with 79 channels. So you have each channel  $800/79 = 10.13$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $10.13 \times 31.6 = 320.11$  times of appearance.

Each Tx-time per appearance is  $375.3 \mu\text{s}$  (see next plot).

So we have  $320.11 \times 375.3 \mu\text{s} = 120.14 \text{ ms}$  per 31.6 seconds.




Verdict: PASS

## 2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/4 = 400$  hops per second with 79 channels. So you have each channel  $400/79 = 5.1$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $5.1 \times 31.6 = 161.16$  times of appearance.

Each Tx-time per appearance is 1.625 ms (see next plot).

So we have  $161.16 \times 1.625 \text{ ms} = 261.89 \text{ ms}$  per 31.6 seconds.




Verdict: PASS

### 3. TIME OF OCCUPANCY (DWEELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet needs 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/6 = 266.67$  hops per second with 79 channels. So you have each channel  $266.67/79 = 3.37$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $3.37 \times 31.6 = 106.49$  times of appearance.

Each Tx-time per appearance is 2.875 ms (see next plot).

So we have  $106.49 \times 2.875 \text{ ms} = 306.16 \text{ ms}$  per 31.6 seconds.



Verdict: PASS


## Modulation: $\Pi/4$ -DQPSK

### 1. TIME OF OCCUPANCY (DWEELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of  $625\mu\text{s}$  with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/2 = 800$  hops per second with 79 channels. So you have each channel  $800/79 = 10.13$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $10.13 \times 31.6 = 320.11$  times of appearance.

Each Tx-time per appearance is  $379.6\mu\text{s}$  (see next plot).

So we have  $320.11 \times 379.6\mu\text{s} = 121.51\text{ ms}$  per 31.6 seconds.




Verdict: PASS

## 2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/4 = 400$  hops per second with 79 channels. So you have each channel  $400/79 = 5.1$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $5.1 \times 31.6 = 161.16$  times of appearance.

Each Tx-time per appearance is 1.622 ms (see next plot).

So we have  $161.16 \times 1.622 \text{ ms} = 261.40 \text{ ms}$  per 31.6 seconds.




Verdict: PASS

### 3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet needs 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/6 = 266.67$  hops per second with 79 channels. So you have each channel  $266.67/79 = 3.37$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $3.37 \times 31.6 = 106.49$  times of appearance.

Each Tx-time per appearance is 2.871 ms (see next plot).

So we have  $106.49 \times 2.871 \text{ ms} = 305.73 \text{ ms}$  per 31.6 seconds.



Verdict: PASS


## Modulation: 8-DPSK

### 1. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH1.

The system makes worst case 1600 hops per second or 1 time slot has a length of  $625\mu\text{s}$  with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/2 = 800$  hops per second with 79 channels. So you have each channel  $800/79 = 10.13$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $10.13 \times 31.6 = 320.11$  times of appearance.

Each Tx-time per appearance is  $383.1\mu\text{s}$  (see next plot).

So we have  $320.11 \times 383.1\mu\text{s} = 122.63 \text{ ms}$  per 31.6 seconds.




Verdict: PASS

## 2. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH3.

A DH3 Packet needs 3 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/4 = 400$  hops per second with 79 channels. So you have each channel  $400/79 = 5.1$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $5.1 \times 31.6 = 161.16$  times of appearance.

Each Tx-time per appearance is 1.628 ms (see next plot).

So we have  $161.16 \times 1.628 \text{ ms} = 262.37 \text{ ms}$  per 31.6 seconds.




Verdict: PASS

### 3. TIME OF OCCUPANCY (DWELL TIME) FOR PACKET TYPE DH5.

A DH5 Packet needs 5 time slots for transmitting and 1 time slot for receiving. Then the system makes worst case  $1600/6 = 266.67$  hops per second with 79 channels. So you have each channel  $266.67/79 = 3.37$  times per second and so for a period of  $0.4 \times 79 = 31.6$  seconds you have  $3.37 \times 31.6 = 106.49$  times of appearance.

Each Tx-time per appearance is 2.871 ms (see next plot).

So we have  $106.49 \times 2.871 \text{ ms} = 305.73 \text{ ms}$  per 31.6 seconds.



Verdict: PASS

## FCC Section 15.247 Subclause (b) / RSS-210 Clause A8.4 (2). Maximum peak output power and antenna gain

### SPECIFICATION

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels: 1 watt (30 dBm).

MAXIMUM OUTPUT POWER. See next plots.

Declared maximum antenna gain: 0 dBi.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

Modulation: GFSK

|                              | Lowest frequency<br>2402 MHz | Middle frequency<br>2441 MHz | Highest frequency<br>2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum peak power (dBm)     | 8.40                         | 8.86                         | 7.10                          |
| Maximum EIRP power (dBm)     | 8.40                         | 8.86                         | 7.10                          |
| Measurement uncertainty (dB) | ±1.5                         |                              |                               |

Modulation: Π/4-DQPSK (2Mbps)

|                              | Lowest frequency<br>2402 MHz | Middle frequency<br>2441 MHz | Highest frequency<br>2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum peak power (dBm)     | 9.23                         | 9.83                         | 7.22                          |
| Maximum EIRP power (dBm)     | 9.23                         | 9.83                         | 7.22                          |
| Measurement uncertainty (dB) | ±1.5                         |                              |                               |

Modulation: 8-DPSK (3Mbps)

|                              | Lowest frequency<br>2402 MHz | Middle frequency<br>2441 MHz | Highest frequency<br>2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum peak power (dBm)     | 9.52                         | 9.95                         | 8.23                          |
| Maximum EIRP power (dBm)     | 9.52                         | 9.95                         | 8.23                          |
| Measurement uncertainty (dB) | ±1.5                         |                              |                               |


The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.

Verdict: PASS

## PEAK OUTPUT POWER (CONDUCTED).


Modulation: GFSK

Lowest Channel: 2402 MHz.



Modulation: GFSK


Middle Channel: 2441 MHz.



## PEAK OUTPUT POWER (CONDUCTED).


Modulation: GFSK

Highest Channel: 2480 MHz.



Modulation:  $\Pi/4$ -DQPSK


Lowest Channel: 2402 MHz



## PEAK OUTPUT POWER (CONDUCTED)


Modulation:  $\Pi/4$ -DQPSK

Middle Channel: 2441 MHz.



Modulation:  $\Pi/4$ -DQPSK


Highest Channel: 2480 MHz.



## PEAK OUTPUT POWER (CONDUCTED).


Modulation: 8-DPSK

Lowest Channel: 2402 MHz



Modulation: 8-DPSK


Middle Channel: 2441 MHz.



# PEAK OUTPUT POWER (CONDUCTED).

Modulation: 8-DPSK

Highest Channel: 2480 MHz.



## FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Band-edge compliance of conducted emissions (Transmitter)


### SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power.

### RESULTS:


#### **Modulation: GFSK**

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

## 2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

## 3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


## Modulation: $\Pi/4$ -DQPSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS


## Modulation: 8-DPSK

1. LOW FREQUENCY SECTION 2402 MHz (HOPPING OFF). See next plot.




Verdict: PASS

2. HIGH FREQUENCY SECTION 2480 MHz (HOPPING OFF). See next plot.




Verdict: PASS

### 3. LOW FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

### 4. HIGH FREQUENCY SECTION (HOPPING ON). See next plot.



Verdict: PASS

## FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Emission limitations conducted (Transmitter)


### SPECIFICATION

In any 100 kHz bandwidths outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

### RESULTS:

#### **Modulation: GFSK**


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS


## 2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS

## 3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limits is the carrier frequency.

Verdict: PASS

## Modulation: $\Pi/4$ -DQPSK


1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS


2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peaks above the limits are the carrier frequencies.

Verdict: PASS

### 3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).




Note: The peak above the limit is the carrier frequency.

Verdict: PASS

### Modulation: 8-DPSK


#### 1. LOWEST CHANNEL (2402 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limits is the carrier frequency.

Verdict: PASS


## 2. MIDDLE CHANNEL (2441 MHz): 30 MHz-25 GHz (see next plot).



Note: The peaks above the limit are the carrier frequencies.

Verdict: PASS

## 3. HIGH CHANNEL (2480 MHz): 30 MHz-25 GHz (see next plot).



Note: The peak above the limit is the carrier frequency.

Verdict: PASS

## FCC Section 15.247 Subclause (d) / RSS-210 Clause A8.5. Emission limitations radiated (Transmitter)

### SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

| Frequency Range (MHz) | Field strength ( $\mu\text{V/m}$ ) | Field strength ( $\text{dB}\mu\text{V/m}$ ) | Measurement distance (m) |
|-----------------------|------------------------------------|---------------------------------------------|--------------------------|
| 0.009-0.490           | 2400/F(kHz)                        | -                                           | 300                      |
| 0.490-1.705           | 24000/F(kHz)                       | -                                           | 300                      |
| 1.705 - 30.0          | 30                                 | -                                           | 30                       |
| 30 - 88               | 100                                | 40                                          | 3                        |
| 88 - 216              | 150                                | 43.5                                        | 3                        |
| 216 - 960             | 200                                | 46                                          | 3                        |
| 960 - 25000           | 500                                | 54                                          | 3                        |

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

### RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

## Frequency range 30 MHz-1000 MHz.

Note: The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode selected in the EUT.

### Spurious levels operating (radiated) closest to limit.

| Spurious frequency (MHz) | Polarization | Detector   | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|------------|-------------------------|------------------------------|
| 83.229                   | V            | Quasi-peak | 23.81                   | ±4.12                        |
| 199.993                  | V            | Quasi-peak | 22.38                   | ±4.12                        |

## Frequency range 1 GHz-25 GHz

Modulation: GFSK

### 1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.32818                  | V            | Peak     | 47.80                   | ± 4.0                        |
|                          | V            | RMS      | 35.76                   | ± 4.0                        |
| 2.488073                 | V            | Peak     | 48.10                   | ± 4.0                        |
|                          | V            | RMS      | 36.36                   | ± 4.0                        |
| 2.671233                 | V            | Peak     | 47.81                   | ± 4.0                        |
|                          | V            | RMS      | 37.01                   | ± 4.0                        |

### 2. CHANNEL: MIDDLE (2441 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.326844                 | V            | Peak     | 47.83                   | ± 4.0                        |
|                          | V            | RMS      | 35.81                   | ± 4.0                        |
| 2.486560                 | V            | Peak     | 49.23                   | ± 4.0                        |
|                          | V            | RMS      | 36.47                   | ± 4.0                        |
| 2.727100                 | V            | Peak     | 48.12                   | ± 4.0                        |
|                          | V            | RMS      | 37.94                   | ± 4.0                        |

### 3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.354367                 | V            | Peak     | 47.47                   | ± 4.0                        |
|                          | V            | RMS      | 36.54                   | ± 4.0                        |
| 2.357196                 | V            | Peak     | 48.44                   | ± 4.0                        |
|                          | V            | RMS      | 35.78                   | ± 4.0                        |
| 2.490708                 | V            | Peak     | 49.08                   | ± 4.0                        |
|                          | V            | RMS      | 36.31                   | ± 4.0                        |

Verdict: PASS

Modulation: Π/4-DQPSK

### 1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 1.983700                 | V            | Peak     | 45.10                   | ± 4.0                        |
|                          | V            | RMS      | 34.07                   | ± 4.0                        |
| 2.368236                 | V            | Peak     | 47.88                   | ± 4.0                        |
|                          | V            | RMS      | 35.72                   | ± 4.0                        |
| 2.494558                 | V            | Peak     | 48.44                   | ± 4.0                        |
|                          | V            | RMS      | 36.86                   | ± 4.0                        |

### 2. CHANNEL: MIDDLE (2441 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.321633                 | V            | Peak     | 47.67                   | ± 4.0                        |
|                          | V            | RMS      | 36.11                   | ± 4.0                        |
| 2.387772                 | V            | Peak     | 47.87                   | ± 4.0                        |
|                          | V            | RMS      | 35.80                   | ± 4.0                        |
| 2.495419                 | V            | Peak     | 49.02                   | ± 4.0                        |
|                          | V            | RMS      | 36.47                   | ± 4.0                        |

### 3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.354289                 | V            | Peak     | 48.23                   | ± 4.0                        |
|                          | V            | RMS      | 36.59                   | ± 4.0                        |
| 2.814567                 | V            | Peak     | 47.98                   | ± 4.0                        |
|                          | V            | RMS      | 37.62                   | ± 4.0                        |
| 2.483638                 | V            | Peak     | 49.40                   | ± 4.0                        |
|                          | V            | RMS      | 37.40                   | ± 4.0                        |

Verdict: PASS

Modulation: 8-DPSK

### 1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.343108                 | V            | Peak     | 47.66                   | ± 4.0                        |
|                          | V            | RMS      | 35.51                   | ± 4.0                        |
| 2.487527                 | V            | Peak     | 48.44                   | ± 4.0                        |
|                          | V            | RMS      | 36.43                   | ± 4.0                        |
| 2.534633                 | V            | Peak     | 48.32                   | ± 4.0                        |
|                          | V            | RMS      | 37.22                   | ± 4.0                        |

### 2. CHANNEL: MIDDLE (2441 MHz).


| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.238167                 | V            | Peak     | 46.53                   | ± 4.0                        |
|                          | V            | RMS      | 35.34                   | ± 4.0                        |
| 2.361892                 | V            | Peak     | 47.63                   | ± 4.0                        |
|                          | V            | RMS      | 35.72                   | ± 4.0                        |
| 2.491291                 | V            | Peak     | 48.13                   | ± 4.0                        |
|                          | V            | RMS      | 36.30                   | ± 4.0                        |

### 3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.356884                 | V            | Peak     | 47.83                   | ± 4.0                        |
|                          | V            | RMS      | 35.55                   | ± 4.0                        |
| 2.494602                 | V            | Peak     | 48.82                   | ± 4.0                        |
|                          | V            | RMS      | 36.44                   | ± 4.0                        |
| 2.691433                 | V            | Peak     | 47.39                   | ± 4.0                        |
|                          | V            | RMS      | 37.17                   | ± 4.0                        |

Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels and all modulation modes).

## FREQUENCY RANGE 1 GHz to 3 GHz.


Modulation: GFSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot is the carrier frequency.


Modulation:  $\Pi/4$ -DQPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.


CHANNEL: Highest (2480 MHz).



Note: The peak shown in the plot is the carrier frequency.


Modulation: 8-DPSK

CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Middle (2441 MHz).



Note: The peak shown in the plot is the carrier frequency.

CHANNEL: Highest (2480 MHz).




Note: The peak shown in the plot is the carrier frequency.


## FREQUENCY RANGE 3 GHz to 18 GHz.

Modulation: GFSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: Π/4-DQPSK


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2441 MHz).




CHANNEL: Highest (2480 MHz).




Modulation: 8-DPSK


CHANNEL: Lowest (2402 MHz).




CHANNEL: Middle (2441 MHz).



CHANNEL: Highest (2480 MHz).



## FREQUENCY RANGE 18 GHz to 25 GHz.




(This plot is valid for all three channels and all modulation modes).


## FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)

CHANNEL: Lowest


Modulation: GFSK



Modulation: Π/4-DQPSK




## Modulation: 8-DPSK




## CHANNEL: Middle


## Modulation: GFSK



## Modulation: $\Pi/4$ -DQPSK




## Modulation: 8-DPSK




CHANNEL: Highest


Modulation: GFSK



Modulation: Π/4-DQPSK




## Modulation: 8-DPSK




## FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)

CHANNEL: Lowest


Modulation: GFSK



Modulation: Π/4-DQPSK




## Modulation: 8-DPSK




## CHANNEL: Middle


## Modulation: GFSK



## Modulation: $\Pi/4$ -DQPSK




## Modulation: 8-DPSK




CHANNEL: Highest


Modulation: GFSK



Modulation:  $\pi/4$ -DQPSK



## Modulation: 8-DPSK



## Appendix B – Test result “Bluetooth Low Energy”

## INDEX

|                                                                                                 |     |
|-------------------------------------------------------------------------------------------------|-----|
| TEST CONDITIONS.....                                                                            | 82  |
| Occupied Bandwidth.....                                                                         | 83  |
| Section 15.247 Subclause (a) (2) / RSS-210 A8.2. (a). 6 dB Bandwidth .....                      | 86  |
| Section 15.247 Subclause (b) / RSS-210 A8.4. (4). Maximum output power and antenna gain .....   | 89  |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations conducted (Transmitter) ..... | 92  |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Band-edge emissions compliance (Transmitter) ..... | 95  |
| Section 15.247 Subclause (e) / RSS-210 A8.5. Power spectral density .....                       | 97  |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations radiated (Transmitter) .....  | 100 |

## TEST CONDITIONS

Power supply (V):

$$V_{\text{nominal}} = 3.8 \text{ Vdc}$$

Type of power supply = DC Voltage from rechargeable battery

Type of antenna = Integral antenna

Declared Gain for antenna = 0 dBi

## TEST FREQUENCIES:

Lowest channel: 2402 MHz

Middle channel: 2440 MHz

Highest channel: 2480 MHz

## CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and connected to the spectrum analyzer using a low loss calibrated RF cable. The measurement readings are corrected with the cable loss (dB).

## RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


## Occupied Bandwidth

### RESULTS


(see next plots).

|                               | Lowest frequency<br>2402 MHz | Middle frequency<br>2440 MHz | Highest frequency<br>2480 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 99% bandwidth (MHz)           | 1.066                        | 1.067                        | 1.068                         |
| -26 dBc bandwidth (MHz)       | 1.275                        | 1.282                        | 1.283                         |
| Measurement uncertainty (kHz) | ±7                           |                              |                               |


## Lowest Channel



## Middle Channel



## Highest channel



## Section 15.247 Subclause (a) (2) / RSS-210 A8.2. (a). 6 dB Bandwidth

### SPECIFICATION

The minimum 6 dB bandwidth shall be at least 500 kHz.

### RESULTS


6 dB Bandwidth (see next plots).

|                               | Lowest frequency<br>2402 MHz | Middle frequency<br>2440 MHz | Highest frequency<br>2480 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 6 dB Spectrum bandwidth (kHz) | 672.7                        | 674.7                        | 670.7                         |
| Measurement uncertainty (kHz) | ±7                           |                              |                               |


Verdict: PASS

## 6 dB BANDWIDTH.


### Lowest Channel



### Middle Channel



## Highest Channel



## Section 15.247 Subclause (b) / RSS-210 A8.4. (4). Maximum output power and antenna gain

### SPECIFICATION

For systems using digital modulation in the 2400-2483.5 MHz band: 1 watt (30 dBm).  
 The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

### RESULTS

The maximum peak conducted output power was measured using the method according to point 9.1.1. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 05/06/2014.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

MAXIMUM OUTPUT POWER. See next plots.

Maximum declared antenna gain: 0 dBi.


|                               | Lowest frequency<br>2402 MHz | Middle frequency<br>2440 MHz | Highest frequency<br>2480 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum conducted power (dBm) | 1.20                         | 1.22                         | -0.06                         |
| Maximum EIRP power (dBm)      | 1.20                         | 1.22                         | -0.06                         |
| Measurement uncertainty (dB)  | ±1.5                         |                              |                               |

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.


Verdict: PASS

## CONDUCTED PEAK POWER.


Lowest frequency



Middle frequency



## Highest frequency



## Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations conducted (Transmitter)

### SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

### RESULTS:

#### Reference Level Measurement

|                                      | Lowest frequency<br>2402 MHz | Middle frequency<br>2440 MHz | Highest frequency<br>2480 MHz |
|--------------------------------------|------------------------------|------------------------------|-------------------------------|
| Reference Level Measurement<br>(dBm) | 0.85                         | 0.93                         | -0.66                         |
| Measurement uncertainty (dB)         | ±1.5                         |                              |                               |

#### Lowest frequency 2402 MHz

All peaks are more than 20 dB below the limit.

#### Middle frequency 2440 MHz


All peaks are more than 20 dB below the limit.

#### Highest frequency 2480 MHz

All peaks are more than 20 dB below the limit.


Verdict: PASS

CH LOW:




Note: The peak above the limit is the carrier frequency.

CH MIDDLE:



Note: The peak above the limit is the carrier frequency.

CH HIGH:



Note: The peak above the limit is the carrier frequency.

## Section 15.247 Subclause (d) / RSS-210 A8.5. Band-edge emissions compliance (Transmitter)


### SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

### RESULTS:

#### 1. LOW FREQUENCY SECTION. CONDUCTED.


See next plot.



Verdict: PASS

## 2. HIGH FREQUENCY SECTION. CONDUCTED.

See next plot.



Verdict: PASS

## Section 15.247 Subclause (e) / RSS-210 A8.5. Power spectral density

### SPECIFICATION

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### RESULTS

The maximum power spectral density level in the fundamental emission was measured using the method PKPSD (Peak PSD) according to point 10.2. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 05/06/2014.


Power spectral density (see next plots).

|                              | Lowest frequency<br>2402 MHz | Middle frequency<br>2440 MHz | Highest frequency<br>2480 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Power spectral density (dBm) | -2.00                        | -1.82                        | -3.32                         |
| Measurement uncertainty (dB) | ±1.5                         |                              |                               |


Verdict: PASS

## Power spectral density.


### Lowest Channel



### Middle Channel



## Highest Channel



## Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations radiated (Transmitter)

### SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

| Frequency Range (MHz) | Field strength ( $\mu\text{V/m}$ ) | Field strength ( $\text{dB}\mu\text{V/m}$ ) | Measurement distance (m) |
|-----------------------|------------------------------------|---------------------------------------------|--------------------------|
| 0.009-0.490           | 2400/F(kHz)                        | -                                           | 300                      |
| 0.490-1.705           | 24000/F(kHz)                       | -                                           | 300                      |
| 1.705 - 30.0          | 30                                 | -                                           | 30                       |
| 30 - 88               | 100                                | 40                                          | 3                        |
| 88 - 216              | 150                                | 43.5                                        | 3                        |
| 216 - 960             | 200                                | 46                                          | 3                        |
| 960 - 25000           | 500                                | 54                                          | 3                        |

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

### RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

## Frequency range 30 MHz-1000 MHz.

The spurious signals detected do not depend on the operating channel.

Spurious levels closest to the limit.

| Spurious frequency (MHz) | Polarization | Detector   | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|------------|-------------------------------|------------------------------|
| 211.269                  | H            | Quasi-peak | 26.58                         | $\pm 4.12$                   |
| 750.104                  | H            | Quasi-peak | 28.37                         | $\pm 4.12$                   |
| 875.113                  | V            | Quasi-peak | 30.70                         | $\pm 4.12$                   |

## Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

Spurious signals with peak levels above the average limit (54 dB $\mu$ V/m at 3 m) are measured with RMS detector for checking compliance with the average limit.

### 1. CHANNEL: LOWEST (2402 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.371615                 | V            | Peak     | 48.01                         | $\pm 4.00$                   |
| 2.497268                 | H            | Peak     | 48.71                         | $\pm 4.00$                   |
| 2.580167                 | V            | Peak     | 49.69                         | $\pm 4.00$                   |
| 13.264250                | V            | Peak     | 52.10                         | $\pm 4.00$                   |
| 17.68125                 | H            | Peak     | 58.36                         | $\pm 4.00$                   |
|                          |              | RMS      | 46.08                         | $\pm 4.00$                   |

### 2. CHANNEL: MIDDLE (2440 MHz).


| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.335668                 | V            | Peak     | 48.11                         | $\pm 4.00$                   |
| 2.497778                 | H            | Peak     | 48.81                         | $\pm 4.00$                   |
| 2.788367                 | H            | Peak     | 49.23                         | $\pm 4.00$                   |
| 14.421250                | H            | Peak     | 54.18                         | $\pm 4.00$                   |
|                          |              | RMS      | 42.85                         | $\pm 4.00$                   |

### 3. CHANNEL: HIGHEST (2480 MHz).

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.372932                 | H            | Peak     | 48.60                         | $\pm 4.00$                   |
| 2.495076                 | V            | Peak     | 49.00                         | $\pm 4.00$                   |
| 2.758167                 | V            | Peak     | 49.25                         | $\pm 4.00$                   |
| 11.24725                 | H            | Peak     | 52.23                         | $\pm 4.00$                   |
| 14.469750                | V            | Peak     | 53.59                         | $\pm 4.00$                   |


Verdict: PASS

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels).

FREQUENCY RANGE 1 GHz to 3 GHz.  
 CHANNEL: Lowest (2402 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

CHANNEL: Middle (2440 MHz).



Note: The peak shown in the plot above the limit is the carrier frequency.


## CHANNEL: Highest (2480 MHz).




Note: The peak shown in the plot above the limit is the carrier frequency.

## FREQUENCY RANGE 3 GHz to 18 GHz.


## CHANNEL: Lowest (2402 MHz).




## CHANNEL: Middle (2440 MHz).



## CHANNEL: Highest (2480 MHz).




## FREQUENCY RANGE 18 GHz to 26 GHz.




(This plot is valid for all three channels).

FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)


CHANNEL: Lowest (2402 MHz).



CHANNEL: Middle (2440 MHz).




## CHANNEL: Highest (2480 MHz).




## FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)


## CHANNEL: Lowest (2402 MHz).



## CHANNEL: Middle (2440 MHz).



## CHANNEL: Highest (2480 MHz).



## Appendix C – Test result “WiFi 2.4 GHz (802.11b/g/n20)”

## INDEX

|                                                                                                |     |
|------------------------------------------------------------------------------------------------|-----|
| TEST CONDITIONS.....                                                                           | 113 |
| Occupied Bandwidth.....                                                                        | 115 |
| Section 15.247 Subclause (a) (2) / RSS-210 A8.2. (a). 6 dB Bandwidth .....                     | 121 |
| Section 15.247 Subclause (b) / RSS-210 A8.4. (4). Maximum output power and antenna gain.....   | 127 |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations conducted (Transmitter)..... | 134 |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Band-edge emissions compliance (Transmitter)..... | 143 |
| Section 15.247 Subclause (e) / RSS-210 A8.5. Power spectral density .....                      | 145 |
| Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations radiated (Transmitter).....  | 152 |

## TEST CONDITIONS

Power supply (V):

$V_{\text{nominal}} = 3.8 \text{ Vdc}$

Type of power supply = DC Voltage from rechargeable battery

Type of antenna = Integral antenna

Declared Gain for antenna = 0 dBi

### TEST FREQUENCIES:

For WiFi 802.11b/g/n20:

Lowest channel (1): 2412 MHz

Middle channel (6): 2437 MHz

Highest channel (11): 2462 MHz

The test set-up was made in accordance to the general provisions of FCC DTS Measurement KDB 558074 D01 DTS Meas Guidance v03r02.

The embedded test mode was used to configure the EUT to continuously transmit at a specified output power with different modes and modulation schemes.

WiFi 2.4 GHz: 802.11b, 802.11g, 802.11n20 (20 MHz channel bandwidth).

The field strength at the band edges was evaluated for each mode and on each chain individually on the lowest and highest channels at the rated power for the channel under test. Where the power at the edge channels was lower than the power at the center channels additional measurements were made at the adjacent channels.

During transmitter test the EUT was being controlled by the embedded test software to operate in a continuous transmit mode on the test channels as required and in each of the different modulation modes.

The data rates of 1Mb/s for 802.11b, 6Mb/s for 802.11g and 6.5 Mb/s for 802.11n20 were selected based on preliminary testing that identified those rates corresponding to the worst cases for output power and band edge levels at restricted bands.

The conducted RF output power was adjusted according to the client's supplied adjustment values (see following table), which were selected in the test software:

| Mode    | BW (MHz) | Channel / Freq. | Data Rate | Power adjustment |
|---------|----------|-----------------|-----------|------------------|
| 802.11b | 20       | 1 / 2412        | 1 Mbps    | 15               |
|         |          | 2 / 2417        |           | 15               |
|         |          | 6 / 2437        |           | 15               |
|         |          | 10 / 2457       |           | 15               |
|         |          | 11 / 2462       |           | 15               |
| 802.11g | 20       | 1 / 2412        | 6 Mbps    | 16               |
|         |          | 2 / 2417        |           | 16               |
|         |          | 3 / 2422        |           | 16               |
|         |          | 6 / 2437        |           | 16               |
|         |          | 9 / 2452        |           | 16               |
|         |          | 10 / 2457       |           | 16               |
|         |          | 11 / 2462       |           | 16               |
| 802.11n | 20       | 1 / 2412        | 6.5 Mbps  | 15               |
|         |          | 2 / 2417        |           | 15               |
|         |          | 3 / 2422        |           | 15               |
|         |          | 6 / 2437        |           | 15               |
|         |          | 9 / 2452        |           | 15               |
|         |          | 10 / 2457       |           | 15               |
|         |          | 11 / 2462       |           | 15               |

## CONDUCTED MEASUREMENTS

The equipment under test was set up in a shielded room and it is connected to the spectrum analyser using a calibrated low loss RF cable. The reading in the spectrum analyser is compensated with the cable loss at each measurement frequency.

## RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30 MHz-1000 MHz (30 MHz-1000 MHz Bilog antenna) and at a distance of 1m for the frequency range 1 GHz-25 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-40 GHz horn antenna).

For radiated emissions in the range 1 GHz-25 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive (wooden) platform one meter above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

## Occupied Bandwidth

### RESULTS

#### 1. WiFi 2.4GHz 802.11 b mode

Occupied Bandwidth (see next plots).

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 99% bandwidth (MHz)           | 17.65                        | 17.85                        | 17.79                         |
| Measurement uncertainty (kHz) | ±21.7                        |                              |                               |

#### 2. WiFi 2.4GHz 802.11 g mode

Occupied Bandwidth (see next plots).

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 99% bandwidth (MHz)           | 18.36                        | 18.45                        | 18.36                         |
| Measurement uncertainty (kHz) | ±21.7                        |                              |                               |


#### 3. WiFi 2.4GHz 802.11 n20 mode

Occupied Bandwidth (see next plots).


|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 99% bandwidth (MHz)           | 18.32                        | 18.29                        | 18.20                         |
| Measurement uncertainty (kHz) | ±21.7                        |                              |                               |

## 1. WiFi 2.4GHz 802.11 b mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.




Highest Channel: 2462 MHz.




## 2. WiFi 2.4GHz 802.11 g mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.




Highest Channel: 2462 MHz.




### 3. WiFi 2.4GHz 802.11 n20 mode

Lowest Channel: 2412 MHz.




**Transmit Freq Error** 72.372 kHz  
**x dB Bandwidth** 17.743 MHz

Middle Channel: 2437 MHz.



**Transmit Freq Error** -38.989 kHz  
**x dB Bandwidth** 17.734 MHz

Highest Channel: 2462 MHz.



## Section 15.247 Subclause (a) (2) / RSS-210 A8.2. (a). 6 dB Bandwidth

### SPECIFICATION

The minimum 6 dB bandwidth shall be at least 500 kHz.

### RESULTS

#### 1. WiFi 2.4GHz 802.11 b mode

6 dB Bandwidth (see next plots).

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 6 dB Spectrum bandwidth (MHz) | 16.360                       | 16.440                       | 16.380                        |
| Measurement uncertainty (kHz) | ±89                          |                              |                               |

Verdict: PASS

#### 2. WiFi 2.4GHz 802.11 g mode

6 dB Bandwidth (see next plots).

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 6 dB Spectrum bandwidth (MHz) | 16.420                       | 16.520                       | 16.360                        |
| Measurement uncertainty (kHz) | ±89                          |                              |                               |

Verdict: PASS

#### 3. WiFi 2.4GHz 802.11 n20 mode


6 dB Bandwidth (see next plots).

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| 6 dB Spectrum bandwidth (MHz) | 17.618                       | 17.598                       | 17.618                        |
| Measurement uncertainty (kHz) | ±89                          |                              |                               |


Verdict: PASS

## 1. WiFi 2.4GHz 802.11 b mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.




Highest Channel: 2462 MHz.




## 2. WiFi 2.4GHz 802.11 g mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.




Highest Channel: 2462 MHz.




### 3. WiFi 2.4GHz 802.11 n20 mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.



Highest Channel: 2462 MHz.



## Section 15.247 Subclause (b) / RSS-210 A8.4. (4). Maximum output power and antenna gain

### SPECIFICATION

The maximum peak conducted output power of the intentional radiator shall not exceed 1 watt (30 dBm).  
The e.i.r.p. shall not exceed 4 W (36 dBm) (Canada).

### RESULTS

The maximum Peak Conducted Output Power was measured using the channel integration with peak detector method according to point 2.0. of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 06/05/2014.

The EIRP power (dBm) is calculated by adding the declared maximum antenna gain to the measured conducted power.

#### 1. WiFi 2.4GHz 802.11 b mode

MAXIMUM OUTPUT POWER. Peak Conducted Output Power (See next plots).

Maximum declared antenna gain: 0 dBi.

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum conducted power (dBm) | 16.48                        | 16.04                        | 16.00                         |
| Maximum EIRP power (dBm)      | 16.48                        | 16.04                        | 16.00                         |
| Measurement uncertainty (dB)  | ±1.5                         |                              |                               |

Verdict: PASS

## 2. WiFi 2.4GHz 802.11 g mode

MAXIMUM OUTPUT POWER. Peak Conducted Output Power (See next plots).

Maximum declared antenna gain: 0 dBi.

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum conducted power (dBm) | 16.61                        | 16.81                        | 16.48                         |
| Maximum EIRP power (dBm)      | 16.61                        | 16.81                        | 16.48                         |
| Measurement uncertainty (dB)  | ±1.5                         |                              |                               |

Verdict: PASS

## 3. WiFi 2.4GHz 802.11 n20 mode

MAXIMUM OUTPUT POWER. Peak Conducted Output Power (See next plots).

Maximum declared antenna gain: 0 dBi.

|                               | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|-------------------------------|------------------------------|------------------------------|-------------------------------|
| Maximum conducted power (dBm) | 15.90                        | 15.53                        | 15.60                         |
| Maximum EIRP power (dBm)      | 15.90                        | 15.53                        | 15.60                         |
| Measurement uncertainty (dB)  | ±1.5                         |                              |                               |


Verdict: PASS

The maximum directional gain of the antenna is less than 6 dBi and therefore the maximum output power is not required to be reduced from the stated values.


## Peak conducted output power.

### 1. WiFi 2.4GHz 802.11 b mode


Lowest frequency 2412 MHz.



Middle frequency 2437 MHz.




Highest frequency 2462 MHz.




## 2. WiFi 2.4GHz 802.11 g mode


Lowest frequency 2412 MHz.



Middle frequency 2437 MHz.




Highest frequency 2462 MHz.




### 3. WiFi 2.4GHz 802.11 n20 mode


Lowest frequency 2412 MHz.



Middle frequency 2437 MHz.



Highest frequency 2462 MHz.



## Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations conducted (Transmitter)

### SPECIFICATION

In any 100 kHz bandwidth outside the frequency band in which the digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.

### RESULTS:

#### 1. WiFi 2.4GHz 802.11 b mode

##### Reference Level Measurement

|                                      | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|--------------------------------------|------------------------------|------------------------------|-------------------------------|
| Reference Level Measurement<br>(dBm) | 4.61                         | 3.80                         | 4.14                          |
| Measurement uncertainty (dB)         | ±1.5                         |                              |                               |

| Lowest frequency 2412 MHz                      | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -15.39      |


| Middle frequency 2437 MHz                      | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -16.20      |

| Highest frequency 2462 MHz                     | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -15.86      |

Verdict: PASS


See next plots.

CH LOW:




Note: The peak above the limit is the carrier frequency.

CH MIDDLE:



Note: The peak above the limit is the carrier frequency.

CH HIGH:



Note: The peak above the limit is the carrier frequency.

## 2. WiFi 2.4GHz 802.11 g mode

### Reference Level Measurement

|                                      | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|--------------------------------------|------------------------------|------------------------------|-------------------------------|
| Reference Level Measurement<br>(dBm) | 5.21                         | 5.16                         | 5.08                          |
| Measurement uncertainty (dB)         | ±1.5                         |                              |                               |

| Lowest frequency 2412 MHz                      | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -14.79      |


| Middle frequency 2437 MHz                      | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -14.84      |

| Highest frequency 2462 MHz                     | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -14.92      |

Verdict: PASS


See next plots.

CH LOW:




Note: The peak above the limit is the carrier frequency.

CH MIDDLE:



Note: The peak above the limit is the carrier frequency.

CH HIGH:



Note: The peak above the limit is the carrier frequency.

### 3. WiFi 2.4GHz 802.11 n20 mode

#### Reference Level Measurement

|                                      | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|--------------------------------------|------------------------------|------------------------------|-------------------------------|
| Reference Level Measurement<br>(dBm) | 4.43                         | 4.20                         | 4.43                          |
| Measurement uncertainty (dB)         | ±1.5                         |                              |                               |

| Lowest frequency 2412 MHz                      | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -15.57      |


| Middle frequency 2437 MHz                      | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -15.80      |

| Highest frequency 2462 MHz                     | Limit (dBm) |
|------------------------------------------------|-------------|
| All peaks are more than 20 dB below the limit. | -15.57      |

Verdict: PASS


See next plots.

CH LOW:




Note: The peak above the limit is the carrier frequency.

CH MIDDLE:



Note: The peak above the limit is the carrier frequency.

CH HIGH:



Note: The peak above the limit is the carrier frequency.

## Section 15.247 Subclause (d) / RSS-210 A8.5. Band-edge emissions compliance (Transmitter)

### SPECIFICATION

Emissions outside the frequency band in which the intentional radiator is operating shall be at least 20dB below the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB.


### RESULTS:

Note: Radiated measurements were used to show compliance with the limits in the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz.

See next plots.


LOW FREQUENCY SECTION 2412 MHz. CONDUCTED.

#### 1. WiFi 2.4GHz 802.11 b mode




Verdict: PASS (NOTE: The limit is set to -20 dBc since the maximum peak conducted output power was measured for this mode.)

## 2. WiFi 2.4GHz 802.11 g mode



Verdict: PASS (NOTE: The limit is set to -20 dBc since the maximum peak conducted output power was measured for this mode.)

## 3. WiFi 2.4GHz 802.11 n20 mode



Verdict: PASS (NOTE: The limit is set to -20 dBc since the maximum peak conducted output power was measured for this mode.)

## Section 15.247 Subclause (e) / RSS-210 A8.5. Power spectral density

### SPECIFICATION

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### RESULTS

The maximum power spectral density level in the fundamental emission was measured using the method PKPSD (peak PSD), according to point 10.2 of Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 558074 D01 DTS Meas Guidance v03r02 dated 06/05/2014.

#### 1. WiFi 2.4GHz 802.11 b mode

Power spectral density (See next plots).

|                              | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Power spectral density (dBm) | 4.73                         | 3.76                         | 4.14                          |
| Measurement uncertainty (dB) | ±1.5                         |                              |                               |

Verdict: PASS

#### 2. WiFi 2.4GHz 802.11 g mode

Power spectral density (See next plots).

|                              | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Power spectral density (dBm) | 5.21                         | 5.16                         | 5.08                          |
| Measurement uncertainty (dB) | ±1.5                         |                              |                               |

Verdict: PASS

### 3. WiFi 2.4GHz 802.11 n20 mode


Power spectral density (See next plots).

|                              | Lowest frequency<br>2412 MHz | Middle frequency<br>2437 MHz | Highest frequency<br>2462 MHz |
|------------------------------|------------------------------|------------------------------|-------------------------------|
| Power spectral density (dBm) | 4.43                         | 4.20                         | 4.43                          |
| Measurement uncertainty (dB) | $\pm 1.5$                    |                              |                               |


Verdict: PASS

## 1. WiFi 2.4GHz 802.11 b mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.




Highest Channel: 2462 MHz.




## 2. WiFi 2.4GHz 802.11 g mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.




Highest Channel: 2462 MHz.




### 3. WiFi 2.4GHz 802.11 n20 mode


Lowest Channel: 2412 MHz.



Middle Channel: 2437 MHz.



Highest Channel: 2462 MHz.



## Section 15.247 Subclause (d) / RSS-210 A8.5. Emission limitations radiated (Transmitter)

### SPECIFICATION

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)):

| Frequency Range (MHz) | Field strength ( $\mu\text{V/m}$ ) | Field strength ( $\text{dB}\mu\text{V/m}$ ) | Measurement distance (m) |
|-----------------------|------------------------------------|---------------------------------------------|--------------------------|
| 0.009-0.490           | 2400/F(kHz)                        | -                                           | 300                      |
| 0.490-1.705           | 24000/F(kHz)                       | -                                           | 300                      |
| 1.705 - 30.0          | 30                                 | -                                           | 30                       |
| 30 - 88               | 100                                | 40                                          | 3                        |
| 88 - 216              | 150                                | 43.5                                        | 3                        |
| 216 - 960             | 200                                | 46                                          | 3                        |
| 960 - 25000           | 500                                | 54                                          | 3                        |

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

### RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-25 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

The equipment transmits continuously in the selected channel so it is not necessary a duty cycle correction factor.

Frequency range 30 MHz-1000 MHz.

The spurious signals detected do not depend on either the operating channel or the modulation mode.

Spurious levels closest to the limit:

| Spurious frequency (MHz) | Polarization | Detector   | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|------------|-------------------------------|------------------------------|
| 47.096                   | PV           | Quasi-Peak | 27.58                         | $\pm 4.12$                   |
| 132.093                  | PV           | Quasi-Peak | 27.25                         | $\pm 4.12$                   |
| 143.975                  | PV           | Quasi-Peak | 31.82                         | $\pm 4.12$                   |
| 480.808                  | PV           | Quasi-Peak | 25.85                         | $\pm 4.12$                   |

Frequency range 1 GHz-25 GHz

The results in the next tables show the maximum measured levels in the 1-25 GHz range including the restricted bands 2.31-2.39 GHz and 2.4835-2.5 GHz (see next plots).

For OFDM modulation modes (802.11g and 802.11n20), a preliminary measurement in the central channel in the range 1-18 GHz was performed to determine the worst case. The lowest and highest channels were measured for out-of-band emissions for the worst case (802.11g).

The field strength at the band edges was evaluated for each mode on the lowest and highest channels at the rated power for the channel under test. Where the power at the edge channels was lower than the power at the center channels additional measurements were made at the adjacent channels.

Spurious signals with peak levels above the average limit (54 dB $\mu$ V/m at 3 m) are measured with RMS detector for checking compliance with the average limit.

## 1. WiFi 2.4GHz 802.11 b mode.

1.1. CHANNEL 1: LOWEST (2412 MHz). Out-of-band spurious emissions in the 1-25 GHz range and inside restricted band 2.31-2.39 GHz.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.389930                 | PV           | Peak     | 53.31                   | ± 4.00                       |
| 2.663633                 | PH           | Peak     | 48.42                   | ± 4.00                       |
| 4.823750                 | PV           | Peak     | 35.22                   | ± 4.00                       |

1.2. CHANNEL 6: MIDDLE (2437 MHz). Out-of-band spurious emissions in the 1-25 GHz range.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.77990                  | PV           | Peak     | 48.97                   | ± 4.00                       |
| 4.874250                 | PV           | Peak     | 35.20                   | ± 4.00                       |

1.3. CHANNEL 11: HIGHEST (2462 MHz). Out-of-band spurious emissions in the 1-25 GHz range and inside restricted band 2.4835-2.5 GHz.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dBμV/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------|------------------------------|
| 2.483640                 | PV           | Peak     | 58.94                   | ± 4.00                       |
|                          |              | RMS      | 41.24                   |                              |
| 2.814367                 | PH           | Peak     | 48.58                   | ± 4.00                       |
| 4.923750                 | PV           | Peak     | 35.51                   | ± 4.00                       |

Verdict: PASS

## 2. WiFi 2.4GHz 802.11 g mode (worst case OFDM)

2.1. CHANNEL 1: LOWEST (2412 MHz). Out-of-band spurious emissions in the 1-25 GHz range and inside restricted band 2.31-2.39 GHz.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.389990                 | PV           | Peak     | 70.83                         | $\pm 4.00$                   |
|                          |              | RMS      | 51.58                         | $\pm 4.00$                   |
| 2.566767                 | PH           | Peak     | 48.76                         | $\pm 4.00$                   |
| 4.824250                 | PH           | Peak     | 37.42                         | $\pm 4.00$                   |
| 9.647750                 | PH           | Peak     | 45.88                         | $\pm 4.00$                   |

2.2. CHANNEL 6: MIDDLE (2437 MHz). Out-of-band spurious emissions in the 1-25 GHz range.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.155767                 | PV           | Peak     | 46.98                         | $\pm 4.00$                   |

2.3. CHANNEL 11: HIGHEST (2462 MHz). Out-of-band spurious emissions in the 1-25 GHz range and inside restricted band 2.4835-2.5 GHz.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.483600                 | PV           | Peak     | 71.18                         | $\pm 4.00$                   |
|                          |              | RMS      | 53.81                         | $\pm 4.00$                   |
| 2.524767                 | PV           | Peak     | 48.26                         | $\pm 4.00$                   |
| 4.923750                 | PV           | Peak     | 35.80                         | $\pm 4.00$                   |

Verdict: PASS

### 3. WiFi 2.4GHz 802.11 n20 mode

#### 3.1. CHANNEL 1 (2412 MHz). Spurious emissions in restricted band 2.31-2.39 GHz.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.38986                  | PV           | Peak     | 71.08                         | $\pm 4.00$                   |
|                          |              | RMS      | 52.37                         | $\pm 4.00$                   |


#### 3.2. CHANNEL 6: MIDDLE (2437 MHz). Out-of-band spurious emissions in the 1-25 GHz range.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.488367                 | PV           | Peak     | 49.79                         | $\pm 4.00$                   |

#### 3.3. CHANNEL 11 (2462 MHz). Spurious emissions in restricted band 2.4835-2.5 GHz.

| Spurious frequency (GHz) | Polarization | Detector | Emission Level (dB $\mu$ V/m) | Measurement Uncertainty (dB) |
|--------------------------|--------------|----------|-------------------------------|------------------------------|
| 2.483540                 | PV           | Peak     | 72.13                         | $\pm 4.00$                   |
|                          |              | RMS      | 53.35                         | $\pm 4.00$                   |

FREQUENCY RANGE 30 MHz-1000 MHz.




(This plot is valid for all three channels and all modulation modes).


FREQUENCY RANGE 1 GHz to 3 GHz.

# 1. WiFi 2.4GHz 802.11 b mode

CHANNEL 1 (2412 MHz).




Note: The peak above the limit is the carrier frequency.  
 CHANNEL 6 (2437 MHz).



Note: The peak above the limit is the carrier frequency.


## CHANNEL 11 (2462 MHz).



Note: The peak above the limit is the carrier frequency.


## 2. WiFi 2.4GHz 802.11 g mode (worst case)

### CHANNEL 1 (2412 MHz).




Note: The peak above the limit is the carrier frequency.

## CHANNEL 6 (2437 MHz).



Note: The peak above the limit is the carrier frequency.


## CHANNEL 11 (2462 MHz).



Note: The peak above the limit is the carrier frequency.

### 3.WiFi 2.4GHz 802.11 n20 mode

CHANNEL 6 (2437 MHz).




Note: The peak above the limit is the carrier frequency.


FREQUENCY RANGE 3 GHz to 18 GHz.

### 1. WiFi 2.4GHz 802.11 b mode


CHANNEL 1 (2412 MHz).



CHANNEL 6 (2437 MHz).




## CHANNEL 11 (2462 MHz).




## 2. WiFi 2.4GHz 802.11 g mode (worst case)


### CHANNEL 1 (2412 MHz).



## CHANNEL 6 (2437 MHz).




## CHANNEL 11 (2462 MHz).




### 3.WiFi 2.4GHz 802.11 n20 mode

CHANNEL 6 (2437 MHz)



FREQUENCY RANGE 18 GHz to 25 GHz. No spurious signals were detected.




(This plot is valid for all modes).

Radiated spurious emissions at band-edges and inside restricted bands 2.31-2.39 GHz and 2.4835 – 2.5 GHz.  
 FREQUENCY RANGE 2.31 GHz to 2.39 GHz. (RESTRICTED BAND)


1. WiFi 2.4GHz 802.11 b mode

CHANNEL 1 (2412 MHz).




2. WiFi 2.4GHz 802.11 g mode

CHANNEL 1 (2412 MHz).



### 3. WiFi 2.4GHz 802.11 n20 mode


CHANNEL 1 (2412 MHz).



FREQUENCY RANGE 2.4835 GHz to 2.5 GHz. (RESTRICTED BAND)


### 1. WiFi 2.4GHz 802.11 b mode

CHANNEL 11 (2462 MHz).



### 2. WiFi 2.4GHz 802.11 g mode

CHANNEL 11 (2462 MHz).



### 3. WiFi 2.4GHz 802.11 n20 mode

CHANNEL 11 (2462 MHz).

