



RF Exposure Evaluation Report

Report No.: SET2014-12801

Product: OBD Telematics Dongle

FCC ID: 2ADKG-CW-601G

Model No.: CW-601GX0

Applicant: Shenzhen Chainway ITS Co., Ltd.

Address: R&D Building A 601, Tsinghua Information Harbor, Hi-Tech
Industrial Park North, Nanshan, Shenzhen, China

Issued by: CCIC-SET

Lab Location: Electronic Testing Building, Shahe Road, Xili, Nanshan District,
Shenzhen, 518055, P. R. China

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of **8** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product: OBD Telematics Dongle

Model No.: CW-601GX0

Applicant: Shenzhen Chainway ITS Co., Ltd.


Applicant Address: R&D Building A 601, Tsinghua Information Harbor,
Hi-Tech Industrial Park North, Nanshan, Shenzhen, China

Manufacturer: Shenzhen Chainway ITS Co., Ltd.


Manufacturer Address: R&D Building A 601, Tsinghua Information Harbor,
Hi-Tech Industrial Park North, Nanshan, Shenzhen,
China

Test Standards: ANSI Std C95.1-1992: Safety Levels with Respect to
Human Exposure to Radio Frequency
Electromagnetic Fields, 3KHz-300GHz.(IEEE Std
C95.1-1992)

Test Result: Pass

Tested by: 
2014.11.24

Haigang He, Test Engineer

Reviewed by: 
2014.11.24

Lu Lei, Senior Engineer

Approved by: 
2014.11.24

Wu Li'an, Manager



Table of Contents

Test Report	2
1 .General Information	4
1.1 Description of EUT	4
1.2 Test specifications	4
2 RF Exposure Limit Introduction	5
3 Conducted RF Output Power (Unit: dBm)	7
4 RF Exposure Evaluation	7

1 .General Information

1.1 Description of EUT

Product Feature & Specification	
DUT Type	OBD Telematics Dongle
Model Name	CW-601GX0
FCC ID	2ADKG-CW-601G
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz
Antenna Type	FIFA Antenna
Antenna gain	-1 dBi
HW Version	OBD II _V24
SW Version	OBD_WM_1.7
Test of Modulation	GMSK

Remark 1: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.2 Test specifications

ANSI Std C95.1-1992	Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3KHz-300GHz.(IEEE Std C95.1-1992)
KDB 447498 D01V05	General RF Exposure Guidance

2 RF Exposure Limit Introduction

An estimation of MPE in this application for product is used to ensure if it complies to the rules of the standard in the regulation list above.

Maximum permissible exposure (MPE) refers to the RF energy that is acceptable for human exposure. It is broken down into two categories, Occupational/controlled and General population/uncontrolled.

Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

We analysis if it comply with the limits for General population/uncontrolled exposure. The FCC's MPE limits for field strength and power density are given in 47CFR 1.1310(Table below).These limits are generally based on recommended exposure guidelines published by the National Council on Radiation Protection and Measurements (NCRP), and also partly based on guidelines recommended by the American National Standards Institute (ANSI) in Section 4.1 of ANSI/IEEE C95.1.

Table: Limits For Maximum Permissible Exposure(MPE)

Limits for Occupational/controlled Exposure				
Frequency Range(MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength(H) (A/m)	Power Density(S) (mW/cm ²)	Averaging Time (minute) E ² , H ² or s
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6



(B) Limits for General Population/uncontrolled Exposure				
Frequency Range(MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density(S) (mW/cm ²)	Averaging Time (minute) E ² , H ² or s
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S=power density

P=power input to the antenna

G=numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the centre of radiation of the antenna

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with $R=20\text{cm}$, and if it is below the limit S, then we can conclude the device complies with the rules. 3 Conducted RF Output Power (Unit: dBm)

3 Conducted RF Output Power (Unit: dBm)

Burst Average power						
Band	GSM850			GSM1900		
Channel	128	190	251	512	661	810
Frequency Band(MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK)	32.81	32.86	32.84	30.44	30.57	30.35
GPRS(GMSK)	32.19	32.36	32.20	29.85	29.79	30.01

4 RF Exposure Evaluation

Frequency Band (MHz)	GSM850	GPRS850
Antenna Gain (dBi)	-1.00	-1.00
Antenna Gain (numeric)	0.79	0.79
Power(mW)	1 931.96	1721.87
R(cm)	20	20
S(mW/ cm ²)	0.30	0.27
MPE Limit(mW/ cm ²)	0.55	0.55
Conclusion	Pass	Pass

Note:

GSM850/GPRS850:(uplink: 824-849MHz, downlink: 869-894MHz)

For the GPRS mode, all the slots and channels were tested and just the worst data was record in this report.

According to the Table, we can conclude the max power density level at 20 cm is 0.30mW/cm², which is below the uncontrolled exposure limit of 0.55mW/cm² at 824MHz, so we can conclude it is into compliance.



Frequency Band (MHz)	GSM1900	GPRS1900
Antenna Gain (dBi)	-1.00	-1.00
Antenna Gain (numeric)	0.79	0.79
Power(mW)	1140.25	1002.31
R(cm)	20	20
S(mW/ cm ²)	0.18	0.16
MPE Limit(mW/ cm ²)	1.00	1.00
Conclusion	Pass	Pass

Note:

GSM1900/GPRS1900:(uplink: 1850-1910MHz, downlink: 1930-1990MHz)

For the GPRS mode, all the slots and channels were tested and just the worst data was record in this report.

According to the Table, we can conclude the max power density level at 20 cm is 0.18mW/cm², which is below the uncontrolled exposure limit of 1.0mW/cm² at 1909MHz, so we can conclude it is into compliance.

** END OF REPORT **