

FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

VisionNova

MODEL No.: VN8-C

FCC ID: 2ADKQ-VN8C

Trade Mark: VisionNova

REPORT NO.: ES150812153E-1

ISSUE DATE: December 30, 2015

Prepared for

Globe International AS

Ljabruveien 39, PO. Box 90 Nordstrand, N-1112 Oslo, Norway

Prepared by

SHENZHEN EMTEK CO., LTD

Bldg 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION	4
3	SUMMARY OF TEST RESULT	5
4	TEST METHODOLOGY	6
4.1	General Description Of Applied Standards	6
4.2	Measurement Equipment Used	6
4.3	Description Of Test Modes	7
5	FACILITIES AND ACCREDITATIONS	8
5.1	Facilities	8
5.2	Laboratory Accreditations And Listings	8
6	TEST SYSTEM UNCERTAINTY	9
7	SETUP OF EQUIPMENT UNDER TEST	10
7.1	Radio Frequency Test Setup 1	10
7.2	Radio Frequency Test Setup 2	10
7.3	Conducted Emission Test Setup	10
7.4	Block Diagram Configuration Of Test System	13
7.5	Support Equipment	13
8	TEST REQUIREMENTS.....	14
8.1	DTS (6db) Bandwidth.....	14
8.2	Maximum Peak Conducted Output Power.....	23
8.3	Maximum Power Spectral Density	24
8.4	Unwanted Emissions In Non-Restricted Frequency Bands	33
8.5	Radiated Spurious Emission	39
8.6	Conducted Emissions Test.....	51
8.7	Antenna Application	54

1 TEST RESULT CERTIFICATION

Applicant: Globe International AS
Ljabruveien 39, PO. Box 90 Nordstrand, N-1112 Oslo, Norway

Manufacturer: Oppolink Technology Ltd.
Unit Q, 2/F, Camelpaint Building Block 3, 60 Hoi Yuen Road, Kwun Tong, Kowloon,
H.K.

EUT Description: VisionNova

Model Number: VN8-C

File Number: ES150812153E-1

Date of Test: August 15, 2015 to October 10, 2015


Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C	PASS


The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 12, 2015 to October 10, 2015

Prepared by : 
Joanna Jiao/Editor

Reviewer : 
Joe Xia/Supervisor

Approve & Authorized Signer : 
Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Device Type	Wifi 2.4G Device
IEEE 802.11 WLAN Mode Supported	☒ 802.11b(20MHz bandwidth) ☒ 802.11g(20MHz bandwidth) ☒ 802.11n(20MHz bandwidth) ☒ 802.11n(40MHz bandwidth)
Data Rate	☒ 802.11 b:1,2,5.5,11Mbps ☒ 802.11 g:6,9,12,18,24,36,48,54Mbps ☒ 802.11n(HT20):MCS0-MCS7 ☒ 802.11n(HT40):MCS0-MCS7
MIMO Mode	N/A
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n
Operating Frequency Range	☒ 2412-2462MHz for 802.11b/g ☒ 2412-2462MHz for 802.11n(HT20) ☒ 2422-2452MHz for 802.11n(HT40)
Number of Channels	☒ 11 channels for 802.11b/g ☒ 11 channels for 802.11n(HT20) ☒ 7 channels for 802.11n(HT40)
Transmit Power Max	19.26dBm for 802.11b 21.11dBm for 802.11g 21.01dBm for 802.11n(HT20) 20.16 dBm for 802.11n(HT40)
Antenna Type	Dipole Antenna
Smart system	☒ SISO for 802.11b/g/n ☐ MIMO for 802.11n
Antenna Gain	0dBi
Power supply	☒ DC supply: DC3.7V internal rechargeable lithium battery or DC 5V from adapter
	☒ Adapter supply: Model: DYS122-050200W-1 Input: 100-240V~ 50/60Hz, 0.3A MAX Output: DC 5.0V, 2.0A

Note: for more details, please refer to the User's manual of the EUT.

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ADKQ-VN8C filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

The system is compliance with Subpart B is authorized under a DOC procedure

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
 FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 FCC KDB 558074 D01 DTS Meas Guidance v03r02

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/17/2015
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/17/2015
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/17/2015
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/17/2015
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/17/2015

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/17/2015
Pre-Amplifier	HP	8447D	2944A07999	05/17/2015
Bilog Antenna	Schwarzbeck	VULB9163	142	05/17/2015
Loop Antenna	ARA	PLA-1030/B	1029	05/17/2015
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/17/2015
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/17/2015
Cable	Schwarzbeck	AK9513	ACRX1	05/17/2015
Cable	Rosenberger	N/A	FP2RX2	05/17/2015
Cable	Schwarzbeck	AK9513	CRPX1	05/17/2015
Cable	Schwarzbeck	AK9513	CRRX2	05/17/2015

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/17/2015
Signal Analyzer	Agilent	N9010A	My53470879	05/17/2015
Power meter	Anritsu	ML2495A	0824006	05/17/2015
Power sensor	Anritsu	MA2411B	0738172	05/17/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (☒802.11b: 1 Mbps; ☒802.11g: 6 Mbps; ☒802.11n (HT20): MCS0; ☒802.11n (HT40): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

☒Frequency and Channel list for 802.11 b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

☒Frequency and Channel list for 802.11 n (HT40):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	8	2447
4	2427	6	2437	9	2452
		7	2442		

☒Test Frequency and Channel for 802.11 b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

☒Test Frequency and channel for 802.11 n (HT40):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

- EMC Lab.
- : Accredited by CNAS, 2013.10.28
The certificate is valid until 2016.10.29
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L229
 - : Accredited by TUV Rheinland Shenzhen, 2015.4
The Laboratory has been assessed according to the requirements ISO/IEC 17025.
 - : Accredited by FCC, April 17, 2013
The Certificate Registration Number is 406365.
 - : Accredited by FCC, July 24, 2013
The Certificate Registration Number is 709623.
 - : Accredited by Industry Canada, November 29, 2012
The Certificate Registration Number is 4480A.

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



7.5 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
1.	N/A	N/A	N/A	N/A	N/A	

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 DTS (6DB) BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Measure and record the results in the test report.

8.1.5 Test Results


Temperature :	28°C	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
☒802.11b	1	2412	10.02	500	PASS
	6	2437	10.05	500	PASS
	11	2462	10.04	500	PASS
☒802.11g	1	2412	15.17	500	PASS
	6	2437	15.17	500	PASS
	11	2462	15.17	500	PASS
☒802.11n (HT20)	1	2412	15.18	500	PASS
	6	2437	15.17	500	PASS
	11	2462	15.18	500	PASS
☒802.11n (HT40)	3	2422	35.31	500	PASS
	6	2437	35.31	500	PASS
	9	2452	35.31	500	PASS


Test Model DTS (6dB) Bandwidth
802.11b
Channel 1: 2412MHz



Test Model DTS (6dB) Bandwidth
802.11b
Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth	
	802.11b	
	Channel 11: 2462MHz	




Test Model

DTS (6dB) Bandwidth
802.11g
Channel 1: 2412MHz




Test Model


DTS (6dB) Bandwidth
802.11g
Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth 802.11g Channel 11: 2462MHz
------------	---




Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 1: 2412MHz




Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth	
	802.11n (HT20)	
	Channel 11: 2462MHz	




Test Model	DTS (6dB) Bandwidth
	802.11n (HT40)
	Channel 3: 2422MHz



Test Model	DTS (6dB) Bandwidth
	802.11n (HT40)
	Channel 6: 2437MHz



Test Model	DTS (6dB) Bandwidth
	802.11n (HT40)
	Channel 9: 2452MHz



8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part 15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The testing follows FCC public Notice DA 00-705 Measurement Guidelines.

The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit=30-(Gain - 6)

8.2.5 Test Results

Temperature :	28°C	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
☒802.11b	1	2412	18.80	30	PASS
	6	2437	19.14	30	PASS
	11	2462	19.26	30	PASS
☒802.11g	1	2412	19.79	30	PASS
	6	2437	21.11	30	PASS
	11	2462	20.52	30	PASS
☒802.11n (HT20)	1	2412	19.85	30	PASS
	6	2437	21.01	30	PASS
	11	2462	20.45	30	PASS
☒802.11n (HT40)	3	2422	18.13	30	PASS
	6	2437	20.16	30	PASS
	9	2452	18.23	30	PASS

8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8-(Gain - 6)

8.3.5 Test Results

Temperature :	28 °C	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
☒802.11b	1	2412	-6.830	8	PASS
	6	2437	-6.826	8	PASS
	11	2462	-4.860	8	PASS
☒802.11g	1	2412	-12.606	8	PASS
	6	2437	-10.567	8	PASS
	11	2462	-12.236	8	PASS
☒802.11n (HT20)	1	2412	-12.588	8	PASS
	6	2437	-11.397	8	PASS
	11	2462	-11.613	8	PASS
☒802.11n (HT40)	3	2422	-17.666	8	PASS
	6	2437	-16.347	8	PASS
	9	2452	-18.472	8	PASS

Test Model	Power Spectral Density
	802.11b
	Channel 1: 2412MHz



Test Model	Power Spectral Density
	802.11b
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11b
	Channel 11: 2462MHz




Test Model

Power Spectral Density
802.11g
Channel 1: 2412MHz




Test Model


Power Spectral Density
802.11g
Channel 6: 2437MHz




Test Model	Power Spectral Density 802.11g Channel 11: 2462MHz
------------	--




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 11: 2462MHz




Test Model	Power Spectral Density
	802.11n (HT40)
	Channel 3: 2422MHz



Test Model	Power Spectral Density
	802.11n (HT40)
	Channel 6: 2437MHz



Test Model	Power Spectral Density
	802.11n (HT40)
	Channel 9: 2452MHz



8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.


8.4.5 Test Results

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:


Test Model	PSD(Power Spectral Density) RBW=100kHz			
	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 1: 2412MHz		☐ Channel 3: 2422MHz	




Test Model	Unwanted Emissions in non-restricted frequency bands			
	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 1: 2412MHz		☐ Channel 3: 2422MHz	




Test Model	Band edge			
	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 1: 2412MHz		☐ Channel 3: 2422MHz	




Test Model	PSD(Power Spectral Density) RBW=100kHz	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	Channel 6: 2437MHz				




Test Model	Unwanted Emissions In Non-Restricted Frequency Bands	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	Channel 6: 2437MHz				




Test Model	PSD(Power Spectral Density) RBW=100kHz			
	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 11: 2462MHz	☐ Channel 9: 2452MHz		



Test Model	Unwanted Emissions In Non-Restricted Frequency Bands			
	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
	☒ Channel 11: 2462MHz	☐ Channel 9: 2452MHz		



Test Model	Band edge	☒ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☐ 802.11n(HT40)
		☒ Channel 11: 2462MHz		☐ Channel 9: 2452MHz	



8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and KDB 558074 DTS 01 Meas. Guidance v03r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	48.5 - 13.8	300
0.490-1.705	24000/F(KHz)	33.8 - 23.0	30
1.705-30	30	29.5	30
30-88	100	40.0	3
88-216	150	43.5	3
216-960	200	46.0	3
Above 960	500	54.0	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz), 200Hz for $f < 150$ KHz (9KHz to 150KHz), 9KHz for $f < 30$ MHz (150KHz to 30KHz)

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the

measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24°C	Test Date:	September 25, 2015
Humidity:	53 %	Test By:	King Kong
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/\text{test distance})$ (dB);

Limit line = Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Temperature :	28°C	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong
Test mode:	802.11b	Frequency:	Channel 1: 2412MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4823.95	V	45.71	28.05	74.00	54.00	-28.29	-25.95
7233.42	V	47.55	31.17	74.00	54.00	-26.45	-22.83
9650.18	V	50.03	32.85	74.00	54.00	-23.97	-21.15
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4821.67	H	41.98	25.23	74.00	54.00	-32.02	-28.77
7233.91	H	45.56	27.50	74.00	54.00	-28.44	-26.50
7650.93	H	45.73	28.39	74.00	54.00	-28.27	-25.61

Temperature :	28℃	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong
Test mode:	802.11b	Frequency:	Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4873.99	V	44.43	27.34	74.00	54.00	-29.57	-26.66
7311.31	V	47.12	30.23	74.00	54.00	-26.88	-23.77
9748.31	V	49.44	33.16	74.00	54.00	-24.56	-20.84
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4871.02	H	40.66	25.29	74.00	54.00	-33.34	-28.71
7310.79	H	44.68	26.47	74.00	54.00	-29.32	-27.53
9748.42	H	45.02	28.68	74.00	54.00	-28.98	-25.32

Temperature :	28℃	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong
Test mode:	802.11b	Frequency:	Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924.36	V	43.62	26.74	74.00	54.00	-30.38	-27.26
7366.03	V	47.25	29.51	74.00	54.00	-26.75	-24.49
9850.73	V	49.92	32.71	74.00	54.00	-24.08	-21.29
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4921.25	H	42.08	25.26	74.00	54.00	-31.92	-28.74
7365.62	H	43.83	25.91	74.00	54.00	-30.17	-28.09
9851.00	H	43.56	27.68	74.00	54.00	-30.44	-26.32

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Temperature :	28℃	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong
Test mode:	802.11nHT40	Frequency:	Channel 3: 2422MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2389.105	H	48.48	74.00	34.90	54.00
2389.105	V	48.86	74.00	35.20	54.00

Temperature :	28℃	Test Date :	September 25, 2015
Humidity :	65 %	Test By:	King Kong
Test mode:	802.11nHT40	Frequency:	Channel 9: 2452MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	PK(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
2483.599	H	51.43	74.00	40.50	54.00
2483.599	V	50.77	74.00	39.30	54.00

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model	Spurious Emission in Restricted Band 2310-2390MHz			
	☐ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☒ 802.11n(HT40)
	☐ Channel 1: 2412MHz	☒ Channel 3: 2422MHz	Polarity: H	
VBW=3MHz		Test By: King Kong		




Test Model	Spurious Emission in Restricted Band 2310-2390MHz			
	☐ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☒ 802.11n(HT40)
	☐ Channel 1: 2412MHz	☒ Channel 3: 2422MHz	Polarity: V	
VBW=3MHz		Test By: King Kong		



Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz			
	☐ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☒ 802.11n(HT40)
	☐ Channel 11: 2462MHz	☒ Channel 9: 2452MHz	Polarity: H	
	VBW=3MHz		Test By: King Kong	




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz			
	☐ 802.11b	☐ 802.11g	☐ 802.11n(HT20)	☒ 802.11n(HT40)
	☐ Channel 11: 2462MHz	☒ Channel 9: 2452MHz	Polarity: V	
	VBW=3MHz		Test By: King Kong	



■ Spurious Emission below 1GHz (30MHz to 1GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:



Site 3m Chamber #3

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Nami Vision

M/N: VN8-C


Mode: 11B 2412

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		227.8800	41.55	-15.37	26.18	46.00	-19.82	QP		
2		276.3800	42.68	-12.61	30.07	46.00	-15.93	QP		
3		335.5500	43.53	-12.70	30.83	46.00	-15.17	QP		
4		540.2200	32.96	-7.48	25.48	46.00	-20.52	QP		
5		588.7200	37.91	-7.07	30.84	46.00	-15.16	QP		
6	*	672.1400	44.00	-6.27	37.73	46.00	-8.27	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Nami Vision

M/N: VN8-C


Mode: 11B 2412

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		227.8800	39.46	-15.37	24.09	46.00	-21.91	QP		
2		335.5500	38.03	-12.70	25.33	46.00	-20.67	QP		
3		419.9400	39.39	-9.43	29.96	46.00	-16.04	QP		
4		515.9700	41.52	-7.67	33.85	46.00	-12.15	QP		
5	!	588.7200	47.67	-7.07	40.60	46.00	-5.40	QP		
6	*	674.0800	47.05	-6.24	40.81	46.00	-5.19	QP		

!:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 53 %
 EUT: Nami Vision
 M/N: VN8-C
 Mode:11B 2437
 Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		227.8800	41.87	-15.37	26.50	46.00	-19.50	QP		
2		276.3800	41.95	-12.61	29.34	46.00	-16.66	QP		
3		335.5500	42.51	-12.70	29.81	46.00	-16.19	QP		
4		540.2200	34.18	-7.48	26.70	46.00	-19.30	QP		
5		588.7200	38.05	-7.07	30.98	46.00	-15.02	QP		
6	*	672.1400	43.69	-6.27	37.42	46.00	-8.58	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL



Site 3m Chamber #3
 Limit: (RE)FCC PART 15 CLASS B
 EUT: Nami Vision
 M/N: VN8-C
 Mode: 11B 2437
 Note:


Polarization: **Vertical**
 Power: AC 120V/60Hz

Temperature: 24 C
 Humidity: 53 %

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		83.3500	40.17	-18.80	21.37	40.00	-18.63	QP		
2		335.5500	36.92	-12.70	24.22	46.00	-21.78	QP		
3		419.9400	40.22	-9.43	30.79	46.00	-15.21	QP		
4		515.9700	41.41	-7.67	33.74	46.00	-12.26	QP		
5	*	588.7200	48.15	-7.07	41.08	46.00	-4.92	QP		
6		672.1400	42.02	-6.27	35.75	46.00	-10.25	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL




Site 3m Chamber #3
 Limit: (RE)FCC PART 15 CLASS B
 EUT: Nami Vision
 M/N: VN8-C
 Mode: 11B 2462
 Note:

Polarization: **Horizontal**
 Power: AC 120V/60Hz
 Temperature: 24 C
 Humidity: 53 %

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		227.8800	42.00	-15.37	26.63	46.00	-19.37	QP		
2		276.3800	42.63	-12.61	30.02	46.00	-15.98	QP		
3		335.5500	42.49	-12.70	29.79	46.00	-16.21	QP		
4		588.7200	37.24	-7.07	30.17	46.00	-15.83	QP		
5	*	672.1400	43.52	-6.27	37.25	46.00	-8.75	QP		
6		713.8500	32.97	-5.55	27.42	46.00	-18.58	QP		

*:Maximum data x:Over limit !:over margin

Operator: CSL



Site 3m Chamber #3

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 CLASS B

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Nami Vision

M/N: VN8-C

Mode:11B 2462

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
		MHz	Level	Factor	ment			Height	Degree	
			dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		227.8800	39.26	-15.37	23.89	46.00	-22.11	QP		
2		335.5500	37.20	-12.70	24.50	46.00	-21.50	QP		
3		419.9400	39.40	-9.43	29.97	46.00	-16.03	QP		
4		515.9700	41.71	-7.67	34.04	46.00	-11.96	QP		
5	!	588.7200	47.48	-7.07	40.41	46.00	-5.59	QP		
6	*	674.0800	47.02	-6.24	40.78	46.00	-5.22	QP		

!:Maximum data x:Over limit !:over margin

Operator: CSL

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results



Site Conduction #2

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Vision Nova


M/N: VN8-C

Mode: ON

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4400	38.80	0.00	38.80	57.06	-18.26	QP	
2		0.4400	27.49	0.00	27.49	47.06	-19.57	AVG	
3		0.8350	36.02	0.00	36.02	56.00	-19.98	QP	
4		0.8350	30.32	0.00	30.32	46.00	-15.68	AVG	
5		2.5100	36.15	0.00	36.15	56.00	-19.85	QP	
6		2.5100	30.19	0.00	30.19	46.00	-15.81	AVG	
7		4.1950	36.30	0.00	36.30	56.00	-19.70	QP	
8		4.1950	31.58	0.00	31.58	46.00	-14.42	AVG	
9		7.5600	34.85	0.00	34.85	60.00	-25.15	QP	
10		7.5600	32.34	0.00	32.34	50.00	-17.66	AVG	
11		25.2250	41.43	0.00	41.43	60.00	-18.57	QP	
12	*	25.2250	36.12	0.00	36.12	50.00	-13.88	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: HJ



Site Conduction #2

Phase: **N**

Temperature: 26

Limit: (CE)FCC PART 15 class B_QP

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Vision Nova

M/N: VN8-C

Mode: ON

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1	*	0.4400	47.69	0.00	47.69	57.06	-9.37	QP	
2		0.4400	33.09	0.00	33.09	47.06	-13.97	AVG	
3		0.8450	43.16	0.00	43.16	56.00	-12.84	QP	
4		0.8450	35.69	0.00	35.69	46.00	-10.31	AVG	
5		1.5500	41.56	0.00	41.56	56.00	-14.44	QP	
6		1.5500	24.48	0.00	24.48	46.00	-21.52	AVG	
7		2.5300	43.15	0.00	43.15	56.00	-12.85	QP	
8		2.5300	34.81	0.00	34.81	46.00	-11.19	AVG	
9		9.2900	38.41	0.00	38.41	60.00	-21.59	QP	
10		9.2900	34.87	0.00	34.87	50.00	-15.13	AVG	
11		27.8750	40.02	0.00	40.02	60.00	-19.98	QP	
12		27.8750	35.99	0.00	35.99	50.00	-14.01	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: HJ

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

PASS.

The EUT has 1 antenna: a Dipole Antenna for wifi 2.4G, the gain is 0 dBi;

Note: ☒ Antenna use a permanently attached antenna which is not replaceable.
☐ Not using a standard antenna jack or electrical connector for antenna replacement
☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.