



# **FCC Part 15B TEST REPORT**

Report No: STS1512126E01

Issued for

LEAGOO Int'l Co., Limited

No.1206-1209, Building B, Huihai Plaza, Heping Road, Longhua New District, Shenzhen, China

Product Name:	WCDMA/GSM MOBILE PHONE
Brand Name:	LEAGOO
Model No.:	Alfa 6
Series Model:	K451A,K451B
FCC ID:	2ADKW-LEAGOO-ALFA6
Test Standard:	FCC Part 15B

Any reproduction of this document must be done in full. No single part of this document may be reproduced wipermission from STS, All Test Data Presented in this report is only applicable to presented Test Sample.AL







Report No.: STS1512126E01

### **TEST RESULT CERTIFICATION**

Applicant's name	LEAGOO Int'l Co., Limited
Address	No.1206-1209, Building B, Huihai Plaza, Heping Road, Longhua New District, Shenzhen, China
	Shenzhen ODX Telecom Equipment Co., Ltd.
Address	2nd Floor of Building B, HongLianYing Technology Park, No.286 of SiLi Road, DaBuXiang Community, Longhua New District, Shenzhen, China
Product description	
Product name	WCDMA/GSM MOBILE PHONE
Brand name	LEAGOO
Model and/or type reference	Alfa 6
Standards	FCC Part 15B
Test procedure	ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Testing Engineer :

(Hakim Hou)

Technical Manager :

(Vita Li)

Authorized Signatory: [howy | one

(Bovey Yang)







# **Table of Contents**

1.	SUMMARY OF TEST RESULTS	5
	1.1 TEST FACTORY	5
	1.2 MEASUREMENT UNCERTAINTY	5
2.	GENERAL INFORMATION	6
	2.1 GENERAL DESCRIPTION OF EUT	6
	2.2 DESCRIPTION OF TEST MODES	7
	2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	7
	2.4 DESCRIPTION OF SUPPORT UNITS	8
	2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3.	EMC EMISSION TEST	10
	3.1 CONDUCTED EMISSION MEASUREMENT 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	10 10
	3.1.2 TEST PROCEDURE	11
	3.1.3 DEVIATION FROM TEST STANDARD	11
	3.1.4 TEST SETUP 3.1.5 EUT OPERATING CONDITIONS	11 11
	3.1.6 TEST RESULTS	12
	3.2 RADIATED EMISSION MEASUREMENT	14
	3.2.1 RADIATED EMISSION LIMITS	14
	3.2.2 TEST PROCEDURE	15
	3.2.3 DEVIATION FROM TEST STANDARD 3.2.4 TEST SETUP	15 16
	3.2.5 EUT OPERATING CONDITIONS	16
	3.2.6 TEST RESULTS	17
4	PHOTOS OF TEST SETLIP	20



Page 4 of 21 Report No.: STS1512126E01

# **Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	31 Dec. 2015	STS1512126E01	ALL	Initial Issue



Report No.: STS1512126E01

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

EMISSION				
Standard	Item	Result	Remarks	
FCC 47 CFR Part 15 Subpart B	Conducted Emission	PASS	Meet Class B limit	
(10-1-05 Edition)	Radiated Emission	PASS	Meet Class B limit	

## NOTE:

(1) " N/A" denotes test is not applicable in this Test Report

#### 1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add.: 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,

Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y  $\pm$  U  $^{,}$  where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2  $^{,}$  providing a level of confidence of approximately 95 %  $^{\circ}$ 

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	±2.88dB
2	Conducted Emission (150KHz-30MHz)	±2.67dB
3	RF power,conducted	±0.70dB
4	Spurious emissions,conducted	±1.19dB
5	All emissions,radiated(<1G) 30MHz-200MHz	±2.83dB
6	All emissions,radiated(<1G) 200MHz-1000MHz	±2.94dB
7	All emissions,radiated(>1G)	±3.03dB
8	Temperature	±0.5°C
9	Humidity	±2%



# 2. GENERAL INFORMATION

# 2.1 GENERAL DESCRIPTION OF EUT

Equipment	WCDMA/GSM MOBILE PHONE
Trade Name	LEAGOO
Model Name	Alfa 6
Series Model	K451A,K451B
Model Difference	Only difference in mode name
lowest radio frequency	523MHz
Power Rating	Adapter: Input: AC100-240V, 300mA, 50/60 Hz Output: DC 5V, 1000mA Battery: Rated Voltage:DC 3.8V capacity: 1600mAh
Hardware version number	V2.1
Software versioning number	LEAGOO_Alfa6_OS_1.1_S151119
Connecting I/O Port(s)	USB Port*1/ Earphone *1
MCU Operating frequency	1.2GHz

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



#### 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	USB port communication with PC


For Conducted Test			
Final Test Mode Description			
Mode 1 USB port communication with PC			

For Radiated Test			
Final Test Mode Description			
Mode 1	USB port communication with PC		

#### NOTE:

- 1. Due to the different configuration and test, in this list only some worse mode. The worst test data of the worse modeis reported by this report.
- 2. We have be tested for all avaiable U.S. voltage and frequencies(For 120V, 50/60Hz and 240V, 50/60Hz) for which the device is capable of operation.

#### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED





## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	WCDMA/GSM MOBILE PHONE	LEAGOO	Alfa 6	N/A	EUT
E-2	PC	4CV428DQXR	500-320cx	4CV428DQYN	N/A
E-3	Keyboard	HP	PR1101U	DKUSB1B06Q42209FBK800	N/A
E-4	Mouse	MOTOSPEED	F66	697738-001	N/A
E-5	Printer	LENOVO	LJ2400L	LP02781702	N/A
C-6	AC (PC Adapter)	LITEON	PA-1650-86	3X06399004	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable (FTP)	NO	97cm	N/A
C-2	USB Cable (FTP)	NO	101cm	N/A
C-3	USB Cable (FTP)	NO	108cm	N/A
C-4	USB Cable (FTP)	NO	120cm	N/A
C-5	AC (Printer Cable) (FTP)	NO	100cm	N/A
C-6	AC (PC Cable) (FTP)	NO	120cm	N/A

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length\_"</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".
- (4) PC is the FCC DOC is approved.



# 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

# Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Loop Antenna	Daze	ZN30900N	SEL0097	2015.10.27	2016.10.26
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D(1201)	9120D-1343	2015.03.06	2016.03.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Temperature & Humitidy	Mieo	HH660	N/A	2015.10.28	2016.10.27
Unversal radio communication tester	R&S	CMU200	111764	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBE CK	AK9515H	SN-96286/9628 7	N/A	N/A

# Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24
Conduction Cable	EM	C01	N/A	N/A	N/A



## 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

## 3.1.1 POWER LINE CONDUCTED EMISSION Limits

EDEOLIENCY (MH-)	Class A (dBuV)		Class B	Standard	
FREQUENCY (MHz)	Quasi-peak	Average	Quasi-peak	Average	Standard
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

#### Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

# The following table is the setting of the receiver

Receiver Parameters	Setting		
Attenuation	10 dB		
Start Frequency	0.15 MHz		
Stop Frequency	30 MHz		
IF Bandwidth	9 kHz		





#### 3.1.2 TEST PROCEDURE


The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support

- a. equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
  - I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the
- cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item -EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

## 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.




# 3.1.6 TEST RESULTS

I	WCDMA/GSM MOBILE PHONE	Model Name.:	Alfa 6
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1500	38.97	11.20	50.17	66.00	-15.83	QP
2	0.1500	14.47	11.20	25.67	56.00	-30.33	AVG
3	0.1788	41.26	10.00	51.26	64.54	-13.28	QP
4	0.1788	23.69	10.00	33.69	54.54	-20.85	AVG
5	0.2335	33.37	9.97	43.34	62.32	-18.98	QP
6	0.2335	13.46	9.97	23.43	52.32	-28.89	AVG
7	0.9706	16.36	9.91	26.27	56.00	-29.73	QP
8	0.9706	5.79	9.91	15.70	46.00	-30.30	AVG
9	4.3905	23.85	10.20	34.05	56.00	-21.95	QP
10	4.3905	10.93	10.20	21.13	46.00	-24.87	AVG
11	11.3570	19.31	10.37	29.68	60.00	-30.32	QP
12	11.3570	9.98	10.37	20.35	50.00	-29.65	AVG

## Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.





Page 13 of 21 Report No.: STS1512126E01


IF())'	WCDMA/GSM MOBILE PHONE	Model Name.:	Alfa 6
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1500	38.98	11.20	50.18	66.00	-15.82	QP
2	0.1500	13.52	11.20	24.72	56.00	-31.28	AVG
3	0.2376	35.60	9.96	45.56	62.18	-16.62	QP
4	0.2376	16.24	9.96	26.20	52.18	-25.98	AVG
5	0.3550	26.99	9.95	36.94	58.84	-21.90	QP
6	0.3550	8.42	9.95	18.37	48.84	-30.47	AVG
7	0.8794	16.82	10.00	26.82	56.00	-29.18	QP
8	0.8794	5.49	10.00	15.49	46.00	-30.51	AVG
9	4.6334	22.47	10.20	32.67	56.00	-23.33	QP
10	4.6334	13.69	10.20	23.89	46.00	-22.11	AVG
11	11.2651	20.57	10.30	30.87	60.00	-29.13	QP
12	11.2651	11.62	10.30	21.92	50.00	-28.08	AVG

#### Remark:

1. Factor = Antenna Factor + Cable Loss - Pre-amplifier.

100.0 dBuV



Report No.: STS1512126E01

# 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 Radiated Emission Limits

In case the emission fall within the restricted band specified on 15.105, then the 15.109 limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

# LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

EDECHIENCY (MH-)	Class A (d	BuV/m) (at 3M)	Class B (dBuV/m) (at 3M)		
FREQUENCY (MHz)	PEAK	AVERAGE	PEAK	AVERAGE	
Above 1000	80	60	74	54	

#### Note:

- (1) The limit for radiated test was performed according to FCC PART 15B.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

# FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



Page 15 of 21 Report No.: STS1512126E01

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	5th harmonic (Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz / 10Hz

Receiver Parameter	Setting	
Attenuation	Auto	
Start ~ Stop Frequency	30MHz~1000MHz/RB 120kHz for QP	

#### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter b. anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. the height of the antenna shall vary between 1m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector d. mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the e. EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


## 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




## 3.2.4 TEST SETUP

# (A) Radiated Emission Test-Up Frequency 30MHz~1GHz



# (B) Radiated Emission Test-Up Frequency Above 1GHz



# 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## 3.2.6 TEST RESULTS


## Between 30-1000MHz

IF())'	WCDMA/GSM MOBILE PHONE	Model Name.:	Alfa 6
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	39.2991	15.42	13.84	29.26	40.00	-10.74	QP
2	99.8777	25.84	10.70	36.54	43.50	-6.96	QP
3	152.6640	24.29	11.90	36.19	43.50	-7.31	QP
4	180.0165	25.78	10.23	36.01	43.50	-7.49	QP
5	300.3672	22.22	14.69	36.91	46.00	-9.09	QP
6	480.5276	19.21	19.95	39.16	46.00	-6.84	QP

### Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Factor = Antenna Factor + Cable Loss.
- 3. N/A means All Data have pass Limit






Page 18 of 21 Report No.: STS1512126E01

H-111.	WCDMA/GSM MOBILE PHONE	Model Name.:	Alfa 6
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Vertical
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.1347	19.04	13.38	32.42	40.00	-7.58	QP
2	153.2004	23.73	11.89	35.62	43.50	-7.88	QP
3	239.9873	26.11	11.81	37.92	46.00	-8.08	QP
4	480.5276	19.01	19.95	38.96	46.00	-7.04	QP
5	721.7260	15.05	24.44	39.49	46.00	-6.51	QP
6	906.4823	12.77	26.77	39.54	46.00	-6.46	QP

#### Remark:

- 1. All readings are Quasi-Peak and Average values.
- 2. Factor = Antenna Factor + Cable Loss.
- 3. N/A means All Data have pass Limit



Report No.: STS1512126E01



#### Above 1GHz

The worst test data above 1 GHz was showed as thefollow:( 1 GHz to 6 GHz.)

H-111.	WCDMA/GSM MOBILE PHONE	Model Name.:	Alfa 6
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	Vertical/Horizontal
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1

Freq.	Ant. Pol	Peak	AV	Ant./CL	Actual Fs		Peak	AV	Peak	AV
(MHz)	H/V	Reading	Reading	CF			Limit	Limit	margin	margin
		(dBuV)	(dBuV)	(dB)	Peak AV		(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)
					(dBuV/m)	(dBuV/m)				
1097.45	Н	57.75	41.28	5.15	62.90	46.43	74.00	54.00	-11.10	-7.57
2866.67	Н	52.97	38.29	9.45	62.42	47.74	74.00	54.00	-11.58	-6.26
N/A										
1069.24	V	52.46	37.55	5.15	57.61	42.70	74.00	54.00	-16.39	-11.30
2896.76	V	49.54	32.14	9.45	58.99	41.59	74.00	54.00	-15.01	-12.41
N/A			/ /							

#### Notes:

- 1. Measuring frequencies from 1 GHz to 6 GHz.
- 2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode of the emission shown in Actual FS column.
- 3. The frequency that above 3GHz is mainly from the environment noise.



# 4. PHOTOS OF TEST SETUP

# Radiated Measurement Photos

30MHz-1GHz



Above 1GHz





# **Conducted Measurement Photos**



\* \* \* \* \* END OF THE REPORT \* \* \* \* \*